START

009816

CLASSIFICATION	DOCUMENT NO. RHO-LD-79
	DATE March 1979 COPY NO.

ISSUING FILE

Rockwell Hanford Operations
Richland, WA 99352

TITLE AND AUTHOR

A History of the 200 Areas Tank Farms

J. D. Anderson
O. C. Mudd

DISTRIBUTION

NAME	BUILDING	AREA	NAME	BUILDING	AREA

JUL 1990
RECEIVED
EDMC

ROUTE TO	PAYROLL NO.	LOCATION	FILES ROUTE DATE

CLASSIFICATION

(TO BE USED ON UNCLASSIFIED AND OFFICIAL USE ONLY DOCUMENTS)

54-6100-151 (6-77)

9212556092 9

RHO-LD-79

UNCLASSIFIED

A History of the 200 Areas Tank Farms

J. D. Anderson
O. C. Mudd

Systems Engineering Department
Waste Technology Group

March 1979

Approved BY: _____
P. M. Nugent, Manager
Waste Technology Group

Reviewed By: _____
G. T. Dukelow, Manager
Tank Farm Process Control

Operated for the Department of Energy by Rockwell Hanford Operations
Under Contract EY-77-C-06-1030

9 2 1 2 5 5 6 0 9 3 0

CONTENTS

Introduction	1
Waste Characteristics	1
T and B Plant	2
Uranium Recovery Plant	6
Redox Plant	7
Purex	9
Storage Facilities	11
Operating Practices	12
Tank Auxiliaries	14
Evaporative Facilities	17
Sluicing Facilities	18
Leak Experience	19
Salt Well Pumping	20

SECTIONS

A Farm

Tanks 101-A - 106-A

AX Farm

101-AX - 104-AX

AY Farm

101-AY, 102-AY

AZ Farm

101-AZ, 102-AZ

B Farm

Tanks 101-B - 112-B, 201-B - 204-B

BX Farm

101-BX - 112-BX

BY Farm

101-BY - 112-BY

C Farm

101-C - 112-C
201-C - 204-C

9 2 1 2 1 5 6 0 9 3 1

S Farm

Tanks 101-S - 112-S

SX Farm

Tanks 101-SX - 115-SX

SY Farm

Tanks 101-SY, 102-SY, 103-SY

T Farm

Tanks 101-T - 112-T
201-T - 204-T

TX Farm

Tanks 101-TX - 118-TX

TY Farm

Tanks 101-TY - 106-TY

U Farm

Tanks 101-U - 112-U
201-U - 204-U

9 2 1 2 5 6 0 9 7 2

ROUGH DRAFT

INTRODUCTION

The purpose of this publication is to record the history of liquid waste generation and its subsequent storage in the tank farms at the Hanford Plant. Presentation of this information should be helpful to plant organizations which generate waste and manage the waste.

Since 1944, radioactive wastes from the processing of irradiated uranium have been stored as alkaline slurries in underground tanks. Between 1943 and 1977, 156 tanks were constructed for this use ranging in capacity from 55,000 gallons to 1 million gallons. These tanks are grouped in 15 tank farms located in the 200 East and 200 West Areas. The oldest tank farms - 241-B, C, T and U - were constructed in 1943-44 concurrently with the bismuth phosphate plants. The first waste was routed to tank storage in December of 1944. Additional tanks in separate tank farm locations have been constructed incorporating various design changes and reflecting various philosophy changes to accomodate the wastes. Currently under construction are ~~thirteen~~ 1 million gallon tanks. Six of these tanks will be designated as the 241-AW tank farm, and seven will be designated as the 241-AN tank farm. This will increase the total number of tank farms to 17, and the total number of tanks to 169. (See Table 1)

The basic containment employed in the design of the tanks in the first twelve farms was the provision ~~of~~ for a reinforced concrete shell with a carbon steel liner. During the history of the tank farms, leaks have been confirmed in 20 of the 156 tanks listed in Table 1. ~~These~~ leaks ~~have~~ occurred in nine tanks storing aging wastes and in eleven tanks holding non-aging wastes. An improved tank design to provide more protection against possible release to the environment of radioactive materials was developed to have a double steel liner within the concrete shell, thereby providing an extra barrier against release of radioactive liquids, plus recovery facilities for any liquid which might collect in the annular space between the liners.

WASTE CHARACTERISTICS

Four basic chemical processing operations were the source of radioactive waste solutions transferred to underground storage (UGS) tanks since startup of the Hanford site. These were the Bismuth Phosphate ($BiPO_4$) process, the

9 2 1 2 5 5 6 0 9 3 3

1A

TABLE 1

Waste Storage Tanks at Hanford

Farm	Steel Tank Liner Specification	Tanks per Farm	Capacity per Tank (Gal)	Capacity per Farm (Gal)	Year Constructed
A	ASTM A283 Grade C	6	1,000,000	6,000,000	1954-55
AX	ASTM A201 Grade C	4	1,000,000	4,000,000	1963-64
AY	ASTM A515 Grade 60*	2	1,000,000	2,000,000	1968-70
AZ	ASTM A515 Grade 60*	2	1,000,000	2,000,000	1971-77
B	ASTM A283 Grade C	16	55,000 (4)	220,000	1943-44
			530,000 (12)	6,360,000	
BX	ASTM A283 Grade C	12	530,000	6,360,000	1946-47
BY	ASTM A283 Grade C	12	750,000	9,000,000	1948-49
C	ASTM A283 Grade C	16	55,000 (4)	220,000	1943-44
			530,000 (12)	6,360,000	
S	ASTM A283 Grade C	12	750,000	9,000,000	1950-51
SX	ASTM A283 Grade C	15	1,000,000	15,000,000	1953-54
SY	ASTM A516 Grade 60*	3	1,000,000	3,000,000	1974-77
T	ASTM A283 Grade C	16	55,000 (4)	220,000	1943-44
			530,000 (12)	6,360,000	
TX	ASTM A283 Grade C	18	750,000	13,500,000	1947-48
TY	ASTM A283 Grade C	6	750,000	4,500,000	1951-52
U	ASTM A283 Grade C	16	55,000 (4)	220,000	1943-44
			530,000 (12)	6,360,000	
	TOTALS	156		100,680,000	

* AY, AZ and SY Constructed liners were heat treated in place for stress relief.

9212556093 4

Tributyl Phosphate (TBP) process, the Redox process, and the Purex process. Three of these were chemical separations programs for recovery of pultonium from irradiated reactor fuels. The fourth (TBP) was designed for recovery of uranium metal waste generated by the $BiPO_4$ process. In all cases, the aqueous wastes were made alkaline for storage in underground steel tanks.

T AND B PLANTS

In the bismuth phosphate ($BiPO_4$) process, the following types of waste were generated in the canyon building and sent to underground storage:

1. Alkaline coating removal waste, containing small amounts of fission products, which was combined with first-cycle decontamination waste for storage. Stack drainage, initially combined with second decontamination-cycle waste, was later combined with first decontamination-cycle waste in May of 1951. The composition was estimated to be approximately:

$NaAlO_2$	1.2 M
NaOH	1.0 M
$NaNO_3$	0.6 M
$NaNO_2$	0.9 M
Na_2SiO_3	0.02M
SpG	1.19M
% Pu	0.4 [redacted]
% U	0.4 [redacted]

2. Metal waste (MW) from the extraction contained all of the uranium, approximately 90 percent of the original fission products activity, and approximately one percent of the product. This waste was brought just to the neutral point with 50 percent caustic and then treated with an excess of sodium carbonate. The procedure yielded almost completely soluble waste at a minimum total volume. The exact composition of the carbonate complex was not known but was assumed

9212556093 5

to be a uranium phosphate-carbonate mixture. The composition was estimated to be approximately:

U	0.5 lb/gal
OH	0.71 M
CO_3	2.4 M
NO_3	2.7 M
PO_4	1.4 M
SpG	1.86
Na	4.8 M

3. Byproduct cake solution and waste solution from the first decontamination waste cycle (1C), containing about ten percent of the original fission activity and ~~two~~ one percent of the plutonium. The composition was estimated to be approximately:

1C	
$CePO_4$	<0.01 M
$Zn_3(PO_4)_2$	<0.01 M
$NaNO_3$	0.85 M
$Fe_2(SO_4)_3$	0.07 M
$NaPO_4$	0.75 M
$Cs(NO_3)_3$	<0.01 M
$NH_4(SO_4)$	0.04 M
$NH_4(SiFe)$	0.07 M
NH_4NO_3	0.06 M
Pu	1%

4. Second decontamination-cycle waste, containing less than 0.1 percent of the fission activity and about one percent of the plutonium. Canyon cell drainage waste, previously disposed to a dry well via the 361 settling tank, was combined with the second decontamination waste stream (2C) subsequent to May of 1951.

2C	
$BiPO_4$	0.08 M
LaF	<0.01 M
KOH	0.45 M
KNO_3	0.01 M
$NaNO_3$	0.34 M
$Cr(NO_3)_3$	<0.01 M

9 2 1 2 5 5 6 0 9 3 6

2C - Continued

NaF	0.03 M
$Mn(NO_3)_2$	0.02 M
NH_4NO_3	0.01 M
Pu	1%

In the 244-CR concentration building, fission activity (<0.001% of that in the starting metal) of the waste was low enough to permit ground disposal. The flow was directed through a settling tank, where the bulk of the fission and product activity settled-out with precipitated phosphates and lanthanum flouride, and then to a reverse or dry well. When it was discovered that the wells were filling up with sand, presumably flowing into the well casing through the lower perforations, the wells were replaced with buried sumps. The underground storage tanks for canyon building wastes were arranged in cascade groups of three so that suspended solids (containing the bulk of the radioactive fission products) could collect in the first tank of each series.

5. The first production run was started in T Plant on December 26, 1944, and in B Plant on April 13, 1945. The waste volumes in gallons per ton of uranium (gallons/TU) were extremely high. For example, during 1944-45 at T Plant when the feed material averaged .38 MWD/T (megawatt days per ton, relative value), a run was limited by batch size and the stored waste produced amounted to 10,602 gallons/TU.

While some improvements were incorporated which effected minor waste volume reductions, the first significant development occurred in September of 1947 when the cribbing of second decontamination-cycle supernatants was started at T Plant. The program was later adopted at B Plant in February of 1948. Prior to this time all second cycle wastes had been stored in underground tanks. The mechanics of ground disposal were similar to that for concentration building waste; i.e., after settling in an underground storage tank, the supernatant was pumped to cribs. The remaining solids, containing nearly all of the initial fission activity but only a fraction (9%) of the original volume, were held in storage.

9 2 1 2 5 5 6 0 9 3 7

In June of 1949, the concept of concentrating first decontamination-cycle wastes by evaporation was proposed. After determining that the approach was economically feasible, facilities for this purpose were installed. The 242-T Evaporator commenced operation on May 1, 1951, and 242-B Evaporator commenced operation of December 14, 1951.

During the lifetime of 242-T, over 8,638,000 gallons of first-cycle feed were processed and an overall 82.1% reduction in volume was realized. The storage space reclaimed by this technique totalled more than 7,089,000 gallons. Subsequently, the equipment processed 5,899,000 gallons of uranium recovery waste, recovering 2,092,000 gallons of storage. The facility was shutdown in July of 1955.

Some 6,027,000 gallons of first-cycle feed were processed in the 242-B Evaporator, achieving a volume reduction of 80.9%. As in the case of the 242-T Evaporator, the overall effectiveness was achieved by making two passes. Usually the first pass gave about 70% reduction, later followed by a second pass (bottoms from first evaporation) which were concentrated approximately 30%. This facility was also later used for evaporating uranium recovery wastes. Before shutdown at the end of Octover of 1954, over 2,298,000 gallons of space were recovered from uranium recovery wastes. Total space recovered by both evaporators amounted to 16,353,000 gallons.

In May of 1953, approval was obtained from Radiological Sciences to pump a limited volume of first-cycle supernatant to ground (trenches) on a specific retention basis. Specific retention refers to the ability of a dry column of soil to retain liquid without penetration of the liquid to the water table. In June of 1954, approval was obtained to dispose of evaporator bottoms in a similar manner. During the period from December 1953 to December 1954, 4,807,000 gallons of first-cycle supernatants and 1,938,000 gallons of first-cycle evaporator bottoms were discharged to ground.

While disposal of first-cycle wastes on a specific retention basis was expedient at the time due to limited storage space, efforts were directed toward minimizing the quantity of activity sent to ground yet retaining the

9 2 1 2 5 5 6 0 9 3 8

desirable feature of high-volume disposal. Although scavenging techniques has been tested previously at the Uranium Recovery Plant, success at T Plant with first-cycle waste was not demonstrated until late in 1954. After difficulty with poor decontamination (attributed to interference from ions in the coating waste) was overcome by segregating the two wastes, routine scavenging of first-cycle waste started on December 31, 1954. Until the shutdown of T Plant in August of 1956, approximately 3,144,000 gallons of scavenged supernatants were discharged to the TY caverns. The effective reduction in volume, as discharged from the building, was approximately 88%.

Briefly summarizing bismuth phosphate plants performance: During twelve years of operation, waste volumes were effectively reduced by a factor of 3.25 from 17,016 gallons/TU to 5,240 gallons/TU.

9 2 1 2 5 5 6 0 9 3 9

URANIUM RECOVERY PLANT

Although the volumes of waste per ton of production varied with the type feed, estimates of 9,200 gallons/TU (unconcentrated) and 5,500 gallons/TU (concentrated) are considered to be reasonably accurate. Subsequent processing in the evaporators reduced the volume to about 3,600 gallons/TU, comparable to the original volume of metal waste discharged by the bismuth phosphate plants. However, the design capacity of the two waste evaporators was only 72,000 gallons per month while the waste generated by the Uranium Recovery Operation ranged as high as 1,676,000 gallons per month. Consequently, it became apparent that new underground waste tanks would be required to accomodate these waste surpluses unless another solution was found.

The imminent shortage was alleviated by the laboratory development of a waste scavenging technique which removed long-lived fission products and permitted ground disposal of the resulting (and relatively inactive) supernatants. Following incorporation of this change in the uranium recovery flowsheet in October of 1954, over 29,156,000 gallons of "In-Plant" scavenged waste were disposed to ground.

Prior to October of 1954, the uranium recovery wastes had been stored in an untreated condition. In November of 1955, scavenging of these wastes was started at the 241-CR facility, resulting in an additional 11,659,000 gallons of "In-Farm" scavenged supernatants being disposed to ground. Thus overall, approximately 41,000,000 gallons of space were recovered. This operation was completed in 1957.

This waste was generated on a 1:1 ratio in the MW processing of the $BiPO_4$ process. The following composition does not list ~~CN~~ (CN^-), but it is known that the waste (TBP) was treated with potassium ferrocyanide ($K_4Fe[CN]_6$) as a Cs scavenger. The supernatant was then decanted to the B-C Crib.

TBP Waste Composition

pH	$\geq$9.5
P	1.29
UNH	0.0026M
SO_4	0.346M
PO_4	0.25M
NO_3	6.14M
Cl	0.022M
Na	7.57M
OH	0.09M
FP	Same as MW

9 2 1 2 5 5 6 0 9 4 0

REDOX PLANT

Responsibility for the Redox Plant was accepted by the Separations section on August 16, 1951, and after several months of operability testing, initial dissolving of a full charge of 100% HAPO level slugs was started January 9, 1952. During the first year of operation, combined salt and coating wastes (segregation of wastes was not practiced until 1955) averaged 4,378 gallons/TU.

In April of 1953, a study was performed to determine the practicability of self-concentrating wastes in the first two cascades of S Farm by disposing of vapor condensate instead of reflusing to the tanks. Concluding that the technique was feasible and that the resulting condensates could be safely cribbed, suitable condensers were installed and the first benefits of self-concentration were realized in August of 1953. Combined with process improvements (e.g., concentrated flowsheet made during the year) the total net effect was to reduce waste volumes approximately 30% below 1952 performance.

During subsequent years, with greater self-concentration being achieved and additional process improvements incorporated in the flowsheet, the trend of waste volumes continued downward. Significant amount the latter were:

1. Initiation of first-stage backcycling in December of 1954, which effected approximately 30% reduction
2. Adoption of full-scale backcycling in March of 1956, which effected an additional 23% reduction, and
3. Reduction of dissolver rinses and line flushes in 1956-57 which cut coating waste volumes in half and lowered overall volumes by about 10%.
4. Recycling of $NaNO_3$

In summary, the combined effects of self-concentration and process improvements during the ~~six~~ fourteen-year life of the Redox Plant successfully reduced waste volumes by a factor of 7.4 - from 4,378 gallons/TU to 594 gallons/TU.

Coating waste (CW) aluminum-clad fuels were declad in a boiling solution of sodium nitrate by adding 50% caustic. The resultant salt waste was sent to a tank separate from high-level waste. Zircaloy-clad fuels were declad in a boiling ammonium nitrate-ammonium fluoride mixture. The resultant coating solution was neutralized with 50% caustic. This solution contained up to 40% slurryable solids.

Redox waste (R) was the high-level component of the process waste. Composition varied, but the following is considered a nominal for all wastes designated R:

Coating Waste CW (Al)		CW (Zircaloy)	
$NaAlO_2$	1.2 M	$ZrO_2 \cdot 2H_2O$	0.1 M
NaOH	1.0 M	NaF	0.7 M
$NaNO_3$	0.6 M	$NaNO_3$	0.02M
$NaNO_2$	0.9 M	KF	0.01M
Na_2SiO_3	0.02M	U	1 x 10-3 lb/gal
SpG	1.19	Pu	1 x 10-3 lb/gal
PU	0.4 %	pH	10
U	0.4 %		

9 2 1 2 5 5 6 0 9 4

Redox Waste (R)	
$NaAlO_2$	1.2 M
NaOH	0.06 M
$NaNO_3$	4.83 M
Na_2CrO_7	0.066M
$Cr(OH)_3$	0.045M
$Na_2(SO_4)$	0.031M
$Fe(OH)_3$	0.016M
SpG	1.29
U	0.05 %
Pu	0.04 %

PUREX

At the completion of operability testing and the processing of cold uranium runs in latter 1955, Purex Plant came on the line as a production facility in January of 1956. High initial waste volumes precluded self-concentration, resulting in two tanks (101-A and 102-A) being partially filled with wastes which never boiled. In May of 1956, the salt waste was routed to a third tank (103-A) and as a result of volume reductions plus temporary segregation of carbonate and organic wastes, sufficient self-heat was generated to start boiling in Tank 103-A on July 5, 1956. Boiling accelerated at a rapid rate, attaining a boiloff peak in June of 1957 of ten gallons per minute. When boiloff greatly exceeded input, water additions became necessary (in February of 1957) to maintain liquid in the tank at a reasonable level.

Coating waste (CW) aluminum-clad fuels were declad in a boiling solution of sodium nitrate by adding 50 percent caustic. Zircaloy-clad fuels were declad in a boiling ammonium nitrate-ammonium fluoride mixture. The resulting coating was neutralized with 50 percent caustic.

Organic wash waste (OWW) - The solvent used in Purex was treated before reuse by washing with potassium permanganate and sodium carbonate, followed by dilute nitric acid and then a sodium carbonate wash. The organic waste streams were combined and sent to boiling waste until 1969 for boil-down. After 1969 the OWW waste was sent to a low-level waste tank in 241-C Farm.

9 2 1 2 5 5 6 0 9 4 2

Neutralized Purex acid waste (P) - The original plant in 1956 neutralized all of the high-level waste and sent it to the 241-A Tank Farm. As fission product recovery started, a portion of the waste was treated for strontium recovery and then neutralized. As of 1967, all of the high-level waste left Purex as an acid solution for treatment at B Plant.

Include sugar decontamination

Two thorium campaigns were run; one in 1966 (1,200,000 gallons), and one in 1970 (3,000,000 gallons), and all of the waste was routed to Tank 104-C. This included equipment flush both before and after the runs. The operating waste amounted to about one-third of the above totals.

Nominal Purex Waste Compositions:

Coating Waste (CW) Al		(CW) Zircaloy	
$NaAlO_2$	1.2 M	$ZrO_2 2H_2O$	0.1 M
NaOH	1.0 M	NaF	0.7 M
$NaNO_3$	0.6 M	$NaNO_3$	0.02M
$NaNO_2$	0.9 M	KF	0.01M
Na_2SiO_3	0.02M	U	1 x 10-3 lb/gal
SpG	1.19M	Pu	1 x 10-3 lb/gal
Pu	0.4 %	Ph	10
U	0.4 %	SpG	1.1

Purex Neutralized High-Level Waste (P)		Purex Organic Wash Waste (OWW)	
Fe	0.4 M	SpG	1.02 M
Na	1.4 M	$NaNO_3$	0.04 M
SO_4	0.90M	Na_2CO_3	0.13 M
PO_4	0.02M	MnO_2	0.004M
Al	0.15 M	U	3×10^{-4} lb/gal
NO_3	1.3 M		

Purex Thorium Campaign (4.5×10^6 gallons)

(about 1/3 of total volume - remainder flushes)

KF	0.12 M
$NaAl(OH)_2$	0.34 M
$NaNO_3$	2.57 M
KNO_3	0.014M
Na_3PO_4	0.09 M
Fe	0.025M
SO_4	0.05 M
NaOH	0.05 M

9212556094 3

STORAGE FACILITIES

Since 1944, a total of 156 underground tanks have been constructed for the retention of radioactive wastes at Hanford. These tanks are strategically located in groups called Farms, containing two to eighteen tanks each. Each of the tanks is constructed of reinforced concrete with a mild steel liner covering the bottom and sidewalls. Most of the tanks are 75' in diameter and are constructed to hold from 15' to 30' of liquid for a nominal capacity of 530,000 to 1,000,000 gallons; sixteen of the tanks are smaller units of the same basic design built to contain 55,000 gallons each. All of the tanks have a minimum of 7' of earth cover for shielding purposes.

Many of the tanks built since 1954 have been equipped with condensers and condensate disposal systems to permit the wastes to self-concentrate. These tanks are equipped with airlift circulators to avoid the fluctuating rate of boiling and resultant tank pressurization that could result from a stagnant self-heating system. Self-boiling has been observed at rates of up to 10 gallons per minute in the SX Farm, and up to 30 gallons per minute in the A Farm.

The original tank farms (T, U, B and C) featured tanks with dished bottoms and a 17-foot operating depth. The BX Farm tanks were built to the original tank design (See Figure 1).

Second generation tank design is embodied in the S, BY, TX and TY Tank Farms and is essentially the same as the original tanks except for increased capacity and a 23-foot operating depth (See Figure 2).

The third and fourth generation tanks are represented by the SX and A design with the operating depth increasing to 31-feet and the A Tanks going to a flat (instead of a dished) bottom (See Figures 3 and 4).

The fifth generation tanks in the AX Farm were essentially the same as the A Tank design with the addition of a grid of drain slots beneath the steel liner bottom (See Figure 5).

9 2 1 2 5 5 6 0 9 4 4

The grids function to collect potential tank leakage. This is then diverted to a leak detection well. The grids also serve as an escape route for free water formed as it is released from the concrete grout during initial heating of the tank.

The latest tank design represented by AY, AZ and SY Farms represents a departure from the basic design reflected in all previous tanks. This design features a heat-treated, stress-relieved primary steel liner and a non-stress-relieved outer steel liner, both inside the reinforced concrete shell (See Figure 6).

OPERATING PRACTICES

The nine single-shell non-boiling tanks in the tank farms are of three sizes: 55,000 gallons; 530,000 gallons, and 750,000 gallons. The 530,000 gallon and 750,000 gallon tanks were originally arranged in cascades of three, four or six tanks; i.e., the tanks were arranged in such a manner that when the first tank in a cascade was filled, it overflowed to the second tanks, then to the third tank, etc. As various programs have been initiated through the years, many of the overflows between tanks in the various cascades have been removed, modified or blanked. A number of the tanks are equipped with air-cooled reflex condensers. Dry wells located within the tank farms are used to monitor the soil for radioactivity, thus serving as a leak detection system. These dry wells extend to a depth of approximately 75 feet, which is several feet below the bottom of the tanks.

The routing of of non-boiling liquid waste from the operating building to the tank farms is done by means of underground lines and diversion boxes where selected underground piping is interconnected by jumpers. Leaks occurring in the diversion boxes or into the surrounding line encasement drain to catch tanks which are then pumped to the large underground storage tanks. Catch tanks and waste storage tanks are inventoried by taking electrode readings of the liquid levels.

9 2 1 2 5 5 6 0 9 4 5

Upon notification from the operating building to the tank farm that a batch of waste is ready to be pumped to underground storage, the tank farm operator determines:

1. That a satisfactory routing is in place from the operating building to the designated receiving tank, and
2. That the receiving tank has sufficient space to accomodate the transfer.

If all conditions are satisfactory for the transfer, the tank farm operator notifies the operating building, and the transfer is started. After completing the transfer, the volume (obtained by difference from electrode measurements of the liquid level of the receiving tank) is logged for future reference.

There are five aging waste tank farms: A, AX, AY, AZ and SX, containing 29 waste storage tanks. The SX Tank Farm, used for storing Redox salt wastes, was the first to be equipped for handling boiling waste solutions, although not all of the SX tanks could accomodate self-boiling wastes. Of the 15 tanks in the farm, only tanks 105 and 107 through 115 were equipped to handle self-boiling wastes.

~~Both~~ The A, AX, AY and AZ tank farms were built to store Purex and B Plant aging wastes. The capacity of these tanks, as well as SX tanks is 1,000,000 gallons. Vapors from the boiling action (or self-concentration) are routed through headers to condensers which are vented to the atmosphere through filters. Condensate is either discarded to cribs or returned to the waste tank where it is used to maintain the desired liquid level.

In the aging waste tanks, heat is generated when the fission products decay radioactively. Most of the heat generated is dissipated by boiling the supernatant, although a small amount of heat is conducted to the ground. The rate of heat generation in a tank is dependent upon the quantity of fission products present which, in turn, is dependent upon:

- The characteristics of the fuel being processed in terms of:
  - Reactor power level (MW/T)
  - Integrated exposure (MWd/T)
  - Cooling time since reactor discharge

9212556094 6

- Rate of tank filling in terms of associated tons of uranium production per day
- The period of time during which a tank receives waste
- Integrated age of the waste in the tank

The SY double-shell tank farm has been placed into service for the storage of concentrated supernatant and two tank farms are under construction (AW and AN Farms) to also store this type of waste. Current plans call for the storage of all tank farm liquid waste to be in double-shell tanks.

After constructing a new waste storage tank, a minimum of 7 inches of water is added to the tank to prevent the bottom liner from buckling under conditions of negative pressure maintained on the tank. A tank volume in excess of 6 inches of water is impossible because of a water seal located in the tank farm vent header.

9 2 1 2 5 5 6 0 9 4 7

TANK AUXILIARIES

Tank auxiliaries are provided to prevent or minimize the escape of radioactive material to the environment. The more significant auxiliary systems are briefly discussed below.

Airlift Circulators

Airlift circulators are installed in aging tanks to promote mixing of the supernatant. By maintaining motion within the body of liquid, the circulators minimize superheat buildup and, consequently, prevent bumping.

The circulators are long, open cylinders of varying lengths immersed in the tank's contents. An air line discharging at the base of the cylinder causes a flow of solution from the bottom to the top of the cylinder. This moves fresh solution from the bottom of the tank to the supernatant layer above.

Ventilation Systems

The waste storage tanks in the T, U, B, C, S, SX, TX and TY (first and second generation) tank farms were equipped with air-cooled condensers of the multi-tube air-fin type vented directly to the atmosphere. These condensers were adequate for the waste temperatures and vapor loads encountered in the original operations (Approximately 180°F for sludge and supernatants).

The SX tanks were the first tanks designed for boiling service and were expected to boil from 1 to 5 years. The heat load on the SX system increased as wastes self-concentrated and it was necessary to install airlift circulators to prevent bumping. This increased the vapor load on the ventilation system. From a practical standpoint, the atmosphere in the tanks was considered as saturated at the ambient temperature (∿180°F), and condensibles were removed before non-condensibles were filtered and discharged to the atmosphere. Dependent upon the status of the tank contents, condensate was either discharged to a crib or returned to the tank to maintain the liquid level.

The A, AX, AY and AZ tank farms have a common ventilation system. Backup facilities are provided by the A Farm vent system. The SY and the future AW and AN farms have their own ventilation system.

9 2 1 2 5 5 6 0 9 4 8

Monitoring Systems

Monitoring devices and systems are used to determine the status of the stored wastes, to measure the potential effects of the stored wastes upon the tank structures, and to indicate real or potential operating problems involving tank failure.

In relating to the waste tank structures themselves, the AX and AY tank designs provided for the installation of thermocouples in various locations within the concrete shell, within the sludge and under the tanks. Using these thermocouples, temperature profiles may be taken as a means of determining thermal stresses within the shell and sludge, and to indicate the need for changes in the mode of operations of the tanks.

The detection and measurement of radiation gives direct information relating to tank integrity, and in the event of tank failure, is used to locate the region (or regions) of failure. Monitoring wells located in the older tank farms are specifically designed for this purpose.

Radiation profiles (also temperature patterns) as a measure of tank condition, are determined by passing detection devices through piping laterals located in the soil beneath the A and SX Tanks.

Monitoring non-boiling tank supernatant and sludge levels indicates possible changes of conditions within the tank. Electrode tapes are used to determine liquid levels; metal plate "floats" (3 to 6 inches in diameter) which will sink until they contact the sludge, are used to determine sludge levels.

Stress gauges have been installed on the AY tank farm tanks to provide a measure of any stress change occurring while the tanks are in service. The stress gauges are welded directly to the inner tank liner.

Equipment provided for the prompt detection and confirmation of leaks in underground waste storage tanks consists primarily of different types of access channels beside and underneath the tanks through which instruments may travel to monitor radiation level and temperature. A brief description of the major leak detection devices follows:

9 2 1 2 5 5 6 0 9 4 9

Buried Horizontal Laterals

The buried horizontal lateral system for radiation detection and temperature measurement in the 241-A and SX tank farms consists of 12-foot diameter caissons sunk approximately 70 feet below grade. From each caisson three laterals are bored horizontally under each tank bottom approximately 10 feet below the base pad elevation.

The insertion of temperature and radiation probes into each lateral for a given tank provides profiles which are used in the evaluation of tank integrity and for the determination of changing conditions in the tank contents.

Wells

The wells used are of two types:

1. Open and dry wells sunk in groups in a tank farm, and
2. Wells extending into the water table below a tank farm site

Each tank (except double-shell tanks) is ringed with a series of dry wells which are six inches in diameter, bottom open ended, and such approximately 75 feet below grade. The opening of the casing is approximately 23 feet below the elevation of the base slab of the tanks. Each dry well is located approximately 10 feet from a tank. The dry wells can accomodate portable gamma and neutron detection devices.

Some wells are customarily sunk to levels below the surface of the water table underlying the tank farm site. Routine monitoring of these wells should spot radionuclides released to the soil in sufficient quantity to reach the water table.

Leak Collection

The AX tank farm provides a system of drain channels in the concrete base slab immediately below the carbon steel tank liner. They drain to a 24-inch 60-foot deep well from which leakage can be pumped. A radiation detection well is located adjacent to this sump-type syste.

The double-shell tanks (AY, AZ and SY tank farms) also have drain channels in the insulating material installed bwtween the steel and concrete prior to the thermal stress-relieving operation. These channels could carry leakage to the annular space between the inner and outer liners. Detection during operation is provided by conductivity probes in the annulus and by radiation alarms in the exhaust system.

EVAPORATIVE FACILITIES

Greater safety in containment of non-boiling liquid wastes is obtained by converting them to the solid form. This has been carried out by two methods of evaporation, ultimately leaving a solid salt cake in the underground tanks. One method no longer in use makes use of in-tank heating to remove water. Both heated air and electric immersion heaters were used. The other method involves the transfer of the liquid waste to a standard evaporator located in a separate building. Bottoms from this evaporator are returned to the underground waste storage tanks where salts drop out and residual supernatant liquors are recycled through other waste tanks for re-evaporation, or are stored in double-shell tanks.

9 2 1 2 5 5 6 0 9 5 0

In 1952, an evaporator system (242-B and 242-T) was installed in each of the two operating areas to remove water from the waste. These two units were operated for approximately four years at which ~~time~~ they were shut down. The 242-B unit was never reactivated; however, the 242-T Evaporator was reactivated on December 3, 1965. Following capacity increasing modifications, the unit was later shut down on April 15, 1976.

In-tank heating was accomplished by the in-tank solidification units designated ITS #1 and ITS #2. Both were located in the BY tank farm in 200-East Area. The ITS #1 unit startup was March 19, 1965, and the ITS #2 unit started up on February 17, 1968. On August 24, 1971, the ITS #1 unit was converted from an evaporator to a cooler for ITS #2. Both units were subsequently shut down on June 30, 1974.

On November 1, 1973, and on March 18, 1977, the 242-S and 242-A Evaporator-Crystallizer units, respectively, were started. These evaporators operate under a vacuum, employing evaporative concentration with subsequent crystallization and precipitation of salt crystals. Both units are still in service.

Additional concentration of wastes was obtained by using the concentrators at Redox and B Plant. The Redox concentrator was used from July 28, 1967 to June 30, 1972, while the B Plant concentrator operated from October 31, 1967, to February 2, 1968.

A summary of the performance obtained in waste concentration is shown in Table 2.

SLUICING FACILITIES

Sluicing operations were first employed at Hanford for the removal of sludges in connection with the TBP Plant recovery of stored neutralized uranium nitrate wastes from the operation of the wartime bismuth phosphate separation process.

Sluicing operations are in use at the present time for the removal of stored sludge for the recovery of strontium.

9212356095 1

18A

TABLE 2

Waste Solidification Performance

Facility	Waste Volume Reduction (in K Gallons)
242-B	7,172
242-T (1950's)	9,181
ITS #1	11,876
ITS #2	15,295
ITS #1 and #2	7,965
242-T (Modified)	24,471
242-S	41,983
242-A	52,421
B Plant (Cell 23)	1,185
Redox	12,393
TOTAL	183,942

As of 12-31-86

9 2 1 2 5 5 6 0 9 5 2

18A

TABLE 2

Waste Solidification Performance
(As of 12/31/77)

Facility	Waste Volume Reduction (in K Gallons)
242-B	7,172
242-T (1950's)	9,181
ITS #1	11,876
ITS #2	15,295
ITS #1 and #2	7,965
242-T (Modified)	24,471
242-S	34,624
242-A	6,622
B Plant (Cell 23)	1,185
Redox	12,393
TOTAL	130,784

9212556093

Sludge is removed from a tank by pumping off the supernatant and exposing the sludge. High pressure pumps (∿180 psig) in the 244-AR vault transfer water (or supernatant) to the tank being sluiced through specially designed nozzles. As the sludge is broken into a slurry, it is transferred to a holding tank, settled and the supernatant is recycled to remove additional sludge.

LEAK EXPERIENCE

As previously discussed, 15 waste storage tank farms (totaling 156 tanks) have been built at Hanford during the last 33 years. Twenty tanks located in seven of the farms are confirmed leakers. The different types of wastes handled, the different thermal conditions prevalent, and the small number of leaks encountered make is difficult to directly compare the tank failures which have occurred. While there are several theories regarding mechanisms for failure (including stress, corrosion, cracking and mechanical tearing of the liner) the extreme difficulty of direct inspection makes it impossible to accurately characterize the failures. There is, in all probability, more than one mechanism responsible. Shifting of a tank liner was observed in 1956 and again in 1958, but no leak was confirmed until 1959. The last tank failure occurred in 1975.

A new design feature to reduce the likelihood of waste escaping to the environment has been included in the last three tanks farms and will also be included in tanks currently under construction. Two steel liners, instead of one, are being used within the concrete shell. The annular spare between these liners will contain any material which might pass through the primary barrier.

Over the past several years, a number of improvements in leak detection capability have been developed and employed to permit the earliest possible recognition of conditions requiring special operating control actions.

The first aging waste tank farms included ground water wells and a few dry wells for monitoring purposes. However, these were limited in number. The

9 2 1 2 5 5 6 0 9 5 4

next step was the installation (in December of 1958) of a prototype horizontal lateral system under the 113-SX tank as a means of confirming a suspected leaking condition. This method of detecting leaks proved to be successful and similar systems were subsequently installed beneath all the aging waste tanks in the SX and A tank farms during 1961. At this time additional dry wells were also installed. A later improvement in leak detection was the incorporation of drain channels and sump collection wells in the AX tank design.

Tanks storing aging wastes have always been equipped with liquid level measurement devices which provide indication of changes in tank contents. The original non-boiling waste tank farms also included dry wells and wells to ground water. Additional wells, however, have been drilled in strategic locations throughout various non-boiling waste tank farms as a result as a means of detecting tank leakages.

A summary of the tank leaks which have occurred is presented in Table 3. Eleven of the twenty tanks in which leaks have occurred have contained non-aging waste; the rest stored aging waste.

SALT WELL PUMPING

In an effort to minimize potential leaks of liquid radioactive waste from underground storage tanks to the Hanford soil, the volume of radioactive wastes is being reduced by concentration. Concentration of these wastes produces a salt cake which is saturated with mother liquor. Much of this mother liquor (termed interstitial liquor) is gravity drainable and needs to be removed to minimize the potential for leakage of radioactive liquids to the surrounding environs. Salt wells are used to collect the drainable interstitial liquor for eventual transfer to concentration facilities and/or storage in double-shell waste tanks.

When a tank is filled with salt cake, an estimated 50% of the salt cake volume is occupied by interstitial liquids. In addition, supernatant liquid may be above the salt cake. The liquid and as much of the interstitial liquid

9 2 1 2 5 5 6 0 9 5 5

Underground Waste Storage Tank Leak Experience

Tank	Year Suspect	Date Confirmed	Volume of Leakage (Gal)	KCi Cs-137	Status
104-A	4-1975	4-1975	500-2,000	0.8-1.8	Interim Stabilized
105-A	1963	11-1963	Small	---	Interim Stabilized
107-B	1968	1980	8,000	2	Interim Stabilized
110-B	1969	1981	<10,000	<4.3	Interim Stabilized
201-B	1968	1980	1,200	0.42	Interim Stabilized
203-B	1982	1983	300	---	Interim Stabilized
102-BX	2-1970	2-1971	70,000	51	Diatomite Added
108-BX	7-1973	2-1974	2,500	0.5	Interim Stabilized
103-BY	7-1969	7-1973	Small	---	Jet Pumping
108-BY	3-1971	3-1972	Small	---	Interim Stabilized
101-C	1968	1980	20,000	2	Interim Stabilized
203-C	1976	1984	400	---	Interim Stabilized
101-U	11-1959	11-1959	30,000	23	Interim Stabilized
104-U*	5-1956	1958	55,000	0.09	Diatomite Added
110-U	7-1975	7-1975	5,000-6,000	0.04-0.05	Interim Stabilized
112-U	1969	1980	8,500	0.85	Interim Stabilized
106-T	5-1973	6-1973	115,000	40	Interim Stabilized
107-TX	1977	1984	<2,500	<2.8	Interim Stabilized
103-TY	5-1973	6-1973	3,000	0.66	Interim Stabilized
104-TY	1973	1981	1,400	0.56	Interim Stabilized
105-TY	9-1960	9-1960	35,000	4	Interim Stabilized
106-TY	7-1959	8-1959	20,000	2	Diatomite Added
107-SX	3-1964	3-1964	Small	---	Sludge Air Cooling
108-SX	12-1962	12-1962	2,400	17	Sludge Air Cooling
109-SX	1-1965	2-1965	Small	---	Sludge Air Cooling
111-SX	5-1974	5-1974	500-2,000	0.6-2.4	Sludge Air Cooling
112-SX	1-1969	1969	30,000	45	Sludge Air Cooling
113-SX**	6-1958	11-1962	15,000	8	Diatomite Added
115-SX***	2-1965	3-1965	50,000	40	Sludge Air Cooling

* Contained water at the time of the leak.
** Contained $NaNO_3$ solution at the time of leak; also some redisual supernatant solution
*** Contained $NaNO_3$ solution at the time of leak.

20 A

TABLE 3

Underground Waste Storage Tank Leak Experience

Tank	Year Suspect	Date Confirmed	Volume of Leakage (Gal)	KCi of Cs-137	Status
104-A	4-1975	4-1975	500-2,000	0.8-1.8	Pumped to heel
105-A	Summer 1963	11-1963	Small	---	Under study
102-BX	2-1970	2-1971	70,000	51	Diatomite added
108-BX	7-1973	2-1974	2,500	0.5	Pumped to heel
103-BY	7-1969	7-1973	Small	---	Salt well pumping
108-BY	3-1971	3-1972	Small	---	Salt well pumping
106-T	5-1973	6-1973	115,000	40	Pumped to heel
101-U	11-1959	11-1959	30,000	23	Isolated
104-U*	5-1956	1958	~~65~~ 55,000	0.09	Diatomite added, Isolated
110-U	7-1975	7-1975	5,000-6,000	0.04-0.05	Salt well pumping
103-TY	5-1973	6-1973	3,000	0.66	Salt well pumping
105-TY	9-1960	9-1960	35,000	4	Isolated
106-TY	7-1959	8-1959	20,000	2	Diatomite added, Isolated
107-SX	3-1964	3-1964	Small	---	Sludge air cooling
108-SX	12-1962	12-1962	2,400	17	Sludge air cooling
109-SX	1-1965	2-1965	Small	---	Sludge air cooling
111-Sx	5-1974	5-1974	500-2,000	0.6-2.4	Sludge air cooling
112-SX	1-1969	Early 1969	30,000	45	Sludge air cooling
113-SX**	6-1958	11-1962	15,000	8	Diatomite added, Isolated
115-SX***	2-1965	3-1965	50,000	40	Sludge air cooling

* Contained water at the time of the leak.
** Contained $NaNO_3$ solution at the time of leak; also some redisual supernatant solution
*** Contained $NaNO_3$ solution at the time of leak.

9212556095 7

as possible is pumped from the tanks via salt wells reaching to the bottom of the tanks. The removal of liquid from a tank could be via a P-10 (called Phase I), a jet pump (called Phase II), or open-hold salt well pumping. The first two are used when the solids in the tank exceed two feet in depth. The open-hole salt well pumping is performed in tanks with less than two feed of solids. It is currently not possible to remove all gravity drainable liquid from a waste tank. The stabilization of a tank is limited by the physical configuration of the waste tank, the physical and chemical characteristics of the solids and liquids, and the limitations of equipment and technology.

Stabilization is the effort to remove the remaining liquid from single-shell storage tanks once they become inactive. The Waste Concentration Program includes two phases of stabilization:

1. Primary stabilization, and
2. Interim stabilization

Primary stabilization is the condition of an inactive waste storage tank after all liquid above the solids (other than isolated surface pockets) has been removed. Primary stabilization is accomplished by either:

1. Use of a conventional vertical turbine pump in a salt well or open hole
2. Use of a low-volume submersible pump
3. *In situ* drying, or
4. Use of a jet pump in a salt well system

Interim stabilization is the condition of an inactive waste storage tank after all of the liquid which can be effectively removed by use of a salt well with a jet pump has been removed. Tanks not requiring salt wells and jet pumps will be interim stabilized by other methods that are to be defined through technology development for each specific tank. As a minimum, tanks not using

9 2 1 2 5 5 6 0 9 5 8

jet pumps can be considered interim stabilized if:

1. All liquid above solids has been removed, including isolated pockets of liquid, and
2. The total liquid volume is less than those interim stabilized using a jet pump. Methods include air drying, other *in situ* drying methods, or dessicant addition.

Interim isolation will be performed on all single-shell storage tanks. A facility will be considered interim isolated when all accesses, not required for long-term surveillance, have been sealed in a way that provides at least one barrier from inadvertent addition of liquid. Methods of isolation must allow for re-entry, if required, for further stabilization and/or retrieval efforts. Partial interim isolation will be performed on selected facilities prior to and durring stabilization. Partial interim isolation includes sealing of all accesses not required for further stabilization efforts.

Table 4 shows the status of the salt well pumping program as of December 31, 1977. It should also be noted that the first Phase I pump was placed into service in the 116-TX tank in February of 1972. The first Phase II pump was installed in 107-BY on November 21, 1975.

9212556095 9

TABLE 4

Salt Well Liquid Recovery

Performance Summary

(~~Report Date~~ As of 12/31/77)

(Values are in K gallons)

FARM	Total Pumped	Volume Solids	Volume Salt Cake	Vol. Drain. Int. Liq.	Drain. Liq. Remaining
A	54	306	184	55	54
AX	0	642	624	187	187
AY	300	52	0	0	0
AZ	2	30	0	0	0
B	226	2,122	627	188	105
BX	16	1,586	203	60	60
BY	617	5,764	4,857	1,457	1,032
C	249	2,079	0	0	0
S	322	5,382	4,205	1,261	1,071
SX	0	4,441	2,894	868	866
SY	374	135	135	40	40
T	534	2,306	0	0	0
TX	807	7,454	7,236	2,170	1,498
TY	86	785	0	0	0
U	30	2,544	1,917	575	571
Total	3,617	35,628	22,882	6,861	5,484

9 2 1 2 5 6 1 9 6 0

TABLE 5

VOLUME AND SOURCE OF TANK FARM WASTE

Year	Production Source	Tons U Processed	Gallons Generated
1944	T Plant	9	139,000
1945	T and B Plants	636	5,656,000
1946	T and B Plants	864	9,404,000
1947	T and B Plants	651	5,900,000
1948	T and B Plants	786	6,341,000
1949	T and B Plants	749	8,152,000
1950	T and B Plants	884	7,962,000
1951	T and B Plants	1,068	11,864,000
1952	T, B and Redox Plants	1,237	11,001,000
1953	T and Redox Plants	1,677	8,211,000
1954	T and Redox Plants	2,598	14,122,000
1955	T and Redox Plants	3,692	19,930,000
1956	T, Redox and Purex Plants	4,890	16,191,000
1957	Redox and Purex Plants	6,226	6,582,000
1958	Redox and Purex Plants	6,462	3,321,000
1959	Redox and Purex Plants	6,025	2,850,000
1960	Redox and Purex Plants	7,004	2,891,000
1961	Redox and Purex Plants	7,292	3,644,000
1962	Redox and Purex Plants	7,028	3,127,000
1963	Redox and Purex Plants	6,718	4,081,000
1964	Redox and Purex Plants	7,552	4,508,000
1965	Redox and Purex Plants	7,488	4,698,000
1966	Redox and Purex Plants	6,114	4,819,000
1967	Purex and Other Plants	4,890	2,954,000
1968	Purex and Other Plants	4,195	8,896,000
1969	Purex and Other Plants	3,069	11,175,000
1970	Purex and Other Plants	1,128	9,567,000
1971	Purex and Other Plants	3,610	9,420,000
1972	Purex and Other Plants	1,089	8,401,000
1973	Other Plants	---	4,013,000
1974	Other Plants	---	6,883,000
1975	Other Plants	---	5,623,000
1976	Other Plants	---	4,939,000
1977	Other Plants	---	7,785,000
	TOTAL	105,629	245,050,000

9 2 1 2 5 5 6 0 9 6 1

TABLE 6

VOLUME REDUCTION EFFORTS IN THE TANK FARMS

Year	Source	Crib	Gallons	Total Volume Reduction
1944	---	---	---	---
1945	---	---	---	---
1946	---	---	---	---
1947	2nd Cycle	T-7	530,000	530,000
1948	2nd Cycle	B-8	857,000	2,061,000
	"	T-7	1,204,000	
1949	2nd Cycle	B-8	767,000	1,986,000
	"	T-7	1,219,000	
1950	2nd Cycle	B-8	991,000	2,307,000
	"	T-7	1,316,000	
1951	2nd Cycle	B-8	1,094,000	4,589,000
	"	T-7	1,738,000	
	242-T	T-19	1,757,000	
1952	2nd Cycle	B-8	254,000	7,778,000
	"	T-7	915,000	
	242-B	B-11	3,465,000	
	242-T	T-19	3,144,000	
1953	2nd Cycle	T-7	663,000	4,905,000
	1st Cycle	B-39	206,000	
	"	T-18	264,000	
	242-B	B-7	1,941,000	
	242-T	T-19	1,831,000	
1954	2nd Cycle	T-7	1,646,000	12,623,000
	242-B	B-7	1,771,000	
	242-T	T-19	1,392,000	
	1st Cycle and TBP	B-35	280,000	
	" "	B-36	513,000	
	" "	B-37	1,141,000	
	" "	B-38	378,000	
	" "	B-39	201,000	
	" "	B-40	433,000	
	" "	B-41	380,000	
	" "	B-43	560,000	
	" "	B-44	814,000	
	First Cycle	T-14	264,000	
	"	T-15	264,000	
	"	T-16	264,000	
	"	T-17	207,000	
	"	T-21	122,000	
	"	T-22	404,000	
	"	T-23	391,000	
	"	T-24	404,000	
	"	T-25	793,000	

9 2 1 2 5 5 6 0 9 6 2

2c

TABLE 6 - Continued

Year	Source	Crib	Gallons	Total Volume Reduction
1955	2nd Cycle	T-7 and T-19	2,045,000	13,178,000
	242-T	T-19	1,057,000	
	1st Cycle & Scav TBP	T-26	2,114,000	
	" "	B-42	396,000	
	" "	B-44	666,000	
	" "	B-45	1,300,000	
	" "	B-46	1,770,000	
	" "	B-47	980,000	
	" "	B-48	1,081,000	
	" "	B-49	1,770,000	
1956	Scav TBP	T-26	1,057,000	17,293,000
	2nd Cycle	T-19	73,000	
	1st Cycle & Scav TBP	B-14	2,301,000	
	" "	B-15	1,184,000	
	" "	B-16	1,480,000	
	" "	B-17	901,000	
	" "	B-18	2,251,000	
	" "	B-20	1,236,000	
	" "	B-21	1,234,000	
	" "	B-22	1,252,000	
	" "	B-23	1,194,000	
	" "	B-24	1,242,000	
	" "	B-25	993,000	
	104-U	~~B-27~~ Leak	840,000 55,000	
1957	Scav TBP	B-15	486,000	14,103,000
	"	B-19	1,691,000	
	"	B-26	713,000	
	"	B-27	1,168,000	
	"	B-28	1,334,000	
	"	B-29	1,279,000	
	"	B-30	1,263,000	
	"	B-31	1,252,000	
	"	B-32	1,260,000	
	"	B-33	1,252,000	
	"	B-34	1,287,000	
	"	B-52	1,118,000	
1958	Scav TBP	B-52	1,139,000	1,154,000
	113-SX	Leak	15,000	
1959	106-TY	Leak	20,000	50,000
	101-U	Leak	30,000	
1960	105-TY	Leak	35,000	35,000
1961	---	---	---	---
1962	108-TX	Leak	2,000	2,000
1963	105-A	Leak	Small	---
1964	107-SX	Leak	Small	---
1965	ITS #1	B-50	1,557,000	1,981,000
	242-T	T-19	374,000	
	115-TX	Leak	50,000	
	109-SX	Leak	Small	

9212556096 3

TABLE 6 - Continued

Year	Source	Crib	Gallons	Total Volume Reduction
1966	ITS #1	B-50	1,227,000	3,321,000
	242-T	T-19	2,094,000	
1967	ITS #1	B-50	2,437,000	6,434,000
	242-T	T-19	1,881,000	
	Redox	S-9	1,194,000	
	B Plant	B-12	922,000	
1968	ITS #1	B-50	1,806,000	11,556,000
	ITS #2	B-57	3,288,000	
	242-T	T-19	2,526,000	
	Redox	S-9	3,673,000	
	B Plant	B-12	263,000	
1969	ITS #1	B-50	1,920,000	14,442,000
	ITS #2	B-57	5,293,000	
	242-T	T-19	3,906,000	
	Redox	S-9	3,293,000	
	112-SX	Leak	30,000	
	103-BY	Leak	Small	
1970	ITS #1	B-50	1,829,000	11,887,000
	ITS #2	B-57	5,107,000	
	242-T	T-19	3,147,000	
	Redox	S-9	1,734,000	
	102-BX	Leak	70,000	
1971	ITS #1	B-50	1,100,000	9,901,000
	ITS #2	B-57	1,607,000	
	ITS #1&2	B-50	2,102,000	
	242-T	T-19	3,718,000	
	Redox	S-9	1,374,000	
	108-BY	Leak	Small	
1972	ITS #1&2	B-50	4,393,000	8,665,000
	242-T	T-19	3,147,000	
	Redox	S-9	1,125,000	
1973	242-S	S-25	1,412,000	4,059,000
	ITS #1&2	B-50	1,529,000	
	242-T	T-19	998,000	
	108-BX	Leak	2,000	
	106-T	Leak	115,000	
	103-TY	Leak	3,000	
1974	242-S	S-25	13,690,000	14,970,000
	ITS #1&2	B-50	59,000	
	242-T	T-19	1,220,000	
	111-SX	Leak	1,000	
1975	242-S	S-25	8,739,000	9,876,000
	242-T	T-19	1,130,000	
	110-U	Leak	6,000	
	104-A	Leak	1,000	
1976	242-S	S-25	6,722,000	7,052,000
	242-T	T-19	330,000	
1977	242-S	S-25	3,508,000	10,331,000
	242-A	A-37	6,823,000	
	TOTAL			197,069,000

9 2 1 2 5 5 6 0 9 6 4

TABLE 7

TANK FARM INVENTORIES

Year	Supernatant	Solid	Total
1944	---	---	139,000
1945	---	---	5,795,000
1946	---	---	15,199,000
1947	---	---	20,569,000
1948	---	---	24,848,000
1949	---	---	31,014,000
1950	---	---	36,670,000
1951	---	---	43,946,000
1952	---	---	47,168,000
1953	44,607,000	5,866,000	50,473,000
1954	44,304,000	7,668,000	51,972,000
1955	49,960,000	8,764,000	58,724,000
1956	48,213,000	9,409,000	57,622,000
1957	39,298,000	10,803,000	50,101,000
1958	41,348,000	10,920,000	52,268,000
1959	44,311,000	10,757,000	55,068,000
1960	47,165,000	10,759,000	57,924,000
1961	50,825,000	10,743,000	61,568,000
1962	53,969,000	10,724,000	64,693,000
1963	57,805,000	10,969,000	68,774,000
1964	61,313,000	10,969,000	73,282,000
1965	62,271,000	13,728,000	75,999,000
1966	63,766,000	13,721,000	77,497,000
1967	58,763,000	15,264,000	74,017,000
1968	55,127,000	16,230,000	71,357,000
1969	51,398,000	16,692,000	68,090,000
1970	46,932,000	18,838,000	65,770,000
1971	43,795,000	21,494,000	65,289,000
1972	43,136,000	21,889,000	65,025,000
1973	42,604,000	22,375,000	64,979,000
1974	29,646,000	27,246,000	56,892,000
1975	23,439,000	29,200,000	52,639,000
1976	20,733,000	29,793,000	50,526,000
1977	12,352,000	35,628,000	47,980,000

9 2 1 2 5 5 6 0 9 6 5

Waste Status Summary of 101-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
30					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3- *					
4-					
1-1956	P	424	--	--	Stopped filling here on 3-21-56
2-	P	424	--	--	
3-	P	419	--	--	New electrode rdg.
4-	P	397	--	-	Less inventory due to vapor loss
1-1957	P	397	--	--	
2-	P	234	--	--	S.S. 234M to 106-C; rec'd 75M
3-	P	484	--	--	437M self conc rec'd 487M
4-	P	388	--	--	672M self conc rec'd 776M

* Dry well 10-01-05 drilled.

9 2 1 2 1 5 6 0 9 5 6

Waste Status Summary of 101-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Stroage	Remarks
1-1958	P	509	509	--	477M Self conc. 548M rec'd 616M water - boiled off
2-	P	564	564	--	97M Self conc. rec'd 133M
3-	P	509	509	--	177M self conc. rec'd 153M
4-	P	498	498	--	232M self conc. rec'd 221M
1-1959	P	500	500	--	283M self cond. rec'd 285M
2-	P	578	578	--	214M self cond. rec'd 296M
3-	P	694	694	--	104M self conc. rec'd 320M
4-	P	614	614	--	182M self conc. rec'd 102M
1-1960	P	674	674	--	179M self conc. 13M recirculatc for flush H_2O added
2-	P	719	719	--	Boiled off 11M rec'd 51M
3-	P	644	644	--	Boiled of 98M rec'd 113M
4-	P	697	697	--	Rec'd 150M 39M boil off
1-1961	P	930	930	--	Rec'd 819M - 6 months report
2-					
3-					
4-	P	910	910	--	6 Months report
1-1962	P	861	861	--	6 Months report
2-*					
3-					
4-	P	558	558	--	6 Months report
1-1963	P	825	825	--	6 months report - rec'd 378M carbonate
2-					
3-					6 months report - rec'd 364M carbonate
4-	P	857	857	--	
1-1964	P	754	754	--	Rec'd 146M carb. 6 months report
2-					
3-					
4-	P	880	880	--	Rec'd 408M carb. 6 months repor

* Dry wells 10-01-01, -03, -04, -06, -08, -10 and -11 drilled.

9212556096 7

Waste Status Summary of 101-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	880	808	72	Rec'd 151 M
2-					
3-	P	886	814	72	Rec'd 112 M
4-	P	668	596	72	Rec'd 4 M, 202 M to 103-C
1-1966	P	833	761	72	446 M to 103-C; 611 from 103-A
2-	P	905	833	72	Rec'd 31 M OWW
3-	P	905	833	72	Rec'd 70 M
4-	P	905	833	72	Rec'd 76 M OWW
1-1967	P	905	833	72	Rec'd 64 M OWW
2-	P	905	833	72	Rec'd 54 M OWW
3-	P	904	824	79	Rec'd 50 M OWW
4-	P	905	825	80	Rec'd 63 M OWW
1-1968	P	358	275	83	Tank equipped for boiling waste Rec'd 28 M OWW, 550 M to 105-A
2-	P	77	27	50	264 to 105-A; test sluicing to 102-A
3-	P	124	74	50	Rec'd 358 M from 103-A; 324 M to 102-A
4-	P	135	85	50	
1-1969	P	990	982	8	Sluicing to 102-A; AR Vault completed 3-25-69. Filled with H_2O for leak test
2-	Water	748	740	8	215 M to 104-A; Leak check satisfactory, water held in tank to maintain tank temperature for emergency use
3-	Water	333	330	3	Spare tank, 335 M H_2O to 104-A
4-	Water	173	162	11	Spare tank 133 M H_2O to 104-A
1-1970	P	462	451	11	Sluicing completed in March 196[illegible] 198 M from 104-AX; rec'd 108 M H_2O; due to increase sludge temp. 198,000 gal. to 104-AX & 198,000 gals H_2O added
2-	P	639	628	11	Rec'd 198 M from 104-SX and 84M H_2O
3-	P	531	520	11	Rec'd Purex supernatant from 104-AX in 1970
4-	P	483	472	11	36M from Purex

9 2 1 2 5 5 6 0 9 6 8

Waste Status Summary of 101-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	P	441	430	11	
2-	P	440	429	11	
3-	P	430	419	11	
4-	P	430	419	11	
1-1972	P	422	411	11	Sluicing completed March 1969 Rec'd Purex supernatant from 104 BX in 1970
2-	P	28	17	11	384M to 105-C
3-	P	32	21	11	35M to 002-AR
4-	P	33	17	16	
1-1973	P	302	17-269	16	257M from B Plant
2-	P-B	928	17-895	16	628M from B Plant
3-	P-B	934	17-901	16	Sluicing completed March 1969; 6M from B Plant
4-	P-B	900	19-865	16	101M from B Plant; 5M from Purex; 79M to 104-C
1-1974	P-B	968	19-933	16	74M from B Plant; 45M to 104-C
2	P-B	962	19-910	33	
3-	P-B	957	19-905	33	
4-	P-B	938	19-886	33	
1-1975	P-B	924	19-872	33	Sluicing completed in March 69
2-	P-B	432	9-390	11	485M to 104-C
3-	B	217	206	11	6M from B Plant; 276M from 102-A; 318M from 106-A 2M H_2O; 818M to 104-C
4-	Water	52	44	8	Sluicing
1-1976	Water	6	5	1	Sluicing; 172M from 106-A, 201M to 104-C
2-	Water	6	3	3	Sluicing completed March 1976
3-	Evap.	157	154	3	Space Low heat
4-	Evap.	930	927	3	Evap. Feed Dil
1-1977	Evap.	809	806	3	Salt receiver, slurry receiver
2-	Evap.	762	759	3	
3-	Resid.	968	883	85	
4-	Resid.	974	889	85	

9212556009969

Waste Status Summary of 101-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	877	500	377	
2-	DSSF	866	489	377	
3-	DSSF	468	91	377	New Photo 5/23/78
4-	DSSF	971	481	490	Solids Deter. Eval. (12/14/78)
1-1979	NCPLX	415	0	415	
2-	NCPLX	545	130	415	New Solids Level 3/31/
3-	NCPLX	938	523	415	New Photo 7/18/79
4-	NCPLX	344	11	333	New Solids Level (12/31/
1-1980	DSSF	435	102	333	
2-1980	CPLX	329	13	316	
3-1980	DSSF	530	214	316	
4-1980	DSSF	931	381	550	Inactive - New Solids Level 11/21/80, New Photo 11/19/80

9 2 1 2 3 5 6 0 9 7 0

Waste Status Summary of 102-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
3-					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3-					
4-					
1-1956	P	130	--	--	Waste routed here on 3/22/56
2-	P	505	--	--	
3-	P	495	--	--	New electrode rdg.
4-	P	463	--	--	
1-1957	P	457	--	--	Latest electrode rdg.
2-	P	374	--	--	77M pumped 106-C
3-	P	149	--	--	237M carb. wash rec'd 70M to 106-C, 292M to 103-C
4-	P	124	--	--	19M to 103-C

9 2 1 2 5 5 6 0 9 7 1

Waste Summary of 102-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	P	399	399	--	186M rec'd 19M water boiled off
2-	P	388	388	--	513M self conc. rec'd 591M
3-	P	465	465	--	371M self conc. rec'd 448M
4-	P	504	504	--	404M self conc. rec'd 435M 267M H_2O boiled off
1-1959	P	495	495	--	447M self conc. rec'd 438M
2-	P	602	602	--	310M self conc. rec'd 414M
3-	P	562	562	--	777M self conc. rec'd 320M
4-	P	689	689	--	973M self conc. rec'd 1100M
1-1960	P	671	671	--	821M self conc. rec'd 603M
2-	P	727	727	--	248M self conc. rec'd 591M
3-	P	800	800	--	453M self conc. rec'd 517M
4-	P	882	882	--	166M self conc. rec'd 375M 292M boil off
1-1961	P	806	806	--	Rec'd 331M - 6 months report
2-					
3-					
4-	P	888	888	--	Rec'd 120M - 6 months report
1-1962	P	847	847	--	6 months report
2-*					
3-					
4-	P	1015	1015	--	6 months report - rec'd 338M car
1-1963	P	965	965	--	6 months report - rec'd 221M car
2-					
3-					6 months report - rec'd 15M cart
4-	P	356	356	--	Supernatant to C-Farm
1-1964	P	787	787	--	Sluicing for sludge removal 6 months report
2-					
3-					
4-	P	930	930	--	Sluicing for sludge removal- 6 months report

* Dry wells drilled:
10-02-01
10-02-03
10-02-05
10-02-06
10-02-08
10-02-10
10-02-11

9 2 1 2 5 6 1 9 7 2

Waste Status Summary of 102-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	888	811	77	6 months report
2-					
3-	P	921	844	77	
4-	P	916	839	77	
1-1966	P	905	828	77	
2-	P	902	825	77	
3-	P	894	817	77	
4-	P	905	828	77	
1-1967	P	902	825	77	
2-	P	939	862	77	
3-	P	932	830	102	
4-	P	862	763	99	
1-1968	P	641	542	99	Equipped for boiling 135M to 103-A
2-	P	668	544	124	Rec'd sludge waste from 101-B
3-	P	465	338	127	459M to 103-A 324M from 101-A
4-	P	440	313	127	
1-1969	P	666	520	146	Rec'd sludge 101-A
2-	P	591	437	154	516M to 105-C; 524 from 106-A
3-	P	679	530	149	680 from 106-A
4-	P	710	561	149	738M from 103 & 106-A; 609M to 105-C
1-1970	P	415	277	138	171M to 105-C
2-	P	206	60	146	206M to 105-C
3-	P	205	59	146	
4-	P-PSS	335	22-179	154	194M from 106-C; 50 from 106-A
1-1971	P-PSS	193	9-30	154	81M from 417-TK, 194 to 106-C
2-	P-PSS	206	12-40	154	
3-	P-PSS	206	12-40	154	
4-	P-PSS	242	54-34	154	39M from 106-A

9212156197 3

Waste Status Summary of 102-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	P-PSS	246	56-36	154	
2-	P-PSS	256	62-40	154	
3-	PSS	175	21	154	
4	PSS	96	27	69	Sluicing
1-1973	---	39	0	39	
2-	water	30	15	15	Sluicing 19M to 103-A
3-	water	32	17	15	
4-	water	30	15	15	
1-1974	water	56	56	0	Sluicing completed Feb. 1974
2-	water	56	56	0	Sluicing completed Feb. 1974
3-	B	173	173	0	46M from B Plant, 27M from AR Vault Sluic. comp. 9-74
4-	B	652	635	17	104M from B Plant; 276M from 106-A, 29M from AR Vault
1-1975	B	839	822	17	147M from B Plant; 49M from AR Vault
2-	B	952	935	17	96M from B Plant; 17M from AR Vault
3-	B	690	673	17	Sluicing completed Sept. 1974
4-	B	690	673	17	
1-1976	B	72	71	1	Sluicing; 130M to 104-C; 6M H_2O; 338M to 103-A; 163M to 106-A
2-	water	39	37	2	Sluicing completed April 1976
3-	water	6	0	6	
4-	Evap. Feed	429	426	3	Evap. feed Dil
1-1977	Evap.	762	759	3	Evap. feed dil., feed & dump
2-	Evap.	762	759	3	
3-	Evap.	316	313	3	
4-	Evap.	385	379	6	

9212556097 4

Waste Status Summary of 102-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	EVAP.	407	399	8	
2-	NCPLX	789	772	17	
3-	NCPLX	143	132	11	Solids Deter. 9/14/78
4-	DSSF	897	880	17	New Photo 9/5/78
1-1979	CPLX	319	302	17	
2-	CPLX	138	121	17	New Photo 5/11/79
3-	CPLX	828	811	17	
4-	NCPLX	102	85	17	
1-1980	DSSF	470	453	17	
2-	NCPLX	228	211	17	
3-	NCPLX	417	400	17	
4-	DSSF	89	67	22	Inactive-New Solids Lev 11/21/80

9 2 1 2 5 6 1 9 7 5

Waste Status Summary of 103-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
3-					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3-					
4- *					
1-1956	--	--	--	--	
2-	P	171	--	--	S.S. rec'd 99M gals
3-	P	449	--	--	S.S. 34M self conc. S.S. 149M self conc.
4-	P	444	--	--	488 M Self Conc.
1-1957	P	369	--	--	S.S. 371M self conc. rec'd 322M plus 40M water
2-	P	470	--	--	S.S. 240M self conc.; rec'd 248M plus 64M water S.S. 75M self conc.; rec'd 149M
3-	P	481	--	--	20M self conc.; 735M added & boiled off
4-					129M self conc.; rec'd 92M carb. 236M water boil off

* Leak detection dry well 10-03-10 drilled.

9 2 1 2 5 6 1 9 7 6

Waste Status Summary of 103-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	P	473	473	--	108M self conc. 179M H_2O boiled off, 115M carb. H_2O
2-	P	462	462	--	108M self. conc. rec'd 97M
3-	P	481	481	--	174M self conc. rec'd 193M
4-	P	509	509	--	298M self conc. rec'd 373M
1-1959	P	548	548	--	212M self conc. rec'd 251M
2-	P	666	666	--	247M self conc. rec'd 263M
3-	P	562	562	--	169M self conc. rec'd 65M
4-	P	539	539	--	46M self conc. rec'd 0M
1-1960	P	473	473	--	66M self conc.
2-	P	526	526	--	rec'd 91M
3-	P	473	473	--	782M self conc. rec'd 325M
4-	P	490	490	--	2M self conc. rec'd 26M 51M boil off
1-1961	P	501	501	--	6 months report
2-					
3-					
4-	P	682	682	--	6 months report
1-1962	P	325	325	--	283M to 105-A - 6 months report
2-*					
3-					
4-	P	294	294	--	6 months report
1-1963	P	267	267	--	6 months report
2-					
3-					
4-	P	270	270	--	6 months report
1-1964	P	116	116	--	Sluicing for sludge removal 6 months report
2-					
3-					
4-**	P	110	110	--	Sluicing for sludge removal 6 months report

Leak detection dry wells drilled:

10-03-01 *
10-03-02 *
10-03-04 *
10-03-05 *
10-03-07 *
10-03-10 *
10-03-11 **

9212569977

Waste Status Summary of 103-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	80	80	--	6 months report, rec'd 262M from CR, 491M to 101-AX Back up tank in event of tank failure
2-					
3-	P	80	80	--	
4-	P	525	525	--	435M from 103-C, back up tank
1-1966	P	140	140	0	141M from 103-C; 61M OWW; 611M to 101-A
2-	P	74	74	0	Rec'd 76M OWW; 66M to 101-AX
3-	P	72	72	0	
4-	P	55	55	0	Sluicing
1-1967	P	55	55	0	
2-	P	33	33	0	Rec'd 62M OWW; 84M to 102-AX
3-	P	30	30	0	
4-	P	54	32	22	
1-1968	P	476	415	61	Equipped for boiling waste Rec'd 481M 105-A; rec'd 135M from 102-A; 553M of Tank 105-A, heel dilutions; 778M to 102-AX
2-	P	465	413	52	549M from 105-A; 560 to 102-A
3-	P	803	701	102	358M to 101-A; rec'd 459M from 102-A
4-	P	741	639	102	
1-1969	P	690	588	102	
2-	P	641	550	91	
3-	P	617	496	121	
4-	P	160	58	102	410M to 102-A
1-1970	P-IX	594	58-434	102	rec'd 377M from 104 BY & 63M H_2O; IX waste due to high salt & low cesium content, will be used to sluice 105-A
2-	P-IX	637	58-477	102	H_2O added to adjust liquid level
3-	P-IX	635	58-475	102	
4-	P-IX	622	45-475	102	Receiving sludge from 105-A
1-1971	P-IX	620	45-473	102	
2-	P-IX	649	48-499	102	
3-	P-IX	630	46-482	102	
4-	P-IX	660	48-510	102	7 from 105-A

9212556097 8

Waste Status Summary of 103-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972-	P-IX	661	48-511	102	
2-	P-IX	346	21-223	102	302M to 105-C
3-	P-IX	358	22-234	102	
4-	P-IX	333	20-211	102	525M from AR Vault, 134 from B Plant, 567 to 104-AX
1-1973	P-IX	349	21-226	102	
2-	P-IX	352	21-229	102	19M from 102-A
3-	P-IX	336	20-214	102	
4-	P-IX	392	25-265	102	71M from B Plant
1-1974	water	227	125	102	244M to 104-A; sluicing
2-	water	41	19	22	Sluicing
3-	water	50	50	0	Sluicing, 347 from AR Vault
4-	water	55	41	14	Sluicing completed 9-74, 266M from AR vault
1-1975	water	28	14	14	
2-	water	212	216	6	128M from 101-AX ; 46M from 104-A; 29M from AR Vault
3-	PSS-B	231	38-179	14	Sluicing completed Sept. '7
4-	PSS-B	481	147-320	14	141M from B Plant; 118M from AR Vault; 2 from C.T. 151-AX
1-1976	PSS-B	974	147-821	6	Sluicing completed 9-74 338M from 102-A
2-	PSS-B	36	3-17	16	920M to 104-C; 13M to 106-A
3-	Evap.	102	85	17	In Farm sluicing
4-	Evap.	3	0	3	Sluicing
1-1977	Evap.	487	484	3	Evap. feed dil., Evap. feed storage.
2	Evap.	102	99	3	
3	Resid.	520	415	105	Resid. liquor, slurry receiv
4	Resid.	641	536	105	

9212556097 9

Waste Status Summary of 103-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	795	589	206	New Photo 1/27/78
2-	DSSF	800	525	275	New Solids Level 4/12/7
3-	DSSF	437	162	275	Solids Level Taken 9/14/78. New Photo 9/5/78
4-	NCPLX	836	533	303	Cross Site Recvr. New Solids Level Adj. 12/14/78
1-1979	NCPLX	470	167	303	
2-	DSSF	638	335	303	
3-	CPLX	644	341	303	
4-	CPLX	627	324	303	New Photo 12/3/79
1-	DSSF	542	239	303	
2-	DSSF	879	576	303	Complexed Slurry
3-	DSSF	532	33	499	Inactive-New Solids Level 8/14/80
4-	DSSF	516	17	499	

9212156190

Waste Status Summary of 104-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
3-					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3- *					
4-					
1-1956	--	--	--	--	--
2-	--	--	--	--	--
3-	--	--	--	--	--
4-	--	--	--	--	--
1-1957	--	--	--	--	--
2-	P	17	--	--	Test water 373M water
3-	P	22	--	--	Test water
4-	P	17	--	--	Test Water

* Leak detection dry well 10-04-04 drilled.

9 2 1 2 5 5 6 0 9 8 1

Waste Status Summary of 104-A Tank-Capacity 1,000,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	P	22	22	0	Test water
2-	P	28	28	0	Test water
3-	P	168	168	0	20M rec'd latest electrode rdg.
4-	P	138	138	0	Latest electrode rdg.
1-1959	P	187	187	0	S.S 38M H_2O; S.S. rec'd 5M; latest electrode rdg.
2-	P	204	204	0	Latest electrode rdg.
3-	P	366	366	0	87M Self conc. rec'd 164M dilute H_2O added
4-	P	369	369	0	222M self conc. rec'd 264M
1-1960	P	743	743	0	140M self conc. rec'd 744M
2-	P	750	750	0	1,181M self conc. rec'd 956M
3-	P	655	655	0	842M self conc. rec'd 1,094M
4-	P	725	725	0	963M self conc. rec'd 1,033M
1-1961	P	842	842	0	Rec'd 1,967M 6 months report
2-*					
3-					
4-	P	886	886	0	Rec'd 157M 6 months report
1-1962	P	952	952	0	Rec'd 1,213M carbonate waste 6 months report
2-					
3-					6 months report
4-	P	682	682	0	Rec'd 628M carbonate
1-1963	P	795	795	0	6 months report
2-					Rec'd 310M carbonate
3-					6 months report
4-	P	824	824	0	Rec'd 438M carbonate
1-1964	P	831	831	0	Rec'd 591M carbonate
2-					6 months report
3-					
4-	P	864	864	0	Rec'd 285M carbonate 6 month report

* Leak detection dry wells drilled;
10-04-01
10-04-05
10-04-07
10-04-08
10-04-10
10-04-11

9212 5 6 1 9 8 2

Waste Status Summary of 104-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	919	773	146	6 months report
2-					rec'd 149M OWW
3-	P	938	792	146	Rec'd 41M OWW
3-	P	932	786	146	Rec'd 72M OWW
1-1966	P	932	786	146	Rec'd 114M OWW
2-	P	941	795	146	Rec'd 55M OWW
3-	P	932	786	146	Rec'd 93M
4-	P	935	789	146	Rec'd 94M OWW
1-1967	P	932	786	146	Rec'd 97M OWW
2-	P	935	789	146	Rec'd 97M OWW
3-	P	924	759	165	Rec'd 119M OWW
4-	P	924	756	168	Rec'd 66M OWW
1-1968	P	927	745	182	Rec'd 106M OWW, Tank equipped for boiling waste
2-	P	971	800	171	
3-	P	976	811	165	
4-	P	983	812	171	
1-1969	P	428	257	171	481M to 105-C
2-	P	308	234	74	188M to 105-C; sluicing started 5-12-69, 1/2 of sludge was sluiced to 160A--215,000 gal. hot water added to soften remaining sludge
3-	P	28	17	11	Sluicing in process
4-	water	960	957	3	Sluicing comp. Oct.; leak check comfirmed the integrity of 104-A & declared a spare
1-1970	water	957	956	1	Spare
2-	water	964	963	1	
3-	water	861	860	1	
4-	water	743	742	1	
1-1971	water	627	626	1	Sluicing comp. Oct. 1969
2-	water	561	560	1	
3-	water	454	453	1	
4-	water	349	348	1	

9212556098 3

Waste Status Summary of 104-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	water	198	197	1	Sluicing completed Oct. 1969 62M to 102-AY
2-	water	275	274	1	Sluicing completed Oct. 1969 60M to 102-AY
3-	water	346	338	8	
4-	B	440	432	8	
1-1973	PSS	773	693	80	358M from AR Vault 276M to 104-AX
2-	PSS	956	876	80	Sluicing completed Oct. 1969 705M from AR Vault; 525M to 101-AX
3-	PSS	912	832	80	
4-	PSS	837	757	80	
1-1974	PSS	503	423	80	23M from 106-A; 244M from 103-A; 643M to 101-AX, 61M from AR vault
2-	PSS	806	726	80	338M from AR Vault
3-	PSS	96	39	57	Sluicing; 96M from AR vault; 46M to 101-AX; 47M to 102-AX; 446M to 104-AX
4-	PSS	55	16	39	sluicing; 545M from AR vault
1-1975	PSS	69	30	39	Sluicing, 264M from AR vault
2-	---	25	0	25	Tanks leaks; 46M to 103-A
3-	---	25	0	25	Tanks leaks;
4-	---	25	0	25	Tanks leaks
1-1976	---	25	0	25	
2-	---	25	0	25	
3-	---	25	0	25	
4-	---	25	0	25	
1-1977	---	25	0	25	Tank leaks
2-	---	25	0	25	Stabilized
3-	---	25	0	25	Stabilized Phase I
4-	---	25	0	25	

9 2 1 2 5 5 6 0 9 8 4

Waste Status Summary of 104-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978		28	0	28	New Sludge Level 1/27/78 Primary Stabilized
2-		28	0	28	
3-		28	0	28	Interim Stabilized
4-		28	0	28	
1-1979		28	0	28	
2-		28	0	28	
3-		28	0	28	
4-		28	0	28	
1-1980		28	0	28	
2-		28	0	28	
3-		28	0	28	
4-		28	0	28	

9212560985

Waste Status Summary of 105-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
3-					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3-					
4-					
1-1956	--	--	--	--	--
2-	--	--	--	--	--
3-	--	--	--	--	--
4-	--	--	--	--	--
1-1957	--	--	--	--	
2-	--	17	--	--	Test water
3-	--	22	--	--	Test water
4-	--	17	--	17	Test water

9212.5619935

Waste Status Summary of 105-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	P	22	22	--	Test Water
2-	P	25	25	--	Test Water
3-	P	30	30	--	Test Water
4-	P	30	30	--	Test Water
1-1959	P	30	30	--	Test Water
2-	P	30	30	--	Test Water
3-	P	30	30	--	Test Water
4-	P	30	30	--	Test Water
1-1960	P	30	30	--	Test Water
2-	P	41	41	--	Latest electrode rdg.
3-	P	47	47	--	Latest electrode rdg.
4-	P	50	50	--	Latest electrode rdg.
1-1961	P	50	50	50	6 months report
2-					
3-					
4-	P	50	50	50	6 months report
1-1962	P	333	333	--	283M 103-A
2-					6 months report
3- *					
4-	P	699	699	--	6 months report
1-1963	P	740	740	--	6 months report
2-					Rec'd 680M IWW; 473M to 103-C
3-					6 months report
4-	P	711	711	--	Rec'd 685M IWW
1-1964	P	715	715	--	Rec'd 763M IWW
2-					6 months report
3-					Rec'd 635M IWW
4-	P	853	853	--	6 months report

* Leak detection dry wells drilled:

10-05-02
10-05-05
10-05-07
10-05-08
10-05-09
10-05-10
10-05-12

9 2 1 2 5 5 6 0 9 3 7

Waste Status Summary of 105-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	866	794	72	6 months report
2-					rec'd 452M cell drainage & flushes
3-	P	864	792	72	
4-	P	858	786	72	
1-1966	P	850	778	72	
2-	P	858	786	72	
3-	P	861	789	72	
4-	P	869	797	72	
1-1967	P	864	792	72	
2-	P	855	792	72	
3-	P	872	762	110	
4-	P	887	777	110	Suspected leaker
1-1968	P	385	205	180	Tank leaks--supernatant remo
2-	P	396	314	82	" " C's diluted from heel; supernatant diluted wi 264M from 101-A & with 287M cesium depleted supernatant waste, 549 transferred to 10
3-	P	77	44	33	Sluicing on Aug. 15
4-	P	88	55	33	Tank leaks--sluicing.
1-1969	P	85	52	33	
2-	P	89	37	52	
3-	P	94	31	63	
4-	P	66	33	33	
1-1970	P	66	33	33	Tank leaks
2-	P	66	33	33	" "
3-	P-IX	66	4-29	33	" " Removal of sludge heel Aug. 25, 1970
4-	P-IX	66	4-29	33	Tank Leaks, Removal of sludg heel Aug. 25, 1970
1-1971	P-IX	89	4-52	33	Tank leaks, no sluicing act.
2-	P-IX	94	4-57	33	
3-	P-IX	87	3-51	33	
4-	IX	37	4	33	7M to 103-A

9212556098 8

Waste Status Summary of 105-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	IX	50	17	33	Tank leaks; no sluicing act.
2-	IX	50	17	33	
3-	IX	47	14	33	
4-	IX	44	11	33	
1-1973	IX	44	11	33	Tank leaks; no sluicing act.
2-	IX	43	10	33	
3-	IX	36	3	33	
4-	IX	50	17	33	
1-1974	IX	50	17	33	Tank leaks no sluicing act
2-	IX	50	17	33	
3-	IX	50	17	33	
4-	IX	52	19	33	
1-1975	IX	52	19	33	Tank leaks; no sluicing act.
2-	IX	52	19	33	
3-	IX	52	19	33	
4-	IX	50	17	33	
1-1976	IX	50	17	33	Tank leaks; no sluicing act.
2-	IX	50	17	33	
3-	---	50	17	33	
4-	---	47	14	33	
1-1977	---	50	17	33	
2-	---	47	14	33	
3-	---	47	14	33	
4-	---	50	17	33	Eval. stero photo

9212556098 9

Waste Status Summary of 105-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	EVAP.	50	17	33	New Photo on 1/30/78
2-	NCPLX	41	8	33	
3-	NCPLX	44	11	33	
4-	NCPLX	39	6	33	
1-1979	NCPLX	39	6	33	
2-	NCPLX	39	6	33	
3-	NCPLX	19	0	19	Interim Stabilized
4-	-	19	0	19	New Photo 6/21/79 New Solids Level 8/23/79
1-1980	-	19	0	19	
2-	-	19	0	19	
3-	-	19	0	19	
4-	-	19	0	19	

9 2 1 2 7 6 0 9 9 0

Waste Status Summary of 106-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	P	234	234	--	Condensate from boiling tanks
2-	P	239	239	--	191M to 101-A Concensate collect
3-	P	245	245	--	Condensate collector
4-	P	278	278	--	Rec'd 33M Flushwater condensate collector
1-1959	P	295	295	--	Condensate collector
2-	P	314	314	--	Condensate collector
3-	P	342	342	--	Condensate collector
4-	P	380	380	--	Condensate collector
1-1960	P	416	416	--	Condensate collector
2-	P	440	440	--	Condensate collector
3-	P	449	449	--	Rec'd 9M flush H_2O from diversion box
4-	P	485	485	--	Rec'd 33M Latest electrode rdg.
1-1961	P	380	380	--	6 Months report
2- *					
3-					
4-	P	715	715	--	Rec'd 1059M - 6 months report
1-1962	P	699	699	--	Rec'd 1370M - 6 months report
2-					
3-					6 Months report
4-	P	883	883	--	Rec'd 1088M IWW; 210M carbonate
1-1963	P	924	924	--	6 Months report
2-					Rec'd 152M IWW
3-					6 Months report
4-	P	915	915	--	Rec'd 327M carbonate
1-1964	P	916	916	--	Rec'd 47M carbonate
2-					6 months report
3-					Rec'd 379M carbonate
4-	P	811	811	--	6 months report

* Leak detection dry wells drilled:

10-06-02
10-06-04
10-06-05
10-06-07
10-06-09
10-06-10
10-06-12

9212556099 1

Waste Status Summary of 106-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-					
3-					
4-					
1-1953					
2-					
3-					
4-					
1-1954					
2-					
3-					
4-					
1-1955					
2-					
3-					
4-					
1-1956	--	--	--	--	--
2-	--	--	--	--	--
3-	--	--	--	--	--
4-	--	--	--	--	--
1-1957	P	88	--	--	De-entrained water
2-	P	94	--	--	De-entrained water
3-	P	124	--	--	De-entrained water
4-	P	184	--	--	Condensate from 101-A & 103-A

9 2 1 2 5 5 6 0 9 9 2

Waste Status Summary of 106-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	875	757	118	6 months report
2-					rec'd 389M OWW
3-	P	880	762	118	Rec'd 221M OWW
4-	P	880	762	118	Rec'd 146M OWW
1-1966	P	877	759	118	Rec'd 138M OWW
2-	P	877	759	118	Rec'd 104M OWW
3-	P	877	759	118	Rec'd 137M
4-	P	880	762	118	Rec'd 122M OWW
1-1967	P	864	746	118	Rec'd 74M OWW
2-	P	870	752	118	Rec'd 98M OWW
3-	P	861	721	140	Rec'd 114M OWW
4-	P	861	685	176	Rec'd 107M OWW
1-1968	P	894	721	173	Tank equipped for boiling waste rec'd 135M OWW
2-	P	936	765	171	Rec'd 20M OWW
3-	P	935	767	168	
4-	P	936	760	176	
1-1969	P	935	760	175	
2-	P	572	345	227	524M to 102-A; rec'd sludge from 104-A; PSN transferred to 105-C following ion exchange processing PSN from 104-A
3-	P	600	346	254	700M from 104-A; 680M to 102- rec'd sludge from 104-A; includes hot water soaks of 104-A sludge
4-	P	263	29	234	328M to 102-A; supernatant removed to prepare for sluic ing
1-1970	P	252	57	195	Sluicing to AR vault was started 2-17-70
2-	P	245	60	185	
3-	P	249	86	163	
4-	P	154	30	124	
1-1971	P	139	41	98	Sluicing to AR Vault
2-	P	142	44	98	No Sluicing activity
3-	P	151	53	98	
4-	P	122	24	98	39M to 102-A, 99M to AR Vaul

9212556099 3

Waste Status Summary of 106-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	P	96	0	96	
2-	P	70	51	19	Sluicing comp. June 1972
3-	P	107	85	22	
4-	P	66	55	11	
1-1973	P	99	88	11	Sluicing comp. June 1972
2-	P	51	40	11	
3-	P	69	58	11	
4-	water	48	42	6	
1-1974	B	206	206	0	138M from B Plant, 23M to 104
2-	B	686	686	0	387M from B Plant, 7M from AR VAult
3-	B	987	975	12	Sluicing comp. in Jan. 1974, 407M from B Plant, 11M from AR Vault
4-	B	751	740	11	276M to 102-A
1-1975	B	814	803	11	
2-	B	842	831	11	7M from 302-B, 9M from A08 174M to 103-A
3-	B	663	652	11	Sluicing comp. Jan. 1974; 53M from B Plant, 90M from AR vault, 2M H_2O; 168M from 103-A; 318 to 101-A
4-	B	817	806	11	Pumping to & receiving from 101-A for sluicing
1-1976	B	820	729	91	Pumping to & receiving from 101-A for sluicing 172 M to 101-A
2-	B	872	781	91	13M from 103-A
3-	Evap	822	822	91	In farm sluicing
4-	Evap	979	877	102	
1-1977	Evap	949	847	102	Sluice mixed
2-	Evap	561	459	102	
3-	Evap	129	49	80	Being sluiced, sluice mix'd sludge
4-	Evap	116	64	52	

9212556099 4

Waste Status Summary of 106-A Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	EVAP.	162	110	52	
2-	NCPLX	83	33	50	New Solids Level 4/30/78 - New Photo 2/22/78
3-	NCPLX	72	22	50	Sluice Mxd. Sludge
4-	NCPLX	72	22	50	
1-1979	NCPLX	127	77	50	
2-	NCPLX	140	90	50	New Photo 5/15/79
3-	NCPLX	140	90	50	
4-	CCPLX	657	607	50	
1-1980	CCPLX	663	613	50	
2-1980	CCPLX	665	569	96	New Solids Level 8/23/79
3-1980	CCPLX	128	34	94	Inactive - New Solids Level 8/14/80 - New Photo 8/6/80.
4-1980	CCW	128	34	94	

9212556099 5

Waste Status Summary of 101-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	NCPLX	9	9	0	In service 7-30-80
4-	NCPLX	9	9	0	

9212561996

Waste Status Summary of 102-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	NCPLX	19	19	0	In service 7-30-80
4-	NCPLX	30	30	0	

9212160997

Waste Status Summary of 103-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	DSSF	10	10	0	In service 7-30-80
4-	DSSF	959	0	959	

9212156799 8

Waste Status Summary of 104-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	NCPLX	9	9	0	In service 7-30-81
4-	NCPLX	0	0	0	

9212156799

Waste Status Summary of 105-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	CCPLX	946	946	-	In service 7-30-80
4-	CCPLX	939	939	-	

9212561000

Waste Status Summary of 106-AW Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1980	-	-	-	-	Under Construction
2-	-	-	-	-	" "
3-	CPLX	54	54	0	In service 7-30-81
4-	CCW	538	538	0	

9212356101

Waste Status Summary of 101-AXTank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P-OWW-FP	847	491-93-263	--	6 months report, rec'd 491M from 103-A; 93M OWW and 263M FP
2-					
3-	FP	646	646	--	138M from 112-B; 339M to 103-
4-	FP	459	459	--	207M from 112-B; 394M to 103-
1-1966	FP	490	490	--	
2-	FP	820	820	--	Rec'd 433M from 103-A; 101AX & OWW
3-	FP	990	990	--	Rec'd 170M
4-	FP	682	682	--	Equipped with steam coil, rec' 27M OWW; 68M boiled off
1-1967	FP	674	674	--	Rec'd 455M boiled off 463M
2-	P	672	672	--	Rec'd 470M; boiled off 472M
3-	P-OWW	666	666	--	Rec'd 491M OWW: Boiled off 49
4-	P	743	743	--	Rec'd 149M OWW; boiled off 31
1-1968	B	839	839	--	Rec'd 384M from cell 25, B Plant--receiving B Plant waste--equpped for boiling waste
2-	B	839	839	--	Rec'd 40MF-16, 62M F-18, 823B
3-	B	831	831	--	156 from 202-A' 557 from 221-
4-	B	833	792	41	84M from Purex (F-18 & R 8)
1-1969	B	985	946	39	294M from 221-B; 84 from 202- removed from service as prima boiling waste receiver
2-	B	985	960	25	3M from Purex
3-	B	990	964	26	
4-	B	985	955	30	
1-1970	B	976	935	41	
2-	B	987	918	69	
3-	B	985	916	69	
4-	B	989	920	69	
1-1971	B	985	929	56	
2-	B	990	934	56	
3-	B	990	934	56	
4-	B	990	934	56	

9212556100 2

Waste Status Summary of 101-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	B	987	931	56	
2-	B	984	928	56	
3-	B	976	920	56	
4-	B	111	53	58	832M to 103-AX
1-1973	B	110	52	58	
2-	PSS	111	53	58	525M from 104-A; 510 to 103-A
3-	PSS	132	74	58	
4-	PSS	329	252	77	217M from 104-A
1-1974	PSS	796	719	77	643M from 104-A; 173M to 103-
2-	PSS	714	637	77	98M to 103-AX
3-	PSS	784	707	77	20 Water; 46M from 104-A
4- *	PSS	787	718	69	
1-1975 **	PSS	495	426	69	278M to 103-AX
2-	PSS	330	261	69	139M from 102-AX; 188M to 103-AX; 128M to 103-A
3-	water	74	13	61	Sluicing; 259M to AR vault
4-	water	80	20	45	
1-1976	water	28	20	8	
2-	water	8	4	4	Sluicing completed in Feb 76; 4M to 103-AX
3-	water	3	0	3	
4-	Evap	66	63	3	
1-1977	Evap	286	283	3	Salt & slurry receiver
2-	Resid.	960	776	184	Resid. liquor, slurry receive
3-	Resid.	954	376	578	
4-	Resid.	963	336	627	

* Leak detection dry wells installed:

11-01-01
11-01-02
11-01-09
11-01-11

** Leak detection dry wells installed

11-01-04
11-01-05
11-01-07

9212556100 3

Waste Status Summary of 101-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	DSSF	963	336	627	Active-HDRL
2-	DSSF	963	336	627	
3-	DSSF	723	96	627	Photo 9/5/78
4-	DSSF	723	96	627	
1-1979	DSSF	723	96	627	
2-	DSSF	723	96	627	
3-	DSSF	723	96	627	
4-	DSSF	627	0	627	
1-1980	NCPLX	616	16	600	New Photo 2/25/80
2-1980	CPLX	605	5	600	
3-1980	DSSF	831	542	289	Adjustment in Salt Cake due to pumping 101AX to 102-A
4-1980	DSSF	762	237	525	New Solids Level 11/3/80 Inactive

9212561004

Waste Status Summary of 102-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	MT	--	--	6 months report
2-					
3-	P	179	(water)	--	
4-	P	184	(water)	--	
1-1966	P	184	(water heel)	--	
2-	P	184	" "	--	
3-	P	330	330	--	Rec'd 108M OWW
4-	P	883	883	--	Rec'd 233M OWW; 295M from 101-AX
1-1967	P	578	578	--	305M to 101-AX
2-	P	359	359	--	Rec'd 47M OWW; 266M to 101-AX
3-	P	135	135	--	Rec'd 40M OWW; 360M to 101-AX
4-	P-OWW	594	594	--	
1-1968	P	648	648	--	Rec'd 469M OWW; rec'd 778M from Tk 105-A; 195M to 105-C as PSN feed for B Plant--back up tank
2-	P	964	964	--	257M to 105-C; 560 from 103-A
3-	P	704	704	--	255M to 105-C; contains supernatant heel dilu's from 105-A that currently is the I column feed
4-	P	294	280	14	410M to 105-C (spare)
1-1969	B	663	663	0	Flushed & preheated for service; 264M (plus flushes) to 105-C
2-	B	820	803	17	867M from B Plant; 43M from Purex; current high level waste receiver
3-	B	895	876	19	515M from B Plant; 33M from Purex current high level waste receiver
4-	B	858	848	10	998M from B Plant; current high level waste receiver
1-1970	B	880	868	12	568M from B Plant current high level waste receiver
2-	B	946	929	17	436M from B Plant, current high level waste receiver
3-	B	954	943	11	20M from B Plant, current high level waste receiver
4-	B	954	926	28	7M from B Plant, current high level waste receiver
1-1971	B	954	929	38	
2-	B	954	916	32	15 from AR vault
3-	B	963	925	38	
4-	B	960	922	38	

9212556100 5

Waste Status Summary of 102-AX Tank-Capacity 1000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	B	953	915	38	
2-	B	957	907	50	
3-	B	952	889	63	
4-	B	954	907	47	
1-1973	B	113	63	50	787M to 103-AX
2-	B	113	63	50	
3-	B	126	76	50	
4-	B	129	79	50	
1-1974	B	132	82	50	
2-	B	151	101	50	
3-	B	238	188	50	17 Water; 47M from 104-A
4-	B	314	264	50	
1-1975	B	349	299	50	
2- *	---	50	0	50	139M to 101-AX; 158M to 103-
3-	B	77	27	50	6 from B plant; 46M from 417 TK; 19M from AR Vault
4-	water	66	19	47	sluicing
1-1976	water	248	226	22	sluicing 140M from B Plant
2-	water	583	566	17	56M from B Plant sluicing
3-	Evap	767	750	17	B Plant Waste Recovery
4-	Evap	72	53	19	
1-1977	Evap.	11	0	11	Sr. sludge sluicing completec
2-	Evap.	6	0	6	
3-	Resid.	30	24	6	Resid. liquor, slurry receive
4-	Resid.	28	22	6	

* Leak detection dry wells installed:

10-02-02
10-02-04
10-02-05
10-02-07
10-02-08
10-02-10
10-02-11
10-02-12
10-02-22

9212561096

Waste Status Summary of 102-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	28	22	6	
2-	* CCPLX	149	143	6	
3-	CCPLX	94	88	6	
4-	CCPLX	91	85	6	
1-1979	CCPLX	105	99	6	New Photo 2/26/79
2-	CCPLX	168	129	39	New Solids Level Ajd. 5/21/79
3-	CPLX	388	349	39	
4-	CPLX	539	500	39	
1-1980	CPLX	740	701	39	
2-	CPLX	87	18	39	
3-	CCPLX	54	25	29	Inactive - New Solids 9/8/80
4-	CCPLX	54	25	29	

* Leak Detection Dry Well 11-02-01 Drilled

9212561017

Waste Status Summary of 103-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	844	844	--	6 months report; rec'd 596M IWW; 66M OWW, receiving at end of period
2-					
3-	P	913	913	--	Rec'd 334MIWW; 160M OWW & 339M from 101-AX
4-	P	883	883	--	Rec'd 360M IWW;282M OWW: 394I from 101-AX
1-1966	P	888	888	--	Rec'd 376M IWW; 251M OWW
2-	P	996	996	--	Rec'd 311M IWW & 58M OWW
3-	P	987	987	--	
4-	P	985	985	--	
1-1967	P	967	967	--	
2-	P	917	917	--	
3-	P	908	894	14	
4-	P	946	946	--	Rec'd 98M OWW
1-1968	P	985	985		Equipped for boiling waste; rec'd 118M OWW
2-	P	976	976	--	Rec'd 88M F-18 & 25M OWW
3-	P	932	932	--	4 from 202-A
4-	P	946	869	77	58M from Purex (F-18 & R-8)
1-1969	P	974	891	83	11M from 221-B; 45M from 202-A
2-	P	1000	924	76	
3-	P	986	903	83	
4-	P	965	882	83	
1-1970	P	985	905	80	
2-	P	986	903	83	
3-	P	971	902	69	
4-	P	971	902	69	
1-1971	P	974	908	66	
2-	P	974	908	66	
3-	P	974	908	66	
4-	P	971	905	66	

9212561003

Waste Status Summary of 103-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	P	976	910	66	
2-	P	976	910	66	
3-	P	685	619	66	678M from 104-AX; 969M to 105-C
4-	P	567	498	69	3 From B Plant; 832 from 101-AX; 102 from 104-AX 921M to 105-C
1-1973	PSS	654	585	69	787M from 102-AX; 82M from 104-AX; 844 to 104-C
2-	PSS	558	489	69	510M from 101-AX; 694 from 104-AX, 1266 M to 105-C
3-	PSS	556	487	69	
4-	PSS	575	506	69	
1-1974	PSS	568	499	69	173M from 101-AX; 219M to 105-C, 1 to 104-C
2-	PSS	653	584	69	98M from 101-AX
3-	PSS	870	798	72	221M from 106-C
4- *	PSS	822	734	88	59M to 105-C
1-1975 **	PSS	987	899	88	278M from 101-AX; 7M from 417 127M to 105-C
2-	PSS	828	740	88	
3-	PSS	622	534	88	342 from AR vault; 544M to 10
4-	PSS	173	85	88	51Mfrom AR Vault; 6M from 152-AX C.T. 490M to 105-C
1-1976	---	88	0	88	36M to 105-C; 29M to 104-AX
2-	water	72	2	70	4M from 103-AX Sluicing
3-	Evap	52	35	17	Sluicing
4-	Evap	17	11	6	
1-1977	Evap.	11	0	11	
2-	Evap.	6	0	6	
3-	Evap.	25	19	6	Sluicing sr. sludge
4-	Evap.	17	11	6	

* Leak detection dry well 11-03-12 drilled.

** Leak detection dry wells drilled:

11-03-02
11-03-05
11-03-07
11-03-09
11-03-10

9 2 1 2 5 6 1 0 7 9

Waste Status Summary of 103-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CC	39	33	6	New Solids Level 1/19/78 Active - Being Sluiced Wait Sluice Eval.
2-	NCPLX	28	22	6	Sluicing Complete
3-	NCPLX	33	27	6	Salt Well Installed
4-	NCPLX	44	38	6	
1-1979	CPLX	547	541	6	
2-	CCPLX	545	539	6	New Solids Level 5/21/79 New Photo 4/11/79
3-	PSSF	888	882	6	
4-	DSSF	888	882	6	
1-1980	DSSF	891	885	6	Slurry Receiver
2-	DSSF	944	934	10	New Solids 6/30/80 Lag Storage - New Photo 4/21/80
3-	NCPLX	879	111	0	
4-	NCPLX	121	0	121	Inactive - New Solids Level 10-8-80

9 2 1 2 5 6 1 0 1 0

Waste Status Summary of 104-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	P	MT	--	--	Back-up tank in event of tank failure 6 months report
2-					
3-	P	344	(water)	--	Back-up tank
4-	P	355	(water)	--	
1-1966	P	355	(water heel)	--	Back-up tank
2-	P	400	(" ")	--	
3-	P	762	762	--	Rec'd 74M
4-	P	886	886	--	Rec'd 388M
1-1967	P	872	872	--	Rec'd 257M
2-	P	872	872	--	Rec'd 465M
3-	P	869	869	--	Rec'd 446M IWW & sumps
4-	P	869	869	--	Rec'd 339M IWW & sumps
1-1968	P	952	952	--	Receives Purex waste except 36M PAW which was received in AR vault--rec'd 235M IWW--equipped for boiling waste
2-	P	979	979	--	Rec'd 88M F-18; 18M from F-16, 2M OWW
3-	P	985	985	--	
4-	P	979	969	10	
1-1969	P	957	949	8	37M from 221-B; 37M from 202-A
2-	P	953	945	8	3M from Purex
3-	P	964	953	11	
4-	P	987	960	27	
1-1970	P	998	940	58	198M to 101-A; Rec'd 198M H_2O
2-	P	998	950	48	198M to 101-A; Rec'd 195M H_2O
3-	P	1000	956	44	
4-	P	1000	948	52	
1-1971	P	1001	954	47	
2-	P	1001	954	47	
3-	P	989	942	47	
4-	P	990	943	47	

9212561011

Waste Status Summary of 104-AXTank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	P	984	937	47	
2-	P	984	937	47	
3-	P	245	198	47	678M from 104-AX; 969M to 105
4-	P	677	622	55	567M from 104-A; 102 to 103-A
1-1973	PSS	825	770	55	276M from 104-A; 82 to 103-AX
2-	PSS	109	54	55	694M to 103-AX
3-	PSS	105	50	55	
4-	PSS	126	82	44	
1-1974	PSS	114	70	44	
2-	PSS	111	67	44	
3-	PSS	763	719	44	146 water; 446M from 104-A
4- *	PSS	732	685	47	
1-1975 **	PSS	690	643	47	
2-	PSS	644	597	47	
3-	PSS	586	539	47	
4-	PSS	547	500	47	
1-1976	PSS	352	308	44	234M to 105-C; 29M from 103-A 9 from 002-AR
2-	PSS	325	281	44	
3-	Evap	261	214	47	Cs feed to be sluiced
4-	Evap	789	742	47	
1-1977	Evap.	171	116	55	
2-	Evap.	61	39	22	
3-	Evap.	17	6	11	Sluiced - waiting photo eval.
4-	Evap.	25	22	3	

* Leak detection dry well 11-04-01 drilled

** Leak detection dry wells drilled:

11-04-05
11-04-07
11-04-08
11-04-10
11-04-11

9 2 1 2 5 5 6 1 0 1 2

Waste Status Summary of 104-AX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	* EVAP.	22	14	8	Active - Being sluiced
2-	NCPLX	11	8	3	Questionable integrity sluicing complete - New solids eval. 5/23/78
3-	-	3	0	3	Inactive - Primary stabilized - New photo 5/8/78
4-	-	3	0	3	
1-1979	NCPLX	6	3	3	
2-	NCPLX	6	3	3	
3-	NCPLX	6	3	3	
4-	NCPLX	6	3	3	
1-1980	NCPLX	6	3	3	
2-		6	3	3	
3-		6	3	3	
4-		6	3	3	

* Leak Detection Dry Well 11-04-19 Drilled

9 2 1 2 5 6 1 9 1 3

Waste Status Summary of 101-AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965					
2-					
3-					
4-					
1-1966					
2-					
3-					
4-					
1-1967					
2-					
3-					
4-					
1-1968					
2-					
3-					
4-					
1-1969					
2-					
3-					
4-					
1-1970					
2-					
3-					
4-					
1-1971					Preheating completed
2-	B	828	828	0	318M from B Plant (cell 25) 3M Purex, placed in service April 1971
3-	B	909	909	0	698 from B Plant (Cell 25)
4-	B	828	828	0	455M from B Plant (Cell 25) 11M From Purex

9212561014

Waste Status Summary of 101-AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	B	918	918	0	716M from B Plant (Cell 25)
2-	B	918	885	33	110M from B Plant (Cell 25) 128M from 151-AX
3-	B	938	905	33	580M from B Plant
4-	B	963	963	0	4 from AR Vault 2 from B Plant
1-1973	B	976	976	0	
2-	B	969	969	0	
3-	B	962	962	0	
4-	B	969	969	0	
1-1974	B	964	964	0	
2-	B	971	971	0	
3-	B	975	975	0	
4-	B	963	911	52	3M from 152-AX Catch Tank
1-1975	B	968	916	52	
2-	B	968	916	52	Aging Waste; 17M from B Plan
3-	B	968	916	52	
4-	B	968	916	52	
1-1976	B	968	916	52	
2-	B	968	916	52	
3-	Aging	976	924	52	
4-	Aging	968	916	52	
1-1977	Aging	963	911	52	Aging waste
2-	Aging	968	916	52	
3-	Aging	971	919	52	
4-	Aging	743	691	52	

9212556101 5

Waste Status Summary of 101-AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CS FD	454	402	52	Active B Plant CS Feed
2-	NCPLX	234	182	52	Sluice mix receiver
3-	NCPLX	358	306	52	Solids deter. 7/28/78
4-	NCPLX	363	311	52	
1-1979	NCPLX	517	465	52	New Photos 3/14/79
2-	NCPLX	567	515	52	
3-	NCPLX	572	520	52	
4-	NCPLX	616	564	52	
1-1980	CCPLX	316	264	52	
2-	CCPLX	602	541	52	New Solids Level 6/30/80
3-	CCPLX	815	754	61	
4-	CCPLX	816	755	61	

9212561016

Waste Status Summary of 102-AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965					
2-					
3-					
4-					
1-1966					
2-					
3-					
4-					
1-1967					
2-					
3-					
4-					
1-1968					
2-					
3-					
4-					
1-1969					
2-					
3-					
4-					
1-1970					
2-					
3-					
4-					
1-1971					
2-	water	217	217	0	Spare
3-	water	212	212	0	"
4-	water	206	206	0	"

9212561017

Waste Status Summary of 102AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	Water	238	238	0	Spare 62M from 104-A
2-	Water	248	248	0	Spare 60M from 104-A
3-	Water	214	214	0	Spare
4-	Water	198	198	0	Spare
1-1973	Water	216	216	0	Spare
2-	Water	212	212	0	Spare
3-	Water	211	211	0	Spare
4-	Water	219	219	0	Spare
1-1974	Water	205	205	0	Spare
2-	Water	205	205	0	Spare
3-	Water	201	201	0	Spare
4-	Water	209	209	0	Spare
1-1975	Water	209	209	0	Spare
2-	Water	209	209	0	Spare
3-	Water	209	209	0	Spare
4-	Water	209	209	0	Spare
1-1976	Water	209	209	0	Spare
2-	Water	209	209	0	Spare
3-	Evap	209	209	0	Aging Waste
4-	Evap	55	55	0	Aging Waste
1-1977	Evap	61	61	0	Aging Waste
2-	Aging	259	259	0	BNW Waste Receiver
3-	Aging	220	220	0	Aging Waste, BNW wst receive
4-	Aging	217	217	0	

9 2 1 2 6 1 0 1 8

Waste Status Summary of 101-AY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	Aging	347	347	0	BNW Waste Receiver
2-	Aging	374	374	0	" " "
3-	DSSF	382	376	0	Solids Deter. 9/14/78
4-	DSSF	388	382	6	
1-1979	DSSF	388	382	6	PNL Waste Receiver
2-	DSSF	388	382	6	New Photo 3/14/79
3-	DSSF	388	382	6	
4-	DSSF	388	382	6	
1-1980	DSSF	388	382	6	
2-	DSSF	690	669	21	New Solids Level 6/30/80
3-	NCPLX	712	691	21	
4-	NCPLX	227	206	21	

9 2 1 2 5 6 1 0 1 9

Waste Status Summary of 101-AZ Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972					
2-					
3-					
4-					
1-1973					
2-					
3-					
4-					
1-1974					
2-					
3-					
4-					
1-1975					
2-					
3-					
4-					
1-1976	--	--	---	--	Under construction
2-	--	--	---	--	Under construction
3-	--	--	---	--	Under construction
4-	Evap	50	50	0	Under construction
1-1977	Evap	50	50	0	
2-	Evap	50	50	0	
3-	Evap	146	146	0	Evap. feed dil., Hi. sr. wst dilute.
4-	Evap	591	591	0	

9212156100

Waste Status Summary of 101-AZ Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CPLX	974	971	3	A-Evap. Feed dil.
2-	CPLX	52	49	3	Solids Eval. 4/10/78
3-	DSSF	950	949	1	Solids Eval. 9/14/78
4-	DSSF	948	947	1	
1-1979	DSSF	942	941	1	
2-	DSSF	945	944	1	New Photo 5/10/79
3-	DSSF	945	944	1	
4-	DSSF	953	952	1	
1-1980	DSSF	961	960	1	
2-	DSSF	941	889	52	New Solids Level 6/30/80
3-	NCPLX	966	894	72	New Photo 4/18/80
4-	NCPLX	795	723	72	

9212561021

Waste Status Summary of 102-AZ Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972					
2-					
3-					
4-					
1-1973					
2-					
3-					
4-					
1-1974					
2-					
3-					
4-					
1-1975					
2-					
3-					
4-					
1-1976	--	28	28	0	Spare
2-	Water	28	28	0	
3-	Evap	105	105	0	Aging Waste
4	Evap	501	501	0	High Sr Waste Dilute
1-1977	Evap	734	734	0	High Sr Waste Dilute
2-	Evap	971	941	0	High Sr Waste Dilute
3-	Resid	756	726	0	Residual liquor, Hi. Sr. Ws
4-	Resid	751	721	0	

9212556102 2

Waste Status Summary of 102-AZ Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CCPLX	748	718	30	Active - HDRL
2-	CCPLX	850	820	30	
3-	CCPLX	879	856	23	Solids Eval. 8/14/78
4-	CCPLX	879	856	23	
1-1979	CCPLX	879	856	23	New Photos 3/14/79
2-	CCPLX	887	864	23	
3-	CCPLX	887	864	23	
4-	CCPLX	893	870	23	
1-1980	CCPLX	895	872	23	
2-	CCPLX	901	899	2	New Solids Level 6/30/80
3-	CCPLX	921	915	2	New Photo 4/18/80
4-	CCPLX	921	915	6	

9 2 1 2 5 6 1 0 2 3

Waste Status Summary of 101-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	MW	168	---	---	First used May 1945 (1st in Cascade)
3	MW	512	---	---	
4	MW	530	---	---	Filled in Oct. 1945
1-1946	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1947	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1948	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1949	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1950	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1951	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

9212561024

Waste Status Summary of 101-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Type Vol.	Liquid In Storage	Solids In Storage	Remarks
					288 removed thru BR 1032
1-1953	MW	1291	In cascade	---	Now processing for feed to TBP Plant
2	MW	---	---	---	Small sludge heel. Less than 1" of water
3	---	0	0	---	Small sludge heel. Less than 1" or water.
4	EB	223	223	0	Finished slucing 12-28-53. Rec'd from 105-B
1-1954	EB	527	527	0	Rec'd from 105-B
2	EB	527	527	0	
3	EB	527	527	0	
4	EB	527	527	0	
1-1955	EB	527	527	0	
2	EB	527	527	0	
3	EB	527	527	0	
4	EB	527	527	0	
1-1956	EB	527	527	0	
2	EB	527	527	0	
3	EB	527	527	0	
4	EB	527	527	0	
1-1957	EB	538	538	0	Latest electrode reading
2	EB	541	435	106	Latest electrode reading
3	EB	318	3	315	223 Scavenged
4	EB	318	3	315	
1-1958	EB	318	3	315	CW (782 TU)
2	EB	321	6	315	CW (771 TU)
3	EB	321	6	315	CW (913 TU)
4	EB	321	6	315	CW (913 TU)
1-1959	EB	321	6	315	CW (913 TU)
2	EB	313	0	315	CW (948 TU)
3	EB	313	0	315	CW (948 TU)
4	EB	316	1	315	CW (935 TU)
1-1960	EB	316	1	315	CW
2	EB	403	88	315	87 water leaked into pipe incasement which drained to 101-B
3	EB	403	88	315	
4	EB	403	88	315	
1-1961	EB	403	88	315	
2	EB	403	88	315	
3	EB	403	88	315	
4	EB	403	88	315	

9 2 1 2 5 5 6 1 0 2 5

Waste Status Summary of 101-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	EB	403	88	315	
2	EB	403	88	315	
3	EB	403	88	315	
4	EB	403	88	315	
1-1963	---	---	---	---	
2	EB	403	201	202	
3	---	---	---	202	
4	EB-CW	525	201-122	202	Rec'd 122 CW
1-1964	EB-CW	525	201-122	202	
2	EB-CW	525	201-122	202	
3	EB-CW	525	201-122	202	
4	EB-CW	525	201-122	202	
1-1965	---	---	---	---	
2	EB-CW	527	241-125	161	Data report covered 6 months
3	EB-CW	527	241-125	161	
4	EB-CW	527	241-125	161	
1-1966	EB-CW	527	241-125	161	
2	EB-CW	527	241-125	161	
3	EB-CW	527	241-125	161	
4	EB-CW	527	241-125	161	
1-1967	EB-CW	527	241-125	161	
2	EB-CW	527	241-125	161	
3	EB-CW	527	241-125	161	
4	EB-CW	527	241-125	161	
1-1968	EB-CW	527	241-125	161	
2	EB-CW	527	241-125	161	
3	EB-CW	527	241-125	161	
4	EB-CW	528	242-125	161	
1-1969	---	151	0	151	373 to 103-BY
2	EB	356	205	151	205 from B Plant
3	BL (EB)	290	139	151	122 from B Plant, 14 from 302-B CT, 202 to 102-B
4	BL (EB)	220	69	151	213 from B Plant, 285 to 102-B
1-1970	BL (EB)	349	198	151	129 from B Plant
2	BL (EB)	403	253	150	336 from B Plant, 281 to 103-BX
3	BL (EB)	355	249	106	388 from B Plant, 437 to 101-BX
4	BL (EB)	497	394	103	591 from B Plant, 448 to 101-BX

9 2 1 2 5 6 1 0 2 6

Waste Status Summary of 101-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	BL (EB)	436	333	103	469 from B Plant, 529 to 101-BX
2	BL (EB)	259	156	103	277 from B Plant, 454 to 101-BX
3	BL (EB)	502	399	103	226 from B Plant, 19 from 002-BXR
4	BL (EB)	469	366	103	157 from B Plant, 190 to 101-BX
1-1972	BL (EB)	508	405	103	256 from B Plant, 4 water, 15 to 102-A, 208 to 101-BX
2	BL (EB)	433	330	103	444 from B Plant, 520 to 101-BX
3	BL (EB)	502	393	109	324 from B Plant, 254 to 101-BX
4	BL (EB)	535	426	109	425 from B Plant, 192 to 101-BX, 199 to 104-BX
1-1973*	BL (EB)	514	405	109	468 from B Plant, 4 to 102-B, 484 to 104-BX
2	BL (EB)	513	404	109	Has an exhauster, New tape
3	BL (EB)	512	403	109	
4	BL (EB)	511	402	109	
1-1974**	BL (EB)	509	400	109	
2	BL (EB)	440	331	109	64 to 106-BX
3	BL (EB)	432	323	109	
4	BL (EB)	334	198	136	Removed from Service, 89 to 103-BX
1-1975***	---	136	0	136	Removed from Service
2	---	136	0	136	Removed from Service
3	---	136	0	136	" " "
4	---	136	0	136	" " "
1-1976	---	103	0	103	" " "
2	---	103	0	103	" " "
3	---	103	0	103	Inactive
4	---	103	0	103	Salt Well Comp.
1-1977	---	103	0	103	Questionable Integrity-Isolated and Stabilized
2	---	103	0	103	Inactive
3	---	103	0	103	Inactive Current Phase I complete
4	---	103	0	103	" " " " "

*Dry Well 20-01-03 drilled.
**Dry Wells 20-01-01, 20-01-05, 20-01-07, and 20-01-11 were drilled.
***Dry Wells 20-01-05 and 20-01-06 were drilled.

9212556102 7

Waste Status Summary of 101-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	103	0	103	Inactive
2-	-	103	0	103	Primary Stabilized
3-	-	103	0	103	P-10 Pmp. removed
4-	-	103	0	103	
1-1979	-	103	0	103	
2-	-	103	0	103	Questionable Integrity
3-	-	103	0	103	
4-	-	103	0	103	
1-1980	-	103	0	103	
2-	-	103	0	103	
3-	-	103	0	103	
4-	-	103	0	103	

9212561098

Waste Status Summary of 102-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	530	---	---	First used Oct. 1945. Filled Dec. 1945
1-1946	MW	530	---	---	(2nd in Cascade)
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1947	NW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1948	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1949	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1950	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1951	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

9212261019

Waste Status Summary of 102-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
					288 M gals. removed thru BR 1032
1-1953	MW	1291	in Cascade	---	Now processing for feed to TBP Plant
2	MW	---	---	---	Small sludge heel. No liquid
3	MW	0	0	---	Small sludge heel. No liquid
4	EB	530	530	0	Received bottoms from 105-B
1-1954	EB	530	530	0	
2	EB	530	530	0	
3	EB	530	530	0	
4	EB	530	530	0	
1-1955	EB	530	530	0	
2	EB	530	530	0	
3	EB	530	530	0	
4	EB	530	530	0	
1-1956	EB	530	530	0	
2	EB	530	530	0	
3	EB	530	530	0	
4	EB	530	530	0	
1-1957	EB	502	502	0	Latest electrode reading
2	EB	502	502	0	
3	EB	84	84	0	423 Scavenged.
4	EB	114	30	84	New electrode reading
1-1958	EB	114	30	84	CW (1535 TU)
2	EB	114	30	84	CW (1535 TU)
3	EB	114	30	84	CW (1817 TU)
4	EB	114	30	84	CW (1817 TU)
1-1959	EB	114	30	84	CW (1817 TU)
2	EB	120	36	84	New Electrode
3	EB	120	36	84	
4	EB	120	36	84	
1-1960	EB	120	36	84	
2	EB	120	36	84	
3	EB	120	36	84	
4	EB	120	36	84	
1-1961	EB	120	36	84	
2	EB	120	36	84	
3	EB	---	---	84	
4	EB	125	41	84	New electrode

9 2 1 2 5 6 1 0 3 0

Waste Status Summary of 102-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	EB	---	---	84	
2	EB	123	39	84	Latest electrode reading
3	EB	123	39	84	
4	EB	123	39	84	
1-1963	---	---	---	---	
2	EB-CW	494	83-371	40	371 from 102-C
3	EB-CW	---	---	---	
4	EB-CW	542	83-419	40	48 CW
1-1964	EB-CW	542	83-419	40	
2	EB-CW	542	83-419	40	
3	EB-CW	---	---	40	
4	EB-CW	535	83-412	40	New electrode (Reading Confirmed)
1-1965	----	----	----	----	
2	EB-CW	532	99-409	24 (EB)	
3	EB-CW	532	99-409	24	
4	EB-CW	532	99-409	24	
1-1966	EB-CW	532	99-409	24	
2	EB-CW	532	99-409	24	
3	EB-CW	532	99-409	24	
4	EB-CW	532	99-409	24	
1-1967	EB-CW	532	99-409	24	
2	EB-CW	532	99-409	24	
3	EB-CW	532	99-409	24	
4	EB-CW	532	99-409	24	
1-1968	EB-CW	531	99-408	24	
2	EB-CW	534	99-411	24	
3	EB-CW	534	99-411	24 (EB)	
4	EB-CW	534	99-411	24	
1-1969	EB	26	2	24	506 to 103-BY
2	EB	25	1	24	
3	BL(EB)	228	204	24	202 from 101-B
4	BL(EB)	513	489	24	285 from 101-B
1-1970	BL(EB)	514	490	24	
2	BL(EB)	98	43	55	415 to 103-C
3	BL-IX	272	38-179	55	179 from 104-BX
4	BL-IX	271	38-178	55	
1-1971*	BL-IX	277	44-178	55	
2	BL-IX	277	44-178	55	
3	BL-IX	499	81-363	55	223 from 110-B
4	BL-IX	81	5- 21	55	419 to 101-TX

*Dry Well 20-02-11 drilled.

9 2 1 2 5 5 6 1 0 3 1

Waste Status Summary of 102-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1972*	BL-IX	95	23-38	34	15 from 101-B
2	EB-BL-IX	186	70-31-51	34	6 from 104-B, 30 from 105-B, 18 from 107-B, 35 pit flushes
3	EB-BL-IX	310	195-31-51	33	102 from 105-B, 24 from 110-B
4	EB-BL-IX	395	280-31-51	33	69 from 105-B, 14 from 110-B
1-1973	EB-BL-IX	485	366-31-51	33	4 from 101-B, 75 from 105-B, 2 from 107-B, 3 from 110-B
2	EB-BL-IX	492	373-35-51	33	3 from 105-B, 1 from 107-B, 3 from 110-B, New tape
3	EB-BL-IX	493	374-35-51	33	
4	EB-BL-IX	497	377-35-52	33	
1-1974	EB-BL-IX	497	377-35-52	33	
2	EB-BL-IX	511	388-36-54	33	4 from 107-B, 8 from 110-B
3	EB-BL-IX	452	340-32-47	33	6 from 107-B, 15 from 110-B, 19 to 103-B, 63 to 106-B
4	EB-BL-IX	462	348-33-48	35	5 from 107-B, 7 from 110-B
1-1975	EB-BL-IX	469	352-33-49	35	1 from 107-B, 2 from 110-B
2	EB-BL-IX	200	134-12-19	35	Interstitial Liquid storage. 1 from 101-B, 3 from 107-B, 3 from 110-B, 279 to 106-Sx.
3	EB-BL-IX	208	740-14-21	35	Interstitial Liquor Storage 3 M from 107-B
4	EB-BL-IX	219	149-14-21	35	Interstitial Liquor Storage 3 M 107-B 5 M from 101-B
1-1976	EB-BL-IX	43	6-1-1	35	Interstitial Liquor Storage 179 M to 103-B 2 M from 110-B
2	EB-BL-IX	48	11-1-1	35	1 from 107-B, 1 from 110-B
3	Evap Feed Dil	59	24	35	Interstitial Liquor Storage
4	Evap Feed Dil	68	17	51	" " "
1-1977	Evap Feed Dil	73	33	40	Interstitial Liquor Storage
2	Evap Feed Dil	79	39	40	" " "
3	EVap Feed Dil	43	3	40	Salt Well Recovery
4	Evap Feed Dil	48	8	40	" " "

* Dry Wells 20-02-03, 20-02-05, 20-02-07, 20-02-09 were drilled.

9 2 1 2 5 5 6 1 0 3 2

Waste Status Summary of 102-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	Dilute FD	51	11	40	Evap. Feed Receiver
2-	NCPLX	54	14	37	Salt Well Receiver
3-	NCPLX	54	17	37	Solid Level Adj. 9/30/78
4-	NCPLX	54	17	37	Inactive
1-1979	NCPLX	51	14	37	
2-	NCPLX	51	14	37	
3-	NCPLX	51	14	37	
4-	NCPLX	51	14	37	
1-1980	NCPLX	51	14	37	
2-	NCPLX	51	14	37	New Photo 4/3/80
3-	NCPLX	51	14	37	
4-	NCPLX	51	14	37	

9212556103 3

Waste Status Summary of 103-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	67	---	---	First used Dec. 1945, Last in Cascade.
1-1946	MW	530	---	---	Filled in March 1946
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1947	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1948	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1949	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1950	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1951	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1952	MW	530	---	---	
2	MW	519	---	---	
3	MW	519	---	---	
4	MW	519	---	---	

9 2 1 2 6 1 0 3 4

Waste Status Summary of 103-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	MW	1291	In cascade	---	Now processing for feed to TBP Plant. 288 removed thru BR 1032
2	MW	359	---	---	Supernatant
3	MW	327	---	---	
4	MW	12	12	0	Trans. to 102-BY. Contains H_2O used in sluicing
1-1954	EB	554	554	0	Rec'd from 105-B
2	EB	554	554	0	
3	EB	554	554	0	
4	EB	554	554	0	
1-1955	EB	554	554	0	
2	EB	554	554	0	
3	EB	554	554	0	
4	EB	554	554	0	
1-1956	EB	554	554	0	
2	EB	554	554	0	
3	EB	554	554	0	
4	EB	554	554	0	
1-1957	EB	554	554	0	Latest electrode reading
2	EB	530	530	0	Latest electrode reading. 71 to 106
3	EB	230	3	227	Latest electrode reading. 292 scavenged.
4	EB	235	8	227	Latest electrode reading.
1-1958	EB	235	8	227	CW (1089TU)
2	EB	238	11	227	CW (1077TU), Latest electrode reading
3	EB	238	11	227	CW (1275TU)
4	EB	238	11	227	CW (1275TU)
1-1959	EB	238	11	227	
2	EB	238	11	227	
3	EB	238	11	227	
4	EB	238	11	227	
1-1960	EB	238	11	227	
2	EB	238	11	227	
3	EB	238	11	227	
4	EB	238	11	227	

9 2 1 2 5 6 1 0 3 5

Waste Status Summary of 103-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961	EB	---	---	227	
2	EB	241	14	227	
3	EB	241	14	227	
4	EB	241	14	227	
1-1962	EB	---	---	227	
2	EB	222	0	227	New Electrode
3	EB	222	---	---	
4	EB	222	2	220	
1-1963	EB	222	---	---	
2	EB	222	163	59	
3	---	---	---	59	
4	EB-CW	503	163-281	59	281 CW
1-1964	---	---	---	59	
2	EB-CW	536	163-314	59	33 CW
3	EB-CW	---	---	59	
4	EB-CW	552	163-330	59	New electrode (Read. confirmed)
1-1965	---	---	---	59	
2	EB-CW	560	163-338	59	New electrode
3	EB-CW	560	163-338	59	
4	EB-CW	560	163-338	59	
1-1966	EB-CW	560	163-338	59	
2	EB-CW	560	163-338	59	
3	EB-CW	560	163-338	59	
4	EB-CW	560	163-338	59	
1-1967	EB-CW	560	163-338	59	
2	EB-CW	560	163-338	59	
3	EB-CW	560	163-338	59	
4	EB-CW	560	163-338	59	
1-1968	EB-CW	558	163-336	59	
2	EB-CW	558	163-336	59	
3	EB-CW	559	163-337	59 (EB)	
4	EB-CW	560	163-338	59	
1-1969	EB	66	7	59	212 From 108-B, 706 to 103-BY
2	CW-OWW	158	57- 42	59	124 from 104B, 207 From 108 B, 597 from 112-B, 33 flushes, 1556 from 103-BX, 2425 to 103-BY
3	---	55	0	55	206 from 106-B, 327 from 107-B 393 from 109-B, 339 from 112-B 724 from 103-BX, 2095 to 103-BY
4	---	55	0	55	

9 2 1 2 5 6 1 0 3 6

Waste Status Summary of 103-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids In Storage	Remarks
1-1970	IX	263	208	55	208 from 111-B
2	IX	541	486	55	279 from 111-B
3	IX	541	486	55	
4	IX	541	486	55	
1-1971	IX	541	486	55	
2	IX	540	481	59	
3	IX	539	480	59	
4	BL-IX	206	37-149	20	490 from 112-B, 824 to 101-TX
1-1972*	---	52	0	52	417 From 108-B, 333 From 109-B, 239 from 111-B, 326 to 109-BY, 264 to 105-C, 553 to 101-TX
2	water	59	7	52	7 pit flushes
3	water	68	16	52	9 pit flushes
4	water	87	35	52	New tape
1-1973	water	87	35	52	
2	IX	270	218	52	184 from 104-BX
3	IX	251	199	52	New tape
4	BNW-N-LW-R-CW-DW-IX-TBP	489	35-48-18-96-18-64-135-23	52	307 from 104-C, 70 to 109-B
1-1974	BNW-N-LW-R-CW-DW-IX-TBP	489	35-48-18-96-18-64-135-23	52	
2	BNW-N-LW-R-CW-DW-IX-TBP	489	35-48-18-96-18-64-135-23	52	
3	BNW-N-LW-R-CW-DW-IX-TBP-EB	504	35-48-18-96-18-64-B5-23-15	52	19 from 102-B
4	BNW-N-LW-R-CW-DW-IX-TBP-EB	499	35-46-17-92-17-61-129-22-14	68	
1-1975	BNW-N-LW-R-CW-DW-IX-TBP-EB	499	33-46-17-92-17-61-129-22-14	68	
2	BNW-N-LW-R-CW-DW-IX-TBP-EB	499	33-46-17-92-17-61-129-22-14	68	
3	BNW-N-LW-R-CW-DW-IX-TBP EB	505	33-47-17-93 17-62-132-22-14	68	5 water
4	224-IX-EB	299	17-120-94	68	669 to 110-SX, 13 water, 145 from 106-B, 305 from 109-B

*Dry Wells 20-03-02, 20-03-03, 20-03-06, 20-03-09, 20-03-11 drilled.

Waste Status Summary of 103-B Tank-Capacity 53m,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	---	131	63	68	Evap. Feed Dil.
2	---	90	22	68	" " "
3	---	90	22	68	Inactivity current
4	---	90	22	68	Inactivity current
1-1978	-	90	22	68	Inactive
2-	NCPLX	92	24	68	
3-	NCPLX	92	24	68	P-10 Pmp. Removed
4-	NCPLX	92	24	68	
1-1979	NCPLX	92	24	68	
2-	NCPLX	92	24	68	Questionable Integrity
3-	NCPLX	92	24	68	
4-	NCPLX	92	24	68	
1-1980	NCPLX	92	24	68	Photo taken 2/7/80
2-	NCPLX	92	24	68	
3-	NCPLX	92	24	68	
4-	NCPLX	92	24	68	

9212261073

Waste Status Summary of 104-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---		
2	---	---	---	---	
3	2C	165	---	---	First used in Aug. 1946 (1st in Cascade)
4	2C	488	---	---	
1-1947	2C	530	---	---	Filled in Feb. 1947
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1948	2C	530	---	---	
2	2C	530	---	---	
3	2C	216	---	---	312 to crib in July and August
4	2C	216	---	---	
1-1949	2C	530	---	---	Filled in March 1949
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1950	2C	530	---	---	
2	2C	501	---	---	cribbed
3	2C	530	---	---	
4	2C	530	---	---	
1-1951	2C	530	---	---	
2	2C	530	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	IC	530	---	---	
2	IC	530	---	---	
3	IC	410	---	---	Partially pumped to 106-B. Not down to sludge
4	EB	531	---	---	Started filling 12-4-52

Waste Status Summary of 104-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	EB	531	222	309	
2	EB	354	45	309	
3	EB	508	199	309	Rec'd TBP Waste Evap. bottoms
4	EB	525	216	309	IC sludge and TBP Evap. bottoms
1-1954	EB	525	216	309	
2	EB	525	216	309	
3	EB	537	228	309	Rec'd drainage from 151-B diversion box
4	EB	537	228	309	
1-1955	EB	537	228	309	
2	EB	537	228	309	
3	EB	537	228	309	
4	EB	537	228	309	
1-1956	EB	537	228	309	
2	EB	537	228	309	
3	EB	537	228	309	
4	EB	537	228	309	
1-1957	EB	535	226	309	Latest electrode reading
2	EB	535	495	40	Latest electrode reading
3	EB	535	170	365	
4	EB	535	5	530	
1-1958	EB	532	2	530	
2	EB	532	2	530	
3	EB	532	2	530	
4	EB	532	2	530	
1-1959	EB	532	2	530	
2	EB	546	16	530	New Electrode
3	EB	546	16	530	
4	EB	546	16	530	
1-1960	EB	546	16	530	
2	EB	546	16	530	
3	EB	546	16	530	
4	EB	546	16	530	
1-1961	EB	546	16	530	
2	EB	546	16	530	
3	EB	546	16	530	
4	EB	546	16	530	

Waste Status Summary of 104-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	EB	546	16	530	
2	EB	546	16	530	
3	EB	546	16	530	
4	EB	546	16	530	
1-1963	EB	546	---	---	
2	EB	546	137	409	
3	EB	546	137	409	
4	EB	546	137	409	
1-1964	EB	---	---	409	
2	EB	542	133	409	New electrode
3	EB	542	133	409	
4	EB	542	133	409	
1-1965	EB	542	133	409	
2	EB	542	133	409	
3	EB	542	133	409	
4	EB	542	133	409	
1-1966	EB	542	133	409	
2	EB	542	133	409	
3	EB	542	133	409	
4	EB	542	133	409	
1-1967	EB	542	133	409	
2	EB	541	132	409	
3	EB	541	132	409	
4	EB	541	132	409	
1-1968	EB	541	132	409	
2	EB	541	132	409	
3	EB	541	132	409 (EB)	
4	EB	541	132	409	
1-1969	EB	541	132	409	
2	EB	417	8	409	124 to 103-B
3	EB	417	8	409	
4	EB	417	8	409	
1-1970	EB	417	8	409	
2	EB	417	3	414	
3	EB	418	18	400	
4	EB	417	17	400	

9 2 1 2 3 6 1 0 1 1

Waste Status Summary of 104-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	EB	417	17	400	
2	EB	418	18	400	
3	EB	418	18	400	
4	EB	418	18	400	
1-1972	EB	418	18	400	
2	EB	415	15	400	6 flush water, 6 to 102-B
3	EB	414	14	400	
4	EB	411	11	400	
1-1973*	EB	408	8	400	
2	EB	403	3	400	
3	EB	404	4	400	
4	EB	404	4	400	
1-1974	EB	405	5	400	
2	EB	407	7	400	
3	EB	407	7	400	
4	---	400	0	400	
1-1975	---	400	0	400	
2	---	400	0	400	
3	---	400	0	400	Salt filled
4	---	400	0	400	" "
1-1976	---	400	0	400	" "
2	---	409	14	395	Salt Well Pumped-Salt Filled
3	---	409	14	395	" " " " "
4	---	409	14	395	" " " " "
1-1977	---	409	14	395	Salt Well Pumped
2	---	409	14	395	" " "
3	---	409	14	395	Inactive Current
4	---	409	14	395	" " Salt Well Installed

*Dry Wells 20-04-03, 20-04-06 drilled.

9 2 1 2 5 5 6 1 0 4 2

Waste Status Summary of 104-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	409	14	395	Inactive Salt Well Installed
2-	NCPLX	409	14	395	
3-	NCPLX	409	14	395	P 10 Pmp Removed
4-	NCPLX	409	14	395	
1-1979	NCPLX	409	14	395	
2-	NCPLX	409	14	395	
3-	NCPLX	409	14	395	
4-	NCPLX	409	14	395	
1-1980	NCPLX	409	14	395	New Photo 1/3/80
2-	NCPLX	409	14	395	
3-	NCPLX	409	14	395	
4-	NCPLX	409	14	395	

9212561013

Waste Status Summary of 105-B Tank--Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	2C	171	---	---	First used Feb. 1947, 2nd in Cascade
2	2C	379	---	---	
3	2C	530	---	---	Filled in Aug. 1947
4	2C	530	---	---	
1-1948	2C	530	---	---	
2	2C	530	---	---	
3	2C	378	---	---	150 to Crib in Sept.
4	---	0	---	---	378 to crib
1-1949	2C	18	---	---	Began fill in March 1949
2	2C	201	---	---	
3	2C	366	---	---	
4	2C	530	---	---	Filled in Nov. 1949
1-1950	2C	530	---	---	
2	2C	0	---	---	530 to crib
3	1C	530	---	---	
4	1C	530	---	---	
1-1951	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1952	1C	530	---	---	
2	1C	530	---	---	
3	EB	172	---	---	Completed pumping 9-11-52
4	EB	227	---	---	

9212610 1

Waste Status Summary of 105-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	EB	491	452	39	Active bottoms tank
2	EB	28	0	39	
3	EB	28	0	39	
4	EB	344	316	28	Active bottoms tank. Pumping to 101-B
1-1954	EB	396	368	28	Active bottoms tank. Pumped to 101-B and 103-B
2	EB	342	314	28	Active bottoms tank. Pumped to 110-B and 111-B
3	EB	519	491	28	Active bottoms tank. Pumped to 109-B
4	EB	516	488	28	
1-1955	EB	516	488	28	
2	EB	516	488	28	
3	EB	516	488	28	
4	EB	516	488	28	
1-1956	EB	516	488	28	
2	EB	516	488	28	
3	EB	516	488	28	
4	EB	516	488	28	
1-1957	EB	497	469	28	Latest electrode reading
2	EB	497	469	28	
3	EB	497	7	490	
4	EB	497	7	490	
1-1958	EB	494	4	490	
2	EB	494	4	490	
3	EB	494	4	490	
4	EB	494	4	490	
1-1959	EB	494	4	490	
2	EB	494	4	490	
3	EB	494	4	490	
4	EB	494	4	490	
1-1960	EB	494	4	490	
2	EB	494	4	490	
3	EB	494	4	490	
4	EB	494	4	490	

9 2 1 2 5 6 1 0 4 5

Waste Status Summary of 105-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	EB	---	---	490	
2	EB	491	1	490	
3	EB	491	1	490	
4	EB	491	1	490	
1-1962	EB	491	1	490	
2	EB	491	1	490	
3	EB	491	1	490	
4	EB	491	1	490	
1-1963	EB	491	1	490	
2	EB	491	1	490	
3	EB	491	1	490	
4	EB	491	1	490	
1-1964	EB	491	1	490	
2	EB	491	1	490	
3	EB	---	---	490	
4	EB	505	15	490	New electrode (Read. Confirmed)
1-1965	EB	505	15	490	
2	EB	505	15	490	
3	EB	505	15	490	
4	EB	505	15	490	
1-1966	EB	505	15	490	
2	EB	505	15	490	
3	EB	505	15	490	
4	EB	505	15	490	
1-1967	EB	505	15	490	
2	EB	505	15	490	
3	EB	505	15	490	
4	EB	505	15	490	
1-1968	EB	505	15	490	
2	EB	503	13	490	
3	EB	503	13	490 (EB)	
4	EB	503	13	490	
1-1969	EB	503	13	490	
2	EB	503	13	490	
3	EB	503	13	490	
4	EB	503	13	490	

9212 5610 16

Waste Status Summary of 105-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1970	EB	502	12	490	
2	EB	502	12	490	
3	EB	502	12	490	
4	EB	503	13	490	
1-1971	EB	502	12	490	
2	EB	502	12	490	
3	EB	502	12	490	
4	EB	503	13	490	
1-1972	EB	501	11	490	
2	EB	501	11	490	4 flush water, 30 to 102-B
3	---	490	0	490	6 flush water, 102 to 102-B
4	---	490	0	490	4 flush water, 69 to 102-B
1-1973	---	490	0	490	
2	---	490	0	490	2 water, 3 to 102-B
3	---	490	0	490	
4	---	490	0	490	
1-1974	---	490	0	490	
2	---	490	0	490	
3	---	490	0	490	
4	---	491	0	491	
1-1975	---	491	0	491	
2	---	491	0	491	
3	---	293	0	293	Salt Filled
4	---	293	0	293	" "
1-1976	---	293	0	293	" "
2	---	293	0	293	RFS Salt Filled
3	---	293	0	293	" " "
4	---	293	0	293	Salt Well Comp.
1-1977	---	293	0	293	Salt Well Comp.
2	---	293	0	293	" " " Stabilized
3	---	293	0	293	Inactive Current-Stabilized Phase I
4	---	293	0	293	" " "

*Dry Well 20-05-06 drilled.

9 2 1 2 6 1 0 7

Waste Status Summary of 105-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	293	0	293	Inactive - Primary stabilized
2-	-	293	0	293	
3-	-	293	0	293	
4-	-	293	0	293	
1-1979	-	293	0	293	
2-	-	293	0	293	Questionable Integrity
3-	-	293	0	293	New Photo 9/26/79
4-	-	293	0	293	
1-1980	-	293	0	293	
2-	-	293	0	293	
3-	-	293	0	293	
4-	-	293	0	293	

9212561003

Waste Status Summary of 106-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	2C	59	---	---	First used in Aug. 1947 (last in Cascade)
4	2C	215	---	---	
1-1948	2C	432	---	---	
2	2C	530	---	---	Filled in May 1948
3	2C	530	---	---	
4	2C	293	---	---	235 to crib in Dec.
1-1949	---	0	---	---	293 to crib
2	---	0	---	---	
3	---	0	---	---	
4	2C	112	---	---	Fill started in Nov.
1-1950	2C	239	---	---	165 to crib in March
2	---	0	---	---	239 to crib
3	---	0	---	---	Future Evaporator Feed Tank
4	---	0	---	---	
1-1951	---	0	---	---	Future feed tank 242-B
2	---	0	---	---	
3	---	---	---	---	
4	---	---	---	---	242-B Evaporator started up Dec. 14 1951
1-1952	---	---	---	---	
2	1C	193	---	---	1st cycle evaporator feed tank
3	1C	448	---	---	Evaporator Feed tank
4	1C	415	---	---	Evaporator Feed Tank

9212161019

Waste Status Summary of 106-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	1C	302	302	0	Evaporator Feed tank
2	EB	213	213	0	Evaporator Feed tank
3	TBP	197	197	0	Evaporator Feed tank, Rec'd TBP waste from 112-C
4	TBP	444	444	0	Evaporator Feed tank
1-1954	TBP	239	239	0	Evaporator Feed Tank
2	TBP	415	415	0	Evaporator Feed Tank
3	TBP	338	201	137	Evaporator Feed Tank
4	TBP	426	289	137	
1-1955	TBP	426	289	137	
2	TBP	426	289	137	
3	TBP	426	289	137	
4	TBP	426	289	137	
1-1956	TBP	426	289	137	
2	TBP	426	289	137	
3	TBP	426	289	137	
4	TBP	426	326	100	
1-1957	TBP	480	380	100	Latest electrode reading
2	TBP	551	426	125	71 from 103-B
3	TBP	552	427	125	Latest electrode reading
4	TBP	172	5	167	380 Scavenged
1-1958	TBP	172	5	167	CW (1321 TU)
2	TBP	230	63	167	CW(1107 TU) New electrode reading
3	TBP	227	60	167	CW (1323 TU)
4	TBP	227	60	167	CW (1323 TU)
1-1959	TBP	167	0	167	Latest electrode reading
2	TBP	178	11	167	11-242-B water flush
3	TBP	189	22	167	
4	TBP-HLO	209	11-31	167	20 from 242-B (HLO)
1-1960	TBP-HLO	230	11-52	167	21 from 242-B (HLO)
2	TBP-HLO	246	11-68	167	16 from 242-B (HLO)
3	TBP-HLO	268	11-90	167	22 from 242-B (HLO)
4	TBP-HLO	273	11-95	167	5 from 242-B (HLO)
1-1961	TBP-HLO	---	---	167	
2	TBP-HLO	288	11-110	167	15 from 242-B (HLO)
3	TBP-HLO	---	---	167	
4	TBP-HLO	304	11-126	167	16 from 242-B (HLO)

9 2 1 2 5 6 1 0 5 0

Waste Status Summary of 106-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	TBP-HLO	---	---	167	
2	TBP-HLO	315	11-137	167	11 from 242-B (HLO)
3	TBP-HLO	---	---	167	
4	TBP-HLO	337	11-159	167	22 from 242-B (HLO)
1-1963	TBP-HLO	---	---	---	
2	TBP-HLO	343	64-165	114	6 from 242-B (HLO)
3	TBP-HLO	---	---	114	
4	TBP-HLO	349	64-171	114	6 from 242-B (HLO)
1-1964	TBP-HLO	---	---	114	
2	TBP-HLO	354	64-176	114	5 from 242-B (HLO)
3	TBP-HLO	---	---	114	
4	TBP-HLO	356	64-178	114	2 from HLO
1-1965	---	---	---	---	
2	TBP-HLO	392	33-214	145	36 from HLO
3	TBP-HLO	392	33-214	145	
4	TBP-HLO	403	33-225	145	11 from HLO
1-1966	TBP-HLO	407	33-229	145	4 from HLO
2	TBP-HLO	407	33-229	145	
3	TBP-HLO	407	33-229	145	
4	TBP-HLO	407	33-229	145	
1-1967	TBP-HLO	409	33-231	145	
2	TBP-HLO	409	33-231	145	
3	TBP-HLO	410	33-232	145	
4	TBP-HLO	410	33-232	145	
1-1968	TBP-HLO	418	33-240	145	8 from 242-B
2	TBP-HLO	418	33-240	145	
3	TBP-HLO	418	33-240	145 (TBP)	
4	TBP-BNW	418	33-240	145	
1-1969	TBP-BNW	418	33-240	145	
2	TBP-BNW	418	33-240	145	
3	BNW	215	70	145	206 to 103-B
4	BNW	216	71	145	
1-1970	BNW	215	70	145	
2	BNW	215	43	172	
3	BNW	215	43	172	
4	BNW	216	44	172	
1-1971	BNW	216	44	172	
2	224-BNW	237	22-43	172	22 from 201-B
3	224-BNW	237	22-43	172	
4	224-BNW	237	22-43	172	

9 2 1 2 5 5 6 1 0 5 1

Waste Status Summary of 106-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1972*	224-BNW	237	22-43	172	
2	224-BNW	222	23-46	153	New tape
3	224-BNW	227	25-49	153	
4	224-BNW	228	25-50	153	
1-1973	224-BNW	228	27-54	147	
2	224-BNW	228	27-54	147	
3	224-BNW	229	27-55	147	
4	224-BNW	229	27-55	147	
1-1974	224-BNW	229	27-55	147	
2	224-BN@	229	27-55	147	
3	224-BNW-EB-BL-1X	289	27-53-50-5-7	147	63 from 102-B
4	224-BNW-EB-BL-IX	285	30-60-56-6-8	125	Has an exhauster
1-1975	224-BNW-EB-BL-IX	285	30-60-56-6-8	125	
2	224-BNW-EB-BL-IX	285	30-60-56-6-8	125	
3	224-BNW-EB-BL-IX	285	30-60-56-6-8	125	145 to 103-B
4	224-BNW-EB-BL-IX	142	3-6-6-1-1	125	
1-1976	224-BNW-EB-BL-IX	142	3-6-6-1-1	125	
2	224-BNW-EB BL-IX	142	17	125	
3	---	142	17	125	
4	---	142	17	125	Evap. Feed. Dil
1-1977	---	142	17	125	Evap. Feed Dil
2	---	142	17	125	" " "
3	---	142	17	125	Inactive Current
4	---	142	17	125	" "

*Dry Well 20-06-02, 20-06-03, 20-06-06, 20-06-11 drilled.

9 2 1 2 5 6 1 0 5 2

Waste Status Summary of 106-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	139	14	125	Inactive
2-	NCPLX	139	14	125	
3-	NCPLX	139	14	125	
4-	NCPLX	139	14	125	P-10 Pmp. removed New Solid Level 12/1/78 New Photo's 10/19/78
1-1979	NCPLX	139	14	125	
2-	NCPLX	139	14	125	
3-	NCPLX	139	14	125	
4-	NCPLX	139	14	125	
1-1980	NCPLX	139	14	125	
2-	NCPLX	139	14	125	
3-	NCPLX	139	14	125	
4-	NCPLX	139	14	125	

9 2 1 2 1 5 6 1 0 1 3

Waste Status Summary of 107B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	1C	168	---	---	First used in May 1945 (First in Cascade)
3	1C	475	---	---	
4	1C	530	---	---	Filled in Oct. 1945
1-1946	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1947	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1948	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1949	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1950	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1951	1C	530	---	---	
2	1C	530	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	EB	220	---	---	
3	EB	461	---	---	Active bottoms tank
4	EB	531	---	---	Cascade to 108-B, 11-25-52

9 2 1 2 1 6 1 0 1 4

Waste Status Summary of 107-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	EB	531	311	220	
2	EB	523	303	220	Re-evaporated bottoms
3	EB	530	358	172	1C re-evaporated bottoms
4	EB	530	358	172	1C re-evaporated bottoms
1-1954	EB	530	358	172 (1C)	1C re-evaporated bottoms
2	EB	530	358	172 (1C)	Scheduled to be pumped to ditch
3	---	225	0	225 (1C)	Pumped to ditch #3
4	EB	488	263	225 (1C)	
1-1955	EB	530	305	225 (1C)	Received TBP evap. bottoms from 110-B Tank
2	EB	530	305	225 (1C)	
3	EB	530	305	225 (1C)	
4	EB	530	305	225 (1C)	
1-1956	EB	530	305	225 (1C)	
2	EB	530	305	225 (1C)	
3	EB	530	305	225 (1C)	
4	EB	530	305	225 (1C)	
1-1957	EB	496	271	225 (1C)	Latest electrode reading
2	EB	532	302	230	New " "
3	EB	271	41	230	264 Scavenged
4	EB	271	10	261	
1-1958	EB	274	13	261	CW (945 TU)
2	EB	271	10	261	CW (956 TU) Latest electrode read.
3	EB	271	10	261	CW (1131 TU)
4	EB	271	10	261	
1-1959	EB	271	10	261	
2	EB	271	10	261	
3	EB	271	10	261	
4	EB	271	10	261	
1-1960	EB	271	10	261	
2	EB	271	10	261	
3	EB	271	10	261	
4	EB	237	0	261	Previous readings were incorrect
1-1961	EB	---	---	261	
2	EB	268	7	261	
3	EB	---	---	261	
4	EB	271	10	261	Latest electrode reading
1-1962	EB	271	10	261	
2	EB	271	10	261	
3	EB	271	10	261	
4	EB	271	10	261	

9 2 1 2 5 5 6 1 0 5 5

Waste Status Summary of 107-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1963	EB	271	---	---	
2	EB	271	0	271	
3	---	---	---	271	
4	CW	535	264	271	264 CW
1-1964	CW	535	264	271	
2	CW	535	264	271	
3	CW	---	---	271	
4	CW	541	270	271	Latest electrode reading
1-1965	---	---	---	---	
2	1C-EB-CW	541	23-46-278	202 (1C)	New electrode
3	1C-EB-CW	549	23-46-278	202	
4	1C-EB-CW	546	23-46-275	202	
1-1966	1C-EB-CW	543	23-46-272	202	
2	1C-EB-CW	543	23-46-272	202	
3	1C-EB-CW	541	23-46-270	202	
4	1C-EB-CW	541	23-46-270	202	
1-1967	1C-EB-CW	538	23-46-267	202	
2	1C-EB-CW	535	23-46-264	202	
3	1C-EB-CW	535	23-46-264	202	
4	1C-EB-CW	535	23-46-264	202	
1-1968	1C-EB-CW	531	23-46-260	202	
2	1C-EB-CW	530	23-46-259	202	
3	1C-EB-CW	530	23-46-259	202 (1C)	
4	1C-EB-CW	528	23-46-257	202	
1-1969	1C-EB-CW	528	23-46-257	202	
2	1C-EB-CW	527	23-46-256	202	
3	---	200	0	200	327 to 103-B
4	---	200	0	200	
1-1970 *	---	200	0	200	
2	---	200	0	200	
3	---	200	0	200	
4	---	200	0	200	
1-1971	---	200	0	200	
2	---	200	0	200	
3	---	200	0	200	
4	---	200	0	200	

*Dry Wells 20-07-05, 20-07-08, 20-07-11 drilled.

9 2 1 2 5 6 1 0 5 6

Waste Status Summary of 107-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1972	---	200	0	200	
2	---	193	0	193	2 flush water, 18 to 102-B
3	---	193	0	193	
4	---	193	0	193	
1-1973	---	193	0	193	Suspect leaker
2	---	193	0	193	1 to 102-B, Suspect leaker
3	---	193	0	193	Suspect leaker
4	---	193	0	193	Suspect leaker
1-1974	---	193	0	193	Suspect leaker
2	---	193	0	193	Suspect leaker
3	---	193	0	193	Suspect leaker, 6 to 102-B
4	---	194	0	194	Suspect leaker, 4 water, 5 to 102-B
1-1975	---	194	0	194	Suspect leaker, 1 to 102-B
2	---	194	0	194	Removed from service 3 to 102-B
3	---	194	0	194	" " "
4	---	194	0	194	" " "
1-1976	---	194	0	194	Removed from service
2	---	194	0	194	" " "
3	---	194	0	194	Inactive
4	---	194	0	194	"
1-1977	---	194	0	194	Questionable Integrity-Salt Well Pumping
2	---	194	0	194	Inactive
3	---	194	0	194	Inactive Current
4	---	194	0	194	" "

*Dry Well 20-07-02 drilled.

9 2 1 2 : 6 1 0 : 7

Waste Status Summary of 107-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	194	0	194	Inactive - Salt Well Installed
2-	-	194	0	194	
3-	-	194	0	194	P-10 Pmp. removed
4-	-	194	0	194	
1-1979	-	194	0	194	New Photo's 2/28/79
2-	-	194	0	194	Questionable Integrity Primary Stabilized
3-	-	194	0	194	<100 gal. pool
4-	-	194	0	194	
1-1980	-	194	0	194	New Solids Level 2/28/80
2-	-	194	0	194	
3-	-	194	0	194	
4-	-	194	0	194	

9 2 1 2 5 5 6 1 0 3

Waste Status Summary of 108-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944*	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	1C	450	---	---	First used Oct. 1945 (2nd in Cascade
1-1946	1C	530	---	---	Fill in Jan. 1946
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1947	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1948	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1949	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1950	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1951	1C	530	---	---	
2	1C	530	---	---	
3					
4					
1-1952					
2	EB	530	---	---	
3	EB	530	---	---	
4	EB	528	---	---	Cascade to 109-B-11-30-52

*Dry Well 20-08-02 drilled.

9 2 1 2 6 1 0 1 9

Waste Status Summary of 108-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	EB	359	325	34	Active bottoms tank. Pumped to 106-B on 2-18-53
2	EB	530	496	34	Re-evaporated bottoms
3	EB	530	496	34	1C re-evaporated bottoms
4	EB	530	496	34	1C re-evaporated bottoms
1-1954	EB	530	496	34 (1C)	1C re-evaporated bottoms
2	EB	530	496	34 (1C)	Scheduled to be pumped to ditch
3	---	65	0	65 (1C)	Pumped to ditch
4	---	65	0	65 (1C)	
1-1955	EB	233	168	65 (1C)	Rec'd TBP evap. bottoms from 110-B
2	EB	233	168	65 (1C)	
3	EB	526	461	65 (1C)	Rec'd from 111-B
4	EB	526	461	65 (1C)	
1-1956	EB	526	461	65 (1C)	
2	EB	526	461	65 (1C)	
3	EB	526	461	65 (1C)	
4	EB	526	461	65 (1C)	
1-1957	EB	527	462	65 (1C)	Latest electrode reading
2	EB	524	410	114	Latest electrode reading
3	EB	128	14	114	396 Scavenged
4	EB	128	14	114	
1-1958	EB	131	17	114	CW (1472 TU)
2	EB	134	20	114	CW (1461 TU) Latest electrode rdg.
3	EB	131	17	114	CW (1742 TU) Latest electrode rdg.
4	EB	134	20	114	CW (1729 TU) Latest electrode rdg.
1-1959	EB	130	16	114	CW (1746 TU) Latest electrode rdg.
2	EB	130	16	114	
3	EB	130	16	114	
4	EB	130	16	114	
1-1960	EB	130	16	114	
2	EB	130	16	114	
3	EB	130	16	114	
4	EB	130	16	114	
1-1961	EB	---	---	114	
2	EB	128	14	114	
3	EB	128	14	114	
4	EB	128	14	114	

9 2 1 2 5 6 1 0 6 0

Waste Status Summary of 108-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	EB	128	14	114	
2	EB	128	14	114	
3	EB	128	14	114	
4	EB	128	14	114	
1-1963	EB	---	---	---	
2	EB	131	11	120	
3	---	---	---	120	
4	EB-CW	541	11-410	120	410 CW
1-1964	EB-CW	541	11-410	120	
2	EB-CW	541	11-410	120	
3	EB-CW	541	11-410	120	
4	EB-CW	541	11-410	120	
1-1965	---	---	---	---	
2	EB-CW	538	6-407	65 (1C)-60 (EB)	
3	EB-CW	538	6-407	65 (1C)-60 (EB)	
4	EB-CW	538	6-407	125	
1-1966	EB-CW	538	6-407	125	
2	EB-CW	538	6-407	125	
3	EB-CW	538	6-407	125	
4	EB-CW	538	6-407	125	
1-1967	EB-CW	538	6-407	125	
2	EB-CW	538	6-407	125	
3	EB-CW	538	6-407	125	
4	EB-CW	538	6-407	125	
1-1968	EB-CW	536	6-405	125	
2	EB-CW	538	6-407	125	
3	EB-CW	538	6-407	65 (1C)-60 (EB)	
4	EB-CW	536	6-405	125	
1-1969	EB-CW	324	6-193	125	212 to 103-B
2	---	117	0	117	207 to 103-B
3	---	117	0	117	
4	IX	545	428	117	428 from 111-B
1-1970	IX	543	426	117	
2	IX	543	426	117	
3	IX	543	426	117	
4	IX	543	426	117	
1-1971	IX	542	425	117	
2	IX	542	420	122	
3	IX	543	421	122	
4	IX	543	465	78	

9211256 1061

Waste Status Summary of 108-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1972*	IX	125	12	113	417 to 103-B
2	IX	125	12	113	
3		127	14	113	
4	---	113	0	113	New tape
1-1973	---	112	0	112	
2	---	111	0	111	
3	---	111	0	111	
4	---	111	0	111	Suspect leaker
1-1974	---	114	0	114	
2	EB	156	42	114	39 from 107-BY
3	EB	156	42	114	
4	EB	156	44	112	
1-1975	EB	156	44	112	
2	EB	156	44	112	
3	EB	156	44	112	
4	EB	156	44	112	
1-1976	EB	156	44	112	
2	EB	156	44	112	
3	---	156	44	112	
4	---	156	44	112	Evap. Feed Dil.
1-1977	---	156	44	112	Evap. Feed Dil
2		112	0	112	" " "
3		112	0	112	" " "
4		103	33	70	Inactive Current

*Dry Wells 20-08-03, 20-08-05, 20-08-07, 20-08-09 drilled.

9 2 1 2 5 6 1 0 6 2

Waste Status Summary of 108-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	103	33	70	Inactive
2-	NCPLX	103	33	70	
3-	NCPLX	103	33	70	
4-	NCPLX	103	33	70	
1-1979	NCPLX	103	33	70	
2-	NCPLX	103	33	70	
3-	NCPLX	103	33	70	
4-	NCPLX	103	33	70	
1-1980	NCPLX	103	33	70	New Photo 1/3/80
2-	NCPLX	103	33	70	
3-	NCPLX	103	33	70	
4-	NCPLX	103	33	70	

9 2 1 2 5 6 1 0 3

Waste Status Summary of 109-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	1C	360	---	---	First used Jan. 1946 (Last in Casca
2	1C	530	---	---	Filled in April 1946
3	1C	530	---	---	
4	1C	530	---	---	
1-1947	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1948	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1949	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1950	1C	530	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	
1-1951	1C	530	---	---	
2	1C	530	---	---	
3					
4					
1-1952					
2	EB	172	---	---	
3	EB	518	---	---	Aug 21, 1952, Switched to 107-B
4	EB	535	---	---	Completed filling 12-4-52

9212561064

Waste Status Summary of 109-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	EB	330	330	0	Pumped to 106-B
2	EB	516	516	0	Re-evaporated bottoms
3	EB	530	530	0	1C re-evaporated bottoms
4	EB	527	527	0	1C re-evaporated bottoms
1-1954	EB	527	527	0	1C re-evaporated bottoms
2	EB	527	527	0	Scheduled to be pumped to ditch
3	EB	497	369	128	Pumped to ditch. Rec'd from 105-B
4	EB	494	366	128	
1-1955	EB	494	366	128	
2	EB	494	366	128	
3	EB	494	366	128	
4	EB	494	366	128	
1-1956	EB	494	366	128	
2	EB	494	366	128	
3	EB	494	366	128	
4	EB	494	366	128	
1-1957	EB	485	357	128	Latest electrode reading
2	EB	485	253	232	
3	---	76	0	76	410 Scavenged
4	---	76	0	76	
1-1958	EB	76	0	76	CW (1675 TU)
2	EB	79	3	76	CW (1664 TU)
3	EB	70	0	70	CW (2009 TU) Latest electrode rdg.
4	EB	73	3	70	CW (1996 TU) Latest electrode rdg.
1-1959	EB	76	6	70	CW (1982 TU) Latest electrode rdg.
2	EB	79	9	70	Latest electrode reading
3	EB	79	9	70	
4	EB	79	9	70	
1-1960	EB	79	9	70	
2	EB	79	9	70	
3	EB	79	9	70	
4	EB	79	9	70	
1-1961	EB	79	9	70	
2	EB	79	9	70	
3	EB	79	9	70	
4	EB	79	9	70	
1-1962	EB	79	9	70	
2	EB	79	9	70	
3	EB	---	---	70	
4	EB	81	11	70	Latest electrode reading

9 2 1 2 5 6 1 0 6 5

Waste Status Summary of 109-B Tank--Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1963	EB	---	---	---	
2	EB	84	0	84	
3	---	---	---	84	
4	CW	541	457	84	457 CW
1-1964	CW	541	457	84	
2	CW	541	457	84	
3	CW	---	---	84	
4	CW	538	454	84	Latest electrode reading
1-1965	---	---	---	---	
2	CW	538	404	134	New Electrode
3	CW	532	398	134	
4	CW	565	431	134	New Electrode
1-1966	CW	565	431	134	
2	CW	565	431	134	
3	CW	565	431	134	
4	CW	565	431	134	
1-1967	CW	565	431	134	
2	CW	565	431	134	
3	CW	565	431	134	
4	CW	565	431	134	
1-1968	CW	565	431	134	
2	CW	565	431	134	
3	CW	565	431	50(CW)-84(EB)	
4	CW	565	431	134	
1-1969	CW	565	431	134	
2	CW	564	430	134	
3	CW	171	37	134	393 to 103-B
4	CW-IX	538	37-367	134	367 from 111-B
1-1970	CW-IX	538	37-367	134	
2	CW-IX	536	8-367	161	
3	CW-IX	536	8-367	161	
4	CW-IX	538	8-369	161	
1-1971	CW-IX	536	8-369	161	
2	CW-IX	536	8-369	161	
3	CW-IX	536	8-367	161	
4	CW-IX	536	8-367	161	
1-1972	CW-IX	205	1- 68	136	333 to 103-B
2	IX	189	53	136	New tape
3	IX	206	70	136	New tape
4	IX	198	62	136	New tape

*Dry Wells 20-09-02, 20-09-06, 20-09-11 drilled.

9 2 1 2 5 5 6 1 0 6 6

Waste Status Summary of 109-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1973	IX	199	63	136	
2	IX	199	63	136	
3	IX	198	62	136	
4	IX	268	132	136	70 from 103-B
1-1974	224-IX	284	16-132	136	1 from 201-B, 3 from 202-B, 6 from 203-B, 6 from 204-B
2	224-IX-EB	393	18-134-105	136	2 from 201-B, 103 from 107-BY
3	224-IX-EB	397	18-136-107	136	4 from 201-B
4	224-IX-EB	403	6-149-117	117	6 from 201-B
1-1975	224-IX-EB	409	21-152-119	117	2 from 201-B
2	224-IX-EB	406	21-150-118	117	1 from 201-B
3	224-IX-EB	409	22-151-119	117	1 from 201-B
4	224-IX-EB	134	1-9-7	117	305 to 303-B
1-1976	224-IX-EB	260	1-7-35	117	4 to 103-B, 102 from 107-S 28 water
2	224-IX-EB	260	1-7-35	117	
3	---	260	143	117	
4	---	260	143	117	Evap. Feed Concentrate Residual Liquor Dilution
1-1977	---	260	143	117	Evap. Feed Conc.-Resid. Liq. Dil.
2	---	150	33	117	" " " " " "
3	---	139	19	120	" " " " " "
4	---	139	19	120	Inactive Current-Solid Level Adj.
1-1978	-	139	19	120	Inactive
2-	NCPLX	139	19	120	New Photo 4/18/78
3-	NCPLX	134	14	120	
4-	NCPLX	134	14	120	
1-1979	NCPLX	134	14	120	
2-	NCPLX	134	14	120	
3-	NCPLX	134	14	120	
4-	NCPLX	134	14	120	
1-1980	NCPLX	134	14	120	New Photo 2/6/80
2-	NCPLX	134	14	120	
3-	NCPLX	134	14	120	
4-	NCPLX	128	8	120	

9212556106 7

Waste Status Summary of 110-B Tank--Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	----	---	---	---	
1-1945	---	---			
2	2C	128	---	---	First used May 1945 (1st in Cascade)
3	2C	350	---	---	
4	2C	530	---	---	Filled in Dec. 1945
1-1946	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1947	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1948	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1949	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1950	2C	530	---	---	
2	---	0	---	---	Cribbed
3	2C	530	---	---	
4	2C	530	---	---	
1-1951	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1952	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	Active cascade
4	5-6-1C-2C	530	---	---	Active cascade

9212 6 1 0 0 3

Waste Status Summary of 110-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	5-6-1C-2C	530	---	---	Receives B Plant flushes
2	5-6-1C-2C	530	---	---	Receives B Plant flushes
3	5-6-1C-2C	530	152	378	Receives B Plant flushes
4	5-6-1C-2C	425	182	243	Pumped to 111-C
1-1954	5-6-1C-2C	421	178	243	
2	5-6-1C-2C-EB	530	132-155(EB)	243	Supernatant cribbed. Rec'd from 105B
3	5-6-1C-2C-EB	530	132-155(EB)	243	
4	5-6-1C-2C-EB	530	132-155(EB)	243	
1-1955	---	348	0	348	Pumped to 107-B and 108-B
2	---	348	0	348	
3	5-6-1C-2C	348	125	243	
4	5-6-1C-2C	451	208	243	Rec'd B Plant flush water
1-1956	5-6-1C-2C	501	258	243	Rec'd B Plant flush water
2	5-6-1C-2C	530	287	243	Rec'd B Plant flush water
3	5-6-1C-2C	530	287	243	Rec'd B Plant flush water
4	5-6-1C-2C	530	287	243	Rec'd B Plant flush water
1-1957	5-6	532	289	243	Rec'd B Plant flush water
2	5-6	535	292	243	Latest electrode reading
3	5-6	535	292	243	
4	5-6	535	292	243	
1-1958	5-6	535	292	243	CW
2	5-6	535	292	243	CW
3	5-6	535	292	243	CW
4	5-6	535	292	243	CW
1-1959	5-6	532	289	243	Latest electrode reading
2	5-6	532	289	243	
3	5-6	532	289	243	
4	5-6	532	289	243	
1-1960	5-6	532	289	243	
2	5-6	532	289	243	
3	5-6	532	289	243	
4	5-6	532	289	243	
1-1961	5-6	---	---	243	
2	5-6	530	287	243	
3	5-6	---	---	243	
4	5-6	538	295	243	8 from B Plant

9 2 1 2 5 6 1 0 6 9

Waste Status Summary of 110-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquids In Storage	Solid In Storage	Remarks
1-1962	5-6	---	---	243	
2	5-6	532	289	243	
3	5-6	532	289	243	
4	5-6	532	289	243	
1-1963	5-6	---	---	---	
2	5-6	530	248	282	Pumping to 112-B
3	---	---	---	282	
4	FP	365	83	282	Rec'd from 221-B, Pumped to 112-B
1-1964	FP	---	---	282	
2	FP	528	246	282	
3	FP	---	---	282	
4	FP	528	246	282	
1-1965	---	---	---	---	
2	FP	543	211	332	New electrode
3	FP	543	211	332	
4	FP	543	211	332	
1-1966	FP	541	209	332	
2	FP	541	209	332	
3	FP	541	209	332	
4	FP	541	209	332	
1-1967	FP	541	209	332	
2	FP	541	209	332	
3	FP	536	293	243	
4	FP	466	223	243	115 from B Plant, 153 to 112-B
1-1968	FP-EB	546	147-156	243	311 from cell 23, 135 from B Plant, 366 to 112-B
2	FP-EB	546	147-156	297	
3	FP-EB	546	93-156	297	
4	BL-EB	545	93-155	297	
1-1969	BL-EB	542	93-152	297	
2	BL-EB	541	93-151	297	
3	BL-IX	534	38-199	297	199 from B Plant(IX), 206 to 112-B
4	BL-IX	534	38-199	297	
1-1970	BL-IX	531	38-196	297	
2	BL-IX	530	38-195	297	
3	BL-IX	530	38-195	297	
4	BL-IX	530	38-195	297	

9 2 1 2 5 5 6 1 0 7 0

Waste Status Summary of 110-B Tank--Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	BL-IX	527	38-192	297	
2	BL-IX	525	38-190	297	
3	BL-IX	301	1-3	297	223 to 102-B
4	BL-IX	301	1-3	297	
1-1972	IX	299	2	297	
2	IX	288	6	282	New tape
3	---	282	0	282	6 flush water, 24 to 102-B
4	---	282	0	282	3 flush water, 14 to 102-B
1-1973	---	282	0	282	1 flush water, 3 to 102-B, suspect leaker
2	---	282	0	282	1 water, 3 to 102-B, suspect leaker
3	---	282	0	282	suspect leaker
4	---	282	0	282	suspect leaker
1-1974	---	282	0	282	suspect leaker
2	---	282	0	282	suspect leaker
3	---	282	0	282	suspect leaker
4	---	282	0	282	suspect leaker, 4 water, 7 to 102-B
1-1975	---	282	0	282	suspect leaker, 2 to 102-B
2	---	282	0	282	Removed from service, 3 to 102-B
3	---	282	0	282	" " " 5 to 102-B
4	---	282	0	282	" " " 5 to 102-B
1-1976	---	282	0	282	" " " 2 to 102-B
2	---	282	0	282	Removed from service, 1 to 102-B
3	---	282	0	282	Salt Well Pumped
4	---	282	0	282	" " "
1-1977	---	282	0	282	Questionable Integrity-Salt Well Pumping
2	---	282	0	282	Inactive Current-Salt Well Pumping
3	---	282	0	282	" " " " "
4	---	282	0	282	" " " " "

*Dry Wells 20-10-02, 20-10-07, 20-10-09, 20-10-12 drilled.

9212556107 1

Waste Status Summary of 110-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	282	0	282	Inactive - Primary Stabilized
2-	-	282	0	282	
3-	-	282	0	282	P-10 Pmp Removed
4-	-	282	0	282	
1-1979	-	282	0	282	
2-	-	282	0	282	Questionable Integrity
3-	-	282	0	282	New Photo 9/5/79
4-	-	282	0	282	
1-1980	-	282	0	282	
2-	-	282	0	282	
3-	-	282	0	282	
4-	-	282	0	282	

9 2 1 2 1 5 6 1 0 7 2

Waste Status Summary of 111-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	2C	181	---	---	First used Dec. 1945, (2nd in Cascac
1-1946	2C	473	---	---	
2	2C	530	---	---	Filled in April 1946
3	2C	530	---	---	
4	2C	530	---	---	
1-1947	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1948	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1949	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1950	2C	530	---	---	
2	2C	1	---	---	Cribbed
3	2C	530	---	---	Filled in July 1950
4	2C	530	---	---	
1-1951	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1952	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	Active cascade
4	5-6-1C-2C	530	---	---	Active cascade

9 2 1 2 3 6 1 0 7 3

Waste Status Summary of 111-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	5-6-1C-2C	530	---	---	Receives B plant flushes
2	5-6-1C-2C	530	---	---	Receives B plant flushes
3	5-6-1C-2C	530	293	237	Receives B plant flushes
4	5-6-1C-2C	530	369	161	Receives B plant flushes
1-1954	5-6-1C-2C	530	369	161	
2	5-6-1C-2C-EB	530	34-335(EB)	161	Supernatant cribbed. Rec'd from 105B
3	5-6-1C-2C-EB	530	34-335(EB)	161	
4	EB	530	335	195	
1-1955	EB	530	335	195	
2	EB	530	335	195	
3	---	249	0	249	Sent to 108-B
4	---	249	0	249	
1-1956	---	249	0	249	
2	5-6-1C-2C	251	2	249	Rec'd B plant flush water
3	5-6-1C-2C	265	16	249	Rec'd B plant flush water
4	5-6-1C-2C	270	27	243	Rec'd B plant flush water
1-1957	5-6	270	109	161	Rec'd B plant flush water
2	5-6	279	118	161	Rec'd B plant flush water
3	5-6	279	118	161	
4	5-6	279	118	161	
1-1958	5-6	282	121	161	Latest electrode reading.CW(915 TU)
2	5-6	282	121	161	
3	5-6	279	118	161	Latest electrode reading.CW(1096 TU)
4	5-6	279	118	161	
1-1959	5-6	334	173	161	New electrode reading
2	5-6	334	173	161	
3	5-6	334	173	161	
4	5-6	334	173	161	
1-1960	5-6	334	173	161	
2	5-6	334	173	161	
3	5-6	334	173	161	
4	5-6	334	173	161	
1-1961	5-6	---	---	161	
2	5-6	332	171	161	
3	5-6	---	---	161	
4	5-6	480	319	161	148 from B plant

9 2 1 2 5 6 1 0 7 4

Waste Status Summary of 111-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	5-6	---	---	161	
2	5-6	554	393	161	68 from B plant
3	5-6	554	393	161	
4	5-6	554	393	161	
1-1963	5-6	---	---	---	
2	5-6	343	43	300	Pumping to 112-B
3	---	---	---	300	
4	FP	337	37	300	Rec'd from 221-B and pumped to 112-B
1-1964	FP	---	---	300	
2	FP	338	38	300	Rec'd from 221-B and pumped to 112-B
3	FP	---	---	300	
4	FP	392	92	300	Rec'd from 221-B and pumped to 112-B
1-1965	---	---	---	---	
2	FP	381	71	310	166 from 221-B, 177 to 112-B
3	FP	442	132	310	61 from 221-B
4	FP	477	167	310	35 from 221-B
1-1966	FP	469	159	310	97 from 221-B, 105 to 112-B
2	FP	436	126	310	61 from 221-B, 94 to 112-B
3	FP	442	132	310	39 from 221-B, 33 to 112-B
4	FP	461	151	310	19 from 221-B
1-1967	FP	497	187	310	36 from 221-B
2	FP	395	85	310	89 from 221-B, 191 to 112-B
3	FP	426	265	161	31 from 221-B
4	FP-EB	523	82-280	161	Cell 23 conc. bottoms recycle
1-1968	FP-EB	521	80-280	161	
2	EB	519	278	241	
3	EB	519	278	241 (FP)	
4	EB	517	276	241	
1-1969	EB	513	272	241	
2	EB	388	147	241	127 to 112-B
3	EB-IX	300	24-35	241	214 from B plant(IX) 312 to 112-BY
4	IX	349	108	241	1119 from B plant(IX), 428 to 108-B, 367 to 109-B, 275 to 112-B
1-1970	IX	431	199	232	276 from B plant(IX), 208 to 103-B
2	IX	503	259	244	265 from B plant(IX), 11 flush, 7 from 301-B, 279 to 103-B
3	IX	503	259	244	
4	IX	502	258	244	

9212561075

Waste Status Summary of 111-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	IX	502	258	244	
2	IX	502	258	244	
3	IX	502	258	244	
4	IX	501	257	244	
1-1972	---	241	0	241	239 to 103-B
2	---	246	0	246	
3	IX	263	17	246	
4	IX	249	3	246	
1-1973*	---	249	0	249	
2	---	249	0	249	
3	---	249	0	249	
4	---	249	0	249	
1-1974	---	249	0	249	
2	---	249	0	249	
3	---	249	0	249	
4	IX	249	3	246	
1-1975	IX	249	3	246	
2	IX	249	3	246	
3	IX	249	3	246	
4	IX	249	3	246	
1-1976	IX	249	3	246	
2	IX	249	3	246	Removed from Service
3	---	249	3	246	
4	---	249	3	246	Evap. Feed Dil.
1-1977	---	249	3	246	Inactive-Minimum Heel
2	---	249	3	246	" " "
3	---	249	3	246	" Current-Minimum Heel
4	---	249	3	246	" " " "

*Dry Well 20-11-09 drilled.

9 2 1 2 5 6 1 0 7 6

Waste Status Summary of 111-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	249	3	246	Inactive
2-	NCPLX	249	3	246	
3-	NCPLX	249	3	246	
4-	NCPLX	249	3	246	New Photo's 11/13/78
1-1979	NCPLX	249	3	246	
2-	NCPLX	249	3	246	Questionable Integrity
3-	NCPLX	249	3	246	
4-	NCPLX	249	3	246	
1-1980	NCPLX	249	3	246	
2-	NCPLX	249	3	246	
3-	NCPLX	249	3	246	
4-	NCPLX	249	3	246	

9212561077

Waste Status Summary of 112-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	2C	342	---	---	First used April 1946(Last in Cascad
3	2C	530	---	---	Filled in August 1946
4	2C	530	---	---	
1-1947	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1948	2C	530	---	---	
2	2C	149	---	---	Cribbed 415. Started receiving in May
3	2C	353	---	---	
4	2C	530	---	---	Filled in December 1948
1-1949	2C	530	---	---	
2	2C	530	---	---	
3	2C	530	---	---	
4	2C	530	---	---	
1-1950	---	0	---	---	Cribbed
2	---	0	---	---	
3	2C	412	---	---	Started receiving in July
4	2C	200	---		756 to crib
1-1951	2C	396	---	---	496 to crib
2	2C	530	---	---	Continuous overflow to crib
3	2C	542	---	---	Continuous overflow to crib
4	2C	542	---	---	Continuous overflow to crib
1-1952	2C	542	---	---	Continuous overflow to crib
2	2C	542	---	---	Continuous overflow to crib
3	2C	542	---	---	Continuous overflow to crib
4	5-6-1C-2C	542	---	---	Continuous overflow to crib

9212961073

Waste Status Summary of 112-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	5-6-1C-2C	542	---	---	Continuous overflow to crib
2	5-6-1C-2C	542	---	---	Continuous overflow to crib
3	5-6-1C-2C	542	542	0	Continuous overflow to crib
4	5-6-1C-2C	542	542	0	Continuous overflow to crib
1-1954	5-6-1C-2C	542	542	0	Continuous overflow to crib
2	5-6-1C-2C	542	542	0	Cascades to crib
3	5-6-1C-2C	542	542	0	
4	5-6-1C-2C	542	542	0	
1-1955	5-6-1C-2C	542	542	0	
2	5-6-1C-2C	542	542	0	
3	5-6-1C-2C	542	542	0	
4	5-6-1C-2C	542	542	0	
1-1956	5-6-1C-2C	542	542	0	
2	5-6-1C-2C	542	542	0	
3	5-6-1C-2C	542	542	0	
4	5-6-1C-2C	542	542	0	
1-1957	5-6	538	538	0	Contaminated with EB
2	5-6	538	515	23	Contaminated with EB
3	5-6	538	515	23	Contaminated with EB
4	---	43	0	43	495 scavenged
1-1958	5-6	43	0	43	CW(1841 TU)
2	5-6	46	3	43	CW(1830 TU)Latest electrode reading
3	5-6	46	3	43	CW(2166 TU)
4	5-6	46	3	43	CW(2166 TU)
1-1959	5-6	46	3	43	Latest electrode reading
2	5-6	46	3	43	
3	5-6	45	2	43	
4	5-6	43	0	43	Latest electrode reading
1-1960	5-6	43	0	43	
2	5-6	43	0	43	
3	5-6	43	0	43	
4	5-6	32	0	43	Shows an unexplained 11,000 decrease
1-1961	5-6	---	---	---	
2	5-6	29	0	29	
3	5-6	---	---	29	
4	5-6	40	11	29	Latest electrode reading

921215 0 1 0 7 9

Waste Status Summary of 112-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	5-6	---	---	35	
2	5-6	35	0	35	
3	5-6	---	---	---	
4	5-6	40	0	40	5 from 221-B
1-1963	5-6	---	---	---	
2	5-6	271	236	35	Receiving from 110-B and 111-B
3	---	---	---	35	
4	FP	524	489	35	Receiving from 110-B and 111-B
1-1964	FP	---	---	35	
2	FP	536	501	35	Receiving from 110-B and 111-B
3	FP	536	501	35	
4	FP	536	501	35	
1-1965	---	---	---	35	
2	FP	450	415	35	117 from 111-B, 263 to 101-AX
3	FP	313	278	35	137 to 101-AX
4	FP	106	71	35	207 to 101-AX
1-1966	FP	211	176	35	105 from 111-B
2	FP	304	269	35	94 from 111-B
3	FP	337	302	35	33 from 111-B
4	FP	337	302	35	
1-1967	FP	337	302	35	
2	FP	528	493	35	191 from 111-B
3	FP	528	488	40	
4	FP-EB	169	80-49	40	Cell 23 conc. feed tank
1-1968	FP-EB	535	291-204	40	366 from 110-B
2	FP-EB	547	325-204	18	
3	FP-EB	547	325-204	18(FP)	
4	BL-EB	547	325-204	18	
1-1969	BL-EB	550	325-207	18	3 from pump testing caisson
2	EB	101	83	18	127 from 111-B,21 from 301-B C.T., 597 to 103-B
3	EB-IX	279	82-179	18	206 from 110-B, 312 from 111-B, 329 to 103-B
4	EB-IX	554	106-430	18	275 from 111-B
1-1970	EB-IX	553	106-429	18	
2	EB-IX	558	106-434	18	
3	EB-IX	558	106-434	18	
4	EB-IX	558	106-434	18	

9 2 1 2 5 5 6 1 0 8 0

Waste Status Summary of 112-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	EB-IX	557	106-433	18	
2	EB-IX	556	106-432	18	
3	EB-IX	557	106-433	18	
4	EB-IX	68	10-40	18	490 to 103-B
1-1972*	EB-IX	87	14-55	18	19 from 301-B
2	EB-IX	90	15-57	18	
3	EB-IX	77	13-50	14	New tape
4	EB-IX	77	13-50	14	
1-1973	EB	302	288	14	ITS bottoms and recycle
2	EB	303	289	14	ITS bottoms and recycle
3	EB	305	291	14	ITS bottoms and recycle
4	EB	305	291	14	ITS bottoms and recycle
1-1974	EB	305	291	14	ITS bottoms and recycle
2	EB	328	314	14	ITS bottoms and recycle
3	EB	329	315	14	ITS bottoms and recycle
4	EB	329	294	35	ITS bottoms and recycle
1-1975	EB	329	294	35	ITS bottoms and recycle
2	EB	329	294	35	ITS bottoms and recycle
3	EB	329	294	35	" " " "
4	EB	329	294	35	" " " "
1-1976	EB	329	294	35	" " " "
2	EB	329	294	35	" " " " (2)
3	---	332	297	35	Evap. Feed Con.
4	---	332	297	35	" " "
1-1977	---	332	297	35	Evap. Feed Con.
2	---	73	38	35	" " "
3	---	40	3	37	Inactive Current
4	---	40	3	37	Inactive Current

(2) Due to the characteristics of the solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of B, BX, BY Farm Tanks.

* Dry Wells 20-12-02, 20-12-03, 20-12-06, 20-12-07, 20-12-11 drilled.

9 2 1 2 5 5 6 1 0 8 1

Waste Status Summary of 112-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	40	3	37	Inactive
2-	NCPLX	40	3	37	
3-	NCPLX	43	6	37	
4-	NCPLX	43	6	37	
1-1979	NCPLX	43	6	37	
2-	NCPLX	43	6	37	Questionable Integrity
3-	NCPLX	43	6	37	
4-	NCPLX	43	6	37	
1-1980	NCPLX	43	6	37	
2-	NCPLX	43	6	37	
3-	NCPLX	43	6	37	
4-	NCPLX	43	6	37	

9212561012

Waste Status Summary of 201-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952	224	54.5	---	---	Active cascade to crib
2	224	54.5	---	---	Active cascade to crib
3	224	54.5	---	---	Active cascade to crib
4	224-MW	54.5	---	---	Active cascade to crib

9 2 1 2 1 5 6 1 0 1 3

Waste Status Summary of 201-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	224-MW	54.5	---	---	Receives B plant flushes
2	224-MW	54.5	0	54.5	
3	224-MW	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1954	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1955	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1956	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1957	224	53	0	54.5	Latest electrode reading
2	224	53	0	54.5	
3	224	53	24.5	28.5	
4	224	53	24.5	28.5	
1-1958	224	53	24.5	28.5	
2	224	53	24.5	28.5	
3	224	53	29.5	23.5	
4	224	51	22.5	28.5	Latest electrode reading
1-1959	224	51	22.5	28.5	
2	224	51	22.5	28.5	New electrode
3	224	51	22.5	28.5	
4	224	52	0	54.5	
1-1960	224	52	0	54.5	
2	224	52	0	54.5	
3	224	52	0	54.5	
4	224	52	0	54.5	
1-1961	224	---	0	54.5	
2	224	50	0	54.5	
3	224	50	0	54.5	
4	224	50	0	54.5	

9 2 1 2 5 5 6 1 0 8 4

Waste Status Summary of 201-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	224	50	0	54.5	
2	224	50	0	54.5	
3	224	---	---	---	
4	224	51	1	50	
1-1963	224	51	1	50	
2	224	51	1	50	
3	224	---	---	50	
4	224	53	3	50	Latest electrode reading
1-1964	224	53	3	50	
2	224	53	3	50	
3	224	53	3	50	
4	224	53	3	50	
1-1965	---	---	---	50	
2	224	56	6	50	
3	224	56	6	50	
4	224	56	6	50	
1-1966	224	56	6	50	
2	224	56	6	50	
3	224	56	6	50	
4	224	56	6	50	
1-1967	224	56	6	50	
2	224	56	6	50	
3	224	56	6	50	
4	224	56	6	50	
1-1968	224	55	5	50	
2	224	55	5	50	
3	224	55	5	50	
4	224	55	5	50	
1-1969	224	55	5	50	
2	224	55	5	50	
3	224	55	5	50	
4	224	55	5	50	
1-1970	224	55	25	30	
2	224	55	25	30	
3	224	55	25	30	
4	224	54	24	30	

9 2 1 2 5 6 1 0 8 5

Waste Status Summary of 201-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	224	54	24	30	
2	224	33	3	30	22 to 106-B
3	224	33	3	30	
4	224	33	3	30	
1-1972	224	33	7	26	
2	224	33	7	26	
3	224	33	7	26	
4	224	33	7	26	
1-1973	224	33	7	26	Suspect leaker
2	224	33	7	26	Suspect leaker
3	224	33	7	26	Suspect leaker
4	224	33	7	26	Suspect leaker
1-1974	224	32	6	26	Suspect leaker, 1 to 109-B
2	224	31	5	26	Suspect leaker, 2 to 109-B
3	224	29	3	26	Suspect leaker, 4 to 109-B
4	---	29	0	29	Suspect leaker, 4 water, 6 to 109-B
1-1975	---	29	0	29	Suspect leaker, 2 to 102-B
2	---	29	0	29	Removed from service, 1 to 109-B
3	---	29	0	29	" " "
4	---	29	0	29	" " "
1-1976	---	29	0	29	" " "
2	---	29	0	29	
3	---	29	0	29	
4	---	29	0	29	Salt Well Comp.
1-1977	---	29	0	29	Questionable Integrity
2	---	29	0	29	
3	---	29	0	29	Inactive-Stabilized
4	---	29	0	29	Inactive Current-Stabilized Phase I

Waste Status Summary of 201-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	29	0	29	Inactive - Primary Stabilized
2-	-	29	0	29	
3-	-	29	0	29	P-10 Pmp. Removed
4-	-	29	0	29	
1-1979	-	28	1	27	New Solids Level 1/29/79
2-	-	28	1	27	Questionable Integrity
3-	-	28	1	27	
4-	-	28	1	27	
1-1980	-	28	1	27	New Photo 2/4/80
2-	-	28	1	27	
3-	-	29	1	28	
4-	-	29	1	28	

9212561037

Waste Status Summary of 202-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952	224	54.5	---	---	Active cascade to crib
2	224	54.5	---	---	Active cascade to crib
3	224	54-5	---	---	Active cascade to crib
4	224-MW	54.5	---	---	Active cascade to crib

9 2 1 2 1 6 1 0 3 3

Waste Status Summary of 202-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	224-MW	54.5	---	---	Receives B plant flushes
2	224-MW	54.5	---	54.5	
3	224-MW	54.5	29.5	25.0	
4	224	54.5	29.5	25.0	
1-1954	224	54.5	29.5	25.0	
2	224	54.5	29.5	25.0	
3	224	54.5	29.5	25.0	Cascades to crib
4	224	54.5	29.5	25.0	Rec'd 5-6 water. Cascades to crib
1-1955	224	54.5	29.5	25.0	
2	224	54.5	29.5	25.0	Cascades to crib
3	224	54.5	29.5	25.0	Rec'd 224-B flush water. Cascades tc crib
4	224	54.5	29.5	25.0	
1-1956	224	54.5	29.5	25.0	
2	224	54.5	29.5	25.0	
3	224	54.5	29.5	25.0	
4	224	54.5	29.5	25.0	
1-1957	224	56	31	25.0	Latest electrode reading
2	224	56	31	25.0	
3	224	56	31	25.0	
4	224	56	31	25.0	
1-1958	224	56	31	25	
2	224	56	31	25	
3	224	56	31	25	
4	224	54	29	25	Latest electrode reading
1-1959	224	54	29	25	
2	224	54	29	25	New electrode
3	224	54	29	25	
4	224	54	29	25	
1-1960	224	54	29	25	
2	224	54	29	25	
3	224	51	26	25	
4	224	51	26	25	
1-1961	224	51	26	25	
2	224	51	26	25	
3	224	51	26	25	
4	224	51	26	25	

9 2 1 2 5 6 1 0 3 9

Waste Status Summary of 202-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	224	---	---	25	
2	224	54.5	29.5	25	7.5 from 221-B
3	224	---	---	25	
4	224	55	30	25	
1-1963	224	55	30	25	
2	224	55	30	25	
3	224	---	---	25	
4	224	54	29	25	Latest electrode reading
1-1964	224	54	29	25	
2	224	54	29	25	
3	224	54	29	25	
4	224	54	29	25	
1-1965	---	---	---	25	
2	224	58	33	25	
3	224	56	31	25	
4	224	56	31	25	
1-1966	224	56	31	25	
2	224	56	31	25	
3	224	56	31	25	
4	224	56	31	25	
1-1967	224	56	31	25	
2	224	56	31	25	
3	224	56	31	25	
4	224	56	31	25	
1-1968	224	56	31	25	
2	224	56	31	25	
3	224	56	31	25	
4	224	56	31	25	
1-1969	224	56	31	25	
2	224	56	31	25	
3	224	56	31	25	
4	224	56	31	25	
1-1970	224	56	27	29	
2	224	56	27	29	
3	224	56	27	29	
4	224	56	27	29	

9 2 1 2 5 5 6 1 0 9 0

Waste Status Summary of 202-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	224	56	27	29	
2	224	56	27	29	
3	224	56	27	29	
4	224	56	27	29	
1-1972	224	56	29	27	
2	224	56	29	27	
3	224	56	29	27	
4	224	56	29	27	
1-1973	224	56	29	27	
2	224	56	29	27	
3	224	56	29	27	
4	224	56	29	27	
1-1974	224	53	26	27	3 to 109-B
2	224	53	26	27	
3	224	53	26	27	
4	224	53	26	27	
1-1975	224	53	26	27	
2	224	53	26	27	
3	224	53	26	27	
4	224	53	26	27	
1-1976	224	53	26	27	
2	224	53	26	27	
3	---	53	26	27	Restricted
4	---	53	26	27	"
1-1977	---	53	26	27	Restricted
2	---	30	3	27	"
3	---	27	0	27	Inactive Current
4	---	27	0	27	" "

9 2 1 2 6 1 0 9 1

Waste Status Summary of 202-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	27	0	27	Inactive
2-	-	27	0	27	
3-	-	27	0	27	
4-	-	27	0	27	
1-1979	-	27	0	27	
2-	-	27	0	27	
3-	-	27	0	27	
4-	-	27	0	27	
1-1980	-	27	0	27	New Photo 2/4/80
2-	-	27	0	27	
3-	-	28	0	28	
4-	-	28	0	28	

9212561392

Waste Status Summary of 203-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952	224	54.5	---	---	Active cascade to crib
2	224	54.5	---	---	Active cascade to crib
3	224	54.5	---	---	Active cascade to crib
4	224-MW	54.5	---	---	Active cascade to crib

9 2 1 2 3 6 1 0 0 3

Waste Status Summary of 203-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	224-MW	54.5	---	---	Receives B plant flushes
2	224-MW	54.5	0	54.5	
3	224-MW	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1954	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1955	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1956	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1957	224	56	1.5	54.5	Latest electrode reading
2	224	56	1.5	54.5	
3	224	56	1.5	54.5	
4	224	56	1.5	54.5	
1-1958	224	56	1.5	54.5	
2	224	56	1.5	54.5	
3	224	56	1.5	54.5	
4	224	55	0.5	54.5	Latest electrode reading
1-1959	224	55	0.5	54.5	
2	224	55	0.5	54.5	
3	224	55	0.5	54.5	
4	224	55	0.5	54.5	
1-1960	224	55	0.5	54.5	
2	224	55	0.5	54.5	
3	224	55	0.5	54.5	
4	224	55	0.5	54.5	
1-1961	224	---	---	54.5	
2	224	54	0	54.5	
3	224	54	0	54.5	
4	224	54	0	54.5	

9212161024

Waste Status Summary of 203-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	224	---	---	54.5	
2	224	56	1.5	54.5	
3	224	56	---	---	
4	224	56	2	54	
1-1963	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	Latest electrode reading
1-1964	224	---	---	54	
2	224	55	1	54	New electrode
3	224	55	1	54	
4	224	55	1	54	
1-1965	---	---	---	54	
2	224	58	4	54	
3	224	56	2	54	
4	224	56	2	54	
1-1966	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1967	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1968	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1969	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1970	224	56	7	49	
2	224	56	7	49	
3	224	56	7	49	
4	224	56	7	49	

Waste Status Summary of 203-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	224	56	7	49	
2	224	56	7	49	
3	224	56	7	49	
4	224	56	7	49	
1-1972	224	56	12	44	
2	224	56	12	44	
3	224	56	12	44	
4	224	56	12	44	
1-1973	224	56	12	44	
2	224	56	12	44	
3	224	56	12	44	
4	224	56	12	44	
1-1974	224	50	6	44	6 to 109-B
2	224	50	6	44	
3	224	50	6	44	
4	224	50	6	44	
1-1975	224	50	6	44	
2	224	50	6	44	
3	224	50	6	44	
4	224	50	6	44	
1-1976	224	50	6	44	
2	224	50	6	44	
3	---	50	5	45	Restricted
4	---	50	5	45	"
1-1977	---	50	5	45	Restricted
2	---	50	5	45	"
3	---	50	3	47	Inactive Current-Solid Level Adj.
4	---	50	3	47	" " " " "

9 2 1 2 1 6 1 0 7 6

Waste Status Summary of 203-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	50	3	47	Inactive
2-	NCPLX	50	3	47	
3-	NCPLX	50	3	47	
4-	NCPLX	50	3	47	
1-1979	NCPLX	50	3	47	New Photo's 3/1/79
2-	NCPLX	50	3	47	
3-	NCPLX	50	3	47	
4-	NCPLX	50	3	47	
1-1980	NCPLX	50	3	47	New Photo 2/6/80
2-	NCPLX	50	3	47	
3-	NCPLX	50	2	48	
4-	NCPLX	50	2	48	

9212561077

Waste Status Summary of 204-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952	224	54.5	---	---	Active cascade to crib
2	224	54.5	---	---	Active cascade to crib
3	224	54.5	---	---	Active cascade to crib
4	224-MW	54.5	---	---	Active cascade to crib

9212161093

Waste Status Summary of 204-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	224-MW	54.5	---	---	Active cascade to crib
2	224-MW	54.5	0	54.5	
3	224-MW	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1954	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1955	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1956	224	54.5	0	54.5	
2	224	54.5	0	54.5	
3	224	54.5	0	54.5	
4	224	54.5	0	54.5	
1-1957	224	56	1.5	54.5	Latest electrode reading
2	224	56	1.5	54.5	
3	224	56	1.5	54.5	
4	224	56	1.5	54.5	
1-1958	224	56	1.5	54.5	
2	224	56	1.5	54.5	
3	224	56	1.5	54.5	
4	224	55	0.5	54.5	Latest electrode readings
1-1959	224	56	1.5	54.5	Latest electrode reading
2	224	56	1.5	54.5	New electrode
3	224	56	1.5	54.5	
4	224	54	0	54	Latest electrode reading
1-1960	224	54	0	54	New electrode installed
2	224	54	0	54	
3	224	54	0	54	
4	224	54	0	54	
1-1961	224	54	0	54	
2	224	54	0	54	
3	224	54	0	54	
4	224	54	0	54	

9 2 1 2 1 6 1 0 7 9

Waste Status Summary of 204-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	224	---	---	54.5	
2	224	56	1.5	54.5	
3	224	56	---	54	
4	224	56	2	54	
1-1963	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	Latest electrode reading
1-1964	224	---	---	54	
2	224	55	1	54	New electrode
3	224	55		54	
4	224	55		54	
1-1965	---	---	---	54	
2	224	58	4	54	
3	224	56	2	54	
4	224	56	2	54	
1-1966	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1967	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1968	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4	224	56	2	54	
1-1969	224	56	2	54	
2	224	56	2	54	
3	224	56	2	54	
4		56	2	54	
1-1970	224	56	8	48	
2	224	56	8	48	
3	224	56	8	48	
4	224	56	8	48	

Waste Status Summary of 204-B Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	224	56	8	48	
2	224	56	8	48	
3	224	56	8	48	
4	224	56	8	48	
1-1972	224	56	10	46	
2	224	56	10	46	
3	224	56	10	46	
4	224	56	10	46	
1-1973	224	56	10	46	
2	224	56	10	46	
3	224	56	10	46	
4	224	56	10	46	
1-1974	224	49	3	46	6 to 109-B
2	224	49	3	46	
3	224	49	3	46	
4	224	49	3	46	
1-1975	224	49	3	46	
2	224	49	3	46	
3	224	49	3	46	
4	224	49	3	46	
1-1976	224	49	3	46	Removed from Service
2	224	49	3	46	
3	---	49	3	46	Restricted
4	---	49	3	46	"
1-1977	---	49	3	46	Restricted
2	---	49	3	46	"
3	---	49	3	46	Inactive Current
4	---	49	3	46	" "

Waste Status Summary of 204-B Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	49	3	46	Inactive
2-	NCPLX	49	3	46	
3-	NCPLX	49	3	46	
4-	NCPLX	49	3	46	
1-1979	NCPLX	49	3	46	
2-	NCPLX	49	3	46	
3-	NCPLX	49	3	46	
4-	NCPLX	49	3	46	New Photo 10/16/79
1-1980	NCPLX	49	3	46	
2-	NCPLX	49	3	46	
3-	NCPLX	50	3	47	
4-	NCPLX	50	3	47	

9212561172

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	MW	303	---	---	Cascade began filling January
2	MW	523	---	---	Cascade full in June
3	MW	523	---	---	Cascade
4	MW	523	---	---	Cascade
1-1949	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1950	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	---	---	
2	MW	211	---	---	Removing Supernatant, MW removal in progress
3	---	165	0	165	MW removal in progress, sludge estimate
4	MW	200	50	150	Sludge estimate, MW removal in progress
1-1954	---	90	0	90	MW removal in progress
2	---	0	---	---	MW removal in progress, was emptied on 6-10-54
3	---	0	---	---	
4	---	0	---	---	
1-1955	---	0	---	---	
2	---	0	---	---	
3	---	0	---	---	
4	---	0	---	---	
1-1956	---	0	---	---	
2	---	0	---	---	
[illegible]	TBP	524	524	---	Rec'd from 106-BY
4	TBP	34	34	---	490 sent to #13BC ditch
1-1957	TBP	114	114	---	Latest electrode reading, rec'd 67 line drainage
2	TBP	114	114	---	
3	TBP	114	114	---	
4	TBP	120	120	---	Latest electrode reading
1-1958	TBP	123	123	---	Latest electrode reading
2	TBP	123	123	---	
3	TBP	125	125	---	Latest electrode reading
4	TBP	125	125	---	
1-1959	TBP	128	128	---	Latest electrode reading
2	TBP	130	130	---	
3	TBP	130	130	---	
4	TBP	131	131	---	Latest electrode reading
1-1960	TBP	131	131	---	
2	TBP	131	131	---	
3	TBP	131	131	---	
4	TBP	131	131	---	

9212556110 4

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	TBP	145	145	---	6 Month Report
3					
4	TBP	145	145	---	6 Month Report
1-1962					
2	TBP-CW	546	226-320	---	399 from 102-C and 103-C
3					6 Month Report
4	TBP-CW	552	226-326	---	New electrode installed
					6 Month Report
1-1963					
2	TBP-CW	554	142-328	84	6 Month Report
3					
4	TBP-CW	554	142-328	84	6 Month Report
1-1964					
2	TBP-CW	554	142-328	84	6 Month Report
3					
4	TBP-CW	557	142-331	84	Latest electrode reading
					6 Month Report
1-1965					
-	TBP-CW	560	158-334	68	6 Month Report
3	TBP-CW	560	158-334	68	
4	TBP-CW	563	158-337	68	
1-1966	TBP-CW	563	158-337	68	
2	TBP-CW	563	158-337	68	
3	TBP-CW	563	158-337	68	
4	TBP-CW	563	158-337	68	
1-1967	TBP-CW	565	158-339	68	
2	TBP-CW	565	158-339	68	
3	TBP-CW	565	158-339	68	
4	TBP-CW	173	1-104	68	392 to 112-B
1-1968	TBP-CW-EB	246	1-104-73	68	Rec'd 73 bottoms (cell 23)
2	TBP-CW-EB	348	10-104-175	59	102 from cell 23 conc.
3	EB	150	91	59	76 from cell 23 conc. 274 to 102-BX
4	BL	200	143	57	144 from 221-B (23-1) 94 to 102-BX
1-1969	BL	530	479	51	330 from221-B (23-1)
2	BL	534	469	65	4 from 221-B (23-1)
3	BL	501	473	28	
4	BL	499	456	43	

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	BL	114	66	48	385 to 103-C
2 *	BL	290	228	62	403 to 103-BX, 299 to 106-BX, 877 from B Plant IX (BL waste that was processed for removal of cesium in preparation for in-tank solidification)
3	OWW-CW-IWW	249	160-30-13	46	437 from 101-B, 849 from 104-C, 1877 to 103-BX, 550 from B Plant IX (Receipts from B Plant IX included: the zeiolite IX bed & flushes, 251 dilutes redox supernatant, the zeolon IX bed & flushes)
4	CW-OWW-RIX	360	28-129-157	46	1796 from B Plant IX, 448 from 101-B, 1614 from 104-C, 2495 to 103-BX, 1251 to 106-BX
1-1971	EB-SIX-RIX	213	33-108-21	51	1830 to 103-BX, 1027 to 106-BX, 529 from 101-B, 348 from 104-C, 1833 from B Plant IX
2	BL-CW-OWW-RIX	466	102-44-48 221	51	
	RIX	143	92	51	1523 from Plant IX, 89 from 104-C, 1375 to 105-SX, 200 to 101-TX, 360 to 103-SX
4	BL-CW-OWW-RIX	245	45-34-12 97	57	1430 from B Plant IX, 190 from 101-B, 102 from 104-C, 424 to 101-SX, 1196 to 105-SX
1-1972	BL-RIX	337	58-222	57	1010 from B Plant IX, 208 from 101-B, 1125 to 105-SX
2	BL-SIX	531	60-414	57	1414 from B Plant IX, 520 from 101-B, 443 to 103-BX, 742 to 102-SX, 390 to 105-SX, 165 to 101-TX
3	BL-IX	475	65-381	29	1100 from B Plant IX, 254 from 101-B, 498 to 101-T, 907 to 101-TX, 4 to 241-UX catch tank
4	BL-IX	146	40-77	29	368 from B Plant IX, 192 from 101-B, 205 to 104-BX, 686 to 101-TX
1-1973	BL-IX	142	39-74	29	
2	BL-IX	149	41-79	29	
3	BL-IX	151	42-80	29	
4	BL-IX	157	38-73	46	Suspect leaker
1-1974	BL-IX	160	39-75	46	Suspect leaker
2	---	46	0	46	Suspect leaker, 115 to 104-BX
	---	46	0	46	Suspect leaker, 1 to 104-BX
	BL-IX	46	1-2	43	Suspect leaker

* Leak Detection Dry Wells drilled:

21-01-01

21-01-03

9211255611106

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1975	BL-IX	46	1-2	43	Suspect leaker
2	BL-IX	46	1-2	43	Removed from service; 1 to 104-BX
3	BL-IX	46	1-2	43	Removed from service; 1 to 104-BX
4	BL-IX	46	1-2	43	Removed from service
1-1976	BL-IX	46	1-2	43	Removed from service; 1 to 104-BX
2	---	46	0	46	Removed from service; 1 to 104-BX
3	---	46	0	46	Removed from service; salt well
4	---	46	0	46	Salt well pumped
1-1977	---	46	0	46	Salt well pumped
2	---	46	0	46	Salt well pumped
3	---	46	0	46	Inactive current
4	---	46	0	46	Inactive current - salt well installed

9 2 1 2 6 1 1 7

Waste Status Summary of 101-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	46	0	46	Inactive - Primary Stabilized
2-	-	46	0	46	
3-	-	46	0	46	
4-	-	46	0	46	
1-1979	-	46	0	46	
2-	-	46	0	46	New Photo 6/22/79
3-	-	46	0	46	
4-	-	46	0	46	
1-1980	-	46	0	46	New Photo 3/17/80
2-	-	46	0	46	
3-	-	46	0	46	
4-	-	46	0	46	

9 2 1 2 5 6 1 1 0 8

Waste Status Summary of 102-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	MW	111	---	---	Cascade begain filling June
3	MW	523	---	---	Cascade full in September
4	MW	523	---	---	
1-1949	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1950	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full supernate jetting from 103 to 102, then cascades to 101-BY
2	MW	523	---	---	Cascade full
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	467	---	---	
3	MW	467	---	---	
4	MW	467	---	---	
1-1953	MW	467	---	---	
2	MW	380	---	---	MW removal in progress
3	MW	346	346	---	MW removal in progress
4	MW	386	386	---	Rec'd MW supervantant from 103-B, MW removal in progress

Waste Status Summary of 102-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	136	136	---	MW removal in progress
2	MW	12	12	---	MW removal in progress
3	---	0	---	---	Sludge only remaining
4	---	0	---	---	
1-1955	---	0	---	---	
2	---	0	---	---	
3	---	0	---	---	
4	---	0	---	---	
1-1956	---	0	---	---	
2	---	0	---	---	
3	TBP	439	439	---	Rec'd from 107-BY
4	TBP	43	43	---	344 to 12 BC ditch, 57 to 13 BC ditch
1-1957	TBP	51	51	---	Latest electrode reading
2	TBP	51	51	---	
3	TBP	51	51	---	
4	TBP	51	51	---	
1958	TBP	54	54	---	Latest electrode reading
	TBP	57	57	---	Latest electrode reading
3	TBP	54	54	---	Latest electrode reading
4	TBP	54	54	---	
1-1959	TBP	54	54	---	
2	TBP	54	54	---	
3	TBP	54	54	---	
4	TBP	54	54	---	
1-1960	TBP	54	54	---	
2	TBP	54	54	---	
3	TBP	54	54	---	
4	TBP	54	54	---	
1-1961					
2	TBP	57	57	---	6 month report
3					
4	TBP	59	59	---	Latest electrode reading 6 month report
1-1962					
2	TBP-CW	359	59-300	---	300 from 102-C and 103-C 6 month report
3					
4	TBP-CW	549	59-490	---	190 from 102-C 6 month report

9212356110

Waste Status Summary of 102-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	TBP-CW	549	59-490	---	6 month report
3					
4	TBP-CW	549	59-490	---	6 month report
1-1964					
2	CW	549	454	95	6 month report
3					
4	CW	549	454	94	6 month report
1-1965					
2	CW	543	481	62	New elect.
3	CW	543	481	62	
4	CW	543	481	62	
1-1966	CW	543	481	62	
2	CW	543	481	62	
3	CW	543	481	62	
4	CW	546	484	62	
1967	CW	546	484	62	
2	CW	546	484	62	
3	CW	546	484	62	
4	CW	543	481	62	
1-1968	CW	513	481	62	673 to cell 23 conc.
2	CW	539	477	62	550 to 103-BY, 576 from 103-BX
3	CW-EB	426	89-275	62	667 from 101 & 103-BX, 780 to 103-TY
4	CW-BL	520	151-308	61	94 from 101-BX
1-1969	CW-BL	520	151-306	63	
2	CW-BL	520	151-297	72	
3	CW-BL	487	137-299	51	
4	CW-BL	508	187-281	40	1909 from 103-BX, 1888 to 103-BY
1-1970	CW-OWW	233	63-135	35	644 to 109-BY, 1394 from 103-BX, 608 to 103-BY, 399 to 102-BY
2 *	BL	41	6	35	413 from 103-BX, 602 to 109-BY
3 **	---	40	0	40	
4	---	40	0	40	
1-1971	---	40	0	40	
2	---	40	0	40	Tank leaks
3	---	40	0	40	Tank leaks
4	---	41	0	41	Tank leaks approximately 105 tons of diatomaceous earth added to the tank

Leak detection dry wells drilled:

*21-02-01	*21-02-06	**21-27-01	**21-27-07	**21-27-10
21-02-03	21-02-07	21-27-02	21-27-08	
21-02-04	21-02-11	21-27-06	21-27-09	

Waste Status Summary of 102-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	---	41	0	41	Tank leaks
2	---	41	0	41	Tank leaks; contains diatomaceous earth
3	---	41	0	41	Tank leaks; contains diatomaceous earth
4	---	41	0	41	Tank leaks; contains diatomaceous earth
1-1973	---	41	0	41	Tank leaks; contains diatomaceous earth
2	---	41	0	41	Tank leaks; contains diatomaceous earth
3	---	41	0	41	Tank leaks; contains diatomaceous earth
4	---	41	0	41	Tank leaks; contains diatomaceous earth
1-1974	---	41	0	41	Tank leaks; contains diatomaceous earth
2	---	41	0	41	Tank leaks; contains diatomaceous earth
3	---	41	0	41	Tank leaks; contains diatomaceous earth
4	---	40	0	40	Tank leaks; contains diatomaceous earth
1-1975	---	40	0	40	Tank leaks; contains diatomaceous earth
2	---	40	0	40	Tank leaks; contains diatomaceous earth
	---	40	0	40	Tank leaks; contains diatomaceous earth
	---	40	0	40	Tank leaks; contains diatomaceous earth
1-1976	---	40	0	40	Tank leaks; contains diatomaceous earth
2	---	40	0	40	Tank leaks; contains diatomaceous earth
3	---	40	0	40	Cont. desiccant
4	---	40	0	40	Leaker desicant add cmp
1-1977	---	40	0	40	Stabilized and isolated; leaks
2	---	40	0	40	Stabilized and isolated; leaks
3	---	40	0	40	Stabilized Phase I, Isolated Phase A
4	---	40	0	40	Stabilized Phase I, Isolated Phase A

9 2 1 2 5 5 6 1 1 1 2

Waste Status Summary of 102-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	40	0	40	Leaker - Primary Stabilized Interim Isolated
2-	-	40	0	40	
3-	-	40	0	40	
4-	-	40	0	40	New Photo 11/13/78
1-1979	-	40	0	40	
2-	-	40	0	40	
3-	-	40	0	40	
4-	-	40	0	40	
1-1980	-	40	0	40	
2-	-	40	0	40	
3-	-	40	0	40	
4-	-	40	0	40	

9212561113

Waste Status Summary of 103-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1948	---	---	---	---	
2	---	---	---	---	
3	MW	9	---	---	Cascade begain filling September
4	MW	491	---	---	
1-1949	MW	523	---	---	Filled in January
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1950	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full, supernate jetting to 102-BX
2	MW	523	---	---	Cascade full
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

Waste Status Summary of 103-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	530	---	
4	MW	530	530	---	
1-1954	---	0	---	---	
2	MW	61	61	---	
3	---	0	---	---	Was emptied on 7-16-54
4	---	0	---	---	
1-1955	---	0	---	---	
2	---	0	---	---	
3	---	0	---	---	
4	---	0	---	---	
1-1956	---	0	---	---	
2	---	0	---	---	
3	TBP	530	530	---	Rec'd from 108-BY
4	TBP	45	45	---	74 to 11 BC ditch, 417 to 12 BC ditch
1957	TBP	45(E)	45	---	Estimated reading
2	TBP	54	54	---	New electrode reading
3	TBP	40	40	---	New electrode reading
4	TBP	40	40	---	New electrode reading
1-1958	TBP	37	37	---	Latest electrode reading
2	TBP	37	37	---	Latest electrode reading
3	TBP	37	37	---	
4	TBP	37	37	---	
1-1959	TBP	37	37	---	
2	TBP	37	37	---	
3	TBP	37	37	---	
4	TBP	45	45	---	
1-1960	TBP	45	45	---	
2	TBP	48	48	---	Reading will be re-checked
3	TBP	48	48	---	
4	TBP	48	48	---	
1-1961					
2	TBP	54	54	---	6 month report
3					
4	TBP	54	54	---	Latest electrode reading 6 month report

9 2 1 2 5 6 1 1 5

Waste Status Summary of 103-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	TBP	54	54	---	6 month report
3					
4	TBP-CW	538	54-484	---	484 from 102-C 6 month report
1-1963					
2	TBP-CW	538	54-484	---	6 month report
3					
4	TBP-CW	538	54-484	---	6 month report
1-1964					
2	CW	522	427	95	New electrode 6 month report
3					
4	CW	516	421	95	New elec. (read. confirmed) 6 month report
1-1965					
2	CW	527	437	90	New elect.
3	CW	527	437	90	
4	CW	527	437	90	
1966	CW	527	437	90	
2	CW	527	437	90	
3	CW	527	437	90	
4	CW	527	437	90	
1-1967	CW	527	437	90	
2	CW	527	437	90	
3	CW	527	437	90	
4	CW	557	467	90	
1-1968	CW	307	217	90	423 from 102-C, 641 to 102-BX
2	CW	209	119	90	576 to 102-BX, 496 from 102-C
3	CW-OWW	343	168-85	90	797 from 102-C, 392 to 102-BX, 289 to 103-TY
4	CW-OWW	314	142-98	74	883 from 102-C, 481 to 103-TY, 431 to 106-BX
1-1969	CW-OWW	378	122-184	72	478 from 102-C, 413 to 103-TY
2	CW-OWW	243	97-70	76	1421 from 102-C, 1556 to 103-B
3	CW-OWW	224	49-157	18	738 from 102-C, 724 to 103-B
4	CW-OWW	304	97-145	62	941 from 102-C, 1048 from 104-C, 1909 to 102-BX

9212556111 6

Waste Status Summary of 103-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW-OWW	110	23-50	37	1182 from 104-C, 17 from 311-ER CT, 1394 to 102-BX
2	CW-OWW-BL	425	64-123-187	51	1691 from 101-B, 101-BX & 104-C, 413 to 102-BX, 213 to 102-BY, 749 to 109-B
3	OWW-CW-1WW	389	269-51-21	48	104 from 104-C, 1877 from 101-BX, 603 to 102-BY, 1413 to 109-BY
4	CW-OWW-RIX	542	44-201-246	51	2495 from 101-BX, 780 to 102-BY, 1561 to 109-BY
1-1971	EB-SIX	442	71-320	51	1830 from 101-BX, 1147 to 102-BY, 785 to 109-BY
2	BL-CW-OWW-RIX	541	120-52-57-261	51	1196 from 101-BY, 899 to 102-BY, 198 to 109-BY
3	CW-OWW	437	201-185	51	896 from 104-C, 425 to 103-SX, 70 to 102-BY, 505 to 109-BY
4	CW-OWW	406	184-168	54	1230 from 104-C, 1260 to 109-BY
1-1972	CW-OWW	420	177-189	54	417 from 108-B, 333 from 109-B, 239 from 111-B, 326 to 109-BY, 264 to 105-C, 553 to 101-TX
	P-SIX-BL-CW-OWW-RIX	542	98-171-60-38-44-77	54	443 from 101-BX, 315 from 105-BX, 135 from 106-B, 595 from 104-C, 1365 to 109-BY
3	BL-CW-OWW-RIX	362	20-216-71-44	11	104 from 106-BX, 758 from 104-C, 1042 to 109-BY
4	CW-OWW	399	298-90	11	132 from 106-BX, 918 from 104-C
1-1973	IX-DW-BNW-PL-N	322	92-95-81-18-2	34	611 from 104-C, 130 from 105-BX, 133 from 106-BX, 980 to 109-BY
2 *	IX-PL-BNW-N-LW-CW	487	183-43-24-69-74-60	34	566 from 104-C, 384 from 105-BX, 785 to 109-BY
3	IX-PL-BNW-N-LW-CW	488	184-43-24-69-74-60	34	
4	IX-PL-BNW-N-LN-CW	503	186-43-24-69-75-30	46	71 from 002-BXR
1-1974	IX-PL-BNW-N-LW-CW	503	186-43-24-69-75-60	46	
2	IX-PL-BNW-N-LW-CW	504	187-43-24-69-75-60	46	
3	IX-PL-BNW-N-LW-CW	504	187-43-24-69-75-60	46	
4	BL-IX-PL-BNW-N-LW-CW	205	89-26-6-3-9-10-8	65	92 to 107-S

Leak detection dry wells drilled:

21-03-03
21-03-05
21-03-12

9211256117

Waste Status Summary of 103-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1975	BL-IX-PL-RNW-N-LW-CW	293	197-18-4-2-6-7-5	54	201 from 101-B, 114 to 106-SX
2	I X	238	184	54	647 from 104-BX, 703 to 106-SX
3	I X	499	445	54	878 from 104-BX, 618 to 106-SX
4	I X	169	115	54	275 from 104-BX, 603 to 110-SX
1-1976	I X	208	154	54	358 from 104-BX, 322 to 110-SX
2	I X	158	104	54	253 from 104-BX, 305 to 110-SX
3 *	Evap.	158	104	54	Low heat
4	Evap.	178	124	54	Low heat
1-1977	Evap.	189	113	76	Low heat
2	Evap.	76	0	76	Inactive - Salt well, pump salt well installed
3	Evap.	76	0	76	Inactive - Salt well, pump salt well installed
4	Evap.	76	0	76	Inactive - Salt well, pump salt well installed

9 2 1 2 6 1 1 8

* Leak detection dry wells drilled:

21-03-07
21-03-11

Waste Status Summary of 103-BX Tank-Capacity 530,000 - Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	76	0	76	Inactive - Salt Well Installed
2-	-	76	0	76	
3-	-	76	0	76	
4-	-	76	0	76	
1-1979	-	76	0	76	New Photo 3/8/79
2-	-	76	0	76	New Photo 6/22/79
3-	-	76	0	76	
4-	-	76	0	76	
1-1980	-	76	0	76	New Photo 2/7/80
2-	-	76	0	76	
3-	-	76	0	76	
4-	-	76	0	76	

9 2 1 2 3 6 1 1 1 9

Waste Status Summary of 104-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1948	---	---	---	---	
	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	MW	1	---	---	Began filling in January
2	MW	523	---	---	Cascade full in April
3	MW	523	---	---	Cascade
4	MW	523	---	---	Cascade
1-1950	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full, overflows to 104-BY
2	MW	523	---	---	Cascade full, overflows to 104-BY
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

9212561120

Waste Status Summary of 104-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	530	---	
4	MW	530	530	---	
1-1954	MW	530	530	---	
2	MW	430	430	---	Supernatant supply to 244-BXR
3	MW	80	0	80	Active sluicing TK
4	MW	145	138	7	Active sluicing TK, slurry storage while sluicing 105-BX with 221-U inoperative
1-1955	MW	20	19	1	
2	---	0	---	---	
3	---	0	---	---	
4	---	0	---	---	
1-1956	---	0	---	---	
2	TBP	530	530	---	Rec'd from 110-BY, filled from 106-BY
3	TBP	530	530	---	filled from 106-BY
	TBP	530	530	---	
1-1957	TBP	51	51	---	522 sent to 13-BC ditch, latest electrode reading
2	TBP	51	51	---	
3	TBP	54	54	---	Latest electrode reading
4	TBP	54	54	---	
1-1958	TBP	54	54	---	
2	TBP	54	54	---	
3	TBP	54	54	---	
4	TBP	54	54	---	
1-1959	TBP	54	54	---	
2	TBP	54	54	---	
3	TBP	54	54	---	
4	TBP	76	76	---	
1-1960	TBP	57	57	---	New electrode installed
2	TBP	57	57	---	
3	TBP	57	57	---	
4	TBP	57	57	---	
1-1961					
2	TBP	59	59	---	6 month report
	TBP	62	62	---	Latest electrode reading 6 month report

Waste Status Summary of 104-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	TBP	62	62	---	
3					
4	TBP-CW	530	62-468	---	468 from 102-C
1-1963					
2	CW	557	445	112	Latest Electrode Reading
3					
4	CW	557	445	112	
1-1964					
2	CW	569	457	112	12 CW from 108-C
3					
4	CW	569	457	112	
1-1965					
2	CW	571	484	87	
3	CW	571	484	87	
4	CW	571	484	87	
1-1966	CW	571	484	87	
2	CW	571	484	87	
3	CW	571	484	87	
4	CW	571	484	87	
1-1967	CW	571	484	87	
2	CW	571	484	87	
3	CW	571	484	87	
4	CW IX-EB	183	7-72-17	87	477 to 103-BY, Received 89 IX and cell 23 bottom
1-1968	EB IX	491	1-405	87	Received 112 IX & 254 (Cell 23) 418 to 106-BX, received 359 IX
2	IX	290	203	87	317 to 104 BY, 126 IX received
3	IX	399	312	87	274 IX received, 184 to 104 BY
4	IX	481	408	73	519 from 221-B (18-1), 437 to 105 BX
1-1969	IX	227	137	90	261 from 221-B (18-1), 516 to 106 BX
2	IX	260	172	88	769 from 221-B (18-1), 452 to 108 BX, 283 to 111 BX
3	IX	524	467	57	611 from B Plant (18-1), 165 to 107 BX, 149 to 111 BX
4	IX	519	454	65	
1-1970	IX	520	455	65	
2	IX	96	31	65	764 from 106 & 110-BX, 1191 to 110-C
3	---	65	0	65	458 from 111 BX, 490 to B & C farm
4	EB	70	5	65	5 from line leak check

Waste Status Summary of 104-BX Tank-Capacity 530,000

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	H_2O-R	523	97-358	68	Received 100 water, 376 from 103-SX, 25 (5 water and 18 RSN) were transferred from 104-BX to B Plant IX.
2	H_2O-R	466	64-334	68	85 from 101 BX, 829 from 102 SK, 132 from 103-SK, 209 dilution water, 1311 to B Plant (TK-17-2)
3	H_2O-R	473	95-310	68	1014 from 102-SX, 274 dilution water, 1278 to B Plant (TK-17-2)
4	H_2O-R	487	90-319	78	1005 from 102-SX, 244 dilution water, 1239 to B Plant (TK-17-2)
1-1972	H_2O-R	443	62-340	41	670 from 102-SX, 136 dilution water, 850 to B Plant (TK-17-2)
2	Water-R	246	32-173	41	230 from 102-SX, 38 dilution water, 440 to B Plant (TK-17-2)
3	R	246	205	41	
4	BL IX	364	84-239	41	749 from B Plant IX, 199 from 101-B_2 205 from 101-BX, 6 flush H_2O.
1-1973	BL IX	512	37-413	62	961 from B Plant IX, 484 from 101-B, 63 to 105-T, 685 to 107-T, 558 to 101-TX
2	IX	496	434	62	1272 from B Plant IX, 184 to 103-B, 532 to 105-BX, 573 to 107-T.
3	IX	495	433	62	
4	IX	501	439	62	
1-1974	IX	149	43	106	10 from 302-C Catch Tank, 363 to 110-S
2	BL IX	277	42-129	106	14 from 311-ER Catch Tank, 115 from 101BX
3	BL IX	480	42-332	106	201 from B Plant, 1 from 101-BX, 2 water
4	BL IX	389	36-288	65	92 to 107-S
1-1975	IX	403	338	65	204 from B Plant, 10 from BX-302-A, 78 from 001-BXR, 278 to 107-S
2	IX	414	349	65	605 from B Plant, 34 from 001-BXR, 7 from 003-BXR, 13 from 011-BXR, 1 from 101-BX, 647 to 103-BX
3	IX	211	146	65	674 from B Plant, 1 from 101-BX, 878 to 103-BX
4	IX	290	225	65	2 water, 32 from 112-BY, 283 to 110-SX
1-1976	IX	351	286	179	410 from B Plant, 358 to 103-BX, 7 from 002-BXR
2	IX	252	187	65	154 from B Plant, 253 to 103-BX
3	Evap.	299	234	65	Lo Heat
4	Evap.	235	170	65	Lo Heat

Leak detection dry wells installed:

21-04-03
21-04-06

Waste Status Summary of 104-BX Tank-Capacity 530,000

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	Evap.	447	382	65	Customer Waste Receiver, Evap. Feed Trans.
2 **	Evap.	373	297	76	Customer Waste Receiver, Evap. Feed Trans.
3	Evap.	241	162	79	Customer Waste Receiver, Evap. Feed Trans.
4	Evap.	142	63	79	Customer Waste Receiver, Evap. Feed Trans.

* Leak detection dry wells installed 2nd quarter 1977:

21-04-01
21-04-04
21-04-08
21-04-11

Waste Status Summary of 104-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	279	165	114	Active Wst. received Evap. Feed Trans. TK.
2-	NCPLX	263	129	134	Solids Level Detm. 4/14/78
3-	NCPLX	271	137	134	
4-	DSSF	312	176	136	Solids Level Adj. 12/14/78 Cross Site Transfer
1-1979	CPLX	136	0	136	
2-	CPLX	136	0	136	
3-	CPLX	147	11	136	
4-	CPLX	216	80	136	
1-1980	DSSF	172	36	136	Liq. Level Adjusted
2-	CPLX	352	216	136	
3-	DSSF	342	206	136	
4-	NCPLX	110	20	90	New Solids Level 11/17/80 * Deactivated

9212 5 6 1 1 2 5

Waste Status Summary of 105-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	MW	361	---	---	Cascade began filling April
3	MW	523	---	---	Cascade full in September
4	MW	523	---	---	Cascade
1-1950	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1953	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	530	---	
4	MW	530	530	---	

Waste Status Summary of 105-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	530	530	---	
2	MW	512	512	---	Transferred to 109-BY
3	MW	48	48	---	Contains water for sluicing
4	MW	54	49	5	Active sluicing TK
1-1955	MW	37	36	1	
2	MW	1	1	---	
3	MW	1	1	---	
4	MW	60	60	---	Leach TK to recover U
1-1956	MW	60	60	---	Leach TK to recover U
2	MW	60	60	---	Leach TK to recover U
3	TBP	524	524	---	Filled from 110-BY
4	TBP	524	524	---	
1-1957	TBP	224	224	---	275 to #14BC ditch, latest electrode reading
2	TBP	224	224	---	
3	TBP	62	62	---	162 to 102-BY
4	TBP	62	62	---	
1-1958	TBP	62	62	---	
2	TBP	62	62	---	
3	TBP	62	62	---	
4	TBP	62	62	---	
1-1959	TBP	98	98	---	New electrode reading
2	TBP	98	98	---	
3	TBP	98	98	---	
4	TBP	98	98	---	
1-1960	TBP	98	98	---	
2	TBP	98	98	---	
3	TBP	98	98	---	
4	TBP	98	98	---	
1-1961					
2	TBP	98	98	---	6 month report
3					
4	TBP	101	101	---	Latest electrode reading 6 month report
1-1962					
2	TBP	101	101	---	6 month report
3					
4	TBP	101	101	---	6 month report
1963					
2	CW	546	440	106	445 from 102-C 6 month report
3					
4	CW	546	440	106	6 month report

Waste Status Summary of 105-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	CW	440	334	106	Pumping to 109-BX
3					
4	CW	541	435	106	103-CW from 102-C
1-1965					
2	TBP-CW	538	3-437	98	
3	TBP-CW	538	3-437	98	
4	TBP-CW	538	3-437	98	
1-1966	TBP-CW	538	3-437	98	
2	TBP-CW	538	3-437	98	
3	TBP-CW	538	3-437	98	
4	TBP-CW	535	3-434	98	
1-1967	TBP-CW	535	3-434	98	
2	TBP-CW	535	3-434	98	
3	TBP-CW	535	3-434	98	
4	TBP-CW	534	3-433	98	
968	CW	435	340	95	321 to 103-BY, 222 from 102-C
2	CW	538	440	98	103 from 102-C
3	CW	109	11	98	429 to 103-BY
4	CW IX	546	11-437	98	437 from 104-BX
1-1969	CW IX	546	11-437	98	
2	CW IX	546	11-437	98	
3	IX	513	448	65	
4	IX	513	448	65	
1-1970	IX	514	449	65	
2	IX	514	449	65	
3	IX	513	448	65	
4	IX	513	448	65	
1-1971	IX	514	449	65	
2	IX	520	455	65	
3 *	IX	523	458	65	
4	IX	523	458	65	
1-1972	IX	516	464	52	
2	IX	201	149	52	3 flush water, 315 to 103-BX
3	IX	194	142	52	
4	IX	56	4	52	133 to 106-BX
973	IX	359	307	52	432 from 108-BX, 130 to 103-BX
	IX	486	434	52	531 from 104-BX, 384 to 103-BX, 17 to 106-BX
3	IX	485	433	52	
4	IX	481	429	52	

*Leak detection dry wells drilled: 21-05-02; 21-05-03; 21-05-05; 21-05-06; 21-05-10; 21-05-12

Waste Status Summary of 105-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	IX	101	49	52	381 to 110-S
2	EB-IX	411	156-203	52	313 from 112-BX
3	EB-IX	416	158-206	52	
4	EB-IX	417	158-205	54	
1-1975	EB-IX	417	158-205	54	
2	EB-IX	436	177-205	54	20 from 101-BY
3	EB-IX	436	177-205	54	
4	EB-IX	189	80-55	54	2 water, 32 from 112-BY, 283 to 110-SX
1-1976	EB-IX	508	398-56	54	311 from 112-BY, 9 from 003-BXR
2	EB-IX	508	398-56	54	
3	EVAP	508	454	54	Evap. feed bottoms
4	EVAP	436	382	54	
1-1977	EVAP	472	418	54	Active evap. feed concentrate; Evap. feed storage
2	EVAP	427	41	62	Active evap. feed concentrate; Evap. feed storage
3	EVAP	131	52	79	Active salt well recovery; Evap. feed storage
4	EVAP	131	52	79	Active salt well recovery; Evap. feed storage

9212556

Waste Status Summary of 105-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	134	55	79	Active-Salt Well Receiver Evap. Feed Storage
2-	NCPLX	128	66	62	Cross Site Receiver
3-	NCPLX	114	49	65	
4-	DSSF	211	138	73	Solids Level Adj. 12/14/78 Cross Site Transfer
1-1979	CPLX	281	176	73	New Photo 3/7/79
2-	CPLX	249	176	73	
3-	CPLX	114	41	73	PMP W/FLX Float
4-	CPLX	112	39	73	
1-1980	DSSF	172	99	73	Cross-Site Transfer
2-	CPLX	378	321	57	New Solids Level 6/30/80
3-	DSSF	305	248	57	
4-	NCPLX	82	25	57	11/17/80 Deactivated

9212561120

Waste Status Summary of 106-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	MW	78	---	---	Cascade began filling September
4	MW	470	---	---	Cascade
1-1950	MW	523	---	---	Cascade filled in January
2	MW	523	---	---	Cascade full
3	MW	523	---	---	Cascade full
4	MW	523	---	---	Cascade full
1-1951	MW	523	---	---	Cascade full
2	MW	523	---	---	Cascade full
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1953	MC	530	---	---	
	MC	530	---	---	
3	MC	530	530	---	
4	MC	530	530	---	

Waste Status Summary of 106-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	530	530	---	
2	MW	530	530	---	
3	MW	1	1	---	Supernatant supply for 109-BY, pumped to 109-BY
4	MW	1	1	---	
1-1955	MW	34	34	---	
2	---	0	---	---	
3	---	0	---	---	
4	---	0	---	---	
1-1956	---	0	---	---	
2	TBP	524	524	---	Filled from 108-BY
3	TBP	524	524	---	
4	TBP	524	524	---	
1-1957	TBP	505	505	---	Latest electrode reading
2	TBP	521	521	---	Latest electrode reading
3	TBP	57	57	---	Latest electrode reading, 467 to 102-BY
4	TBP	57	57	---	
1-1958	TBP	57	57	---	
2	TBP	57	57	---	
3	TBP	57	57	---	
4	TBP	57	57	---	
1-1959	TBP	98	98	---	New electrode reading
2	TBP	98	98	---	
3	TBP	98	98	---	
4	TBP	98	98	---	
1-1960	TBP	98	98	---	
2	TBP	98	98	---	
3	TBP	98	98	---	
4	TBP	98	98	---	
1-1961					
2	TBP	98	98	---	
3					
4	TBP	98	98	---	
1-1962					
2	TBP	98	98	---	
3					
4	TBP	98	98	---	
1-1963					
2	TBP-CW	541	98-443	---	443 from 102-C 6 month report
3					
4	TBP-CW	541	98-443	---	6 month report

Waste Status Summary of 106-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	TBP-CW	541	98-443	---	
3					
4	TBP-CW	543	98-445	---	
1-1965					
2	TBP-CW	543	44-445	54	
3	TBP-CW	543	44-445	54	
4	TBP-CW	543	44-445	54	
1-1966	TBP-CW	543	44-445	54	
2	TBP-CW	543	44-445	54	
3	TBP-CW	543	44-445	54	
4	TBP-CW	543	44-445	54	
1-1967	TBP-CW	541	44-443	54	
2	TBP-CW	541	44-443	54	
3	CW	65	11	54	476 to 103-BY
4	CW	62	8	54	
968	CW-EB IX	480	79-205-142	54	Received 418 from 104-BX
2	CW-EB IX	480	79-205-142	54	
3	EB-CW	403	50-299	54	408 from 111-BX & 112-BX, 485 to 103-BY
4	---	33	0	33	1782 from BX Farm, 2152 to 103-BY
1-1969	IX	550	517	33	516 from 104-BX
2	IX	552	519	33	
3	IX	517	517	0	
4	IX	516	516	0	
1-1970	IX	514	514	0	
2	IX-BL	334	35-299	0	479 to 104-BX, 299 from 101-BX
3	IX-BL	334	35-299	0	
4	BL-OWW-RIX	541	100-204-200	37	1251 from 101-BX, 1048 to 103-TY
1-1971	EB-SIX	411	74-294	43	1027 from 101-BX, 356 to 103-BY, 798 to 118-TX
2 *	BL-CW-OWW-RIX	495	111-48-52-241	43	2297 from 101-BX, 1205 to 101-TX, 966 to 105-TX, 43 to 102-BY
3	BL-CW-OWW-RIX	466	104-45-49-225	43	30 to 109-BY
4	BL-CW-OWW-RIX	466	102-44-48-221	51	
1-1972	BL-CW-OWW-RIX	465	104-45-49-227	65	
2	BL-CW-OWW-RIX	318	68-29-32-149	40	
3	BL-CW-OWW-RIX	202	47-20-22-103	10	104 to 103-BX
	BL-CW-OWW-IX	200	14-6-6-164	10	133 from 105-BX, 132 to 103-BX
1-1973	BL-CW-OWW-IX	73	5-2-2-54	10	10 flush water, 133 to 103-BX
2	BL-CW-OWW-IX	347	5-2-2-328	10	17 from 105-BX, 271 from 109-BX
3	BL-CW-OWW-IX	348	5-2-2-329	10	
4	BL-CW-OWW-IX	348	5-2-2-329	10	

* Leak detection dry wells drilled: 21-06-01; 21-06-02; 21-06-03; 21-06-10

Waste Status Summary of 106-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	BL-CW-OWW-IX	394	5-2-2-375	10	43 from 108-BX
2	BL-CW-OWW-IX	182	26-1-1-144	10	64 from 101-B, 2 from 108-BX, 277 to 107-S
3	BL-CW-OWW-IX	251	26-1-1-213	10	1 from 108-BX, 66 from 107-BX
4	BL-CW-OWW-IX-EB	315	25-1-1-201-61	26	1 from 108-BX, 61 from 112-BY
1-1975	BL-CW-OWW-IX-EB	464	25-1-1-201-210	26	1 water, 25 from 107-BY, 123 from 110-BY
2	EB-IX-BL	230	170-30-4	26	114 from 110-BY, 66 from 112-BY, 413 to 106-SX
3	EB-IX-BL	230	170-30-4	26	
4	EB-IX-BL	230	170-30-4	26	
1-1976	EB-IX-BL	277	217-30-4	26	6 from 112-BY
2	EB-IX-BL	323	240-53-4	26	46 from 112-BY
3	EVAP	323	297	26	Lo Heat
4	EVAP	101	75	26	Lo Heat
1-1977	EVAP	233	207	26	Active - space - low heat
2	EVAP	70	44	26	Active - space - low heat
3	EVAP	43	14	29	Inactive current
4	EVAP	43	14	29	Inactive current - open hole salt well

9 2 1 2 5 5 6 3

Waste Status Summary of 106-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	43	14	29	Inactive-Open Hole Salt Well
2-	NCPLX	43	14	29	
3-	NCPLX	43	14	29	
4-	NCPLX	43	14	29	Pmp w/flx float new photo 11/2/78
1-1979	NCPLX	43	14	29	
2-	NCPLX	43	14	29	
3-	NCPLX	43	14	29	
4-	NCPLX	43	14	29	
1-1980	NCPLX	43	14	29	
2-	NCPLX	43	14	29	
3-	NCPLX	43	14	29	
4-	NCPLX	43	14	29	

9 2 1 2 1 5 6 1 1 3 5

Waste Status Summary of 107-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
948	---	---	---	---	
2	---	---	---	---	
3	1C	41	---	---	Began filling September
4	1C	332	---	---	
1-1949	1C	523	---	---	Cascade full in March
2	1C	523	---	---	Cascade
3	1C	523	---	---	Cascade full
4	1C	523	---	---	Full
1-1950	1C	523	---	---	Full
2	1C	523	---	---	Full
3	1C	523	---	---	Full
4	1C	523	---	---	Cascade
1-1951	1C	523	---	---	Cascade
2	1C	523	---	---	Cascade
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	437	---	---	Finished pumping 12/18/52; down to sludge
953	---	437	---	437	
	TBP	530	---	437	
3	TBP	530	93	437	
4	TBP	530	93	437	

Waste Status Summary of 107-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	TBP	530	93	437	
2	TBP	530	93	437	Overflow to 108-BX; plugged
3	TBP	530	93	437	
4	TBP	530	93	437	
1-1955	TBP	530	93	437	
2	TBP	530	93	437	
3	TBP	530	93	437	
4	TBP	530	93	437	
1-1956	TBP	530	93	437	
2	TBP	530	93	437	
3	TBP	530	93	437	
4	TBP	530	93	437	
1-1957	TBP	530	93	437	Latest electrode reading
2	TBP	565	12	437	Latest electrode reading
3	TBP	565	128	437	
4	TBP	565	128	437	
1-1958	TBP	565	128	437	
2	TBP	563	126	437	Latest electrode reading
3	TBP	563	126	437	
4	TBP	563	126	437	
1-1959	TBP	563	126	437	
2	TBP	563	126	437	
3	TBP	563	126	437	
4	TBP	563	126	437	
1-1960	TBP	563	126	437	
2	TBP	563	126	437	
3	TBP	563	126	437	
4	TBP	563	126	437	
1-1961					
2	TBP	563	126	437	6 month report
3					
4	TBP	565	128	437	Latest electrode reading 6 month report
1-1962					
2	TBP	563	126	437	Latest electrode reading
3					6 month report
4	TBP	563	126	437	6 month report
1963					
	TBP	560	113	447	6 month report
3					
4	TBP	560	113	447	6 month report

Waste Status Summary of 107-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	TBP	558	111	447	6 month report
3					
4	TBP	549	102	447	New electrode (reading confirmed) 6 month report
1-1965					
2	1C-TBP	563	9-126	428	New electrode
3	1C-TBP	563	9-126	428	
4	1C-TBP	563	9-126	428	
1-1966	1C-TBP	563	9-126	428	
2	1C-TBP	563	9-126	428	
3	1C-TBP	563	9-126	428	
4	1C-TBP	563	9-126	428	
1-1967	1C-TBP	563	9-126	428	
2	1C-TBP	563	9-126	428	
3	1C-TBP	563	9-126	428	
4	1C-TBP	563	9-126	428	
968	1C-TBP	567	9-130	428	
2	1C-TBP	568	9-131	428	
3	1C-TBP	567	9-130	428	
4	---	409	0	409	158 to 106-BX
1-1969	---	409	0	409	
2	---	409	0	409	
3	IX	541	165	376	165 from 107-BX
4	IX	541	165	376	
1-1970	IX	541	165	376	
2	IX	541	165	376	
3	IX	541	165	376	
4	IX	541	165	376	
1-1971	IX	541	165	376	
2	IX	538	162	376	
3	IX	538	162	376	
4	IX	538	162	376	
1-1972	IX	538	162	376	
2	IX	538	162	376	
3	IX	538	162	376	
4	IX	538	162	376	
973	IX	537	161	376	
	IX	537	161	376	
3	IX	541	165	376	
4*	IX	539	163	376	

* Leak detection dry wells drilled: 21-07-03; 21-07-06

Waste Status Summary of 107-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	IX	539	163	376	
2	IX	539	163	376	
3	IX	474	98	376	66 to 106-BX
4	IX	472	96	376	Awaiting solidification
1-1975	IX	472	96	376	Awaiting solidification
2	IX	472	96	376	
3	IX	472	96	376	
4	IX	472	96	376	
1-1976	IX	472	96	376	
2	IX	472	96	376	
3	EVAP	475	99	376	Evap. feed dil.
4	EVAP	475	99	376	
1-1977	EVAP	475	99	376	Evap. feed dil.
2	EVAP	376	0	376	Evap. feed dil.
3	EVAP	376	0	376	Inactive current
4	EVAP	376	0	376	Inactive current; open hole salt well

9 2 1 2 5 6 9

Waste Status Summary of 107-BX Tank-Capacity ≐530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	376	0	376	Inactive
2-	-	376	0	376	
3-	-	376	0	376	
4-	-	376	0	376	
1-1979	-	376	0	376	New photo 3/9/79
2-	-	376	0	376	
3-	-	376	0	376	
40	-	376	0	376	
1-1980	-	376	0	376	
2-	-	376	0	376	
3-	-	376	0	376	
4-	-	376	0	376	

9 2 1 2 5 6 1 1 0

Waste Status Summary of 108-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	1C	136	---	---	Cascade begin fill March
2	1C	390	---	---	Cascade
3	1C	523	---	---	Cascade filled in September
4	1C	523	---	---	Full
1-1950	1C	523	---	---	Full
2	1C	523	---	---	Full
3	1C	523	---	---	Full
4	1C	523	---	---	Cascade
1-1951	1C	523	---	---	Cascade
2	1C	523	---	---	Cascade
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	21	---	---	Finished pumping to 11,000 heel, 1-1-52. 23,000 gallons of 1C supernate was lost to ground from 108-BX pumping operation on 12-16-52.

* Leak detection dry well 21-08-02 drilled.

Waste Status Summary of 108-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	---	10	---	10	Pumped down to Heel 1-1-53
2	TBP	530	---	10	
3	TBP	530	520	10	
4	TBP	530	520	10	
1-1954	TBP	276	266	10	Trans. to 106-B on 3-21-54
2	TBP	530	520	10	Received from 109-BX
3	TBP	530	520	10	
4	TBP	530	520	10	
1-1955	TBP	530	442	88	
2	TBP	530	442	88	
3	TBP	530	442	88	
4	TBP	530	442	88	
1-1956	TBP	530	442	88	
2	TBP	530	442	88	
3	TBP	530	442	88	
4	TBP	530	442	88	
1-1957	TBP	535	447	88	Latest electrode reading
2	TBP	568	480	88	New electrode reading
3	TBP	568	480	88	
4	---	87	0	87	481 scavenged
1-1958	---	87	0	87	
2	TBP	84	4	80	Latest electrode reading
3	TBP	84	4	80	
4	TBP	84	4	80	
1-1959	TBP	84	4	80	
2	TBP	84	4	80	
3	TBP	84	4	80	
4	TBP	84	4	80	
1-1960	TBP	84	4	80	
2	TBP	84	4	80	
3	TBP	84	4	80	
4	TBP	84	4	80	
1-1961					
2	TBP	84	4	80	6 month report
3					
4	TBP	90	10	80	New electrode 6 month report
1-1962					
2	TBP	90	10	80	6 month report
3					
4	TBP	90	10	80	6 month report

Waste Status Summary of 108-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	TBP	92	35	57	6 month report
3					
4	TBP	90	33	57	6 month report
1-1964					
2	TBP-CW	544	33-454	57	454 from 108-C
3					
4	TBP-CW	544	33-454	57	
1-1965					
2	CW	530	440	90	New electrode
3	CW	530	440	90	
4	CW	530	440	90	
1-1966	CW	530	440	90	
2	CW	530	440	90	
3	CW	530	440	90	
4	CW	530	440	90	
1-967	CW	530	440	90	
2	CW	530	440	90	
3	CW	530	440	90	
4	CW	530	440	90	
1-1968	CW	530	440	90	
2	CW	530	440	90	
3	CW	530	440	90	
4	---	87	0	87	443 to 106-BX
1-1969	---	87	0	87	
2	IX	539	452	87	452 from 104-BX
3	IX	506	452	54	
4	IX	506	452	54	
1-1970	IX	506	452	54	
2	IX	506	452	54	
3	IX	506	452	54	
4	IX	508	454	54	
1-1971	IX	508	454	54	
2	IX	505	451	54	
3	IX	505	451	54	
4 *	IX	506	452	54	
972**	IX	505	451	54	
	IX	502	468	34	
3	IX	505	471	34	
4	IX	508	474	34	

* Leak detection dry well 21-08-12 drilled

** Leak detection dry wells drilled: 21-08-06; 21-08-07

Waste Status Summary of 108-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973	IX	74	40	34	432 to 105-BX
2 *	IX	72	38	34	
3	IX	72	38	34	
4	IX	71	37	34	Suspect leaker
1-1974	---	34	0	34	Tank leaks, 43 to 106-BX
2	---	34	0	34	Tank leaks, 2 to 106-BX
3	---	34	0	34	Tank leaks, 1 to 106-BX
4	IX	15	2	13	Tank leaks, 1 to 106-BX
1-1975	IX	15	2	13	Tank leaks
2	IX	15	2	13	Tank leaks
3	IX	15	2	13	Tank leaks
4	IX	15	2	13	Tank leaks
1-1976	IX	15	2	13	Tank leaks
2	---	15	0	15	Tank leaks
3	---	15	0	15	Tank leaks, salt well pumped
4	---	15	0	15	Tank leaks
1-1977	---	15	0	15	Tank leaks
2	---	15	0	15	Tank leaks
3	---	15	0	15	Inactive, leaker stabilized Phase I
4	---	15	0	15	Inactive, leaker stabilized Phase I

* Leak detection dry wells drilled:

21-08-04
21-08-05
21-08-10

Waste Status Summary of 108-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	26	0	26	Leaker-Primary stabilized - New Solids Rdg. 3/31/78
2-	-	26	0	26	
3-	-	26	0	26	
4-	-	26	0	26	
1-1979	-	26	0	26	
2-	-	26	0	26	
3-	-	26	0	26	
4-	-	26	0	26	
1-1980	-	26	0	26	New photo 2/29/80
2-	-	26	0	26	
3-	-	26	0	26	
4-	-	26	0	26	

9 2 1 2 5 6 1 1 6 5

Waste Status Summary of 109-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	Not used
4	---	---	---	---	Not used
1-1950	---	---	---	---	Not used
2	---	---	---	---	Not used
3	---	---	---	---	Not used
4	1C	160	---	---	Began filling November
1-1951	1C	160	---	---	Cascade
2	1C	160	---	---	Cascade
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	

Waste Status Summary of 109-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	530	---	34	Pumped down to Heel 1-22-53, Cascade to 107-BY on 2-27-53
2	TBP	530	---	34	
3	TBP	524	490	34	
4	TBP	183	149	34	Transferred to 106-B & rec'd TBP waste; active TBP waste receiver pumps to 106-B Evap. feed Tank pumped supernatant to ditch
1-1954	TBP	349	312	34	Active TBP waste receiver pumps to 106-B Evap. feed tank
2	TBP	377	343	34	Active TBP waste receiver pumps to 106-B Evap. feed tank
3	TBP	520	206	314	In active TBP waste receiver, received TBP waste
4	TBP	520	206	314	
1-1955	TBP	520	222	298	
2	TBP	520	222	298	
3	TBP	520	222	298	
	TBP	520	222	298	
1-1956	TBP	520	222	298	
2	TBP	520	222	298	
3	TBP	520	222	298	
4	TBP	520	222	298	
1-1957	TBP	519	221	298	Latest electrode reading
2	TBP	552	232	320	New electrode, latest electrode reading
3	TBP	549	229	320	Latest electrode reading
4	TBP	304	6	298	245 scavenged
1-1958	TBP	307	9	298	Latest electrode reading
2	TBP	304	6	298	Latest electrode reading
3	TBP	304	6	298	
4	TBP	304	6	298	
1-1959	TBP	304	6	298	
2	TBP	304	6	298	
3	TBP	304	6	298	
4	TBP	304	6	298	
1-1960	TBP	304	6	298	
2	TBP	304	6	298	
3	TBP	304	6	298	
	TBP	304	6	298	
1-1961					
2	TBP	301	3	298	6 month report
3					
4	TBP	301	3	298	6 month report

Waste Status Summary of 109-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	TBP	301	3	298	6 month report
3					
4	TBP	301	3	298	6 month report
1-1963					
2	TBP	301	3	298	6 month report
3					
4	TBP	301	3	298	6 month report
1-1964					
2	TBP	301	57	244	6 month report
3					
4	TBP-CW	541	57-240	244	240 CW from 102-C 6 month report
1-1965					
2	TBP-CW	541	5-240	296	
3	TBP-CW	541	5-240	296	
4	TBP-CW	541	5-240	296	
1966	TBP-CW	541	5-240	296	
2	TBP-CW	541	5-240	296	
3	TBP-CW	541	5-240	296	
4	TBP-CW	538	5-237	296	
1-1967	TBP-CW	538	5-237	296	
2	TBP-CW	538	5-237	296	
3	TBP-CW	538	5-237	296	
4	TBP-CW	556	5-255	296	Received 18 IX test runs.
1-1968	TBP-CW	557	5-256	296	
2	TBP-CW	557	5-256	296	
3	TBP-CW	557	5-256	296	
4	---	283	0	283	274 to 106-BX.
1-1969	IX	514	231	283	231 from 221-B (18-1)
2	IX	514	231	283	
3	IX	487	237	250	
4	IX	486	236	250	
1-1970	IX	486	236	250	
2	IX	486	236	250	
3	IX	486	236	250	
4	IX	483	233	250	

Waste Status Summary of 109-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	IX	484	234	250	
2	IX	486	236	250	
3	IX	475	225	250	
4	IX	475	225	250	
1-1972	IX	473	223	250	
2	IX	475	264	211	
3	IX	473	262	211	
4	IX	491	280	211	
1-1973	IX	488	277	211	
2 *	IX	213	2	211	4 flush water. 271 to 106-BX.
3	---	211	0	211	
4	---	211	0	211	2 to 106-BX.
1-1974	---	211	0	211	
2	---	211	0	211	
3	---	211	0	211	
4	IX	205	5	200	Salt filled.
1-1975	IX	205	5	200	Salt filled.
2	IX	205	5	200	Phosphoric prototype.
3	IX	205	5	200	Phosphoric prototype.
4	IX	208	8	200	Phosphoric prototype.
1-1976	IX	208	8	200	Phosphoric prototype-removed from service
2	---	208	0	208	Removed from service.
3	---	208	0	208	Needs longer salt well.
4	---	208	0	208	Needs longer salt well.
1-1977	---	208	0	208	Contains salt, needs longer salt well
2	---	208	0	208	Contains salt, needs longer salt well
3	---	208	0	208	Inactive current, needs longer salt well
4	---	208	0	208	Inactive current, needs longer salt well

* Leak detection dry wells drilled:

21-09-02
21-09-04
21-09-08
21-09-12

Waste Status Summary of 109-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	208	0	208	Inactive - Salt Well Installed
2-	-	208	0	208	
3-	-	208	0	208	
4-	-	208	0	208	P-10 Pmp removed
1-1979	-	208	0	208	
2-	-	208	0	208	
3-	-	208	0	208	
4-	-	208	0	208	
1-1980	-	208	0	208	New photo 2/28/80
2-	-	208	0	208	
3-	-	208	0	208	
4-	-	208	0	208	

9 2 1 2 5 6 1 1 0

Waste Status Summary of 110-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	1C	66	---	---	Began filling September.
4	1C	414	---	---	
1-1950	1C	523	---	---	Cascade full in January.
2	1C	523	---	---	Full.
3	1C	523	---	---	Full.
4	1C	523	---	---	
1-1951	1C	523	---	---	
2	1C	523	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	

Waste Status Summary of 110-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	530	---	133	
2	1C	530	---	133	
3	1C	530	397	133	
4	1C	322	189	133	
1-1954	1C	276	0	276	
2	EB	530	294	236	Received from 105-B.
3	EB	530	294	236	Received from 105-B.
4	EB	530	294	236	
1-1955	EB	530	294	236	
2	EB	530	294	236	
3	EB	530	294	236	
4	EB	530	294	236	
1-1956	EB	530	294	236	
2	EB	530	294	236	
3	EB	530	294	236	
4	EB	530	294	236	
57	EB	497	261	236	Latest electrode reading.
	EB	527	279	248	Latest electrode reading.
3	EB	527	279	248	
4	---	326	0	326	201 Scavenged.
1-1958	---	326	0	326	
2	EB	367	41	326	New electrode reading.
3	EB	367	41	326	
4	EB	367	41	326	
1-1959	EB	367	41	326	
2	EB	368	42	326	
3	EB	368	42	326	
4	EB	368	42	326	
1-1960	EB	368	42	326	
2	EB	368	42	326	
3	EB	368	42	326	
4	EB	368	42	326	
1-1961					
2	EB	367	41	326	6 month report
3					
4	EB	389	63	326	22 flush from BXR Vault. 6 month report
1 62					
	EB	392	66	326	Latest electrode reading. 6 month report
3					
4	EB	395	69	326	Latest electrode reading. 6 month report

Waste Status Summary of 110-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	1C-EB	395	39-159	197	6 month report
3					
4	1C-EB	392	39-156	197	Latest electrode reading. 6 month report
1-1964					
2	1C-EB	392	39-156	197	6 month report
3					
4	1C-EB-CW	546	39-156-154	197	154 CW from 102-C. 6 month report
1-1965					
2	EB-CW	543	115-151	277	
3	EB-CW	543	115-151	277	
4	EB-CW	543	115-151	277	
1-1966	EB-CW	543	115-151	277	
2	EB-CW	543	115-151	277	
3	EB-CW	543	115-151	277	
4	EB-CW	543	115-151	277	
1-1967	EB-CW	543	115-151	277	
2	EB-CW	543	115-151	277	
3	EB-CW	543	115-151	277	
4	EB-CW	543	115-151	277	
1-1968	EB-CW	554	115-162	277	Received 11 from Catch Tank.
2	EB-CW	554	115-162	277	
3	EB-CW	554	115-162	277	
4	EB	315	38	277	239 to 106-BX.
1-1969	EB-IX	542	36-229	277	229 from 221-B (18-1)
2	EB-IX	542	36-229	277	
3	EB-IX	509	124-229	156	
4	EB-IX	509	124-229	156	
1-1970	EB-IX	509	124-229	156	
2	EB	224	68	156	285 to 104-BX.
3	EB	227	71	156	
4	EB	227	71	156	
1-1971	EB	227	71	156	
2	EB	231	75	156	
3 *	EB	224	68	156	
4	EB	231	75	156	
1-1972	EB	464	174	290	ITS bottoms and recycle.
2	EB	491	264	227	ITS bottoms and recycle.
3	EB	492	265	227	ITS bottoms and recycle.
4	EB	494	267	227	ITS bottoms and recycle.

* Leak detection dry wells drilled: 21-10-01; 21-10-05; 21-10-07; 21-10-11

Waste Status Summary of 110-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973	EB	510	283	227	ITS bottoms and recycle.
2	EB	514	276	238	ITS bottoms and recycle.
3	EB	501	263	238	ITS bottoms and recycle.
4 *	EB	499	261	238	ITS bottoms and recycle.
1-1974	EB	499	211	288	ITS bottoms and recycle.
2	EB	500	212	288	ITS bottoms and recycle.
3	EB	500	212	288	ITS bottoms and recycle.
4	EB	499	250	249	ITS bottoms and recycle.
1-1975	EB	499	250	249	ITS bottoms and recycle.
2	EB	499	250	249	ITS bottoms and recycle.
3	EB	499	250	249	ITS bottoms and recycle.
4	EB	499	250	249	ITS bottoms and recycle.
1-1976	EB	499	250	250	ITS bottoms and recycle.
2	EB	499	250	249	ITS bottoms and recycle.
3	EVAP	499	250	249	Activity restricted.
4	EVAP	499	250	249	
1-1977	EVAP	499	250	249	(189 sludge & 60 salt cake) Evap. feed concentrate
2	EVAP	249		249	(189 sludge & 60 salt cake) Inactive salt well, pump salt well installed
3	EVAP	249	0	249	Inactive current, salt well installed
4	EVAP	249	0	249	Inactive current, salt well installed

* Leak detection dry well 21-10-03 drilled.

Waste Status Summary of 110-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1979	-	249	0	249	Inactive - Salt Well Installed
2-	-	249	0	249	Questionable Integrity Tank
3-	-	249	0	249	
4-	-	249	0	249	New Photo 11/14/78
1-1979	-	249	0	249	
2-	-	249	0	249	
3-	-	249	0	249	
4-	-	249	0	249	
1-1980	-	202	2	200	New Photo 2/19/80
2-	-	202	2	200	
3-	-	202	2	200	
4-	-	202	2	200	

9 2 1 2 5 6 1 1 5

Waste Status Summary of 111-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	1C	281	---	---	Cascade began filling January.
2	1C	523	---	---	Full in May.
3	1C	523	---	---	Full.
4	1C	523	---	---	
1-1951	1C	523	---	---	
2	1C	523	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	525	---	---	
3	1C	525	---	---	
4	1C	525	---	---	

Waste Status Summary of 111-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	525	---	---	
2	1C	530	---	---	
3	1C	530	530	---	
4	1C	530	530	---	
1-1954	1C	530	498	32	
2	1C-EB	256	41-183	32	Pumped to Crib No. 2.
3	1C-EB	530	41-457	32	
4	1C-EB	530	41-457	32	
1-1955	1C-EB	530	41-457	32	
2	1C-EB	530	41-457	32	
3	1C-EB	530	41-457	32	
4	1C-EB	530	41-457	32	
1-1956	1C-EB	530	41-452	32	
2	1C-EB	530	41-457	32	
3	1C-EB	530	41-457	32	
4	1C-EB	530	41-457	32	
1-1957	1C-EB	535	41-462	32	Latest electrode reading.
2	1C-EB	568	11-495	62	Latest electrode reading.
3	1C-EB	568	11-495	62	Latest electrode reading.
4	---	51	0	51	514 scavenged.
1-1958	---	51	0	51	
2	---	51	0	51	
3	---	51	0	51	
4	---	51	0	51	
1-1959	---	51	0	51	
2	---	51	0	51	
3	---	51	0	51	
4	---	51	0	51	
1-1960	---	51	0	51	
2	---	51	0	51	
3	---	51	0	51	
4	---	51	0	51	
1-1961					
2	---	51	0	51	6 month report
3					
4	1C	57	6	51	New electrode reading. 6 month report

Waste Status Summary of 111-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	1C	57	6	51	6 month report
3					
4	1C	57	6	51	6 month report
1-1964					
2	1C-CW	544	6-487	51	487 from 108-C. 6 month report
3					
4	1C-CW	543	6-486	51	6 month report
1-1965					
2	CW	541	462	79	
3	CW	541	462	79	
4	CW	541	462	79	
1-1966	CW	541	462	79	
2	CW	541	462	79	
3	CW	541	462	79	
4	CW	541	462	79	
1-1967	CW	541	462	79	
2	CW	541	462	79	
3	CW	541	462	79	
4	CW	541	462	79	
1-1968	CW	540	461	79	
2	CW	540	461	79	
3	CW	343	264	79	198 to 106-BX.
4	CW	107	28	79	236 to 106-BX.
1-1969	CW	107	28	79	
2	CW IX	390	28-283	79	283 from 104-BX.
3	CW IX	506	41-432	33	149 from 104-BX.
4	CW IX	505	41-431	33	
1-1970	CW IX	505	41-431	33	
2	CW IX	505	41-431	33	
3	CW	47	14	33	458 to 104-BX.
4	CW	48	15	33	
1-1971	CW	51	18	33	
2*	CW	47	14	33	
3	EB	102	69	33	
4	EB	235	202	33	

*Leak detection dry wells drilled:

21-11-04 21-11-10
21-11-05 21-11-11
21-11-07

Waste Status Summary of 111-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	395	277	118	ITS bottoms and recycle.
2	EB	362	294	68	ITS bottoms and recycle.
3	EB	363	295	68	ITS bottoms and recycle.
4	EB	400	332	68	ITS bottoms and recycle.
1-1973	EB	239	171	68	ITS bottoms and recycle.
2	EB	308	180	128	ITS bottoms and recycle.
3 *	EB	281	153	128	ITS bottoms and recycle.
4	EB	321	193	128	ITS bottoms and recycle.
1-1974	EB	387	153	234	ITS bottoms and recycle.
2	EB	404	170	234	ITS bottoms and recycle.
3	EB	508	274	234	ITS bottoms and recycle.
4	EB	508	292	216	ITS bottoms and recycle.
1-1975	EB	508	292	216	ITS bottoms and recycle.
2	EB	508	292	216	ITS bottoms and recycle.
3	EB	508	292	216	ITS bottoms and recycle.
4	EB	508	292	216	ITS bottoms and recycle.
1-76	EB	510	294	216	ITS bottoms and recycle.
2	EB	510	294	216	ITS bottoms and recycle.
3	EVAP	510	294	216	Activity restricted.
4	EVAP	510	294	216	
1-1977	EVAP	475	259	216	(68 sludge & 148 salt cake) Evap. feed concentrate salt well installed
2	EVAP	260	44	216	(68 sludge & 148 salt cake) Active restricted, Evap. feed conc. SW installed
3	EVAP	230	14	216	(68 sludge & 148 salt cake) Inactive current; salt well installed
4	EVAP	233	22	211	(68 sludge & 143 salt cake) Inactive current; salt well installed

* Leak detection dry well 21-11-03 drilled.

Waste Status Summary of 111-BXTank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	233	22	211	Inactive - Salt Well Installed
2-	NCPLX	233	22	211	Questionable Integrity Tank
3-	NCPLX	233	22	211	
4-	NCPLX	233	22	211	
1-1979	NCPLX	233	22	211	
2-	NCPLX	233	22	211	
3-	NCPLX	233	22	211	
4-	-	233	22	211	
1-1980	NCPLX	233	22	211	New Photo 3/6/80
2-	NCPLX	233	22	211	
3-	NCPLX	233	22	211	
4-	NCPLX	233	22	211	

9 2 1 2 5 6 1 1 5 0

Waste Status Summary of 112-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	

Waste Status Summary of 112-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	530	---	239	
2	1C	530	---	239	
3	1C	530	291	239	
4	1C	323	84	239	Pumping supernatant to ditch.
1-1954	1C	323	53	270	
2	1C	320	50	270	
3	1C-EB	391	50-71	270	To be spare for TBP scavenged waste.
4	1C-EB	391	50-71	270	To be spare for TBP scavenged waste.
1-1955	1C-EB	391	50-71	270	Spare for TBP scavenged waste.
2	1C-EB	391	50-71	270	Spare for TBP scavenged waste.
3	1C-EB	391	50-71	270	Spare for TBP scavenged waste.
4	1C-EB	391	50-71	270	Spare for TBP scavenged waste.
1-1956	1C-EB	391	50-71	270	Spare for TBP scavenged waste.
2	1C-EB	391	50-71	270	
3	1C-EB	391	50-71	270	
4	1C-EB	391	50-71	270	
1-1957	1C-EB	398	50-78	270	Estimated reading. Latest electrode reading.
2	1C-EB	433	33-113	287	New electrode reading.
3	1C-EB	433	33-113	287	
4	1C-EB	433	33-113	287	
1-1958	1C-EB	433	33-113	287	
2	1C-EB	433	33-113	287	
3	1C-EB	433	33-113	287	
4	1C-EB	433	33-113	287	
1-1959	1C-EB	433	33-113	287	
2	1C-EB	433	33-113	287	
3	1C-EB	433	33-113	287	
4	1C-EB	433	33-113	287	
1-1960	1C-EB	439	33-119	287	New electrode installed.
2	1C-EB	439	33-119	287	
3	1C-EB	441	33-121	287	Latest electrode reading.
4	1C-EB	441	33-121	287	
1-1961					
2	1C-EB	450	33-130	287	6 month report
3					
4	1C-EB	453	33-133	287	Latest electrode reading. 6 month report

Waste Status Summary of 112-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	1C-EB	450	33-130	287	
3					
4	1C-EB	450	33-130	287	
1-1963					
2	1C-EB	453	49-133	271	
3					
4	1C-EB	453	49-133	271	
1-1964					
2	1C-EB	450	49-130	271	
3					
4	1C-EB-CW	549	49-130-99	271	99 CW from 102-C.
1-1965					
2	1C-EB-CW	546	2-130-96	318	
3	1C-EB-CW	546	2-130-96	318	
4	1C-EB-CW	546	2-130-96	318	
1-1966	1C-EB-CW	546	2-130-96	318	
2	1C-EB-CW	546	2-130-96	318	
3	1C-EB-CW	546	2-130-96	318	
4	1C-EB-CW	546	2-130-96	318	
1-1967	1C-EB-CW	546	2-130-96	318	
2	1C-EB-CW	546	2-130-96	318	
3	1C-EB-CW	541	2-130-91	318	
4	1C-EB-CW	541	2-130-91	318	
1-1968	1C-EB-CW	554	2-130-104	318	Received 13 from CT.
2	1C-EB-CW	554	2-130-104	318	
3	EB	354	36	318	200 to 106-BX.
4	EB	354	36	318	
1-1969	EB-IX	532	35-179	318	179 from 221-B (18-1)
2	EB-IX	532	35-179	318	
3	EB-IX	499	186-179	134	
4	EB-IX	499	186-179	134	
1-1970	EB-IX	499	186-179	134	
2	EB-IX	499	186-179	134	
3	EB-IX	499	186-179	134	
4	EB-IX	499	186-179	134	

Waste Status Summary of 112-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	EB-IX	499	186-179	134	
2	EB-IX	499	186-179	134	
3 *	EB-IX	499	186-179	134	
4	EB-IX	499	186-179	134	
1-1972	EB-IX	498	185-179	134	
2	EB-IX	497	184-179	134	
3	EB-IX	496	134-130	232	
4	EB-IX	508	140-136	232	
1-1973	EB-IX	512	150-146	216	
2 **	EB-IX	511	149-146	216	
3	EB-IX	497	142-139	216	
4	EB-IX	496	141-139	216	
1-1974	EB-IX	495	140-139	216	
2	--	216	0	216	313 to 105-BX.
3	--	216	0	216	
4	EB-IX	194	8-8	178	Awaiting solidification.
1-1975	EB-IX	194	8-8	178	
2	EB-IX	194	8-8	178	
3	EB-IX	194	8-8	178	
4	EB-IX	194	8-8	178	
1-1976	EB-IX	194	8-8	178	
2	EB-IX	194	8-8	178	
3	EVAP	202	24	178	Evap. Feed dil.
4	EVAP	202	24	178	
1-1977	EVAP	202	24	178	Evap. feed dil.
2	EVAP	178	0	178	Evap. feed dil - salt well installed
3	EVAP	178	0	178	Inactive spare current
4	EVAP	178	0	178	Inactive current salt well installed

* Leak detection dry wells drilled:

21-12-02
21-12-05
21-12-07
21-12-10

** Leak detection dry well 21-12-12 drilled.

Waste Status Summary of 112-BX Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	178	0	178	Inactive - Salt Well Installed
2-	-	178	0	178	
3-	-	178	0	178	
4-	-	169	0	169	Solids Level Adj. 11/3/78
1-1979	-	169	0	169	
2-	-	169	0	169	
3-	-	169	0	169	
4-	-	169	0	169	
1-1980	-	169	0	169	New Photo 3/10/80
2-	-	169	0	169	
3-	-	169	0	169	
4-	-	169	0	169	

9 2 1 2 5 6 1 1 5 5

101-BY-1

Waste Status Summary of 101-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4					
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	MW	290	290	---	Began filling March.
2	MW	661	661	---	
3	MW	744	744	---	Cascade full September.
4	MW	744	744	---	Cascade full September.
1-1951	MW	744	744	---	Cascade full.
2	MW	744	744	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	
1-1953	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	

Waste Status Summary of 101-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	1	1	---	Transfer to 103-BY.
2	---	---	---	---	Was emptied on May 17, 1954.
3	---	---	---	---	
4	---	---	---	---	
1-1955	TBP	681	681	---	Received from 108-BY.
2	TBP	750	750	---	
3	TBP	750	750	---	
4	TBP	750	750	---	
1-1956	TBP	750	750	---	Scvg. waste awaiting rework.
2	TBP	750	750	---	Scvg. waste awaiting rework.
3	MW	750	750	---	
4	TBP	750	750	---	
1-1957	TBP	717	717	---	
2	TBP	262	262	---	
3	TBP	40	40	---	225m scavenged. Latest electrode reading.
4	TBP	40	40	---	
1-1958	TBP	40	40	---	
2	TBP	59	59	---	New electrode reading.
3	TBP	59	59	---	
4	TBP	59	59	---	
1-1959	TBP	59	59	---	
2	TBP	59	59	---	
3	TBP	59	59	---	
4	TBP	60	60	---	Latest electrode reading.
1-1960	TBP	60	60	---	
2	TBP	60	60	---	
3	TBP	60	60	---	
4	TBP	394	394	---	Received 275m CW from 108-C. Received 77m from 108-C.
1-1961	---	---	---	---	
2	TBP-CW	483	247 236	---	Received 89m from 108-C
3	---	---	---	---	
4	TBP-1C-CW	728	247 439 42	---	Received 245m from 107-C.

9 2 1 2 5 5 1 1 0 7

Waste Status Summary of 101-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962	---	---	---	---	
2	TBP-1C-CW	728	247-439 42	---	
3	---	---	---	---	
4	TBP-1C-CW	728	247-439-42	---	
1-1963	---	---	---	---	
2	TBP-1C-CW	730	210-439 44	37	
3	---	---	---	---	
4	TBP-1C-CW	741	210-439-55	37	New electrode installed.
1-1964	---	---	---	---	
2	TBP-1C-CW	744	210-439-58	37	
3-	---	---	---	---	
4	TBP 1C-CW	744	210-439 58	37	
1-1965	---	---	---	---	
2	CW	582	582	0	762m ITS boil-off.
3	CW	601	601	---	502m ITS boil-off.
4	CW	541	541	---	293m ITS boil-off.
1-1966	CW	590	590	---	240m ITS boil-off.
2	CW	612	612	---	410m ITS boil-off.
3	CW	585	585	0	
4	CW	409	409	0	28m recovered butts.
1-1967	CW	409	409	0	Status not determined.
2	CW	407	409	0	Status not determined.
3	CW	407	298	109	Demonstrating solidification.
4	CW	406	30	376	Demonstrating solidification.

9212556168

Waste Status Summary of 101-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	CW	406	28	378	Demonstrating solidification.
2	EB	406	28	378	Demonstrating solidification.
3	EB	407	29	378	Demonstrating solidification.
4	EB	407		29	
1-1969	EB	407	126	281	Demonstrating solidification.
2	EB	407	133	274	Demonstrating solidification.
3	EB	739	429	310	331 from 105-BY.
4	EB	737	405	332	Demonstrating solidification.
1-1970	EB	737	400	337	
2	EB	744	407	337	
3	EB	743	406	337	
4	EB	747	407	340	
1-1971	EB	745	405	340	
2	EB	733	347	386	769 from 108-BY; 782 to 101-BX.
3 *	EB	736	350	386	
4	EB	737	339	398	
1-1972	EB	737	339	398	ITS - bottoms and recycle.
2	EB	739	341	398	ITS - bottoms and recycle.
3	EB	740	322	418	ITS - bottoms and recycle.
4	EB	734	316	418	ITS - bottoms and recycle.
1-1973	EB	738	320	418	ITS - bottoms and recycle.
2	EB	737	319	418	ITS - bottoms and recycle
3	EB	738	320	418	ITS - bottoms and recycle.
4	EB	739	321	418	ITS - bottoms and recycle.
1-1974	EB	740	322	418	ITS - bottoms and recycle.
2	EB	746	328	418	ITS - bottoms and recycle
3 **	EB	748	330	418	ITS - bottoms and recycle
4	EB	747	349	398	ITS - bottoms and recycle 6 to 109-BY (1 water).
1-1975	EB	747	349	398	ITS - bottoms and recycle.
2	EB	728	330	398	ITS - bottoms and recycle 20 to 105-BX.
3	EB	728	330	398	
4	EB	728	330	398	ITS - bottoms and recycle.

* Dry Wells No.'s 22-01-01, 22-01-04, and 22-01-07 were drilled.

** Dry Wells No.'s 22-01-03, and 22-01-10 were drillled.

9212556116 9

Waste Status Summary of 101-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	EB	728	330	398	ITS - bottoms and recycle.
2	EB	728	330	398	ITS - bottoms and recycle.
3	EVAP.	733	335	398	Con. feed.
4	EVAP.	579	181	398	
1-1977	EVAP.	458	60	398	Salt Well Pumped
2	EVAP.	447	8	439	" " "
3	EVAP.	447	8	439	Inactive Current
4	EVAP.	447	8	439	" "
1-1978	NCPLX	450	11	439	Inactive
2-	NCPLX	450	11	439	
3-	NCPLX	447	8	439	
4-	NCPLX	447	8	439	
1-1979	NCPLX	447	8	439	
2-	NCPLX	447	8	439	
3-	NCPLX	447	8	439	
4-	NCPLX	447	8	439	
1-1980	NCPLX	447	8	439	New Photo 3-20-80
2-	NCPLX	447	8	439	
3-	NCPLX	447	8	439	
4-	NCPLX	443	4	439	

9212561170

Waste Status Summary of 102-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	MW	480	480	---	Cascade began filling September.
4	MW	744	744	---	Cascade full in October.
1-1951	MW	744	744	---	Cascade full.
2	MW	744	744	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	

* Dry Well No. 22-02-07 was drilled.

9 2 1 2 5 5 6 1 1 7 1

Waste Status Summary of 102-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	
1-1954	MW	497	497	---	Supernatant blend supply.
2	---	---	---	---	
3	---	---	---	---	Was emptied on July 13, 1954.
4	---	---	---	---	
1-1955	TBP	326	326	---	Received from 105-BY.
2	TBP	720	720	---	
3	TBP	720	720	---	
4	TBP	720	720	---	
1-1956	TBP	720	720	---	Scvg. waste awaiting rework.
2	TBP	720	720	---	Scvg. waste awaiting rework.
3	MW	720	720	---	
4	TBP	720	720	---	
1-1957	TBP	722	722	---	
2	TBP	488	488	---	
3	TBP-CW	400	350-32	18	Received 28m; 498m to BC-19 trench. Received 679m; 297m to BC-19.
4	TBP	43	25	18	132m to BC-20; 107m to BC-21; 311m from 107-BY; 429m to 1C-22.
1-1958	TBP	43	25	18	
2	TBP	43	25	18	
3	TBP	43	25	18	
4	TBP	43	25	18	
1-1959	TBP	43	25	18	
2	TBP	46	28	18	
3	TBP	46	28	18	
4	TBP	46	28	18	
1-1960	TBP	46	28	18	New electrode installed.
2	TBP	48	48	---	
3	TBP	48	48	---	
4	TBP	48	48	---	
1-1961					
2	TBP	48	48	---	6 month report
3					
4	TBP	51	33	18	Latest electrode reading. 6 month report
1-1962					
2	TBP	51	33	18	6 month report
3					
4	TBP	54	36	18	Latest electrode reading. 6 month report

9 2 1 2 5 6 1 1 7 2

Waste Status Summary of 102-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	TBP	48	19	29	Latest electrode reading.
3					6 month report
4	TBP	48	19	29	6 month report
1-1964					
2	TBP	48	19	29	6 month report
3					
4	TBP-CW	442	19-394	29	394 CW from 102-C.
					6 month report
1-1965					
2	TBP-CW	700	48-652	0	Received 258m CW from 102-C.
3	TBP-CW	728	48-680	0	28m from 102-C.
4	TBP-CW	728	48-680	0	
1-1966	TBP-CW	730	48-682	0	
2	TBP-CW	733	48-685	0	
3	TBP-CW	733	48-685	0	
4	CW	722	-722	0	61m recovered by ITS
1-1967	CW	631	631	0	638m reclaimed by ITS
2	CW	593	593	0	722m reclaimed by ITS
3	CW	597	597	0	506m reclaimed by ITS
4	CW	608	608	0	521m reclaimed by ITS
1-1968	CW	561	561	0	231m reclaimed by ITS No. 1.
2	EB	593	593	0	520m reclaimed by ITS No. 1.
3	EB	601	287	314	548m reclaimed by ITS No. 1.
4	EB	578	328	250	507m reclaimed by ITS No. 1.
1-1969	EB	510	260	250	353m reclaimed by ITS No. 1
2	EB	590	340	250	617m evaporated by ITS No.1
3	EB	607	357	250	154 to 105-BY.
					450 evaporated by ITS No. 1
4	EB	583	333	250	657 from 103-BY; 182 to 105-BY.
					500 evaporated by ITS No.1
1-1970	EB	630	380	250	293 from 103-BY; 399 from 102-BX;
*					70 to 105-BY; 573 evaporated by ITS No. 1
2	EB	596	346	250	213 from 103-BX; 89 to 105-BY;
					106 evaporated by ITS No. 1
3	EB	639	389	250	603 from 103-BX; 66 to 105-BY;
					493 evaporated by ITS No. 1
4	EB	530	280	250	780 from 103-BX; 286 to 105-BY;
					603 evaporated by ITS No. 1

* Dry Wells No.'s 22-02-01 and 22-02-09 were drilled.

9212556117 3

Waste Status Summary of 102-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	EB	601	351	250	1147 from 103-BX; 514 to 105-BY; 562 evaporated by ITS No.1
2	EB	637	482	155	899 from 103-BX; 43 from 106-BX; 367 to (105-BY); 538 evaporated by Its-1.
3	EB	623	468	155	ITS - 1 cooler and recycle 70 from 103-BX.
4	EB	579	424	155	ITS - 1 cooler and recycle.
1-1972	EB	630	433	197	ITS - bottoms and recycle.
2	EB	618	421	197	ITS - bottoms and recycle.
3	EB	609	412	197	ITS - bottoms and recycle.
4	EB	590	344	246	ITS - bottoms and recycle.
1-1973	EB	590	396	194	ITS- bottoms and recycle.
2	EB	631	437	194	ITS- bottoms and recycle.
3 *	EB	637	443	194	ITS- bottoms and recycle.
4	EB	635	427	208	ITS- bottoms and recycle.
1-1974	EB	630	422	208	ITS- bottoms and recycle.
2	EB	629	421	208	ITS- bottoms and recycle; 12 to 110-BY.
3	EB	628	420	208	ITS- bottoms and recycle 102 to 111-BX; 98 from 112-BY.
4	EB	629	429	200	ITS- bottoms and recycle.
1-1975	EB	629	429	200	ITS- bottoms and recycle.
2	EB	629	429	200	ITS- bottoms and recycle.
3	EB	629	429	200	Tank leaks.
4	EB	629	429	200	ITS- bottoms and recycle.
1-1976	EB	629	429	200	ITS- bottoms and recycle.
2	EB	626	426	200	ITS- bottoms and recycle.
3	EVAP.	626	426	200	Active restricted.
4	EVAP.	626	426	200	
1-1977	EVAP.	593	393	200	Evap. Feed Con.
2	EVAP.	450	217	233	Contain Salt
3	EVAP.	436	0	436	Inactive Current
4	EVAP.	436	0	436	" "

* Dry Wells No.'s 22-02-02 and 22-02-05 were drilled.

9211256117 4

Waste Status Summary of 102 BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	436	0	436	
2-	-	417	0	417	Solid Level Adj. 6/30/78
3-	-	417	0	417	
4-	-	417	0	417	
1-1979	-	417	0	417	
2-	-	417	0	417	
3-	-	417	0	417	New photo 9/27/79
4-	-	417	0	417	
1-1980	-	417	0	417	Unknown Pool volume
2-	-	417	0	417	
3-	-	417	0	417	
4-	-	417	0	417	

9 2 1 2 3 5 6 1 1 7 5

Waste Status Summary of 103-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	429	429	---	Cascade began filling October.
1-1951	MW	744	744	---	Full in March.
2	MW	744	744	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	664	664	---	
2	MW	664	664	---	
3	MW	664	664	---	
4	MW	664	664	---	

9 2 1 2 5 6 1 1 7 6

Waste Status Summary of 103-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	664	664	---	
2	MW	745	745	---	
3	MW	745	745	---	
4	MW	745	745	---	
1-1954	MW	382	382	---	Transfer to 104, 5-C.
2	---	---	---	---	Transfer to 109-BY Tank; was emptied on June 3, 1954.
3	---	---	---	---	
4	---	---	---	---	
1-1955	TBP	128	128	---	Received from 110-BY.
2	TBP	739	739	---	
3	TBP	739	739	---	
4	TBP	739	739	---	
1-1956	TBP	739	739	---	Scvg. waste awaiting rework.
2	TBP	739	739	---	Scvg. waste awaiting rework.
3	MW	739	739	---	
4	TBP	739	739	---	
1-1957	TBP	732	732	---	
2	TBP	733	733	---	
3	TBP	26	26	---	550m scavenged - 157m scvg. Received 421m from 106-C.
4	TBP-P	447	26-421	---	
1-1958	TBP-P	736	26-710	---	286m from 103-C.
2	TBP-P	730	26-704	---	New electrode reading.
3	TBP-P	730	26-704	---	
4	TBP-P	730	26-704	---	
1-1959	TBP-P	728	26-702	---	
2	TBP-P	722	26-696	---	
3	TBP-P	722	26-696	---	
4	TBP-P	722	26-696	---	
1-1960	TBP-P	722	26-696	---	
2	TBP-P	722	26-696	---	
3	TBP-P	722	26-696	---	
4	TBP-P	722	26-696	---	
1-1961	---	---	---	---	
2	TBP-P	722	26-696	---	
3	---	---	---	---	
4	TBP-P	736	26-710	---	Latest electrode reading.

9 2 1 2 5 6 1 1 7 7

Waste Status Summary of 103-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962	---	---	---	---	
2	TBP-P	725	26-699	---	Latest electrode reading.
3	---	---	---	---	
4	TBP-P	725	26-699	---	
1-1963	---	---	---	---	
2	TBP-P	722	26-675	21	
3	---	---	---	---	
4	TBP-P	722	26-675	21	
1-1964	---	---	---	---	
2	TBP-P	714	26-667	21	New electrode.
3	---	---	--	---	
4	TBP-P	739	26-692	21	New electrode (reading confirmed).
1-1965	---	---	---	---	
2	TBP-P	596	26-570	0	143m to 101-BY (TTS) (ITS decant. tank)
3	CW	703	703	0	Received 628m; 521m to 101-BY.
4	CW	494	494	0	24m from 111-BY; 233m to 101-BY.
1-1966	CW	519	519	0	314m from 111-BY; 289m to 101-BY.
2	CW	590	590	0	503m from 102-BY; 432m to 101-BY.
3	CW	662	662	0	Received 533m; 461m to 101-BY.
4	CW	739	739	0	127m from 102-C; 50m to 102-BY.
1-1967	CW	541	541	0	349 from 106-BY; 547 to 102-BY.
2	CW	615	615	0	ITS - feed tank.
3	CW	526	526	0	ITS - feed tank.
4	CW	526	526	0	ITS - feed tank.
1-1968	CW	569	569	0	ITS - No. 1&2 feed tank.
2	CW	569	569	0	ITS - No. 1&2 feed tank.
3	CW	456	456	0	ITS - No. 1 feed tank.
4	CW-OWW	519	306-213	0	2,153 from 106-BX; 814 to 102-BY.
1-1969	EB-CW	213	89-124	0	1,585 from 101-B; 102-B and 103-B; 693 to 102-BY; 1,197 to 109-BY.
2	CW-OWW	566	328-238	0	2,425 from 103-B; 696 to 102-BY; 1,376 to 109-BY.
3	CW-OWW	483	130-352	1	2,095 from 103-B; 620 to 102-BY; 1,558 to 109-BY.
4	CW-OWW	542	214-320	8	1,888 from 102-BX; 657 to 102-BY; 1,172 to 109-BY.

9 2 1 2 5 5 6 1 1 7 8

Waste Status Summary of 103-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970 *	CW-OWW	239	76-160	3	608 from 102-BY; 293 to 102-BY; 617 to 109-BY.
2	CW-OWW-EB	442	76-160-202	4	202 from 105-BY.
3	CW-OWW-EB	439	76-160-199	4	
4	CW-OWW-EB	700	76-160-455	9	261 from 105-BY.
1-1971	EB	711	646	65	To ITS - 2 bottom service in January.
2	EB	689	561	128	ITS - 2 bottoms and recycle.
3	EB	714	572	142	ITS - 2 bottoms and recycle.
4	EB	398	196	202	ITS - 2 bottoms and recycle.
1-1972	EB	443	145	298	ITS - bottoms and recycle.
2	EB	454	103	351	ITS - bottoms and recycle.
3 **	EB	620	192	428	ITS - bottoms and recycle.
4	EB	476	48	48	ITS - bottoms and recycle.
1-1973	EB	469	0	469	ITS - bottoms and recycle.
2	EB	483	14	469	Tank leaks.
3 ***	EB	461	3	458	Tank leaks, 25 to 109-BY.
4	EB	464	6	458	Tank leaks, 4 to 109-BY.
1-1974	EB	464	6	458	Tank leaks.
2	EB	464	6	458	Tank leaks, 5 to 109-BY.
3	---	469	0	469	Tank leaks, 13 to 109-BY.
4	---	461	0	461	Tank leaks.
1-1975	---	461	0	461	Tank leaks, 5 to 109-BY.
2	---	461	0	461	Tank leaks.
3	---	461	0	461	Tank leaks.
4	---	461	0	461	Tank leaks, 4 to 109-BY.
1-1976	---	461	0	461	Tank leaks, 5 to 109-BY.
2	---	461	0	461	Tank leaks, 1 to 109-BY.
3	---	461	0	461	Tank leaks.
4	---	461	0	461	Tank leaks.
1-1977	---	461	0	461	Leaker Stabilized
2	---	461	0	461	"
3	---	461	0	461	"
4	---	461	0	461	" Salt Well Installed

* Dry Wells No.'s 22-03-01, 22-03-05 and 22-03-09 were drilled.

** Dry Wells No.'s 22-03-04, and 22-03-06 were drilled.

*** Dry Wells No.'s 22-03-07, 22-03-08, 22-03-10 were drilled.

Waste Status Summary of 103 BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	461	0	461	
2-	-	461	0	461	
3-	-	461	0	461	
4-	-	461	0	461	
1-1979	-	461	0	461	
2-	-	461	0	461	
3-	-	461	0	461	New Photo 8/2/79
4-	-	461	0	461	
1-1980	-	461	0	461	Unknown Pool Volume New Photo 1/17/80
2-	-	461	0	461	Solids Level Taken 2/1/80
3-	-	461	0	461	
4-	-	461	3	458	

9 2 1 2 5 6 1 1 3 0

Waste Status Summary of 104-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	MW	11	11	--	
2	MW	11	11	---	
3	MW	11	11	---	
4	MW	11	11	---	
1-1951	MW	200	200	---	Began filling March.
2	MW	744	744	---	Cascade filled in June.
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	
1-1953	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	

9 2 1 2 3 5 6 1 1 3 1

Waste Status Summary of 104-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	758	758	---	
2	---	---	---	---	Transferred to 109-BY and 244-BXR.
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	TBP	112	112	---	
3	TBP	714	714	---	
4	TBP	78	78	---	Caverned during month.
1-1956	TBP	78	78	---	
2	TBP	78	78	---	
3	MW	403	100	303	Received from 107-BY.
4	TBP	546	223	323	Received from 106, 8 and 10-BY.
1-1957	TBP	563	240	323	Latest electrode reading.
2	TBP	571	294	277	8m received from 108-BY.
3	TBP	598	354	244	Received 27m from 108-BY.
4	TBP	574	330	244	Latest electrode reading. New electrode reading.
1-1958	TBP	574	330	244	
2	TBP	574	330	244	
3	TBP	574	330	244	
4	TBP	571	327	244	New electrode reading.
1-1959	TBP	571	327	244	
2	TBP	571	327	244	
3	TBP	567	323	244	Installed new electrode.
4	TBP	567	323	244	
1-1960	TBP	567	323	244	
2	TBP	563	319	244	Electrode being rechecked.
3	TBP	563	319	244	
4	TBP	563	319	244	
1-1961	---	---	---	---	
2	TBP	565	321	244	
3	---	---	---	---	
4	TBP-CW	703	321-138	244	138m from 107-C.
1-1962	---	---	---	---	
2	TBP-CW	717	321-152	244	14m from 107-C.
3	---	---	---	---	
4	TBP-CW	717	321-152	244	
1-1963	---	---	---	---	
2	TBP-CW	714	302-149	263	
3	---	---	---	---	
4	TBP-CW	714	302-149	263	

9211255611382

Waste Status Summary of 104-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964	---	---	---	---	
2	TBP-CW	714	302-149	263	
3	---	---	---	---	
4	TBP-CW	714	302-149	263	
1-1965	---	---	---	---	
2	TBP-CW	717	338-152	227	
3	TBP-CW	717	338-152	227	
4	TBP-CW	717	338-152	227	
1-1966	TBP-CW	717	338-152	227	
2	TBP-CW	717	338-152	227	
3	TBP-CW	717	338-152	227	
4	TBP-CW	719	338-154	227	119m concentrate from 101-BY.
1-1967	TBP-CW	719	338-154	227	
2	TBP	205	---	205	514m to 103-BY.
3	CW	249	5	244	Received 44m from 102-C.
4	CW	653	409	244	Received 404m from 102-C.
1-1968	CW	730	486	244	Received 77m from 102-C.
2	1X	546	334	212	500 to 103-BY; 317 from 104-BX.
3	1X	741	497	244	184 from 104-BX.
4	1X	741	497	244	
1-1969	1X	741	497	244	
2	1X	741	508	233	
3	1X	740	496	244	
4	1X	748	508	240	New measuring tape.
1-1970	1X	211	5	206	377 to 103-A, 151 to 110-C
2 *	EB	579	535	44	Placed in bottoms in June by receiving from 110-BY.
3	EB	623	511	112	ITS - 2 bottoms and recycle.
4	EB	664	533	131	ITS - 2 bottoms and recycle.
1-1971	EB	677	527	150	ITS - 2 bottoms and recycle.
2	EB	701	551	150	ITS - 2 bottoms and recycle.
3	EB	662	237	425	ITS - 2 bottoms and recycle.
4	EB	662	44	618	ITS - 2 bottoms and recycle.
1-1972	EB	662	44	618	ITS - bottoms and recycle.
2	EB	670	52	618	ITS - bottoms and recycle.
3	EB	664	354	310	ITS - bottoms and recycle.
4	EB	707	397	310	ITS - bottoms and recycle.
1-1973	EB	668	199	469	ITS - bottoms and recycle.
2	EB	693	224	469	ITS - bottoms and recycle.
3	EB	697	228	469	ITS - bottoms and recycle.
4	EB	657	29	628	ITS - bottoms and recycle.

* Dry Wells No.'s 22-04-01, 22-04-05, 22-04-09 were drilled.

9 2 1 2 5 5 6 1 1 8 3

Waste Status Summary of 104-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	718	249	469	ITS - bottoms and recycle.
2	EB	719	250	469	ITS - bottoms and recycle.
3 *	EB	718	249	469	ITS - bottoms and recycle.
4	EB	717	248	469	ITS - bottoms and recycle.
1-1975	EB	717	248	469	ITS - bottoms and recycle.
2	EB	717	248	469	ITS - bottoms and recycle.
3	EB	717	248	469	
4	EB	717	248	469	ITS - bottoms and recycle.
1-1976	EB	717	248	469	ITS - bottoms and recycle.
2	EB	717	248	469	ITS - bottoms and recycle.
3	EVAP.	719	250	469	Evaporator feed bottoms.
4	EVAP.	670	201	469	
1-1977	EVAP.	634	165	469	Evap. Feed Con. Salt Well Installed
2	EVAP.	634	165	469	" " " " "
3	EVAP.	631	8	623	Inactive Current Pump Removed
4	EVAP.	631	8	623	" " " "

* Dry Wells No.'s 22-04-07 and 22-04-11 were drilled.

Waste Status Summary of 104-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978		634	11	623	Inactive
2-	NCPLX	634	11	623	
3-	NCPLX	634	11	623	
4-	NCPLX	634	11	623	
1-1979	NCPLX	634	11	623	P-10 PMP Removed
2-	NCPLX	634	11	623	
3-	NCPLX	634	11	623	
4-	NCPLX	634	11	623	
1-1980	NCPLX	634	11	623	
2-	NCPLX	634	11	623	
3-	NCPLX	634	11	623	
4-	NCPLX	634	11	623	

9 2 1 2 5 6 1 1 3 5

Waste Status Summary of 105-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	MW	20	20	---	Cascade began filling June.
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	491	491	---	
2	MW	491	491	---	
3	MW	491	491	---	
4	MW	491	491	---	
1-1953	MW	491	491	---	
2	MW	495	495	---	
3	MW	497	497	---	
4	MW	497	497	---	

Waste Status Summary of 105-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	497	497	---	
2	MW	497	497	---	
3	MW	1	1	---	For TBP scvg. sludge.
4	TBP	399	385	14 est.	Received from 107 and 110-BY.
1-1955	TBP	222	206	16	Received from 110-BY.
2	TBP	222	206	16	
3	TBP	260	244	16	
4	TBP	371	355	16	Cribbed during month.
1-1956	TBP	551	201	350	
2	TBP	708	324	384	
3	MW	403	19	384	
4	TBP	706	322	384	
1-1957	TBP	706	322	384	
2	TBP	409	25	384	297m to No. 16 BC trench.
3	TBP	417	204	213	8m line flush.
4	TBP	428	215	213	New electrode reading.
1-1958	TBP	428	215	213	
2	TBP	431	218	213	Latest electrode reading.
3	TBP	431	218	213	
4	TBP	429	216	213	
1-1959	TBP	428	215	213	New electrode reading.
2	TBP	428	215	213	
3	TBP	428	215	213	
4	TBP	428	215	213	
1-1960	TBP	428	215	213	
2	TBP	428	215	213	
3	TBP	428	215	213	
4	TBP	428	215	213	
1-1961	---	---	---	---	
2	TBP-CW	519	215-91	213	Received 91m from 108-C. 6 Mo. Report
3	---	---	---	---	
4	TBP-CW	711	215-283	213	192m from 107-C. 6 Month Report
1-1962	---	---	---	---	
2	TBP-CW	711	215-283	213	6 Month Report
3	---	---	---	---	
4	TBP-CW	711	215-283	213	6 Month Report
1-1963	---	---	---	---	
2	TBP-CW	711	206-283	222	6 Month Report
3	---	---	---	---	
4	TBP-CW	711	206-283	222	6 Month Report

9212256117

Waste Status Summary of 105-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964	---	---	---	---	
2	TBP-CW	708	206-280	222	6 Month Report
3	---	---	---	---	
4	TBP-CW	708	206-280	222	6 Month Report
1-1965	---	---	---	---	
2	TBP-CW	711	242-283	186	6 Month Report
3	TBP-CW	711	242-283	186	
4	TBP-CW	711	242-283	186	
1-1966	TBP-CW	711	242-283	186	
2	TBP	208	22	186	503m to 103-BY.
3	TBP	178	178	0	
4	CW	326	326	0	
1-1967	CW	323	323	0	Status not determined.
2	CW	323	323	0	
3	CW	326	287	39	ITS bottoms receiver.
4	CW	326	238	88	ITS bottoms receiver.
1-1968	EB	605	517	88	Received 279m from 102-BY.
2	EB	495	407	88	110 to 109-BY.
3	EB	411	253	158	340 to 109-BY; 256 from 102-BY.
4	EB	741	583	158	330 from 102-BY.
1-1969	EB	670	505	165	408 from 102-BY; 481 to 106-BY.
2	EB	671	518	153	330 from 102-BY.
3	EB	494	300	194	154 from 102-BY; 331 to 101-BY.
4	EB	675	486	189	182 from 102-BY.
1-1970	EB	745	554	191	70 from 102-BY.
2	EB	631	415	216	202 to 103-BY; 89 from 102-BY.
3 *	EB	722	423	299	To ITS - 2 bottoms service in August.
4	EB	681	382	299	286 from 102-BY; ITS - 2 bottoms.
1-1971	EB	675	335	340	514 from 102-BY; ITS - 2 bottoms.
2	EB	668	199	469	ITS - 2 bottoms; 367 from 102-BY, 4 H_2O.
3	EB	700	231	469	ITS - 2 bottoms and recycle.
4	EB	711	58	653	ITS - 2 bottoms and recycle.
1-1972	EB	678	25	653	ITS - bottoms and recycle.
2	EB	701	48	653	ITS - bottoms and recycle.
3	EB	642	51	591	ITS - bottoms and recycle.
4	EB	664	73	591	ITS - bottoms and recycle.
1-1973	EB	666	38	628	ITS - bottoms and recycle.
2	EB	666	38	628	ITS - bottoms and recycle.
3	EB	657	29	628	ITS - bottoms and recycle.
4	EB	657	29	628	ITS - bottoms and recycle.

* Dry Wells NO.'s 22-05-01, 22-05-05 and 22-05-09 were drilled.

9 2 1 5 5 6 1 1 8 8

Waste Status Summary of 105-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	656	28	628	ITS - bottoms and recycle.
2	EB	652	24	628	ITS - bottoms and recycle.
3	---	628	0	628	ITS - bottoms and recycle; 73 to 109-BY, 29 to 106-BY.
4	---	626	0	626	Removed from service (2 water) 16 to 109-BY.
1-1975	---	626	0	626	Removed from service, 4 to 109-BY.
2	---	626	0	626	Removed from service, 27 to 109-BY.
3	---	626	0	626	Removed from service, 11 to 109-BY.
4	---	626	0	626	Removed from service, 6 to 109-BY.
1-1976	---	626	0	626	Removed from service.
2	---	626	0	626	Removed from service.
3	---	626	0	626	Inactive salt well pumping.
4	---	626	0	626	
1-1977	---	626	0	626	Salt Well Pumped 63 T Cement added
2	EVAP.	626	0	626	" " " " " " "
3	EVAP.	626	0	626	Inactive Current 63 T Cement added
4	EVAP.	626	0	626	" " " " " "
1-1978	-	626	0	626	Primary stabilized
2-	-	626	0	626	Questionable Integrity
3-	-	626	0	626	
4-	-	626	0	626	
1-1979	-	626	0	626	P-10 Pmp removed
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	
1-1980	-	626	0	626	
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	

9212556118 9

Waste Status Summary of 106-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	---	---	---	
2	MW	---	---	---	
3	MW	---	---	---	
4	MW	---	---	---	

* Dry well No. 22-06-07

9 2 1 2 5 6 1 1 9 0

Waste Status Summary of 106-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	0	0	---	
2	1C	758	758	---	
3	1C	758	758	---	
4	1C	755	755	---	
1-1954	1C	756	756	---	
2	1C	756	756	---	
3	1C	756	756	---	To be pumped to trench.
4	TBP	15	15	---	For TBP scvg. sludge.
1-1955	TBP	728	688	40 est.	Received from WR Vault.
2	TBP	736	629	107 est.	
3	TBP	736	629	107	
4	TBP	746	626	120	O.K. to be cribbed.
1-1956	TBP	551	401	150	Scvg. waste receiver.
2	TBP	723	543	180	Pumped to RC-2 crib. S.S. active receiver.
3	TBP	629	465	164	S.S. 539m to No. 8 BC ditch.
4	TBP	717	549	168	S.S. 484m to BC No. 10 ditch. S.S. received from 241-WR and ditched 77m gallons.
1-1957	TBP	722	611	111	176m pumped to B-C 86; S.S. active TBP receiving.
2	TBP	725	614	111	Increase due to flushes.
3	TBP	739	628	111	14m line flush.
4	TBP	257	146	111	482m to BC-2 crib.
1-1958	TBP	257	146	111	
2	TBP	257	146	111	
3	TBP	257	146	111	
4	TBP	257	146	111	
1-1959	TBP	241	130	111	New electrode reading.
2	TBP	252	141	111	New electrode.
3	TBP	252	141	111	
4	TBP	252	141	111	
1-1960	TBP	252	141	111	
2	TBP	252	141	111	
3	TBP	252	141	111	
4	TBP	252	141	111	
1-1961	---	---	---	---	
2	TBP	249	138	111	6 Month Report
3	---	---	---	---	
4	TBP-CW	505	138-256	111	256m from 107-C. 6 Month Report

9 2 1 2 5 6 1 1 9 1

Waste Status Summary of 106-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	TBP-CW	623	138-374	111	118m from 107-C. 6 months report
3					
4	TBP-CW	623	138-374	111	6 months report
1-1963					
2	TBP-CW	620	99-371	150	6 months report
3					
4	TBP-CW	620	99-371	150	6 months report
1-1964					
2	TBP-CW	620	99-371	150	6 months report
3					
4	TBP-CW	620	99-371	150	6 months report
1-1965	---	---	---	---	
2	TBP-CW	620	146-371	103	
3	TBP-CW	620	146-371	103	
4	TBP-CW	620	146-371	103	
1-1966	TBP-CW	620	146-371	103	
2	TBP-CW	620	146-371	103	
3	TBP-CW	744	146-495	103	124m from 102-C.
4	TBP-CW	744	146-495	103	
1-1967	TBP-CW	395	146-146	103	349 to 103-BY
2	CW	272	169	103	294m to 103-BY; 171m from 102-C.
3	CW	741	638	103	Received 469m from 102-C.
4	CW	740	637	103	
1-1968	CW	739	636	103	
2	CW	253	150	103	486 to 103-BY.
3	CW	253	150	103	
4	CW	253	150	103	
1-1969	CW-EB	736	150-481	105	481 from 106-BY.
2	CW-EB	737	150-494	93	
3	CW-EB	732	150-486	96	
4	CW-EB	732	150-487	95	
1-1970	CW-EB	733	630	103	
2	CW-EB	743	150-497	96	
3 *	EB	689	591	98	To bottoms service in August.
4	EB	675	511	164	ITS - 2 bottoms and recycle.
1-1971	EB	689	440	249	ITS - 2 bottoms and recycle.
2	EB	706	418	288	ITS - 2 bottoms and recycle.
3	EB	670	382	288	ITS - 2 bottoms and recycle.
4	EB	706	418	288	ITS - 2 mini-cooler and recycle.

** Dry Wells No.'s 22-06-01, 22-06-05 and 22-06-09 were drilled.

9212556119 2

Waste Status Summary of 106-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	580	284	296	ITS - bottoms and recycle.
2	EB	655	359	296	ITS - bottoms and recycle.
3	EB	697	401	296	ITS - bottoms and recycle.
4	EB	704	141	563	ITS - bottoms and recycle.
1-1973	EB	710	263	447	ITS - bottoms and recycle.
2	EB	677	183	494	ITS - bottoms and recycle.
3	EB	704	210	494	ITS - bottoms and recycle.
4	EB	692	198	494	ITS - bottoms and recycle.
1-1974	EB	692	198	494	ITS - bottoms and recycle.
2	EB	701	207	494	ITS - bottoms and recycle.
3 *	EB	697	203	494	ITS - bottoms and recycle 29 from 105-BY, 2 water, 36 to 109-BY.
4	EB	697	277	420	ITS - bottoms and recycle.
1-1975	EB	697	277	420	ITS - bottoms and recycle.
2	EB	697	346	351	ITS - bottoms and recycle.
3	EB	697	346	351	
4	EB	681	330	351	ITS - bottoms and recycle, 16 to 109-BY.
1-1976	EB	681	330	351	ITS - bottoms and recycle.
2	EB	681	330	351	ITS - bottoms and recycle.
3	EVAP.	684	333	351	Active restricted.
4	EVAP.	684	333	351	
1-1977	EVAP.	593	0	593	Salt Well Pumping
2	EVAP.	593	0	593	" " "
3	EVAP.	626	0	626	Inactive Current-Salt Well Installed
4	EVAP.	626	0	626	" " " " "

* Dry Well No. 22-06-11 was drilled.

Waste Status Summary of 106-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1- 1978	-	626	0	626	
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	
1-1979	-	626	0	626	
2-	-	626	0	626	
3-	-	626	0	626	New Photo 8/22/79
4-	-	626	0	626	
1-1980	-	626	0	626	Liquid Pools
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	

9212561194

Waste Status Summary of 107-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	1C	11	11	---	September
4	1C	106	106	---	Began filling in December.
1-1951	1C	744	744	---	Cascade filled in March.
2	1C	744	744	---	Cascade.
3	---	---	---	---	
4	---	---	---	---	
1-1952	1C	758	758	---	
2	1C	758	758	---	
3	1C	334	334	---	Partially pumped 9/25 to 9/28.
4	1C-TBP	1	1	---	Pumped to 106-B--not complete; pumped to liquid heel 12/6/52; no supernate pumped to 106-B in November.
1-1953	1C-TBP	743	1-741	1	Cascade 109-BX - 107-BY. Abandoned 3/25/53.
2	1C-TBP	758	1-756	1	
3	1C-TBP	758	1-756	1	
4	1C-TBP	758	1-756	1	

Waste Status Summary of 107-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C-TBP	758	1-756	1	
2	1C-TBP	758	1-756	1	
3	1C-TBP	101	1-56	44	Pumping to 106-B to be used for TBP scvg. waste.
4	1C-TBP	35	1-33	1	TBP scvg. waste receiver.
1-1955	1C-TBP	276	1-203	72 est.	Scvg. waste receiver.
2	1C-TBP	48	1-2	45	Scvg. waste receiver.
3	1C-TBP	739	1-596	142	Going to BY No. 4 cavern at scvg. waste receiver.
4	1C-TBP	177	1-29	147	Caverned during month.
1-1956	1C-TBP	180	1-19	160	Scvg. waste receiver.
2	1C-TBP	225	1-56	168	Will be pumped to 111-BY; pumped to 109 and 112-BY.
3	1C-TBP	87	---	87	Transferring to 102-BY; 522m to No. 8 BC ditch.
4	TBP	755	605	150	S.S. 627m received; S.S. 301m from 221-U; S.S. received from 241-WR and ditch 588m.
1-1957	TBP	524	374	150	Estimated reading; S.S. received 330m gallons; 561m sent to No. 14 BC ditch.
2	TBP	722	572	150	S.S. received 198m gallons.
3	TBP	486	308	178	198m to BC-18 trench; 38m to BC-19 trench.
4	TBP	172	---	172	Latest electrode reading. 311m to 102-BY.
1-1958	TBP	172	---	172	
2	TBP	172	---	172	
3	TBP	172	---	172	
4	TBP-CW	574	22-402	150	363m from 105-C - 11m flush. Latest electrode reading.
1-1959	TBP-CW	744	22-572	150	Rec'd 170 M from 105-C
2	TBP-CW	771	22-599	150	
3	TBP-CW	771	22-599	150	
4	TBP-CW	771	22-599	150	
1-1960	TBP-CW	771	22-599	150	
2	TBP-CW	771	22-599	150	
3	TBP-CW	771	22-599	150	
4	TBP-CW	771	22-599	150	
1-1961					
2	TBP-CW	733	22-561	150	6 months report
3					
4	TBP-CW	736	22-564	150	Latest electrode reading. 6 months report

9212556119 6

Waste Status Summary of 107-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	TBP-CW	736	22-564	150	6 months report
3					
4	TBP-CW	736	22-564	150	6 months report
1-1963					
2	CW	736	558	178	6 months report
3					
4	CW	728	550	178	New electrode installed. 6 months report
1-1964					
2	CW	730	552	178	6 months report
3					
4	CW	730	552	178	6 months report
1-1965	---	---	---	---	
2	TBP-CW	730	22-558	150	
3	TBP-CW	730	22-558	150	
4	TBP-CW	730	22-558	150	
1-1966	TBP-CW	730	22-558	150	
2	TBP-CW	730	22-558	150	
3	TBP-CW	733	22-561	150	
4	TBP-CW	733	22-561	150	
1-1967	TBP-CW	733	22-561	150	
2	TBP-CW	733	22-561	150	
3	TBP-CW	733	22-561	150	
4	TBP-CW	733	22-561	150	
1-1968	TBP-CW	733	22-561	150	
2	TBP-CW	733	22-561	150	
3	TBP-CW	733	22-561	150	
4	TBP-CW	730	22-558	150	
1-1969	TBP-CW	729	22-557	150	
2	TBP-CW	728	22-556	150	
3	TBP-CW	726	22-554	150	
4	EB	649	499	150	ITS - 2 bottoms and recycle.
1-1970 *	EB	651	593	58	ITS - 2 bottoms and recycle.
2	EB	678	617	61	ITS - 2 bottoms and recycle.
3	EB	638	595	43	ITS - 2 bottoms and recycle.
4	EB	656	550	106	ITS - 2 bottoms and recycle.
1-1971	EB	624	507	117	ITS - 2 bottoms and recycle.
2	EB	674	557	117	ITS - 2 bottoms and recycle.
3	EB	605	488	117	ITS - 2 bottoms and recycle.
4	EB	664	547	117	ITS - 2 bottoms and recycle.

* Dry Wells No.'s 22-07-01, 22-07-05, 22-07-09 were drilled.

9 2 1 2 5 5 6 1 9 7

Waste Status Summary of 107-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	689	572	117	ITS - bottoms and recycle.
2	EB	634	517	117	ITS - bottoms and recycle.
3	EB	648	531	117	ITS - bottoms and recycle.
4	EB	646	529	117	ITS - bottoms and recycle.
1-1973 *	EB	649	474	175	ITS - bottoms and recycle
2	EB	635	460	175	ITS - bottoms and recycle.
3	EB	633	458	175	ITS - bottoms and recycle.
4	EB	659	484	175	ITS - bottoms and recycle.
1-1974	EB	653	478	175	ITS - bottoms and recycle.
2 **	EB	492	48	444	ITS - bottoms and recycle; 39 to 108-8; 103 to 109-B; 23 to 112-B.
3	EB	492	48	444	ITS - bottoms and recycle.
4	EB	491	308	183	ITS - bottoms and recycle.
1-1975	---	367	0	367	ITS - bottoms and recycle; 25 to 106-BX; 99 to 110-BY.
2	---	367	0	367	ITS - bottoms and recycle; 85 to 110-BY.
3	---	367	0	367	Removed from service; 20 to 110-BY.
4	---	367	0	367	Removed from service; 9 to 110-BY.
1-1976	---	367	0	367	Removed from service; 12 to 110-BY.
2	---	367	0	367	Removed from service.
3	---	367	0	367	Inactive - Salt well pumped
4	---	367	0	367	
1-1977	---	367	0	367	Salt Well Pumping- Phase II
2	EVAP.	367	0	367	" " " " "
3	EVAP.	367	0	367	Inactive Current-Phase II pumping
4	EVAP.	367	0	367	" " " " "

* Dry Wells No.'s 22-07-02 drilled.

** Dry Wells No.s 22-07-07, 22-07-04 drilled.

9 2 L 2 5 5 6 1 3 8

Waste Status Summary of 107-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	326	0	326	Primary Stabilized
2-	-	326	0	326	
3-	-	326	0	326	Proto Jet Pump
4-	-	326	0	326	
1-1979	-	326	0	326	
2-	-	326	0	326	New Photo 6/21/79
3-	-	326	0	326	Interim Stabilized
4-	-	326	0	326	
1-1980	-	326	0	326	
2-	-	326	0	326	
3-	-	326	0	326	
4-	-	326	0	326	

9212561179

Waste Status Summary of 108-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949 *	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	1C	20	20	---	Cascade began filling March.
2	1C	538	538	---	Cascade.
3	---	---	---	---	
4	---	---	---	---	
1-1952	1C	753	753	---	
2	1C	753	753	---	
3	1C	753	753	---	
4	1C	753	753	---	

* Dry Well 22-08-07 drilled.

9 2 1 2 5 6 1 2 0

Waste Status Summary of 108-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	753	753	---	
2	TBP	687	687	---	
3	TBP	687	687	---	
4	TBP	687	687	---	
1-1954	TBP	702	702	---	
2	TBP	702	702	---	
3	TBP	266	266	---	To be used for TBP scvg. waste.
4	TBP	127	127	---	TBP scvg. waste receiver.
1-1955	TBP	78	45	33	Scvg. waste receiver.
2	TBP	140	42	98 est.	Scvg. waste receiver.
3	TBP	376	179	197	
4	TBP	200	0	200	Caverned during month.
1-1956	TBP	713	508	205	Scvg. waste receiver.
2	TBP	179	---	179	S.S. active receiver.
3	TBP	523	329	194	S. S. 543,000 gallons received. S.S. 250m to No. 9 BC ditch.
4	TBP	656	455	201	S.S. 258m to BC No. 9 ditch. 539m gallons to No. 11 BC ditch. S.S. 457 received from 221-U.
1-1957	TBP	722	521	201	Latest electrode reading. S.S. 512m to No. 6 crib acting TBP. S.S. received 280m gallons.
2	TBP	722	473	249	S.S. 470m gallons to No. 15 BC ditch. 279 received from 112-C. Latest electrode reading.
3	TBP	213	---	213	27m to 104-BY; 482m to BC; Latest electrode reading.
4	TBP	211	1	210	
1-1958	TBP	211	1	210	
2	TBP	211	1	210	Latest electrode reading.
3	TBP	211	1	210	
4	TBP	244	34	210	Latest electrode reading.
1-1959	TBP	557	557	---	S.S. received 305m from 105-C.
2	TBP-CW	744	557-187	---	
3	TBP-CW	744	557-187	---	
4	TBP-CW	744	347-187	210	

Waste Status Summary of 108-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	TBP-CW	744	247-187	210	
2	TBP-CW	738	347-181	210	Latest electrode reading.
3	TBP-CW	738	347-181	210	
4	TBP-CW	738	347-181	210	
1-1961					
2	TBP-CW	706	34-462	210	6 months report
3					
4	TBP-CW	706	34-462	210	6 months report
1-1962					
2	TBP-CW	706	34-462	210	6 months report
3					
4	TBP-CW	706	34-462	210	Latest electrode reading. 6 months report
1-1963					
2	TBP-CW	703	42-459	202	6 months report
3					
4	TBP-CW	703	42-459	202	6 months report
1-1964					
2	TBP-CW	695	42-451	202	New electrode. 6 months report
3					
4	TBP-CW	697	42-453	202	Latest electrode reading. 6 months report
1-1965					
2	TBP-CW	700	66-456	178	6 months report
3	TBP-CW	700	66-456	178	
4	TBP-CW	700	66-456	178	
1-1966	TBP-CW	700	66-456	178	
2	TBP-CW	700	66-456	178	
3	TBP-CW	700	66-456	178	
4	TBP-CW	697	66-453	178	
1-1967	TBP-CW	697	66-453	178	
2	TBP-CW	697	66-453	178	
3	TBP-CW	697	66-453	178	
4	TBP-CW	697	66-453	178	
1-1968	TBP-CW	695	66-451	178	
2	EB	557	379	178	532 to 109-BY; 394 from 111-BY.
3	EB	657	532	125	ITS No. 2 - bottoms and recycle.
4	EB	604	479	125	ITS No. 2 - bottoms and recycle.
1-1969	EB	582	417	165	ITS - 2 bottoms and recycle.
2	EB	585	363	222	ITS - 2 bottoms and recycle.
3	EB	574	380	194	ITS - 2 bottoms and recycle.
4	EB	574	341	233	ITS - 2 bottoms and recycle.

9 2 1 2 5 5 6 1 2 0 2

Waste Status Summary of 108-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970 *	EB	706	482	224	ITS - 2 bottoms and recycle.
2	EB	657	481	176	ITS - 2 bottoms and recycle.
3	EB	740	446	194	ITS - 2 bottoms and recycle.
4	EB	659	594	65	ITS - 2 bottoms and recycle.
1-1971	EB	692	594	98	ITS - 2 bottoms and recycle.
2	EB	385	0	385	ITS - 2 bottoms and recycle; 296 evaporated by ITS-2 769 to 101-BY.
3	EB	388	0	388	ITS - 2 bottoms and recycle.
4	EB	381	0	381	ITS - 2 bottoms and recycle.
1-1972	EB	381	0	381	ITS - bottoms and recycle.
2	EB	381	0	381	Tank leaks, 49 to 109-BY.
3	EB	381	0	381	Tank leaks, 7 flush water, 18 to 109-BY.
4	EB	312	8	304	Tank leaks, 16 flush water added, 8 to 109-BY.
1-1973 **	EB	312	8	304	Tank leaks.
2	EB	304	0	304	Tank leaks.
3	---	304	0	304	Tank leaks.
4	---	304	0	304	Tank leaks.
1-1974	---	304	0	304	Tank leaks, 8 to 109-BY.
2	---	304	0	304	Tank leaks, 5 to 109-BY.
3	---	304	0	304	Tank leaks, 10 to 109-BY.
4	---	359	0	359	Tank leaks, 6 to 109-BY, 2 water.
1-1975	---	359	0	359	Tank leaks, 4 to 109-BY.
2	---	359	0	359	Tank leaks, 6 to 109-BY.
3	---	359	0	359	Tank leaks, 5 to 109-BY.
4	---	359	0	359	Tank leaks, 3 to 109-BY.
1-1976	---	359	0	359	Tank leaks, 5 to 109-BY.
2	---	359	0	359	Tank leaks, 2 to 109-BY.
3	---	359	0	359	Tank leaks.
4	---	359	0	359	Tank leaks.
1-1977	---	359	0	359	Tank Leaks Salt Well Pumping
2	EVAP.	359	0	359	" " " " "
3	EVAP.	359	0	359	" " " " "
4	EVAP.	u59	0	359	" " Salt Well Pump Installed

* Dry Well 22-08-01, 22-08-05, 22-08-09 drilled.

** Dry Well 22-08-02, 22-08-06, 22-08-12 drilled.

Waste Status Summary of 108-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	359	0	359	Primary Stabilized
2-	-	359	0	359	
3-	-	359	0	359	P-10 Pmp. Removed
4-	-	359	0	359	
1-1979	-	359	0	359	
2-	-	359	0	359	
3-	-	359	0	359	
4-	-	359	0	359	
1-1980	-	359	0	359	New Photo 1/16/80
2-	-	359	0	359	1000 Gal. pool
3-	-	359	0	359	
4-	-	359	0	359	

9 2 1 2 5 6 1 2 7 4

Waste Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	TBP	---	---	---	Supernate tank.
2	TBP	---	---	---	TBP supernate tank - 200-E Area.
3	TBP	---	---	---	TBP supernate tank - 200-E Area.
4	TBP	---	---	---	TBP supernate tank - 200-E Area.

9212561205

Waste Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	448	448	---	Supernate from 103-B on 1/8/53.
2	MW	448	448	---	Supernate.
3	MW	44	44	---	Supernatant.
4	MW	44	44	---	Supernatant.
1-1954	MW	281	281	---	Supernatant received from 108 and 101-BY via 103-BY pump.
2	MW	408	408	---	Transfer to 104-C Tank.
3	MW	34	34	---	Transferred to 104-C Tank.
4	MW	477	477	---	Received from 112-BY--pumped to 104-C; supernatant pump tank.
1-1955	MW	551	551	---	Received from 104-C supernatant pump tank.
2	MW	237	237	---	
3	TBP	34	34	---	Sluicing to be done.
4	TBP	34	34	---	
1-1956	TBP	34	34	---	
2	TBP	722	722	---	Received from 107-BY.
3	TBP	722	686	36	
4	TBP	722	656	66	
1-1957	TBP	722	656	66	Latest electrode reading.
2	TBP	66	0	66	Received 195m gallons from 112; 677 sent to No. 16 - BC ditch.
3	TBP	48	2	46	Latest electrode reading.
4	TBP	48	2	46	
1-1958	TBP	48	2	46	
2	TBP	46	---	46	
3	TBP	46	---	46	
4	TBP	46	---	46	
1-1959	TBP	47	1	46	Latest electrode reading.
2	TBP	47	1	46	
3	TBP	47	1	46	
4	TBP	47	1	46	
1-1960	TBP	47	1	46	
2	TBP	47	1	46	
3	TBP	47	1	46	
4	TBP	47	1	46	

9 2 1 2 5 5 6 1 2 0 6

Waste Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	TBP	48	2	46	6 months report
3					
4	TBP	51	5	46	6 months report
1-1962					
2	TBP-CW	623	5-572	46	435m from 107-C, 6 months report 137m from 109-C.
3					
4	TBP-CW	623	5-572	46	6 months report
1-1963					
2	CW	623	547	76	6 months report
3					
4	CW	634	558	76	New electrode installed. 6 months report
1-1964					
2	CW	629	553	76	New electrode. 6 months report
3					
4	CW	623	547	76	New electrode (reading confirmed). 6 months report
1-1965					
2	CW	642	585	57	Received 19m during 112-BY to 101-BY. 6 months report
3	CW	642	585	57	
4	CW	642	585	57	
1-1966	CW	642	585	57	
2	CW	642	585	57	
3	CW	139	82	57	503m to 103-BY.
4	CW	486	429	57	347m from 102-C.
1-1967	CW	642	585	57	156m from 102-C.
2	CW	742	685	57	Received 100m from 102-C.
3	CW	742	685	57	
4	CW	742	685	57	
1-1968	CW	743	686	57	
2	CW	269	212	57	1116 to 103-BY; 642 from 108, 105-BY.
3	CW	556	519	37	ITS - No. 2 feed tank.
4	CW-OWW	596	320-222	54	ITS - No. 2 feed tank.

9 2 1 2 5 5 6 1 2 0 7

Waste Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	EB-CW	558	200-286	72	ITS - 2 feed tank; 1197 from 103-BY.
2	EB-CW-OWW	596	382-74-53	87	ITS - 2 feed tank; 1376 from 103-BY.
3	EB-CW-OWW	655	432-39-105	79	ITS - 2 feed tank; 1558 from 103-BY.
4	EB	593	479	114	ITS - 2 feed tank; 1172 from 103-BY.
1-1970 *	EB	607	417	190	ITS - 2 feed tank; 617 from 103-BY; 644 from 102-BX.
2	EB	574	454	120	ITS - 2 feed tank; 602 from 102-BX; 749 from 103-BY.
3	EB	579	451	128	ITS - 2 feed tank; 1413 from 103-BX; 66 from 102-BY (to 105-BY).
4	EB	598	456	142	ITS - 2 feed receiving tank; 1561 from 103-BX.
1-1971	EB	589	439	150	ITS - 2 feed receiving tank; 785 from 103-BX.
2	EB	608	480	128	ITS - 2 feed receiving tank; 198 from 103-BX.
3	EB	618	490	128	ITS - 2 feed receiving tank; 505 from 103-BX; 30 from 106-BX; 56 steam sparger; 35 flush water.
4	EB	598	445	153	ITS - 2 feed receiving tank; 1.260 from 103-BX; 125 flush water.
1-1972	EB	623	470	153	ITS - feed receiving tank; 1415 from 103-BX; 165 flush water; 1312 evaporated.
2	EB	600	378	222	ITS - feed receiving tank; 1364 from 103-BX; 134 flush water; 49 from 108-BY; 1416 evaporated.
3	EB	620	360	260	ITS - feed receiving tank; 1042 from 103-BX; 18 from 108-BY; 167 flush water; 1239 evaporated.
4	EB	612	278	334	ITS - feed receiving tank; 986 from 103-BX; 8 from 109-BY; 137 flush water; 1044 evaporated.

* Dry Well 22-09-01, 22-09-05, 22-09-08 drilled.

9 2 1 2 5 5 6 1 2 0 8

Water Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973	EB	613	232	381	Its - feed receiving tank; 980 from 103-BX; 127 flush water; 1011 evaporated.
2	EB	602	024	398	ITS - feed receiving tank; 785 from 103-BX; 86 flush water; 793 evaporated.
3	EB	603	205	398	ITS - receiving tank; 25 from 103-BY.
4	EB	587	176	411	ITS - feed receiving tank; 86 water; 4 from 103-BY; 11 evaporated.
1-1974 *	EB	594	183	411	ITS - feed receiving tank; 56 water; 8 from 108-BY; 6 evaporated.
2	EB	581	148	433	ITS - feed receiving tank; 5 from 103-BY; 5 from 108-BY; 28 to 112-BY; 15 water; 0 evaporated.
3	EB	602	169	433	ITS - feed receiving tanks; 13 from 103-BY; 73 from 105-BY; 36 from 106-BY; 10 from 108-BY; 111 to 112-BY.
4	EB	557	132	425	ITS - feed receiving tank; 6 from 101-BY; 16 from 105-BY; 6 from 108-BY; 71 to 112-BY.
1-1975	EB	571	146	425	ITS - feed receiving tank; 5 from 103-BY; 4 from 105-BY; 4 from 108-BY.
2	EB	541	116	425	ITS - feed receiving tank; 27 from 105-BY; 6 from 108-BY; 65 to 112-BY.
3	EB	565	140	425	11 from 105-BY; 5 from 108-BY; 8 water.
4	EB	598	173	425	ITS - feed receiving tank; 4 from 103-BY; 6 from 105-BY; 16 from 106-BY; 3 from 108-BY; 4 water.
1-1976	EB	576	151	425	ITS - feed receiving tank; 34 to 112-BY; 5 from 103-BY; 5 from 108-BY; 2 from 105-BY.
2	EB	585	160	425	ITS - feed receiving tank; 1 from 103-BY; 2 from 108-BY.
3	EVAP.	593	168	425	Con. feed.
4	EVAP.	596	171	425	

* Dry Well 22-09-02, 22-09-07, 22-09-11 drilled.

9212556120 9

Waste Status Summary of 109-BY Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	EVAP.	459	33	425	Con. Feed
2	EVAP.	442	9	433	Con. Feed Salt Well Installed
3	EVAP.	444	11	433	Salt Well Receiver
4	EVAP	447	14	433	" " "
1-1978		458	25	433	
2-	NCPLX	455	22	433	
3-	NCPLX	458	25	433	
4-	NCPLX	461	28	433	
1-1979	NCPLX	466	33	433	P-10 Removed
2-	NCPLX	466	33	433	
3-	NCPLX	466	33	433	New Sludge Level 8/9/79
4-	NCPLX	466	33	433	New Photo 7/17/79
1-1980	NCPLX	466	33	433	
2-	NCPLX	466	33	433	
3-	NCPLX	466	33	433	
4-	NCPLX	466	33	433	

9212556120

Waste Status Summary of 110-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	1C	638	638	---	1C Tank now filling B Plant.
2	1C	653	653	---	1C Tank now filling B Plant.
3	1C	722	722	---	Abandoned as 1st cycle cascaded.
	1C	732	732	---	Active 1st cycle - Tank 221-B.

Waste Status Summary of 110-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	732	732	---	
2	Supernate 1C	731	731	---	
3	Supernate 1C	731	731	---	
4	1C	731	731	---	
1-1954	Supernate 1C	731	731	---	
2	Supernate 1C	731	731	---	
3	Supernate 1C	37	37	---	Supernatant pumped to ditch. Started receiving TBP scvg. waste.
4	TBP	261	210	51	Scvg. waste receiver.
1-1955	TBP	729	608	121 Est.	Pumped to BY No. 9 ditch, 103-BY and 105-BY scvg. waste receiver.
2	TBP	640	555	85	Receiving TBP waste.
3	TBP	238	238	---	Scvg. waste receiver.
4	TBP	722	574	148	Scvg. waste receiver.
1-1956	TBP	724	574	150	Scvg. waste receiver.
2	TBP	724	724	---	S.S. active receiver.
3	TBP	722	511	211	S.S. pumped to 105-BY. 504m gallons pumped to No. 7BC S.S.
4	TBP	229	---	229	S.S. 495m to BC No. 10 ditch. S.S. received from 241-WR. 528m gallons sent to No. 12BC.
1-1957	TBP	442	232	210	S.S. active TBP receiver. 283m sent to No. 14 BC ditch.
2	TBP	697	492	205	S.S. received 181m gallons. S.S. 87m received. 13m to No. 17 BC trench.
3	TBP	224	13	211	316m to BC-17, 146m to latest electrode reading.
4	TBP-CW	304	14-80	210	67m from 105-C and 13m flush.
1-1958	TBP-CW	607	224-173	210	298m from 105-C.
2	TBP-CW	604	224-170	210	
3	TBP-CW	611	224-177(E)	210	
4	TBP-CW	717	224-283	210	103m from 105-C. Latest electrode reading.
1-1959	TBP-CW	717	224-283	210	
2	TBP-CW	716	224-282	210	
3	TBP-CW	716	224-282	210	
4	TBP-CW	739	224-305	210	

9 2 1 2 5 5 6 1 2 1 2

Waste Status Summary of 110-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	TBP-CW	739	224-305	210	
2	TBP-CW	739	224-305	210	
3	TBP-CW	739	224-305	210	
4	TBP-CW	739	224-305	210	
1-1961	---	---	---	---	[6 months report
2	TBP-CW	708	224-274	210	
3	---	---	---	---	[6 months report
4	TBP-CW	708	224-274	210	
1-1962	---	---	---	---	[6 months report
2	TBP-CW	708	224-274	210	
3	---	---	---	---	[6 months report
4	TBP-CW	708	224-274	210	
1-1963	---	---	---	---	[6 months report
2	TBP-CW	706	224-236	246	
3	---	---	---	---	[6 months report
4	TBP-CW	706	224-236	246	
1-1964	---	---	---	---	[6 months report
2	TBP-CW	706	224-236	246	
3	---	---	---	---	
4	TBP-CW	706	224-236	246	[6 months report
1-1965	---	---	---	---	[6 months report
2	TBP-CW	703	224-249	230	
3	TBP-CW	706	224-252	230	
4	TBP-CW	713	224-249	230	
1-1966	TBP-CW	706	224-252	230	
2	TBP-CW	706	224-252	230	
3	TBP-CW	700	224-246	230	Latest electrode reading.
4	TBP-CW	700	224-246	230	
1-1967	TBP-CW	706	224-252	230	
2	TBP-CW	697	224-243	230	
3	TBP-CW	693	224-239	230	
4	TBP-CW	693	224-239	230	
1-1968	TBP-CW	706	224-252	230	13m correction.
2	TBP-CW	706	224-252	230	
3	TBP-CW	706	224-252	230	
4	CW	706	476	230	
1-1969	CW	701	471	230	
2	CW-EB	642	394-59	189	Added to ITS -2 bottoms and recycle system 6/27/69.
3	EB	692	569	123	ITS - 2 bottoms and recycle.
4	EB	703	580	123	ITS - 2 bottoms and recycle.

9 2 1 2 5 5 6 1 2 1 3

Waste Status Summary of 110-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970 *	EB	627	426	201	ITS - 2 bottoms and recycle.
2	EB	519	329	190	ITS - 2 bottoms and recycle.
3	EB	664	453	211	ITS - 2 bottoms and recycle.
4	EB	697	420	277	ITS - 2 bottoms and recycle.
1-1971	EB	675	398	277	ITS - 2 bottoms and recycle.
2	EB	690	413	277	ITS - 2 bottoms and recycle.
3	EB	708	431	277	ITS - 2 bottoms and recycle.
4	EB	645	368	277	ITS - 2 bottoms and recycle.
1-1972	EB	628	351	277	ITS - bottoms and recycle.
2	EB	714	437	277	ITS - bottoms and recycle.
3	EB	667	390	277	ITS - bottoms and recycle.
4	EB	644	367	277	ITS - bottoms and recycle.
1-1973	EB	672	395	277	ITS - bottoms and recycle.
2	EB	653	376	277	ITS - bottoms and recycle.
3	EB	706	429	277	ITS - bottoms and recycle.
4	EB	673	396	277	ITS - bottoms and recycle.
1-1974 **	EB	670	393	277	ITS - bottoms and recycle.
2	EB	690	413	277	ITS - bottoms and recycle, 12 from 102-BY.
3	EB	688	411	277	ITS - bottoms and recycle.
4	EB	689	393	296	ITS - bottoms and recycle.
1-1975	EB	684	388	296	ITS - bottoms and recycle, 123 to 106-BX, 99 from 107-BY.
2	EB	645	349	296	ITS - bottoms and recycle, 114 to 106-BX, 85 from 110-BY.
3	EB	667	371	296	20 from 107-BY.
4	EB	673	377	296	ITS - bottoms and recycle.
1-1976	EB	684	388	296	ITS - bottoms and recycle.
2	EB	684	338	296	ITS - bottoms and recycle.
3	EVAP.	678	382	296	Con. feed bottoms.
4	EVAP.	678	382	296	
1-1977	EVAP.	609	233	376	Con. Feed Btms. Salt Well Installed
2	EVAP.	532	156	376	" " " " " "
3	EVAP.	549	80	469	Salt Well Receiver Solid Level Adj.
4	EVAP.	560	91	469	" " " " " "

* Dry Well 22-10-05, 22-10-10 drilled.
** Dry Well 22-10-07, 22-10-09 drilled.

9 2 1 2 5 5 6 1 2 1 4

Waste Status Summary of 110-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	571	102	469	
2-	NCPLX	579	110	469	
3-	NCPLX	582	113	469	
4-	NCPLX	585	116	469	
1-1979	NCPLX	585	116	469	Active salt well Receiver
2-	NCPLX	552	83	469	New Photo 6/29/79
3-	NCPLX	530	61	469	New Photo 8/17/79
4-	NCPLX	530	61	469	Inactive
1-1980	NCPLX	508	3	505	
2-	NCPLX	508	3	505	
3-	NCPLX	508	3	505	
4-	NCPLX	508	3	505	

9 2 1 2 5 5 6 1 2 1 5

Waste Status Summary of 111-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	758	758	---	
2	MW	758	758	---	
3	MW	758	758	---	
4	MW	758	758	---	Receives high TBP wastes for temp. storage (received 11,000 gallons in December).

9 2 1 2 5 6 1 2 1 6

Waste Status Summary of 111-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	759	759	---	Receives high waste from TBP into temp. storage.
2	MW	758	758	---	Received 6,000 gallons of 1-2 material which cascaded to 112-BY. Receives misc.-
3	MW	758	758	---	
4	MW	758	758	---	
1-1954	MW	758	758	---	
2	MW	758	758	---	Receives high uranium waste.
3	MW	758	758	---	Receives high uranium waste from TBP and hot semi-works.
4	MW	24	24	---	
1-1955	MW	11	11	---	Active sluicing tank.
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1956	---	---	---	---	
2	TBP	526	526	---	
3	TBP	26	26	---	To go to BX No. 3 crib in 500m gallons went to No. 3BC.
4	TBP	26	26	---	
1-1957	TBP	35	9	26	Latest electrode reading. Received 300m from 1050.
2	OWW-CW	706	34-646	26	
3	OWW-CW	706	34-646	26	Latest electrode reading.
4	OWW-CW	706	34-646	26	
1-1958	OWW-CW	706	34-646	26	
2	OWW-CW	706	34-646	26	
3	OWW-CW	706	34-646	26	
4	OWW-CW	706	34-646	26	
1-1959	OWW-CW	711	34-651	26	Latest electrode reading.
2	OWW-CW	711	34-651	26	
3	OWW-CW	711	34-651	26	
4	OWW-CW	711	34-651	26	
1-1960	OWW-CW	711	34-651	26	
2	OWW-CW	711	34-651	26	
3	OWW-CW	711	34-651	26	
4	OWW-CW	711	34-651	26	
1-1961	---	---	---	---	] 6 months report
2	OWW-CW	711	34-651	26	
3	---	---	---	---	
4	OWW-CW	614	34-654	26	Latest electrode reading. [6 months report

9 2 1 5 6 1 2 1 7

Waste Status Summary of 111-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962	---	---	---	---	[6 months report
2	OWW-CW	714	34-654	26	
3	---	---	---	---	[6 months report
4	CWW-CW	714	34-654	26	
1-1963	---	---	---	---	[6 months report
2	OWW-CW	717	34-659	24	
3	---	---	---	---	
4	OWW-CW	717	34-659	24	[6 months report
1-1964	---	---	---	---	[6 months report
2	OWW-CW	717	34-659	24	
3	---	---	---	---	[6 months report
4	OWW-CW	717	34-659	24	
1-1965	---	---	---	---	[6 months report
2	OWW-CW	739	34-679	26	New electrode.
3	CW	367	341	26	372m to 103-BY.
4	CW	343	317	26	24m to 103-BY.
1-1966	CW	29	3	26	314m to 102-BY.
2	CW	585	559	26	556m from 102-C.
3	CW	741	715	26	170m from 102-C; 14m to 112-BY.
4	CW	741	689	26	
1-1967	CW	739	713	26	
2	CW	739	713	26	
3	CW	739	713	26	
4	CW	752	726	26	Received 13m - ITS No. 2 preparation.
1-1968	CW	36	10	26	716m to 103-BY.
2	EB	629	603	26	379 to 108-BY; 972 from 112-BY.
3	EB	576	431	145	ITS No. 2 bottoms and recycle.
4	EB	640	495	145	ITS No. 2 bottoms and recycle.
1-1969	EB	541	493	48	ITS - 2 bottoms and recycle.
2	EB	600	548	52	ITS - 2 bottoms and recycle.
3	EB	570	469	101	ITS - 2 bottoms and recycle.
4	EB	642	500	142	ITS - 2 bottoms and recycle.
1-1970 *	EB	618	352	266	ITS - 2 bottoms and recycle.
2	EB	668	378	290	ITS - 2 bottoms and recycle.
3	EB	666	343	323	ITS - 2 bottoms and recycle.
4	EB	695	22	673	ITS - 2 bottoms and recycle.

* Dry Well 22-11-01, 22-11-05, 22-11-09, drilled.

9212556128

Waste Status Summary of 111-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	EB	685	12	673	ITS - 2 bottoms.
2	EB	693	7	686	ITS - 2 bottoms.
3	EB	697	11	686	ITS - 2 bottoms.
4	EB	692	6	686	ITS - 2 bottoms. & Recycle
1-1972	EB	688	494	194	ITS - bottoms and recycle.
2	EB	686	574	112	ITS - bottoms and recycle.
3	EB	653	511	142	ITS - bottoms and recycle.
4	EB	662	520	142	ITS - bottoms and recycle.
1-1973	EB	650	508	142	ITS - bottoms and recycle.
2	EB	649	507	142	ITS - bottoms and recycle.
3	EB	624	482	142	ITS - bottoms and recycle.
4	EB	677	535	142	ITS - bottoms and recycle.
1-1974 *	EB	677	535	142	ITS - bottoms and recycle.
2	EB	711	569	142	ITS - bottoms and recycle.
3	EB	673	531	142	ITS - bottoms and recycle.
4	EB	673	374	299	ITS - bottoms and recycle.
1-1975	EB	673	374	299	ITS - bottoms and recycle.
2	EB	673	374	299	ITS - bottoms and recycle.
3	EB	673	374	299	
4	EB	670	371	299	ITS - bottoms and recycle.
1-1976	EB	670	371	299	ITS - bottoms and recycle.
2	EB	670	371	299	ITS - bottoms and recycle.
3	EVAP.	670	371	299	Contains salt - feed bottoms.
4	EVAP.	670	371	299	
1-1977	EVAP.	670	371	299	Contains salt Feed Btms.
2	EVAP.	615	316	299	" " " "
3	EVAP.	510	0	510	Inactive Current
4	EVAP.	615	0	615	Inactive Current

* Dry Well 22-11-07 drilled.

9212556129

Waste Status Summary of 111-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	615	0	615	New Photo 2/6/78
2-	-	615	0	615	
3-	-	615	0	615	
4-	-	615	0	615	
1-1979	-	615	0	615	
2-	-	615	0	615	
3-	-	615	0	615	
4-	-	615	0	615	
1-1980	-	615	0	615	
2-	-	615	0	615	New Solids Level 6/30/80
3-	-	615	0	615	
4-	-	622	0	622	

9212561220

Waste Status Summary of 112-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	MW	252	252	---	MW tank now filling - B Plant.
					MW tank now filling - B Plant.
2	MW	271	271	---	MW tank now filling - B Plant.
3	MW	294	294	---	Active - MW tank - 221-B.
4	MW	362	362	---	Abandoned by B Plant as metal waste cascade. Waste will be cribbed.

9 2 1 2 3 6 1 2 2 1

Waste Status Summary of 112-BY Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	389	389	---	
2	MW	400	400	---	Waste from TBP and hot semi-works. Waste from TBP and hot semi-works.
3	MW	394	394	---	Receives misc. waste from TBP and hot semi-works.
4	MW	394	394	---	Receives misc. waste from TBP and hot semi-works.
1-1954	MW	394	394	---	Receives high uranium from TBP and hot semi-works.
2	MW	394	394	---	Receives high uranium waste from TBP and hot semi-works.
3	MW	394	394	---	Receives high uranium waste from TBP and hot semi-works.
4	MW	1	1	---	
1-1955	MW	1	1	---	
2	MW	5	5	---	
3	---	---	---	---	Sluicing.
4	---	---	---	---	
1-1956	---	---	---	---	
2	TBP	477	477	---	Received from 107-BY.
3	TBP	697	697	---	
4	TBP	697	697	---	
1-1957	TBP	695	695	---	Latest electrode reading.
2	TBP	183	183	---	373m from 3330 S.S. 93m received from TBP, S.S. 77m received 385m to No. 15BC ditch; and 297m to No. 16BC ditch.
3	TBP-CW	631	183-448	---	Received 250m from 105-C Latest electrode reading-received 200m from 105-C.
4	TBP-CW	755	183-572	---	Received 124m from 105-C.
1-1958	TBP-CW	755	183-572	---	
2	TBP-CW	755	183-572	---	
3	TBP-CW	755	183-572	---	
4	TBP-CW	755	183-572	---	
1-1959	TBP-CW	755	183-572	---	
2	TBP-CW	755	183-572	---	
3	TBP-CW	755	183-572	---	
4	TBP-CW	755	183-572	---	
1-1960	TBP-CW	755	183-572	---	
2	TBP-CW	741	183-558	---	
3	TBP-CW	741	183-558	---	
4	TBP-CW	741	183-558	---	

Waste Status Summary of 112-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961	---	---	---	---	[6 months report
2	TBP-CW	741	183-558	---	
3	---	---	---	---	
4	TBP-CW	741	183-558		[6 months report
1-1962	---	---	---	---	[6 months report
2	TBP-CW	741	183-558	---	
3	---	---	---	---	
4	TBP-CW	741	183-558	---	[6 months report
1-1963	---	---	---	---	
2	TBP-CW	744	183-532	29	[6 months report
3	---	---	---	---	
4	TBP-CW	744	183-532	29	[6 months report
1-1964	---	---	---	---	
2	TBP-CW	755	183-543	29	[6 months report
3	---	---	---	---	
4	TBP-CW	755	183-543	29	[6 months report
1-1965	---	---	---	---	
2	TBP-CW	279	183-72	24	457m to 101-BY (ITS) [6 months report 19m to 109-BY.
3	CW	48	24	24	256m to 103-BY; 25m from 102-C.
4	CW	312	288	24	264m from 102-C.
1-1966	CW	730	706	24	418m from 102-C.
2	CW	730	706	24	
3	CW	744	720	24	14m from 111-BY.
4	CW	744	720	24	
1-1967 *	CW	750	726	24	
2	CW	751	727	24	
3	CW	751	727	24	
4	CW	756	732	24	Received 4m - ITS No. 2 preparation.
1-1968	CW	547	523	24	741m reclaimed by ITS No. 2.
2	EB	605	588	17	1204 reclaimed by ITS No. 2.
3	EB	612	610	2	80 reclaimed by ITS No. 2.
4	EB	574	572	2	1263 reclaimed by ITS No. 2.
1-1969	EB	722	679	43	1208 reclaimed by ITS 2.
2	EB	725	666	59	1332 evaporated by ITS 2.
3	EB	703	624	79	1512 evaporated by ITS 2.
4	EB	689	610	79	1241 evaporated by ITS 2.
1-1970	EB	708	623	85	1216 evaporated by ITS 2.
2	EB	706	612	94	1096 evaporated by ITS 2.
3	EB	712	567	145	1303 evaporated by ITS 2.
4	EB	704	540	164	1492 evaporated by ITS 2.

9 2 1 2 5 5 6 1 2 2 3

Waste Status Summary of 112-BY Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	EB	700	445	255	1311 evaporated by ITS 2.
2	EB	699	640	59	297 (H_2O)
3	EB	716	550	166	714 evaporated by ITS 1 and 2.
4	EB	722	528	194	1604 evaporated by ITS 1 and 2.
1-1972	EB	664	368	296	
2	EB	672	338	334	ITS - bottoms and recycle.
3	EB	670	336	334	ITS - bottoms and recycle.
4	EB	663	348	315	ITS - bottoms and recycle.
1-1973	EB	689	401	288	ITS - bottoms and recycle.
2	EB	679	391	288	ITS - bottoms and recycle.
3	EB	688	357	311	ITS - bottoms and recycle.
4	EB	703	372	331	ITS - bottoms and recycle.
1-1974	EB	681	350	331	ITS - bottoms and recycle.
2	EB	702	371	331	ITS - bottoms and recycle; 28 from 109-BY.
3	EB	703	372	331	ITS - bottoms and recycle; 98 to 102-BY; 111 from 109-BY.
4	EB	711	401	310	ITS - bottoms and recycle; 61 to 106-BX; 71 from 106-BY.
1-1975	EB	706	396	310	ITS - bottoms and recycle.
2	EB	706	396	310	ITS - bottoms and recycle; 65 from 109-BY; 66 to 106-BX.
3	EB	706	396	310	
4	EB	673	363	310	ITS - bottoms and recycle, 32 to 105-BX.
1-1976	EB	340	30	310	ITS - bottoms and recycle; 46 to 106-BX; 311 to 105-BX; 34 from 109-BY.
2	---	310	0	310	Removed from service, 46 to 106-BX.
3	---	310	0	310	Salt well pumping - complete.
4	---	310	0	310	
1-1977	---	310	0	310	Salt Well Pump
2	EVAP.	310	0	310	Salt Well Pump
3	EVAP.	310	0	310	Inactive Current Phase I Complete
4	EVAP.	310	0	310	Inactive Current Phase I Complete

9 2 1 2 5 5 6 1 2 2 4

Waste Status Summary of 112-BY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	310	0	310	Primary Stabilized
2-	-	310	0	310	
3-	-	310	0	310	
4-	-	310	0	310	
1-1979	-	310	0	310	
2-	-	310	0	310	P-10 Pmp Removed
3-	-	310	0	310	
4-	-	310	0	310	
1-1980	-	310	0	310	
2-	-	310	0	310	
3-	-	310	0	310	
4-	-	310	0	310	

9 2 1 2 5 6 1 2 2 5

Waste Status Summary of 101-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	MW	111	---	---	1st Cascade, began filling in March 1946
2-	MW	528	---	---	Full in May 1946
3	MW	528	---	---	Cascading
4	MW	528	---	---	Cascade full in October 1946
1-1947	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1951	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	

Waste Status Summary of 101-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquids in Storage	Solids in Storage	Remarks
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	---	---	---	984 in Cascade, Cascade now Processing for feed to TBP Plant
1-1953	MW	---	---	---	1507 in 101 thru 106-C. 1651 removed thru batch CR 1218
2	TBP	422	---	---	MW removal completed 5-14. TBP waste started 5-15
3	TBP	222	---	---	Received TBP waste and pumped to 103-C
4	TBP	517	---	---	Received TBP waste
1-1954	TBP	510	---	---	
2	TBP	510	---	---	Overflow line partially plugged
3	TBP	510	---	---	Overflow partially plugged
4	TBP	510	---	---	Overflow partially plugged
1-1955	TBP	510	---	---	Overflow partially plugged
2	TBP	510	---	---	Overflow partially plugged
3	TBP	510	---	---	Overflow partially plugged
4	TBP	326	---	---	Overflow partially plugged
1-1956	TBP	485	---	---	Overflow partially plugged. Received TBP in January
2	TBP	485	---	---	Overflow partially plugged
3	TBP	161	---	---	Being scavenged & pumped to 112-C
4	TBP	131	---	---	30 Scavenged in October
1-1957	TBP	98	---	---	Latest electrode readings, enough for 1451 TU
2	TBP	483	---	---	Feed tank for Scvg. opr.
3	EB	178	---	---	Feed tank for scvg. opr.
4	TBP	131	---	---	Feed tank for scvg. opr.
1-1958	TBP	150	52	98	Latest electrode reading
2	TBP	125	27	98	New electrode reading
3	TBP	125	27	98	
4	TBP	125	27	98	
1-1959	TBP	125	27	98	
2	TBP	128	30	98	
3	TBP	131	33	98	Latest electrode reading
4	TBP	131	33	98	

9 2 1 2 3 6 1 2 2 7

Waste Status Summary of 101-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquids in Storage	Solids in Storage	Remarks
1-1960	TBP	131	33	98	
2	TBP	131	33	98	
3	TBP	131	33	98	
4	TBP-CW	150	33-19	98	Rec'd 19M CW
1-1961					
2	CW	510	379	98	Rec'd 423M CW (6 month report)
3					
4	CW	510	379	98	6 month report
1-1962					
2	CW	524	393	98	Rec's 214M; 699M to BX
3					6 month report
4	CW	524	393	98	6 month report
1-1963					
2	CW	524	393	109	6 month report
3					
4	CW-P	370	(94-276)	109	276M from 102A 6 month report
1-1964					
2	CW-P	542	(94-448)	109	Rec'd 172M from 103A
3					
4	CW-P	546	(94-452)	109	New elect. (Read. Confirmed)
1-1965					
2	CW-P	574	43-480	51	28M from CR
3	CW-P	568	43-474	51	
4	CW-P	565	43-471	51	
1-1966	CW-P	563	43-469	51	
2	CW-P	571	43-477	51	New electrode
3	CW-P	656	43-471	51	
4	CW-P	563	43-469	51	
1-1967	CW-P	557	43-463	51	
2	CW-P	555	43-461	51	
3	CW-P	555	43-461	51	
4	CW-P	549	43-455	51	
1-1968	CW-P	545	39-455	51	
2	CW-P	545	39-455	51	Tk. 102-C rec'd 200 OWW & 359 CW from Purex 599 to 105BX & 103BX
3	CW-P	545	39-455	51	TK 102-C rec'd 521CW & 265 OWW
4	CW-P	541	39-451	51	

Waste Status Summary of 101-C Tank-Capacity 530,00 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	CW-P	541	39-451	51	
2	CW-P	538	39-448	51	
3	CW-P	538	39-393	106	
4	P	132	7	125	404 to 105-C
1-1970 *	P	134	47	87	
2	P	134	47	87	
3	P	136	55	81	Possible Leaker
4	P	138	57	81	
1-1971	P	131	50	81	
2	P	131	50	81	
3	P	128	47	81	
4	P	127	46	81	
1-1972	P	125	44	81	
2	P	125	44	81	
3	P	124	43	81	
4	P	120	39	81	
1-1973	P	121	40	81	
2	P	120	39	81	
3	P	120	39	81	
4	P	131	50	81	Suspect leaker
1-1974	P	129	48	81	Suspect leaker
2	P	128	47	81	Suspect leaker
3	---	81	0	81	Suspect leaker, 49 to 104-C
4	P	92	30	62	Suspect leaker
1-1975	P	92	30	62	Suspect leaker
2	P	92	30	62	Removed from service
3	P	92	30	62	Removed from service
4	P	92	30	62	Removed from service
1-1976	P	92	30	62	Removed from service
2	—	73	0	73	
3	—	73	0	73	Salt Well Pumped
4	—	73	0	73	" " "
1-1977	—	73	0	73	
2	—	73	0	73	
3	—	73	0	73	
4	—	73	0	73	Inactive Current Salt well Installed

* Dry Wells 30-01-01, 30-01-06, 30-01-09, 30-01-12 drilled.

9 2 1 2 5 6 1 2 2 9

Waste Status Summary of 101-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	73	0	73	Primary Stabilized
2-	-	73	0	73	Questionable integrity
3-	-	73	0	73	
4-	-	73	0	73	
1-1979	-	73	0	73	
2-	-	73	0	73	
3-	-	73	0	73	
4-	-	73	0	73	
1-1980	-	73	0	73	
2-	-	73	0	73	
3-	-	73	0	73	
4-	-	73	0	73	

9 2 1 2 5 5 6 1 2 3 0

Waste Status Summary of 102-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	MW	195	---	---	Cascade, began filling in May 1946
3	MW	528	---	---	Filled in August
4	MW	528	---	---	Cascade full in October 1946
1-1947	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1951	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	---	---	---	984 in Cascade, cascade now processing for feed to TBP plant

921261231

Waste Status Summary of 102-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	---	---	---	1507 in 101 thru 106-C, 1651 removed thru batch CR 1218
2	MW	---	---	---	Small sludge heel
3	TBP	467	---	---	Received TBP waste
4	TBP	508	---	---	Received TBP waste
1-1954	TBP	530	---	---	
2	TBP	530	---	---	
3	TBP	530	---	---	
4	TBP	530	---	---	
1-1955	TBP	530	---	---	
2	TBP	530	---	---	
3	TBP	530	---	---	
4	TBP	530	---	---	
1-1956	TBP	530	---	---	
2	TBP	530	---	---	
3	TBP	530	---	---	
4	TBP	530	---	---	
1-1957	TBP	98	---	---	Latest electrode reading
2	OWW	48	---	---	Scavenged during month
3	TBP	48	---	---	
4	TBP	48	---	---	
1-1958	TBP	150	52	98	Latest electrode reading
2	TBP	37	37	---	Latest electrode reading
3	TBP	37	37	---	
4	TBP	37	37	---	
1-1959	TBP	37	37	---	
2	TBP	37	37	---	
3	TBP	34	34	---	Latest electrode reading
4	TBP	34	34	---	
1-1960	TBP	34	34	---	
2	TBP	34	34	---	
3	TBP-CW	378	34-344	---	SS 344 CW & Dilution Rec'd
4	TBP-CW	491	34-457	---	140 CW rec'd, previous reading were incorrect
1-1961					
2	TBP-CW	521	34-487	---	6 month report
3					
4	TBP-CW	519	34-485	---	6 month report

Waste Status Summary of 102-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	CW	356	356		6 month report
3					
4	CW	370	370	---	Rec'd 986, 1142 to BX 6 month report
1-1963					
2	CW	334	334	---	Rec'd 829 CW (6 month report)
3					
4	CW	450	450	---	Rec'd 854 CW (6 month report)
1-1964					
2	CW	407	407	---	Rec'd 881 CW from 202-A
3					
4	CW	442	442	---	1065 Rec'd, 1030 to other tanks
1-1965					
2	CW	326	88	238	Rec'd 1220 CW & 36 from 108-C
3	CW	447	209	238	Rec'd 350, 232 to BY & T
4	CW	461	223	238	Rec'd 278, 264, to 112 BY
1-1966	CW	472	234	238	Rec'd 429 CW, 418 to 112 BY
2	CW	472	234	238	Rec'd 443 CW & TH, 113 from 108C, 556 to 111 BY
3	CW	464	226	238	Rec'd 282, 290 to BY
4	CW	453	215	238	Rec'd 444 CW, 474 to BY
1-1967	CW	499	261	238	370 rec'd, 324 to T & BY
2	CW	486	248	238	387 rec'd, 400 to B & TY
3	CW	486	248	238	513 Purex CW, 513 to BY
4	CW	444	206	238	362 Purex CW, 404 to BY
1-1968	CW	476	238	238	Rec'd 731 CW
2	CW-OWW	466	28-200	238	200 OWW & 359 CW from Purex, 599 to 105 BX & 103 BX
3	CW-OWW	455	147-70	238	521 CW & 265 OWW, 765 to 103 BX
4	CW-OWW	457	89-61	307	885 from Purex, 883 to 103 BX
1-1969	CW-OWW	462	52-78	332	483 from Purex, 478 to 103 BX
2	CW-OWW	458	52-37	369	872 from Purex
3	CW-OWW	501	41-109	351	780 from Purex, 738 to 103 BX
4	CW-OWW	486	42-99	345	550 from Purex, 375 from 108C, 941 to 103 BX

Waste Status Summary of 102-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW-OWW	486	48-112	326	
2	CW-OWW	486	48-126	312	
3	CW-OWW	486	48-139	299	
4	CW-oww	486	48-139	299	
1-1971	CW-OWW	480	48-133	299	
2	CW-OWW	480	48-133	299	
3	CW-OWW	480	48-133	299	
4	CW-OWW	479	48-132	299	
1-1972	CW-OWW	475	47-129	299	
2	CW-OWW	477	47-131	299	
3	CW-OWW	474	46-129	299	
4	CW-OWW	475	46-130	299	
1-1973	CW-OWW	484	48-137	299	
2	CW-OWW	483	48-136	299	
3	CW-OWW	465	43-123	299	
4	CW-OWW	466	43-124	299	
1-1974	CW-OWW	467	43-125	299	
2	CW-OWW	467	43-125	299	
3	CW-OWW	467	43-125	299	
4	CW-OWW	466	34-100	332	
1-1975	CW-OWW	466	34-100	332	
2	CW-OWW	466	34-100	332	
3	CW-OWW	466	34-100	332	
4	CW-OWW	431	25-74	332	111 to 103C
1-1976	CW-OWW	431	30	62	Removed from service
2	---	431	0	431	" " "
3	---	431	0	431	
4	---	431	0	431	
1-1977	---	431	0	431	
2	---	431	0	431	Salt Well Pumped
3	---	431	0	431	" " "
4	---	431	0	431	Inactive Current Salt Well Installed

9 2 1 5 5 6 1 2 3 4

Waste Status Summary of 102-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	431	0	431	Inactive
2-	-	431	0	431	
3-	-	431	0	431	
4-	-	431	0	431	
1-1979	-	431	0	431	
2-	-	431	0	431	
3-	-	431	0	431	
4-	-	431	0	431	
1-1980	-	431	0	431	
2-	-	431	0	431	
3-	-	431	0	431	
4-	-	431	0	431	

9 2 1 2 1 5 6 1 2 3 5

Waste Status Summary of 103-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	MW	333	---	---	Last in Cascade, began filling August 1946
4	MW	528	---	---	Filled in October 1946
1-1947	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1951	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1952	MW	519	---	---	
2	MW	519	---	---	
3	MW	519	---	---	Supernate to pump to 109-C
4	MW	---	---	---	984 in Cascade, Cascade now processing for feed to TBP plant

9 2 1 2 5 5 6 1 2 3 6

Waste Status Summary of 103-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	---	---	---	1507 in 101 thru 106-C. 1651 removed thru CR 1218
2	MW	45	---	---	MW removal in progress
3	TBP	508	---	---	Pumped MW waste to 106-C and received TBP waste from 101-C
4	TBP	560	---	---	Received TBP waste
1-1954	TBP	560	---	---	
2	TBP	560	---	---	
3	TBP	560	---	---	
4	TBP	560	---	---	
1-1955	TBP	560	---	---	
2	TBP	560	---	---	
3	TBP	560	---	---	
4	TBP	560	---	---	
1-1956	TBP	560	---	---	
2	TBP	560	---	---	
3	TBP	560	---	--	
4	TBP	560	---	--	
1-1957	TBP	98	---	---	Latest electrode reading
2	P	37	---	---	Scavenged during month
3	TBP-P	329	---	---	292M from 102-A
4	TBP-P	348	---	---	19 from 102-A
1-1958	TBP-P	62	37-25	---	286 to 103 BY
2	TBP-P	62	37-25	---	
3	TBP-P	46	37-9	---	New electrode reading
4	TBP-P	46	37-9	---	
1-1959	TBP-P	45	37-8	---	
2	TBP-P	48	37-11	---	Latest electrode reading
3	TBP-P	45	37-8	---	Latest electrode reading
4	TBP-P	45	37-8	---	
1-1960	TBP	45	37-8	---	
2	TBP-P-CW	309	37-8-264	---	SS 265 CW rec'd
3	TBP-P-CW	416	37-8-371	---	SS 107 CW rec'd
4	TBP-P-CW	524	37-8-479	---	108 CW rec'd
1-1961					
2	TBP-P-CW	557	37-8-512	---	6 month report
3					
1	TBP-P-CW	563	37-8-578	---	New electrode (6month report)

9 2 1 2 6 1 2 3 7

Waste Status Summary of 103-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	CW	227	227	---	6 month report
3					
4	CW	57	57	---	6 month report
1-1963					
2	CW-P	530	57-473	---	473 from 105-A 6 month report
3					
4	P	469	469	---	Supernatant from 103-A 6 month report
1-1964					
2	P	442	442	---	6 month report
3					
4	P	420	520	---	Used for Cs recovery 6 month report
1-1965					
2	P	458	458	---	Used for Cs recovery
3	P	455	455	---	Used for Cs recovery
4	P	222	222	---	435 to 103-A, 202 from 101A, Cs recovery
1-1966	P	527	527	---	141 to 103A, 446 from 101A, Cs recovery
2	P	497	497	---	Cs recovery
3	P	494	494	---	For Cs recovery
4	P	475	475	---	For Cs recovery
1-1967	P	450	450	---	For Cs recovery
2	P	439	439	---	For Cs recovery
3	P	433	398	35	For Cs recovery
4	P	433	398	35	For Cs recovery
1-1968	P	436	401	35	For Cs recovery
2	P	435	400	35	For Cs recovery
3	P	433	398	35	Cs feed
4	P	431	396	35	Cs feed
1-1969	P	431	396	35	
2	P	429	394	35	
3	P	103	68	35	326 to 105C
4	P	103	68	35	
1-1970	P-BL	491	68-388	35	385 from 101-BK, 3 from water flush
2	BL (EB)	109	24	85	415 from 102-B, 798 to 105-C
3	BL-PSS	180	12-69	99	69 from 106C
4	BL-PSS	279	12-168	99	99 from 106C

Waste Status Summary of 103-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	---	92	0	92	257 from 106-C, 444 to 106-C
2	---	92	0	92	
3	---	90	0	90	
4	---	102	0	102	
1-1972	---	102	0	102	
2	---	102	0	102	
3	CW-OWW	539	345-104	90	437 from 104-C
4	CW	92	2	90	443 to 104-C
1-1973	CW	94	4	90	
2	BNW-N-LW-CW-PL	239	36-59-25-26-3	90	145 from 104-C
3	LNW-N-LW-CW-PL	390	73-122-51-48-6	90	151 from 104-C
4	BNW-N-LW-CW-PL	392	73-124-51-48-6	90	
1-1974 *	BNW-N-LW-P-B-CW-DW-IX-EB-PL	508	84-144-51-24-54-49-2-3-1-6	90	114 from 104-C
2	BNW-LW-R-B-CW-DW-IX-PL	343	51-86-31-15-33-30-1-2-4	90	165 to 104-C
3	BNW-N-LW-PL-B-CW-EB	107	3-5-2-2-2-2-1	90	59 from 104-C, 297 to 107-S
4	BL	224	151	73	409 from 106-C, 7 to 107-S, 281 to 101-TX
1-1975	BNW-N-LW-CW-DW-IX-EB-B-PL-BL	516	24-41-5-10-4-11-31-4-44-269	73	108 from 104-C, 404 from 106-C, 65 from 107-C, 66 from 112-C, 349 to 106-SX
2	BNW-N-PL-EB-P-B	164	1-2-5-3-2-78	73	399 from 104-C, 258 from 106-C, 426 to 106-SX, 584 to 101-TX
3	OWW-CW-IX	109	5-10-21	73	195 from 107-C, 364 from 109-C, 400 from 112-C, 1014 to 106-SX
4	CW-OWW	106	9-24	73	111 from 102-C, 426 from 108-C, 85 from 109-C, 85 from 112-C, 711 to 106-SX

* Dry Well 30-03-01. 30-03-03, 30-03-05, 30-03-07, 30-03-09 drilled.

9212556123 9

Waste Status Summary of 103-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	BNW-N-LW-CW-DW-IX-TBP-R-R-OWW-	274	1-4-1-121-5-12-1-7-37-9-3	73	1 from 107-C, 27 from 108-C, 9 from 109-C, 62 from 110-C, 63 from 111-C, 3 from 112-C
2	BNW-N-LW-CW-DW-IX-TBP-R Oww-RIX-EB	288	1-4-1-135-5-12-1-7-37-9-3	73	1 from 108-C, 4 from 110-C, 2 from 111-C, 1 from 112-C, 5 Water
3	Feed Dil.	321	248	73	Purex Waste Storage
4	Feed Dil.	345	272	73	Evap. B Plant Waste Recovery
1-1977	Feed Dil.	384	316	68	Evap. B Plant Waste Recovery
2	Feed Dil.	387	319	68	" " " " "
3	SR. SLUDGE	274	124	150	" " " " "
4	SR. SLUDGE	422	269	153	" " " " "
1-1978	-	235	71	164	
2-	NCPLX	260	93	167	Active-SW RCR-Evap. Feed
3-	NCPLX	242	113	175	Solids Level eval 9/18/78
4-	NCPLX	296	121	175	
1-1979	NPCLX	301	126	175	
2-	NCPLX	307	132	175	
	NCPLX	200	25	175	
4-	NPCLX	200	25	175	Inactive
1-1980	NCPLX	200	25	175	
2-	NCPLX	200	25	175	
3-	NCPLX	200	25	175	
4-	NCPLX	200	25	175	

Waste Status Summary of 104-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	356	---	---	1st in Cascade, began filling October 1946
1-1947	MW	528	---	---	Full in February 1947
2	MW	528	---	---	Cascading to 105-C
3	MW	528	---	---	Cascading to 105-C & 106-C
4	MW	528	---	---	Cascade full in November 1947
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	--	
1-1951	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

Waste Status Summary of 104-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	---	---	1507 in 101 thru 106-C. 1651 removed thru CR 1218
2	MW	530	---	---	
3	MW	46	---	---	MW removal in progress
4	MW	0	---	---	Sluicing
1-1954	MW	312	---	---	Supernatant supply to 244-CR. Sluiced until 1-4-54
2	MW	323	---	---	Supernatant supply to 244-CR. Rec'd from 109-BY
3	MW	271	---	---	Supernatant supply to 244-CR. Rec'd from 109-BY
4	MW	494	---	---	Supernatant supply to 244-CR. Rec'd from 109-BY
1-1955	MW	0	---	---	Tank to be declared empty
2	MW	0	---	0	
3	MW	0	---	0	
4	TBP	420	---	0	Received TBP in October from 112-
1-1956	CW	224	---	45 (TBP)	Emptied in January & started receiving CW in January
2	CW	439	---	45	Received CW
3	CW	176	---	45	Pumped 429 to 105-C. Receiving CW
4	CW	406	---	45	Received 230 CW
1-1957	CW	464	---	---	Latest electrode reading - est. reading SS 5M CW rec'd
2	CW	541	---	---	SS 71M gals, 61M gal, 113M gals, CW rec'd, cascading to 105-C
3	CW	543	---	46	
4	CW	535	---	46	SS
1-1958	CW	538	447	46	SS
2	CW	535	444	46	SS, 154 CW rec'd
3	CW	541	450	46	Latest electrode reading
4	CW	541	450	46	
1-1959	CW	524	433	46	
2	CW	517	426	46	Latest electrode reading
3	CW	524	433	46	Latest electrode reading
4	CW	524	433	46	
1-1960	CW	538	447	46	14 from 106-SX
2	CW	538	447	46	
3	CW	538	447	46	
4	CW	538	447	46	

Waste Status Summary of 104-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	CW	538	447	46	[6 month report
3					
4	CW	541	450	46	Latest electrode reading [6 month report
1-1962					
2	CW	538	447	46	Latest electrode reading [6 month report
3					
4	CW	538	447	46	
1-1963					
2	CW	543	397	101	Latest electrode reading [6 month report
3					
4	CW	541	395	101	Latest electrode reading [6 month report
1-1964					
2	CW	539	393	101	Latest electrode reading [6 month report
3					
4	CW	539	393	101	
1-1965					
2	CW	554	419	90	15 from CR [6 month report
3	CW	560	425	90	
4	CW	560	425	90	
1-1966	CW	560	425	90	
2	CW	532	397	90	New electrode
3	CW	532	397	90	
4	CW	532	397	90	
1-1967	CW	532	397	90	
2	CW	532	397	90	
3	CW	532	397	90	
4	CW	532	397	90	
1-1968	CW	531	396	90	
2	CW	531	396	90	
3	CW	530	395	90	
4	CW	530	440	90	
1-1969	XW	530	440	90	
2	CW	200	110	90	330 to 102-C
3	CW	200	110	90	
4	CW-OWW	246	83-73	90	523 from Purex, 572 from 107-C & 111-C, 1,048 to 103-BX

Waste Status Summary of 104-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW-OWW	347	80-171	96	737 from 109-C & 112-C, 546 from Purex, 1182 to 103-BX
2	CW-OWW	296	50-97	149	821 from Purex, 135 from 201, 202, 203, & 204-C, 1007 to 103-BX
3	OWW-CW-IWW	480	307-58-23	92	1136 from Purex, 104 to 103-BX, 848 to 101-BX
4	CW-OWW	453	58-263	132	1547 from Purex, 40 from 011-CR, 1614 to 101-BX
1-1971	OWW (Flushes)	481	328	153	377 from Purex, 348 to 101-BX
2	CW-OWW	507	169-185	153	1,118 from Purex, 1,092 to 101-BX
3	CW-OWW	466	163-150	153	89 to 101-BX, 947 from Purex, 896 to 103-B
4	CW-OWW	437	192-70	175	973 from Purex, 326 from 110-C, 1,230 to 103-BX, 102 to 101-BX
1-1972 *	CW-OWW	351	79-84	188	727 from Purex, 253 from 107-C, 195 from 108-C, 1262 to 103-BX
2	CW-OWW-P	366	25-31-112	198	541 from Purex, 69 from 108-C, 595 to 103-BX
3	OWW-P	384	61-125	198	1247 from Purex, 758 to 103-BX, 437 to 104-C, 34 to 105-C
4	N-BNW- OWW CW-EB	334	90-14-14-6-12	198	117 from Purex, 443 from 103-C, 309 from 107-U, 918 to 103-BX
1-1973	CW-BNW-PL-N	517	153-133-29-4	198	46 from Purex, 748 from 107-U, 611 to 103-BX
2	BNW-N-LW-CW-PL	332	33-55-23-20-3	198	44 from Purex, 481 from 107-U, 145 to 103-C, 566 to 103-BX
3	BNW-N-LW-R-CW-DW-IX-TBP	483	32-44-17-89-17-59-6-21	198	222 from 101-TY, 354 from 107-U, 151 to 103-C, 31 to 107-C, 245 to 108-C
4	P-B-CW-N-BNW-DW-IX-ER	436	34-77-1-28-15-2-4-1	274	31 from Purex, 79 from 101-A 367 from 107-U, 307 to 103-B, 213 to 107-C
1-1974 **	P-B-N-BNW-IX	439	54-93-11-6-1	274	27 from Purex, 35 from CR Vault, 4 from 302-A Catch Tank, 45 from 101-A, 1 from 103-AX, 1 water, 114 to 103-C
2	BNW-N-LW-B-CW-P	337	13-22-8-8-8-4	274	16 from Purex, 165 from 103-C, 65 from 111-C, 13 water, 358 to 107-S
3	BNW-N-LW-B-CW-PL-EB	340	8-13-4-4-4-4-29	274	10 from Purex, 49 from 101-C, 3 water, 59 to 103-C
4	BNW-N-LW-B-CW-PL-EB	351	13-21-6-6-6-17-47	235	11 from Purex

* Dry Wells 30-04-02, 30-04-08, 30-04-12 drilled.

**Dry Wells 30-04-01, 30-04-03, 30-04-04, 30-04-05 drilled.

9 2 1 2 5 6 1 2 4 4

Waste Status Summary of 104-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1975	BNW-N-LW-B-CW-PL-EB	296	5-8-2-2-2-25-17	235	50 from Purex, 108 to 103-C
2	P-B	417	4-178	235	33 from Purex, 485 from 101-A, 399 to 103-C
3	BL	299	64	235	14 from Purex, 818 from 101-A, 101 from 106-C, 1 water, 1044 to 101-TX
4	PL-BL	513	13-265	235	38 from Purex, 4 from 151-A-CT, 595 from 106-C, 193 to 101-TX, 229 to 106-U
1-1976	PL-B	362	13-114	235	20 from Purex, 130 from 102-A, 201 from 101-A, 477 from 106-C, 483 to 106-SX, 322 to 102-U, 173 to 106-U
2	PSS-B	505	41-229	235	12 from Purex, 148 from 106-C, 920 from 103-A
3	Feed Dil.	420	185	235	Purex Waste Storage
4	Feed Dil.	373	127	246	Purex Waste Storage
1-1977	Feed Dil.	406	138	268	Purex Waste Storage
2	Feed Dil.	453	185	268	" " "
3	Feed Dil.	334	60	274	" " "
4	Feed Dil.	340	50	290	" " "
1-1978	-	409	105	304	New Solids Level 1/10/78
2-	NCPLX	329	25	304	Active Wst. - RCR
3-	NCPLX	378	74	304	
4-	NCPLX	464	160	304	
1-1979	CPLX	315	11	304	
2-	CPLX	345	41	304	
3-	CPLX	365	61	304	
4-	CPLX	450	146	304	New Solids Level 8/3/79
1-1980	CPLX	315	22	293	Inactive 3/31/80
2-	CPLX	315	22	293	
3-	CPLX	315	22	293	
4-	CPLX	315	22	293	

9 2 1 2 5 6 1 2 4 5

Waste Status Summary of 105-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	MW	208	---	---	2nd in Cascade, began filling February 1947
2	MW	528	---	---	Full in June 1947
3	MW	528	---	---	Cascading to 106-C
4	MW	528	---	---	Cascade full in November 1947
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1951	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1952	MW	530	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	

Waste Status Summary of 105-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	---	---	1507 in 101 thru 106-C. 1651 removed thru batch CR 1218
2	MW	530	---	---	
3	MW	202	---	---	MW removal in progress
4	MW	48	---	---	MW removal in progress
1-1954	MW	453	---	---	Supernatant, sluiced until 1-8-54
2	---	---	---	---	Transferred MW supernate to 104-C. (Last transf. in June)
3	TBP	546	---	---	Received TBP waste during July
4	TBP	546	---	---	
1-1955	TBP	546	---	---	
2	TBP	546	---	---	
3	TBP	546	---	---	
4	TBP	546	---	---	
1-1956	TBP	252	---	---	Pumped in March
2	TBP	79	---	15 (TBP)	Scavenging finished in April
3	TBP-CW	508	---	15	Received 429 from 104-C in August
4	TBP-CW	508	---	15	
1-1957	TBP-CW	538	---	---	Latest electrode reading
2	TBP-CW	406	---	---	300M pumped to 111-BY
3	TBP-CW	178	---	---	SS 250M to 112-BY, rec'd 98M-SS rec'd 121M CW
4	TBP-CW	381	79-302	---	SS 380 CW rec'd, 185 to 110-BY
1-1958	TBP-CW	475	79-396	---	395 CW rec'd, 298 to 110-BY
2	TBP-CW	541	79-462	---	SS 35CW rec'd
3	TBP-CW	541	79-462	---	
4	TBP-CW	461	79-382	---	SS 391 CW rec'd, 471 to 107 & 110-BY
1-1959	TBP-CW	271	79-192	---	SS 285 CW rec'd, 170 to 107-BY, 305 to 108-BY
2	TBP-CW	142	79-63	---	SS 324 CW rec'd, 261 to 109-C
3	TBP-CW	309	79-230	---	SS 361 CW rec'd, 154 to 109-C
4	TBP-CW	431	79-352	---	SS 309 CW rec'd, 187 to 111-C
1-1960	TBP-CW	461	79-382	---	SS 314 CW rec'd, 65 acid flush 39 to 105-C
2	TBP-CW	529	79-450	---	SS 66 CW rec'd, latest electrode reading
3	TBP-CW	529	79-450	---	
4	TBP-CW	529	79-450	---	

Waste Status Summary of 105-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solid in Storage	Remarks
1-1961					
2	TBP-CW	521	79-442	---	[6 months report
3					
4	TBP-CW	521	79-442	---	[6 months report
1-1962					
2	TBP-CW	519	79-440	---	Latest in electrode reading
3					
4	TBP-CW	519	79-440	---	[6 months report
1-1963					
2	CW	125	125	---	39 cl to 102-C [6 months report
3					
4	CW-P	532	125-407	---	407 from 102-A [6 months report
1-1964					
2	CW-P	522	125-397	---	New electrode
3					
4	CW-P	516	125-391	---	New elect. (reading confirmed)
1-1965					
2	CW-P	491	125-257	109	25 lost from steaming
3	CW-P	491	125-257	109	
4	CW-P	483	125-249	109	
1-1966	CW-P	475	125-241	109	
2	CW-P	450	125-216	109	New electrode
3	CW-P	450	125-216	109	
4	CW-P	442	125-208	109	8 loss from steaming
1-1967	CW-P	439	125-205	109	
2	CW-P	435	125-201	109	
3	CW-P	431	106-216	109	4 evaporation
4	CW-P	359	106-144	109	Feed TK PSN to B-PH, 72 pumped
1-1968	P	542	433	109	Rec'd 656 PSN, 470 to 221-B
2	P	392	283	109	264 PSN from 102-AX, 404 to 221-B
3	P	444	335	109	255 from 102-AX, 204 to 221-B, IX
4	P	384	288	96	410 from 102-AX, 470 to 221-B, IX COL
1-1969	P	378	269	109	334 from 102-AX, 532 from 104-A, 866 from A-AX farms, 872 to B Plant IX
2	P	490	391	99	706 from A farm, 580 to B Plant IX
3	P	366	227	139	501 from A farm, 326 from 103-C, 10 from flushes, 960 to B Plant IX
4	P	450	217	233	609 from 102-A, 580 from 101-C & 106-C, 1,106 to B Plant IX

9 2 1 2 5 6 1 2 4 8

Waste Status Summary of 105-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	P	348	225	123	171 from 102-A, 267 to B Plant IX
2	BL	198	62	136	208 from 102-A, 798 from 103-C, 1155 to B Plant IX (contained BL requiring a reduction in cesium prior to in-tank solidification)
3	BL-H_2O-R	497	29-53-276	139	Rec'd 454 of redox waste & 87 of dilution water from 101-TX, B Plant IX rec'd 230 (BL-18, water-34, R-178 from 105-C
4	H_2O-RSN	447	33-258	156	Rec'd 485 RSN & 17 water from 101-TX, 228 RSN from 105-TX, 681 RSN from 102-TX, & 158 of dilution water. B Plant IX rec'd 1619 as follows: 1412 of RSN, 195 of water, 12 of BL
1-1971	PSS	211	49	162	561 RSN & 127 dilution water from 106-TX, & 827 PSS from 106-C, B Plant IX rec'd
2	PSS	211	47	164	1748 as follows: RSN 819, H20 160 PSS 769
3	PSS	216	52	164	
4	PSS	253	89	164	
1-1972 *	PSS	510	412	98	264 from 103-B
2	PSS	400	302	98	384 from 101-A, 302 from 103-A, 795 to B Plant (TK 17-2)
3	P-Water	471	328-45	98	969 from 103-AX 34 from 104-C, 250 water, 1182 to B Plant (TK 17-2)
4	P	411	313	98	921 from 103-AX, 141 from 104-BX, 1123 to B Plant (TK 17-2)
1-1973	P	326	228	98	844 from 103-AX, 930 to B Plant (TK 17 -2)
2	PSS	227	115	112	1266 from 103-AX, 1363 to B Plant (TK 17-2)
3	PSS	239	127	112	
4	PSS	234	122	112	
1-1974**	PSS	447	335	112	219 from 103-AX
2	PSS	442	330	112	
3	PSS	231	119	112	203 to B Plant
4	PSS	279	140	139	59 from 103-AX

* Dry Wells 30-05-02, 30-05-04, 30-05-10 drilled.

** Dry Wells 30-05-03, 30-05-05, 30-05-06, 30-05-07, 30-05-08, 30-05-09 drilled.

9 2 1 2 5 5 6 1 2 4 9

Waste Status Summary of 105-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1975	PSS	224	85	139	127 from 103-AX, 178 to B Plant
2	PSS	233	94	139	525 from 103-AX, 516 to B Plant
3	PSS	235	96	139	544 from 103-AX, 125 water, 665 to B Plant
4	PSS	483	344	139	490 from 103-AX, 119 water, 361 to B Plant
1-1976	PSS	381	242	139	234 from 104-AX, 15 water, 36 from 103-AX, 384 to B Plant
2	PSS	222	83	139	160 to B Plant
3	Cs. Feed	367	228	139	
4	---	299	160	139	Ion-Exchange Feed
1-1977	---	224	57	167	Ion-Exchange Feed
2	---	224	57	167	" " "
3		224	57	167	B Plant Cs. Feed
4		447	280	167	B Plant Cs. Feed
1-1978	NCPLX	343	176	167	
2-	NCPLX	310	143	167	B Plt. CS Feed
3-	NCPLX	227	60	167	
4-	NCPLX	343	176	167	
1-1979	NCPLX	224	57	167	PSS
2-	NCPLX	172	5	167	New Photo 6/27/79
3-	CPLX	172	22	150	Solids Level adj. 5/21/79
4-	CPLX	172	22	150	
1-1980	CPLX	172	22	150	
2-	CPLX	172	22	150	
3-	CPLX	172	22	150	
4-	CPLX	172	22	150	

9 2 1 2 5 5 6 1 2 5 0

Waste Status Summary of 106-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	MW	388	---	---	3rd in Cascade, began filling in July 1947
4	MW	528	---	---	Full in November 1947
1-1948	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1949	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1950	MW	528	---	---	
2	MW	528	---	---	
3	MW	528	---	---	
4	MW	528	---	---	
1-1951	MW	551	---	---	23 water from hose
2	MW	551	---	---	
3	MW	551	---	---	
4	MW	551	---	---	
1-1952	MW	519	---	---	
2	MW	519	---	---	
3	MW	519	---	---	
4	MW	519	---	---	

Waste Status Summary of 106-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solid in Storage	Remarks
1-1953	MW	---	---	---	1507 in 101 thru 106-C. 1651 removed thru CR 1218
2	MW	76	---	---	Supernatant supply
3	MW	439	---	---	Rec'd MW supernatant from 103-C
4	MW	143	---	---	MW supernatant blend tank
1-1954	MW	50	---	---	MW supernatant blend tank
2	MW	50	---	---	MW supernatant blend tank
3	TBP	538	---	---	Rec'd TBP waste during August
4	TBP	538	---	---	
1-1955	TBP	538	526	12 (TBP)	
2	TBP	538	526	12	
3	TBP	538	526	12	
4	TBP	538	526	12	
1-1956	TBP	538	526	12	
2	TBP	538	526	12	
3	TBP	538	526	12	
4	TBP	538	526	12	
1-1957	TBP	519	507	12	Latest electrode reading, enough for 171 TU
2	P	37	25	12	Rec'd 234 from 101-A &77 from 102-A, 476 scvg during month
3	TBP-P	524	31-481	12	Rec'd 170 from 102-A (CW)
4	TBP-P	106	14-63	29	New electrode reading, 456 to 103-BY
1-1958	TBP-P	106	14-63	29	
2	TBP-P-CW	232	14-63-126	29	
3	TBP-P-CW	519	14-63-413	29	7 to 110-BX,SS 294-CW rec'd
4	TBP-P-CW	535	14-63-429	29	Latest electrode reading
1-1959	TBP-P-CW	510	14-63-429	29	
2	TBP-P-CW	510	14-63-429	29	
3	TBP-P-CW	510	14-63-429	29	
4	TBP-P-CW	510	14-63-429	29	
1-1960	TBP-P-CW	510	14-63-429	29	
2	TBP-P-CW	527	14-63-421	29	SS 17 CW rec'd
3	TBP-P-CW	527	14-63-421	29	
4	TBP-P-CW	527	14-63-421	29	

Waste Status Summary of 106-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	TBP-P-CW	527	14-63-421	29	[6 months report
3					
4	TBP-P-CW	527	14-63-421	29	[6 months report
1-1962					
2	TBP-P-CW	527	14-63-421	29	[6 months report
3					
4	TBP-P-CW	527	14-63-421	29	[6 months report
1-1963					
2	TBP-P-CW	530	19-63-421	24	[6 months report
3					
4	P	538	514	24	427 from 102-A
1-1964					
2	P	522	498	24	New electrode [6 months report
3					
4	P	505	481	24	[6 months report
1-1965					
2	P	541	479	62	36 from CR vault
3	P	546	484	62	
4	P	549	487	62	
1-1966	P	549	487	62	
2	P	519	457	62	New electrode
3	P	519	457	62	
4	P	527	465	62	New electrode
1-1967	P	527	465	62	
2	P	527	465	62	
3	P	527	465	62	
4	P	527	465	62	
1-1968	P	66	4	62	461 PSN to 105-C
2	P	72	10	62	
3	P	70	8	62	
4	P	70	8	62	
1-1969	P	124	62	62	54 from 002 AR (101-A sludge wash)
2	P	244	182	62	120 from 002 AR sludge washes
3	P	293	231	62	50 from 002 AR sludge washes
4	P(PSS)	167	110	57	52 from 002 AR, 176 to 105-C

Waste Status Summary of 106-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	P (PSS)	222	165	57	55 from 002 AR
2	P (PSS)	379	313	57	149 from 002 AR
3	P (PSS)	517	438	79	216 from 002 AR, 69 to 103-C
4	PSS	530	385	145	303 from 002 AR, 99 to 103-C, 194 to 102-A
1-1971	PSS	212	62	150	131 from 002 AR, 444 from 103-C, 194 from 102-A, 267 to 103-C, 827 to 105-C
2	PSS	212	62	150	
3	H_2O-PSS	239	63-26	150	63 water
4	H_2O-PSS	235	59-26	150	16 water, 22 condensate
1-1972 *	PSS	233	83	150	
2	PSS	235	110	125	
3	PSS	244	119	125	
4	PSS	248	123	125	
1-1973	PSS	255	130	125	
2	PSS	249	124	125	
3	PSS	241	116	125	
4	PSS	238	113	125	
1-1974 **	PSS	237	112	125	
2	PSS	250	125	125	
3	PSS-BL	324	45-154	125	238 from B Plant, 15 from 154-B catch tank, 3 water, 221 to 103-AX
4	BL	420	314	106	506 from B Plant, 1 water, 409 to 103-C
1-1975	BL	373	267	106	356 from B Plant, 404 to 103-C
2	BL	345	239	106	236 from B Plant, 7 from 302-CT, 258 to 103-C
3	BL	469	363	106	242 from B Plant, 101 to 104-C
4	BL	288	182	106	414 from B Plant, 595 to 104-C
1-1976	BL	329	223	106	581 from B Plant, 477 to 104-C
2	BL	499	393	106	319 from B Plant, 148 to 104-C
3	Sr. Sludge	422	316	106	B Plant Waste Recovery
4	Sr. Sludge	233	127	106	B Plant Waste Recovery
1-1977	Sr Sludge	373	228	145	B Plant Waste Recovery
2	Sr Sludge	480	335	145	" " " "
3	Sr Sludge	398	253	145	" " " "
4	---	384	228	156	

* Dry Wells 30-06-02, 30-06-04, 30-06-10 drilled.

** Dry Wells 30-06-03, 30-06-09, 30-06-12 drilled.

Waste Status Summary of 106-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CPLX	255	99	156	Active-Receiving B Plt. Wst.
2-	CPLX	356	200	156	
3-	CPLX	444	288	156	
4-	CPLX	422	280	142	Solids level evaluated 11/3/78
1-1979	NCPLX	202	5	197	Solids level 3/31/79 Inactive
2-	CPLX	219	22	197	New photo 4/5/79
3-	CPLX	219	22	197	
4-	CPLX	219	22	197	
1-1980	CPLX	219	22	197	
2-	CPLX	219	22	197	
3-	CPLX	219	22	197	
4-	CPLX	219	22	197	

9212156125

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	1C	53	---	---	Added in April 1946
3	1C	53	---	---	
4	1C	53	---	---	
1-1947	1C	53	---	---	
2	1C	274	---	---	1st in cascade, began filling April 1947
3	1C	528	---	---	Full September 1947
4	1C	528	---	---	Cascading to 108-C
1-1948	1C	528	---	---	Cascading to 108-C
2	1C	528	---	---	Cascading to 108-C & 109-C
3	1C	528	---	---	Cascade full in September 1948
4	1C	528	---	---	
1-1949	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1950	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1951	1C	528	---	---	
2	1C	528	---	---	
3	1C	---	---	---	
4	1C	---	---	---	
1-1952	1C	399	---	399 (TBP)	
2	1C	399	---	399	
3	1C	399	---	399	
4	TBP	547	148	399	Overflow line to 108-C plugged 12-18-52

9 2 1 2 5 6 1 2 5 6

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	518	119	399 (TBP)	Overflow to 108-C plugged
2	TBP	519	120	399	Overflow to 108-C plugged
3	TBP	530	131	399	Overflow to 108-C plugged
4	TBP	530	131	399	Overflow to 108-C plugged
1-1954	TBP	530	131	399	Overflow to 108-C plugged
2	TBP	530	131	399	Overflow to 108-C plugged
3	TBP	530	131	399	Overflow to 108-C plugged
4	TBP	530	131	399	Overflow to 108-C plugged
1-1955	TBP	530	131	399	Overflow to 108-C plugged
2	TBP	530	131	399	Overflow to 108-C plugged
3	TBP	530	131	399	Overflow partially plugged
4	TBP	530	131	399	
1-1956	TBP	530	131	399	
2	TBP	530	131	399	
3	TBP	530	131	399	
4	TBP	375	---	375	155 scavenged during October
1-1957	1C	376	1	375	Latest electrode reading, 3" gain (flushes)
2	1C	381	6	375	Latest electrode reading
3	1C	392	17	375	Latest electrode reading, 30 line flush rec'd
4	1C	411	36	375	19 line flushes rec'd
1-1958	1C	425	50	375	17 line flushes, latest electrode reading
2	1C	425	50	375	
3	1C	422	47	375	Latest electrode reading
4	1C	425	50	375	Latest electrode reading
1-1959	1C	425	50	375	
2	1C	422	47	375	Latest electrode reading
3	1C	422	47	375	
4	1C	422	47	375	
1-1960	1C	422	47	375	
2	1C	422	47	375	
3	1C	422	47	375	
4	1C	422	47	375	

9 2 1 2 5 6 1 2 7

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	~~Liquid~~ in Storage	Solids in Storage	Remarks
1-1961					
2	1 C	439	64	375	[6 months report
3					
4	CW	483	108	375	858 to BY, 902 CW rec'd [6 months report
1-1962					
2	CW	384	9	375	468 rec'd, 567 to BY [6 months report
3					
4	CW	384	9	375	
1-1963					
2	CW	384	63	321	[6 months report
3					
4	CW	381	60	321	Latest electrode reading
1-1964					
2	CW	381	60	321	[6 months report
3					
4	CW-HS	383	60-2	321	2 rec'd [6 months report
1-1965					
2	CW-HS	395	156-14	225	12 from CR vault
3	CW-HS	425	156-44	225	30 from HS
4	CW-HS	466	156-85	225	41 from HS
1-1966	CW-HS	527	126-146	255	61 from HS
2	CW-HS	464	126-83	255	102 to 108-C, rec'd 39 HS
3	CW-HS	486	126-105	255	Rec'd 23 HS
4	CW-HS	527	126-146	255	41 from HS
1-1967	CW-HS-HLO	530	126-146-3	255	3 from HLO
2	CW-HS-HLO	528	126-144-3	255	
3	CW-HS-HLO	528	126-144-3	255	
4	CW-HS-HLO	534	126-150-3	255	6 from HSW
1-1968	CW-HS-HLO	534	123-150-3	255	
2	CW-HS-HLO	534	123-150-3	255	
3	CW-HS-HLO	534	123-150-3	255	
4	CW-SSW-BNW	528	126-144-3	255	
1-1969	CW-SSW-BNW	528	126-144-3	255	
2	CW-SSW-BNW	525	126-141-3	255	
3	CW-SSW BNW	524	126-141-2	255	
4	CW	301	46	255	223 to 104-C

9212556128

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW	303	48	255	
2	CW	304	104	200	
3	CW-IX	547	129-223	195	245 from 104-BX
4	CW-IX	547	129-223	195	
1-1971	CW-IX	546	129-222	195	
2	CW-IX	546	128-221	197	
3	CW-IX	546	128-221	197	
4	CW-IX	541	126-218	197	
1-1972	CW-IX	288	33-58	197	253 to 104-C
2	CW-IX	289	33-59	197	
3	CW-IX	289	30-53	206	
4	CW-IX	260	20-34	206	
1-1973	CW-IX	260	20-34	206	
2	CW-IX	261	20-35	206	
3	BNW-N-LW-CW-DW-IX	299	7-9-4-24-13-36	206	31 from 104-C
4	BNW-N-LW-CW-DW-IX-EB	513	72-127-6-27-19-51-5	206	213 from 104-C
1-1974 *	BNW-N-LW-CW-DW-IX-EB	514	72-128-6-27-19-51-5	206	
2	BNW-N-LW-CW-DW-IX-EB	514	72-128-6-27-19-51-5	206	
3	BNW-N-LW-CW-DW-IX-EB	515	72-129-6 27-19-51-5	206	
4	BNW-N-LW-CW-DW-IX-EB	513	75-135-6-28-20-53-5	191	
1-1975	BNW-N-LW-CW-DW-IX-EB	450	60-108-5-23-16-43-4	191	65 to 103-C
2	BNW-N-LW-CW-DW-IX-EB	450	60-108-5-23-16-43-4	191	
3	BNW-N-LW-CW-DW-IX-EB	255	15-26-1-6-4-11-1	191	195 to 103-C
4	BNW-N-LW-CW-DW-IX-EB	255	15-26-1-6-4-11-1	191	

* Dry Wells 30-07-01, 30-07-02, 30-07-05, 30-07-07, 30-07-08, 30-07-10, 30-07-11 drilled.

9 2 1 2 5 6 1 2 5 9

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	BNW-N-LW-CW-DW-IX-EB	257	15-28-1-6-4-11-1	191	Removed from service 1 to 103-C
2	BNW-N-LW-CW-DW-IX-EB	257	15-28-1-6 4-11-1	191	RFS
3	---	257	66	191	Salt Well Pumped
4	---	257	66	191	" " "
1-1977	---	257	66	191	Salt Well Pumped
2	---	249	58	191	" " "
3	Sr Sludge	450	259	191	Sludge Waste Recovery
4	Sr Sludge	367	71	296	" " "

9212556126 0

Waste Status Summary of 107-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NCPLX	340	3	337	Inactive
2-	NCPLX	340	3	337	
3-	NCPLX	337	0	337	New Solids Level 7/19/78
4-	NCPLX	337	0	337	
1-1979	NCPLX	337	0	337	
2-	NCPLX	337	0	337	
3-	NCPLX	337	0	337	
4-	NCPLX	337	0	337	
1-1980	NCPLX	337	0	337	
2-	NCPLX	337	0	337	
3-	NCPLX	337	0	337	
4-	NCPLX	337	0	337	

9212561261

Waste Status Summary of 108-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944 *	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	1C	53	---	---	2nd in cascade, began filling September 1947
4	1C	249	---	---	
1-1948	1C	528	---	---	Full in March 1948
2	1C	528	---	---	Cascading to 109-C
3	1C	528	---	---	Cascade full in September 1948
4	1C	528	---	---	
1-1949	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1950	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1951	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	---	---	---	
1-1952	1C	---	---	---	
2	1C	34	---	34 (IC)	Finished pumping on 4-15-52
3	1C	34	---	34	
4	TBP	85	51	34	Overflow line from 108-C. plugged 12-13-52

* Dry Well 30-08-02 drilled.

Waste Status Summary of 108-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	527	493	34 (IC)	Now receiving TBP process waste
2	TBP	530	496	34	
3	TBP	530	496	34	
4	TBP	530	496	34	
1-1954	TBP	530	496	34	
2	TBP	530	496	34	
3	TBP	530	496	34	
4	TBP	530	496	34	
1-1955	TBP	530	496	34	
2	TBP	530	496	34	
3	TBP	530	496	34	
4	TBP	530	496	34	
1-1956	TBP	80	46	34	Non-disposable material. Transferred to 001-CR
2	TBP	530	496	34	Non-cribbable material
3	TBP	78	44	34	Pumped 399 to BC #7 ditch and 24 to BC #8 ditch
4	TBP	78	44	34	
1-1957	IC-TBP	78	34-10	34	Latest electrode reading
2	IC-TBP	78	34-10	34	
3	EB	532	498	34	Latest electrode reading, 463 to BC-19, rec'd 465, 451 from 111-C
4	TBP	472	393	79	774 to BC-20 & 21, 714 rec'd
1-1958	TBP	175	96	79	297 to BC-22 trench
2	TBP	175	96	79	
3	TBP	175	96	79	
4	TBP	175	96	79	
1-1959	TBP	175	96	79	
2	TBP	183	104	79	
3	TBP	188	109	79	Latest electrode reading
4	TBP	188	109	79	
1-1960	TBP	494	415	79	306 from 105-C
2	TBP	494	415	79	
3	TBP-CW	430	39-312	79	
4	TBP	166	87	79	334 to 101-BY
1-1961					
2	CW	486	407	79	180 to BY, 500-CW rec'd
3					[6 months report
4	CW	486	407	79	

Waste Status Summary of 108-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	CW	486	407	79	[6 months report
3					
4	CW	486	407	79	[6 months report
1-1963					
2	CW	483	404	79	[6 months report
3					
4	CW	486	404	79	Latest electrode reading
1-1964					
2	CW	426	347	79	60 to BX [6 months report
3					
4	CW	426	347	79	[6 months report
1-1965					
2	CW-HS	568	356-106	98	142 from HS, 36 to 102-C
3	CW-HS	532	328-106	98	
4	CW-HS	532	328-106	98	
1-1966	CW-HS	532	328-106	98	
2	CW-HS	521	328-95	98	113 to 102-C, 13 to 109-C
3	CW-HS	521	328-95	98	
4	CW-HS	521	328-95	98	New electrode
1-1967	CW-HS	521	328-95	98	
2	CW-HS	521	328-95	98	
3	CW-HS	521	328-95	98	
4	CW-HS	517	328-91	98	
1-1968	CW-HS	516	327-91	98	
2	CW-HS	516	327-91	98	
3	CW-HS	516	327-91	98	
4	CW-SSW	514	327-89	98	
1-1969	CW-SSW	514	327-89	98	
2	CW-SSW	514	327-89	98	
3	CW-SSW	513	327-88	98	
4	CW	138	40	98	
1-1970	CW	138	40	98	
2	CW-OWW-IX	532	40-33-364	95	395 from 110-C
3	CW-OWW-IX	532	66-33-364	69	
4	CW-OWW-IX	532	66-33-364	69	
1-1971	CW-OWW-IX	532	66-33-364	69	
2	CW-OWW-IX	532	66-33-364	69	
3	CW-OWW-IX	532	66-33-364	69	
4	CW-OWW-IX	532	66-33-364	69	

Waste Status Summary of 108-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	CW-OWW-IX	334	38-19-208	69	195 to 104-C
2	CW-OWW-IX	266	28-14-155	69	69 to 104-C
3	CW-OWW-IX	266	27-14-149	76	
4	CW-OWW-IX	271	28-14-153	76	
1-1973	CW-OWW-IX	270	28-14-152	76	
2	CW-OWW-IX	270	28-14-152	76	
3	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	27-38-15-43-51-157-18-77-14	76	245 from 104-C
4	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	27-38-15-43-51-157-18-77-14	76	
1-1974 *	BNW-N-LW-CW-DW-IX-TBP-R-OWW	515	27-38-15-43-51-156-18-77-14	76	
2	BNW-N-LW-CW-DW-IX-TBP-R-OWW	515	27-38-15 43-51-156-18-77-14	76	
3	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	27-38-15-43-51-157-18-77-14	76	
4	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	28-39-15-44-52-162-18-79-14	65	
1-1975	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	28-39-15-44-52-162-18-79-14	65	
2	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	28-39-15-44-52-162-18-79-14	65	
3	BNW-N-LW-CW-DW-IX-TBP-R-OWW	516	28-39-15-44-52-162-18-79-14	65	
4	BNW-N-LW-CW-DW-IX-TBP-R-OWW	87	1-2-1-2-3-7-1-4-1	65	426 to 103-C

* Dry Well 30-08-02, 30-08-12 drilled.

9 2 1 2 5 5 6 1 2 6 5

Waste Status Summary of 108-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	N-CW-DW-IX-R-OWW	76	1-1-2-4-2-1	65	Removed from service 27 to 103-C
2	N-CW-DW-IX-R-OWW	76 76	1-1-2-4-2-1	65	RFS 1 to 103-C
3	---	65	0	65	Salt Well Pumped
4	---	65	0	65	" " "
1-1977	---	65	0	65	Salt Well Pumped
2	---	65	0	65	" " "
3	---	65	0	65	Inactive Current
4	---	65	0	65	Inactive Current Salt Well Pumped
1-1978	-	65	0	65	
2-	-	65	0	65	
3-	-	65	0	65	
4-	-	65	0	65	
1-1979	-	65	0	65	
2-	-	65	0	65	
3-	-	65	0	65	
4-	-	65	0	65	
1-1980	-	65	0	65	
2-	-	65	0	65	
3-	-	65	0	65	
4-	-	65	0	65	

Waste Status Summary of 109-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	1 C	288	---	---	3rd in cascade, began filling in April 1948
3	1 C	528	---	---	Filled in September 1948
4	1 C	528	---	---	
1-1949	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1950	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1951	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1952	1 C	525	---	---	
2	1 C	311	301	10	Pumping to 106-B
3	1 C	10	---	10 (IC)	Finished pumping 7-25-52
4	TBP	496	486	10	Temp supernate tank for C Farm MW removal operations

Waste Status Summary of 109-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	182	172	10 (IC)	Tank was emptied 1/9/53 Rec'd TBP in March
2	TBP	521	511	10	Filled in April
3	TBP	521	511	10	
4	TBP	521	511	10	
1-1954	TBP	521	511	10	
2	TBP	521	511	10	
3	TBP	521	511	10	
4	TBP	521	511	10	
1-1955	TBP	521	511	10	
2	TBP	521	511	10	
3	TBP	521	511	10	
4	TBP	204	194	10	Pump to 001-CR at intervals for scvg treatment
1-1956	TBP	530	520	10	Decant tank. Emptied in January. Filled in February
2	TBP	530	520	10	Non-cribbable material
3	TBP	530	520	10	Non-cribbable scvg. TBP waste
4	TBP	241	231	10	484 transferred to BC #10 ditch in October
1-1957	IC-TBP	238	203	35	Latest electrode reading
2	TBP	79	28	51	To be cribbed, 462 to #17 BC trench, 456 to #15 BC ditch
3	EB	340	305	35	Rec'd 716, 245 to BC-6 crib, 443 to BC 20
4	EB	543	453	90	456 rec'd, 253 to BC-21
1-1958	EB	112	22	90	431 to BC-22 trench
2	EB	112	22	90	
3	EB	112	22	90	
4	EB	112	22	90	
1-1959	EB	112	22	90	
2	EB-CW	373	22-261	90	261 CW from 105-C
3	EB-CW	540	22-428	90	154 from 105-C, latest electrode reading
4	EB-CW	540	22-428	90	
1-1960	EB-CW	540	22-428	90	
2	EB-CW	540	22-428	90	
3	EB-CW	540	22-428	90	
4	EB-CW	546	22-434	90	6 back flush rec'd

Waste Status Summary of 109-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	EB-CW	549	22-437	90	[6 months report
3					
4	EB-CW	549	22-437	90	[6 months report
1-1962					
2	EB-CW-FP	433	22-300-21	90	137 to BY, rec'd 21 HS
3					
4	EB-CW-FP	491	22-300-79	90	58 from HS [6 months report
1-1963					
2	EB-CW-FP	494	22-300-82	90	[6 months report
3					
4	EB-CW-HS	497	22-300-85	90	Latest electrode reading
1-1964					
2	EB-CW-HS	532	22-300-120	90	Rec'd 35 HS [6 months report
3					
4	EB-CW-HS	535	22-300-123	90	[6months report
1-1965					
2	EB-CW-HS	554	33-300-142	79	19 from HS [6 months report
3	EB-CW-HS	554	33-300-142	79	
4	EB-CW-HS	554	33-300-142	79	
1-1966	EB-CW-HS	552	33-300-140	79	
2	EB-CW-HS	565	33-300-153	79	13 from 108-C
3	EB-CW-HS	565	33-300-153	79	
4	EB-CW-HS	552	33-300-140	79	New electrode
1-1967	EB-CW-HS	552	33-300-140	79	
2	EB-CW-HS	552	33-300-140	79	
3	EB-CW-HS	552	33-300-140	79	
4	EB-CW-HS	549	33-300-137	79	
1-1968	EB-CW-HS	549	38-300-137	79	
2	EB-CW-HS	543	33-300-131	79	
3	EB-CW-HS	543	33-300-131	79	
4	EB-CW-SSW	543	33-300-131	79	
1-1969	EB-CW-SSW	543	33-300-131	79	
2	EB-CW-SSW	543	33-300-131	79	
3	EB-CW-SSW	543	33-300-131	79	
4	EB-CW-SSW	543	33-300-131	79	

9 2 1 2 3 5 6 1 2 9

Waste Status Summary of 109-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW	165	86	79	19 from 203-C, 397 to 104-C
2	CW-IX	541	60-375	106	375 from 110-C
3	CW-IX	543	73-375	95	
4	CW-IX	543	73-375	95	
1-1971	CW-IX	542	73-374	95	
2	CW-IX	542	73-374	95	
3	CW-IX	542	73-374	95	
4	CW-IX	542	73-374	95	
1-1972	CW-IX	540	73-372	95	
2	CW-IX	540	73-372	95	
3	CW-IX	540	73-372	95	
4	CW-IX	530	71-364	95	
1-1973	CW-IX	529	71-363	95	
2	CW-IX	529	71-363	95	
3	CW-IX	505	67-343	95	
4	CW-IX	504	67-342	95	
1-1974 *	CW-IX	504	67-342	95	
2	CW-IX	504	67-342	95	
3	CW-IX	504	67-342	95	
4	CW-IX	505	70-356	79	
1-1975	CW-IX	505	70-356	79	
2	CW-IX	505	70-356	79	
3	CW-IX	142	10-53	79	364 to 103-C
4	---	62	0	62	
1-1976	---	62	0	62	Removed from Service 9 to 103-C
2	---	62	0	62	" " "
3	---	62	0	62	Salt Well Pumped
4	---	62	0	62	" " "
1-1977	---	62	0	62	Salt Well Pumped
2	---	62	0	62	" " "
3	---	62	0	62	" " "
4	---	62	0	62	Inactive Current Salt Well Pumped

* Dry Well 30-09-01, 30-09-02, 30-09-06, 30-09-10, 30-09-11 drilled.

9 2 1 2 5 6 1 2 7 0

Waste Status Summary of 109-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	62	0	62	Inactive
2-	-	62	0	62	
3-	-	62	0	62	
4-	-	62	0	62	
1-1979	NCPLX	68	6	62	
2-	NCPLX	68	6	62	
3-	NCPLX	68	6	62	
4-	NCPLX	68	6	62	
1-1980	NCPLX	68	6	62	
2-	NCPLX	68	6	62	
3-	NCPLX	68	6	62	
4-	NCPLX	68	6	62	

9 2 1 2 5 6 1 2 7 1

Waste Status Summary of 110-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---				
2	---				
3	---				
4	---				
1-1945	---				
2	---				
3	---				
4	---				
1-1946	---				
2	1 C	337	---	---	1st in cascade, began filling in May 1946
3	1 C	528	---	---	Filled in August
4	1 C	528	---	---	Cascading to 111-C
1-1947	1 C	528	---	---	Cascading to 111-C & 112-C
2	1 C	528	---	---	Cascade filled in April 1947
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1948	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1949	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1950	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1951	1 C	528	---	---	
2	1 C	528	---	---	
3	1 C	528	---	---	
4	1 C	528	---	---	
1-1952	1 C	530	---	---	
2	1 C	530	299	231 (IC)	
3	1 C	231	---	231	Finshed pumping to 106-B 7-22-52
4	TBP	490	259	231	Active receiver of TBP wastes. Overflow to 111-C plugged on 11-15-52

Waste Status Summary of 110-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Totl.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	538	307	231 (IC)	Overflow to 111-C plugged
2	TBP	538	307	231	Overflow to 111-C plugged
3	TBP	538	307	231	Overflow to 111-C plugged
4	TBP	538	307	231	Overflow to 111-C plugged
1-1954	TBP	538	307	231	Overflow to 111-C plugged
2	TBP	538	307	231	Overflow to 111-C plugged
3	TBP	538	307	231	Overflow to 111-C plugged
4	TBP	538	307	231	
1-1955	TBP	538	307	231	
2	TBP	538	307	231	
3	TBP	538	307	231	
4	TBP	538	307	231	
1-1956	TBP	265	34	231	Transferred to 001-CR in March
2	OWW	436	205	231	Received OWW in June
3	OWW	491	260	231	Received OWW
4	OWW	491	260	231	No OWW received
1-1957	1C-OWW	513	282	231	Latest electrode reading
2	1C-OWW	508	277	231	Latest electrode reading
3	1C-OWW	510	279	231	Latest electrode reading
4	1C-OWW	510	279	231	
1-1958	1C-OWW	508	277	231	Latest electrode reading
2	1C-OWW	508	277	231	
3	1C-OWW	508	277	231	
4	1C-OWW	508	277	231	Latest electrode reading
1-1959	1C-OWW	508	277	231	
2	1C-OWW	507	276	231	Latest electrode reading
3	1C-OWW	507	276	231	
4	1C-OWW	507	276	231	
1-1960	1C-OWW	507	276	231	
2	1C-OWW	507	276	231	
3	1C-OWW	507	276	231	
4	1C-OWW	455	224	231	Latest electrode reading
1-1961					
2	1C-OWW	505	274	231	
3					
4	1C-OWW	510	279	231	Latest electrode reading
1-1962					
2	1C-OWW	510	279	231	
3					
4	1C-OWW	508	277	231	Latest electrode reading

9 2 1 2 5 5 6 1 2 7 3

Waste Status Summary of 110-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	1 C-OWW	505	1-274	230	[6 months report
3					
4	1 C-OWW	505	1-274	230	[6 months report
1-1964					
2	1 C-OWW	505	1-274	230	[6 months report
3					
4	1 C-OWW	513	1-282	230	New elect. (reading confirmed) [6 months report
1-1965					
2	1 C-OWW	508	40-277	191	[6 months report
3	1 C-OWW	508	40-277	191	New electrode
4	1 C-OWW	508	40-277	191	
1-1966	1 C-OWW	505	40-274	191	
2	1 C-OWW	508	40-277	191	
3	1 C-OWW	508	40-277	191	
4	1 C-OWW	508	40-277	191	
1-1967	1 C-OWW	508	40-277	191	
2	1 C-OWW	508	40-277	191	
3	1 C-OWW	508	40-277	191	73 to Cell 23
4	1 C-OWW	435	40-204	191	
1-1968	1 C-OWW	435	40-204	191	
2	1 C-OWW	435	40-204	191	
3	1 C-OWW	435	40-204	191	
4	1 C-OWW	435	40-204	191	
1-1969	1 C-OWW	435	40-204	191	
2	OWW	220	29	191	215 to 102-C
3	OWW	224	33	191	
4	OWW	224	33	191	
1-1970	OWW-IX	375	33-151	191	151 from 104-BY
2	EB-IX	470	56-203	211	1192 from 104-BX, 1097 to 108-C, 109-C & 112-C
3	EB-IX	536	84-263	189	66 from 104-BX
4	EB-IX	536	84-263	189	
1-1971	EB-IX	536	84-263	189	
2	EB-IX	536	84-263	189	
3	EB-IX	536	84-263	189	
4	EB-IX	2[illegible]1	5-17	189	326 to 104-C

Waste Status Summary of 110-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	CW-OWW-EB-RIX	376	80-85-5-17	189	160 from 103-BX
2	CW-OWW-EB-RIX	376	80-85-5-17	189	
3	CW-OWW-EB-RIX	376	82-88-5-18	183	
4	CW-OWW-EB-RIX	376	82-88-5-18	183	
1-1973	CW-OWW-EB-RIX	376	82-88-5-18	183	
2	CW-OWW-EB-RIX	376	82-88-5-18	183	
3	CW-OWW-EB-RIX	376	83-88-5-18	183	
4	CW-OWW-EB-RIX	376	82-88-5-18	183	
1-1974 *	CW-OWW-EB-RIX	376	75-80-5-16	200	
2	CW-OWW-EB-RIX	376	75-80-5-16	200	
3	CW-OWW-EB-RIX	376	75-80-5-16	200	
4	CW-OWW-EB-RIX	376	70-75-5-15	211	
1-1975 **	CW-OWW-EB-RIX	376	70-75-5-15	211	
2	CW-OWW-EB-RIX	376	70-75-5-15	211	
3	CW-OWW-EB-RIX	268	24-25-2-6	211	109 to 112-C
4	CW-OWW-EB-RIX	268	24-25-2-6	211	

* Dry Wells 30-10-01. 30-10-02, 30-10-09 drilled.

**Dry Wells 30-10-11 drilled.

9 2 1 2 5 6 1 2 7 5

Waste Status Summary of 110-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	CW-OWW-EB-RIX	233	9-10-1-2	211	Removed from Service 62 to 103-C
2	---	211	0	211	Removed from Service 4 to 103-C
3	---	211	0	211	Salt Well Pumped
4	---	211	0	211	" " "
1-1977	---	211	0	211	Salt Well Pumped
2	---	211	0	211	" " "
3	---	211	0	211	" " "
4	---	211	0	211	Inactive Current Salt Well Installed
1-1978	-	211	0	211	
2-	-	211	0	211	
3-	-	211	0	211	
4-	-	211	0	211	
1-1979	NCPLX	213	2	211	Questionable Integrity Primary Stabilized
2-	NCPLX	213	2	211	
3-	NCPLX	213	2	211	
4-	NCPLX	213	2	211	New Photo 8/8/79
1-1980	NCPLX	213	2	211	
2-	NCPLX	213	2	211	
3-	NCPLX	213	2	211	
4-	NCPLX	213	2	211	

Waste Status Summary of 111-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	1C	331	---	---	2nd in Cascade, began filling August 1946
4	1C	528	---	---	Filled in November 1946
1-1947	1C	528	---	---	Cascading to 112-C
2	1C	528	---	---	Cascade filled April 1947
3	1C	528	---	---	
4	1C	528	---	---	
1-1948	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1949	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1950	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1951	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1952	1C	530	---	---	
2	1C	530	494	36 (IC)	
3	1C	36	---	36	Finished pumping to 106-B
4	TBP	139	103	36	Overflow from 110-C plugged on 11-15-52

9 2 1 2 5 6 1 2 7 7

Waste Status Summary of 111-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	TBP	536	500	36 (IC)	
2	TBP	536	500	36	
3	TBP	536	500	36	
4	TBP	536	500	36	
1-1954	TBP	536	500	36	
2	TBP	536	500	36	
3	TBP	536	500	36	
4	TBP	536	500	36	
1-1955	TBP	536	500	36	
2	TBP	536	500	36	
3	TBP	536	500	36	
4	TBP	536	500	36	
1-1956	TBP	530	494	36	Emptied in January. Rec'd scvg. waste from 001-CR in Feb. Non-disposable material
2	TBP	530	494	36	Non-cribbable material
3	OWW	56	20	36	Pumped to BC #7 ditch in Aug & Sep Rec'd OWW in Sept.
4	OWW	70	34	36	Rec'd 14 OWW
1-1957	IC-OWW-CW	332	36-34-262	---	SS, 263 CW rec'd
2	TBP	521	508	13	Inc due to line drainage, 462 to #17 BC trench, SS 77 CW rec'd, 373 to 111-BY
3	EB	549	495	54	451 to 108-C, 888 rec'd, 297 to BC-20, 465 to BC-18 ditch
4	EB	98	3	95	336 rec'd, 346 to BC-22, 414 to BC 21
1-1958	EB	101	6	95	Latest electrode reading
2	EB	101	6	95	
3	EB	101	6	95	
4	EB	88	88	95	Latest & new electrode reading
1-1959	EB	90		95	
2	EB	90		95	
3	EB	111	16	95	Latest electrode reading, increase To be investigated.
4	EB-CW	298	0-203	95	187 from 105-C
1-1960	EB-CW	337	242	95	39 from 105-C
2	EB-CW	337	242	95	
3	EB-CW	337	242	95	
4	EB-CW	309	214	95	Latest electrode reading, 5 CW rec'd

9 2 1 2 5 5 6 1 2 7 8

Waste Status Summary of 111-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	EB-CW	345	250	95	
3					
4	EB-CW	345	250	95	
1-1962					
2	EB-CW	345	250	95	
3					
4	EB-CW-FP	370	250-25	95	25 from HS
1-1963					
2	EB-CW-FP	431	250-86	95	Rec'd 61 from HS
3					
4	EB-CW-HS	472	250-127	95	Rec'd 41 from semiworks
1-1964					
2	EB-CW-HS	539	250-194	95	Rec'd 101 HS
3					
4	EB-CW-HS	539	250-194	95	
1-1965					
2	EB-CW-HS	519	7-257-174	81	New elect.
3	EB-CW-HS	520	7-257-175	81	New electrode
4	EB-CW-HS	516	7-257-171	81	
1-1966	EB-CW-HS	513	7-257-168	81	
2	EB-CW-HS	510	7-257-168	81	
3	EB-CW-HS	510	7-257-168	81	
4	EB-CW-HS	508	7-257-168	81	
1-1967	EB-CW-HS	508	7-257-163	81	
2	EB-CW-HS	503	7-257-158	81	
3	EB-CW-HS	503	7-257-158	81	
4	EB-CW-HS	502	7-257-157	81	
1-1968	EB-CW-HS	499	7-254-157	81	
2	EB-CW-HS	499	7-254-157	81	
3	EB-CW-HS	499	7-254-157	81	
4	EB-CW-SSW	499	7-254-157	81	
1-1969	EB-CW-SSW	498	7-254-156	81	
2	EB-CW-SSW	497	7-254-155	81	
3	EB-CW-SSW	497	7-254-155	81	
4	CW	147	66	81	349 to 104-C
1-1970 *	CW	147	66	81	
2	CW	146	50	96	
3	CW	150	58	92	
4	CW	151	59	92	

* Dry Wells 30-11-01, 30-11-06, 30-11-09 drilled.

Waste Status Summary of 111-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	CW	151	59	92	
2	CW	151	59	92	
3	CW	151	59	92	
4	CW	151	59	92	
1-1972	CW	150	58	92	
2	CW	172	96	76	22 from 301-C
3	CW	174	98	76	
4	CW	172	96	76	
1-1973	CW	172	96	76	
2	CW	172	96	76	
3	CW	172	96	76	
4	CW	171	95	76	
1-1974	CW	171	95	76	Suspect leaker
2	CW	114	38	76	Suspect leaker. 65 to 104-C
3	CW	115	39	76	Suspect leaker
4	CW	114	52	62	Suspect leaker
1-1975 *	CW	114	52	62	Suspect leaker
2	CW	114	52	62	Removed from service
3	CW	114	52	62	Removed from service
4	CW	114	52	62	Removed from service
1-1976	CW	73	11	62	Removed from service. 63 to 103-C
2	---	62	0	62	Removed from service 2 to 103-C
3	---	62	0	62	Salt Well Pumped
4	---	62	0	62	" " "
1-1977	---	62	0	62	Salt Well Pumped
2	---	62	0	62	" " "
3	---	62	0	62	" " "
4	---	62	0	62	" " "

* Dry Wells 30-11-05, 30-11-11 drilled.

Waste Status Summary of 111-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	62	0	62	Inactive
2-	-	62	0	62	Questionable Integrity
3-	-	62	0	62	
4-	-	62	0	62	
1-1979	-	62	0	62	
2-	-	62	0	62	
3-	-	62	0	62	
4-	-	62	0	62	
1-1980	-	62	0	62	
2-	-	62	0	62	
3-	-	62	0	62	
4-	-	62	0	62	

9 2 1 2 5 6 1 2 3 1

Waste Status Summary of 112-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	1C	225	---	---	3rd in cascade, began filling November 1946
1-1947	1C	512	---	---	
2	1C	528	---	---	Finished fill April 1947
3	1C	528	---	---	
4	1C	528	---	---	
1-1948	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1949	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1950	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1951	1C	528	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	528	---	---	
1-1952	1C	525	---	---	
2	1C	99	84	15	Partially pumped to 106-B. To be finished at a later date
3	1C	17	2	15	Finished pumping to 106-B on 8-15-52
4	1C	17	2	15	

9212556128 2

Waste Status Summary of 112-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C-TBP	249	2-232	15	Started filling in January
2	1C-TBP	517	2-500	15	Filled in April
3	1C-TBP	178	2-161	15	Pumped TBP waste to 106-B
4	1C-TBP	145	2-128	15	
1-1954	1C-TBP	145	2-128	15	
2	1C-TBP	433	2-416	15	Rec'd TBP waste during June
3	1C-TBP	466	2-449	15	Rec'd material from 301-C catch tank
4	1C-TBP	466	2-449	15	
1-1955	1C-TBP	466	2-449	15	
2	TBP	466	449	17	
3	TBP	466	449	17	
4	TBP	524	507	17	Pumped to 104-C in October. Rec'd TBP in December
1-1956	TBP	340	323	17	Pumped in March. Rec'd scvg waste from 001-CR
2	TBP	530	513	17	Rec'd scvg waste from 001-CR in April. Non-cribbable material
3	TBP	417	400	17	Rec'd scvg waste from 001-CR vault. Pumped 336 to BC #3 crib
4	---	39	---	39	Pumped 476 to BC #10 ditch in October
1-1957	TBP	156	117	39	27" gain. Flushing BX line, latest electrode reading
2	TBP	54	33	21	483 to 102-BY, 474 to 108-BY, 487 rec'd
3	EB	541	502	39	450 to BC-6, 459 rec'd, rec'd 478 scvg waste
4	TBP	516	477	39	869 rec'd, 470 to BC-6, 414 to BC-21
1-1958	TBP	84	38	46	432 to BC-22 trench
2	TBP	84	38	46	
3	TBP	84	38	46	
4	TBP	134	88	46	Latest new electrode reading
1-1959	TBP	137	91	46	
2	TBP	137	91	46	
3	TBP	84	38	46	Latest electrode reading
4	TBP	136	90	46	
1-1960	TBP	137	91	46	
2	TBP	137	91	46	
3	TBP	263	217	46	SS rec'd 126 CW & dilution
4	TBP	367	313-8	46	Latest electrode reading. 137 CW rec'd

9 2 1 2 5 6 1 2 8 3

Waste Status Summary of 112-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	TBP-CW	455	90-319	46	[6 month report]
3					
4	TBP-CW-HS	486	90-319-31	46	31 from HS [6 month report]
1-1962					
2	TBP-CW-FP	508	90-319-53	46	22 from HS [6 month report]
3					
4	TBP-CW-FP	505	90-319-50	46	Latest electrode reading [6month report]
1-1963					
2	TBP-CW-FP	510	90-319-55	46	Latest electrode reading [6 month report]
3					
4	TBP-CW-HS	513	90-319-58	46	Latest electrode reading [6 month report]
1-1964					
2	TBP-CW-HS	547	90-319-92	46	[6 month report]
3					
4	TBP-CW-HS	547	90-319-92	46	] 6 month report]
1-1965					
2	TBP-CW-HS	538	8-319-83	128	New electrode
3	TBP-CW-HS	538	8-319-83	128	New electrode
4	TBP-CW-HS	538	8-319-83	128	
1-1966	TBP-CW-HS	538	8-319-83	128	
2	TBP-CW-HS	535	8-319-80	128	
3	TBP-CW-HS	535	8-319-80	128	
4	TBP-CW-HS	535	8-319-80	128	
1-1967	TBP-CW-HS	535	8-319-80	128	
2	TBP-CW-HS	535	8-319-80	128	
3	TBP-CW-HS	535	8-319-80	128	
4	TBP-CW-HS	535	8-319-80	128	
1-1968	TBP-CW-HS	534	8-318-80	128	
2	TBP-CW-HS	534	8-318-80	128	
3	TBP-CW-HS	534	8-318-80	128	
4	TBP-CW-SSW	534	8-318-80	128	
1-1969	TBP-CW-SSW	534	8-318-80	128	
2	TBP-CW-SSW	532	8-318-72	128	
3	TBP-CW-SSW	532	8-318-72	128	
4	TBP-CW-SSW	532	8-318-72	128	

9 2 1 2 5 5 6 1 2 8 4

Waste Status Summary of 112-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW	213	85	128	21 from 301-C catch tk, 340 to 104-C
2	CW-IX	541	76-327	138	327 from 110-C
3	CW-IX	543	80-327	136	
4	CW-IX	543	80-327	136	
1-1971	CW-IX	543	80-327	136	
2	CW-IX	543	80-327	136	
3	CW-IX	543	80-327	136	
4	CW-IX	543	80-327	136	
1-1972	CW-IX	542	80-326	136	
2	CW-IX	543	80-327	136	
3	CW-IX	543	83-340	120	
4	CW-IX	532	81-331	120	
1-1973	CW-IX	532	81-331	120	
2	CW-IX	531	81-330	120	
3	CW-IX	531	81-330	120	
4	CW-IX	531	81-330	120	
1-1974	CW-IX	530	81-329	120	
2	CW-IX	530	81-329	120	
3	CW-IX	530	81-329	120	
4	CW-IX	532	80-324	128	
1-1975 *	CW-IX	483	70-285	128	19 from 301-C, 66 to 103-C
2	CW-IX	483	70-285	128	
3	CW-OWW-EB-RIX	194	28-30-2-6	128	109 from 110-C, 400 to 103-C
4	---	109	0	109	85 to 103-C
1-1976	---	109	0	109	Removed from service 3 to 103-C
2	---	109	0	109	Removed from service 1 to 103-C
3	---	109	0	109	Salt Well Pumped
4	---	109	0	109	" " "
1-1977	---	109	0	109	Salt Well Pumped
2	---	109	0	109	" " "
3	---	109	0	109	" " "
4	---	109	0	109	Inactive Current Salt Well Installed

* Dry Wells 30-12-01, 30-12-03, 30-12-09 drilled.

9 2 1 2 5 5 6 1 2 8 5

Waste Status Summary of 112-C Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	109	0	109	
2-	-	109	0	109	
3-	-	109	0	109	
4-	-	109	0	109	New Photo 11/16/78
1-1979	-	109	0	109	
2-	-	109	0	109	
3-	-	109	0	109	
4-	-	109	0	109	
1-1980	-	109	0	109	
2 *	-	109	0	109	
3-	-	109	0	109	
4-	-	109	0	109	

* 30-12-13 dry well drilled 5-78

9 2 1 2 5 5 1 2 3 6

Waste Status Summary of 201-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	55	---	---	Filled during March & November
1-1948	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1949	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1950	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1951	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1952	MW	54.5	---	---	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	52.5	---	---	

Waste Status Summary of 201-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	52.5	---	---	
2	MW	54.5	---	---	Cascade now processing. For feed to TBP Plant
3	MW	54.5	---	---	
4	MW	15.7	---	---	MW removal in progress. Supernatant transferred to 106-C
1-1954	MW	0	0	0	Declared empty on 3-17-54
2	MW	0	0	0	
3	MW	0	0	0	
4	MW	0	0	0	
1-1955	MW	0	0	0	
2	SSW	13	---	0	Started receiving in May
3	SSW	30	30	0	
4	SSW	57	57	0	
1-1956	SSW	54.5	54.5	0	
2	SSW	54.5	54.5	0	
3	SSW	54.5	54.5	0	
4	SSW	54.5	54.5	0	
1-1957	HOT-SEMI	54	54	---	
2	HOT-SEMI	54	54	---	
3	HOT-SEMI	55	55	---	Latest electrode reading
4	HOT-SEMI	55	55	---	
1-1958	HOT-SEMI	55	55	---	
2	HOT-SEMI	55	55	---	
3	HOT-SEMI	55	55	---	
4	HOT-SEMI	55	55	---	
1-1959	HOT-SEMI	54	54	---	
2	HOT-SEMI	54	54	---	
3	HOT-SEMI	54	54	---	
4	HOT-SEMI	55	55	---	Latest electrode reading
1-1960	HOT-SEMI	55	55	---	
2	HOT-SEMI	55	55	---	
3	HOT-SEMI	55	55	---	
4	HOT-SEMI	55	55	---	
1-1961					
2	HOT-SEMI	56	56	---	
3					
4	HOT-SEMI	56	56	---	

Waste Status Summary of 201-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	HOT-SEMI	56	56	---	
3					
4	HOT-SEMI	56	56	---	
1-1963					
2	HOT-SEMI	56	56	---	
3					
4	HOT-SEMI	54	54	---	
1-1964					
2	HOT-SEMI	54	54	---	
3					
4	HOT-SEMI	54	54	---	
1-1965					
2	HS	54	54	---	
3	HS	54	54	---	
4	HS	52	52	---	
1-1966	HS	52	52	---	
2	HS	52	52	---	
3	HS	52	52	---	
4	HS	52	52	---	
1-1967	HS	55	55	---	
2	HS	55	55	---	
3	HS	55	55	---	
4	HS	55	55	---	
1-1968	HS	55	55	---	
2	HS	55	55	---	
3	HS	55	55	---	
4	SSW	55	55	---	
1-1969	SSW	55	55	---	
2	SSW	55	55	---	
3	SSW	55	55	---	
4	SSW	55	---	---	
1-1970	SSW	55	54	1	
2	---	1	0	1	54 to 104-C
3	---	1	0	1	
4	---	1	0	1	
1-1971	---	1	0	1	
2	---	1	0	1	
3	---	1	0	1	
4	---	1	0	1	

Waste Status Summary of 201-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	---	1	0	1	
2	---	1	0	1	
3	---	1	0	1	
4	---	1	0	1	
1-1973	---	1	0	1	
2	---	1	0	1	
3	---	1	0	1	
4	---	3	2	1	
1-1974	---	3	2	1	
2	---	3	2	1	
3	---	3	2	1	
4	---	3	3	0	
1-1975	SSW	4	4	0	
2	SSW	4	4	0	
3	SSW	4	4	0	
4	SSW	4	4	0	
1-1976	SSW	4	4	0	Removed from service
2	SSW	4	4	0	" " "
3	---	4	4	0	Evap. Active Restricted
4	---	4	4	0	" " "
1-1977	---	4	4	0	Evap. Active Restricted
2		4	4	0	" " "
3		4	4	0	" " "
4		4	4	0	" Inactive

9 2 1 2 5 6 1 2 9 0

Waste Status Summary of 201-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	4	4	0	
2-	NCPLX	4	4	0	
3-	NCPLX	4	4	0	
4-	NCPLX	4	4	0	
1-1979	NCPLX	4	4	0	
2-	NCPLX	4	4	0	
3-	NCPLX	4	4	0	
4-	NCPLX	4	4	0	
1-1980	NCPLX	4	4	0	
2-	NCPLX	4	4	0	
3-	NCPLX	4	4	0	
4-	NCPLX	4	4	0	

9212161291

Waste Status Summary of 202-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	55	---	---	Filled in March & November
1-1948	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1949	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1950	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1951	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1952	MW	54.5	---	---	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	54.5	---	---	

Waste Status Summary of 202-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	54.5	---	---	
2	MW	8	---	---	Cascade now processing for feed to TBP Plant
3	MW	8	---	---	
4	MW	43.7	---	---	MW removal in progress. Supernatant transferred to 106-C
1-1954	MW	0	0	0	Sluicing completed in January
2	MW	0	0	0	
3	MW	0	0	0	
4	MW	0	0	0	
1-1955	MW	0	0	0	
2	MW	0	0	0	
3	MW	0	0	0	
4	SSW	6	---	0	
1-1956	SSW	23.5	---	0	Received in February
2	SSW	54.5	---	0	Filled in May
3	SSW	54.5	---	0	
4	SSW	54.5	---	0	
1-1957	HOT-SEMI	56	---	---	
2	HOT-SEMI	56	---	---	Latest electrode reading
3	HOT-SEMI	56	---	---	
4	HOT-SEMI	56	---	---	
1-1958	HOT-SEMI	56	---	---	
2	HOT-SEMI	56	---	---	
3	HOT-SEMI	56	---	---	
4	HOT-SEMI	55	---	---	New electrode reading
1-1959	HOT-SEMI	55	---	---	
2	HOT-SEMI	55	---	---	
3	HOT-SEMI	55	---	---	
4	HOT-SEMI	55	---	---	
1-1960	HOT-SEMI	55	---	---	
2	HOT-SEMI	55	---	---	
3	HOT-SEMI	55	---	---	
4	HOT-SEMI	55	---	---	
1-1961					
2	HOT-SEMI	56	---	---	[6 month report]
3					
4	HOT-SEMI	56	---	---	[6 month report]

Waste Status Summary of 202-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	HOT-SEMI	56	---	---	[6 month report]
3					
4	HOT-SEMI	56	---	---	[6 month report]
1-1963					
2	HOT-SEMI	56	---	---	[6 month report]
3					
4	HOT-SEMI	57	---	---	[6 month report]
1-1964					
2	HOT-SEMI	55	---	---	New electrode [6 month report]
3					
4	HOT-SEMI	55	---	---	[6 month report]
1-1965					
2	HS	55	---	---	[6 month report]
3	HS	55	---	---	
4	HS	55	---	---	
1-1966	HS	55	---	---	
2	HS	55	---	---	
3	HS	55	---	---	
4	HS	55	---	---	
1-1967	HS	55	---	---	
2	HS	55	---	---	
3	HS	55	---	---	
4	HS	55	---	---	
1-1968	HS	55	---	---	
2	HS	55	---	---	
3	HS	55	---	---	
4	SSW	55	---	---	
1-1969	SSW	55	---	---	
2	SSW	55	---	---	
3	SSW	55	---	---	
4	SSW	55	---	---	
1-1970	SSW	55	---	---	
2	---	0	0	---	55 to 104-C
3	---	0	0	---	
4	---	0	0	---	

Waste Status Summary of 202-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	---	0	0	---	
2	---	0	0	---	
3	---	0	0	---	
4	---	0	0	---	
1-1972	---	0	0	---	
2	---	0	0	---	
3	---	0	0	---	
4	---	0	0	---	
1-1973	---	0	0	0	
2	---	0	0	0	
3	---	0	0	0	
4	---	1	1	0	
1-1974	---	1	1	0	
2	---	2	2	0	
3	---	2	2	0	
4	---	2	2	0	
1-1975	SSW	2	2	0	
2	SSW	2	2	0	
3	SSW	2	2	0	
4	SSW	2	2	0	
1-1976	SSW	2	2	0	Removed from service
2	SSW	2	2	0	
3	---	2	2	0	Active Restricted
4	---	2	2	0	" "
1-1977	---	2	2	0	Active Restricted
2	---	2	2	0	" "
3	---	2	2	0	Inactive Current
4	---	2	2	0	" "

Waste Status Summary of 202-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	2	2	0	
2-	NCPLX	2	2	0	
3-	NCPLX	2	2	0	
4-	NCPLX	2	2	0	
1-1979	NCPLX	2	2	0	New Solids Level 1/19/79
2-	NCPLX	2	2	0	
3-	NCPLX	2	2	0	
4-	NCPLX	2	2	0	
1-1980	NCPLX	2	2	0	
2-	NCPLX	2	2	0	
3-	NCPLX	3	2	1	
4-	NCPLX	1	0	1	

9 2 1 2 5 6 1 2 9 6

Waste Status Summary of 203-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	41	---	---	Filled in March & November
1-1948	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1949	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1950	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1951	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1952	MW	54.5	---	---	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	54.5	---	---	
1-1953	MW	54.5	---	---	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	14.8	---	---	MW removal in progress. Supernatant transferred to 106-C

9 2 1 2 6 1 2 9 7

Waste Status Summary of 203-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	0	0	0	Sluicing completed in February
2	MW	0	0	0	
3	MW	0	0	0	
4	MW	0	0	0	
1-1955	MW	0	0	0	
2	MW	0	0	0	
3	MW	0	0	0	
4	SSW	5	---	0	
1-1956	SSW	5	---	0	
2	SSW	5	---	0	
3	SSW	22	---	0	Received in Aug & Sept
4	SSW	34.5	---	0	Rec'd in October
1-1957	HOT-SEMI	36	---	---	SS latest electrode reading
2	HOT-SEMI	35	---	---	Latest electrode reading
3	HOT-SEMI	35	---	---	
4	HOT-SEMI	35	---	---	
1-1958	HOT-SEMI	35	---	---	
2	HOT-SEMI	35	---	---	
3	HOT-SEMI	35	---	---	
4	HOT-SEMI	35	---	---	
1-1959	HOT-SEMI	34	---	---	
2	HOT-SEMI	34	---	---	
3	HOT-SEMI	34	---	---	
4	HOT-SEMI	34	---	---	
1-1960	HOT-SEMI	34	---	---	
2	HOT-SEMI	34	---	---	
3	HOT-SEMI	34	---	---	
4	HOT-SEMI	34	---	---	
1-1961					
2	HOT-SEMI	34	---	---	[6 month report]
3					
4	HOT-SEMI	34	---	---	[6 month report]
1-1962					
2	HOT-SEMI	34	---	---	[6 month report]
3					
4	HOT-SEMI	34	---	---	[6 month report]
1-1963					
2	HOT-SEMI	34	---	---	[6 month report]
3					
4	HOT-SEMI	35	---	---	[6 month report]

Waste Status Summary of 203-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	HOT-SEMI	35	---	---	[6 month report]
3					
4	HOT-SEMI	35	---	---	[6 month report]
1-1965					
2	HS	33	---	---	New elect. [6 month report]
3	HS	33	---	---	New electrode
4	HS	33	---	---	
1-1966	HS	33	---	---	
2	HS	33	---	---	
3	HS	33	---	---	
4	HS	33	---	---	
1-1967	HS	34	---	---	
2	HS	34	---	---	
3	HS	34	---	---	
4	HS	34	---	---	
1-1968	HS	34	---	---	
2	HS	34	---	---	
3	HS	34	---	---	
4	SSW	34	---	---	
1-1969	SSW	34	---	---	
2	SSW	34	---	---	
3	SSW	34	---	---	
4	SSW	34	---	---	
1-1970	SSW	18	13	5	19 to 109-C
2	SSW	6	1	5	12 to 104-C
3	SSW	6	1	5	
4	SSW	6	1	5	
1-1971	SSW	6	1	5	
2	SSW	6	1	5	
3	SSW	6	1	5	
4	SSW	6	1	5	
1-1972	SSW	6	3	3	
2	SSW	6	3	3	
3	SSW	6	3	3	
4	SSW	6	3	3	
1-1973	SSW	6	3	3	
2	SSW	6	3	3	
3	SSW	6	3	3	
4	SSW	7	4	3	

Waste Status Summary of 203-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	SSW	7	4	3	
2	SSW	8	5	3	
3	SSW	8	5	3	
4	SSW	7	4	3	
1-1975	SSW	7	4	3	
2	SSW	8	5	3	
3	SSW	8	5	3	
4	SSW	8	5	3	
1-1976	SSW	8	5	3	Removed from service
2	SSW	8	5	3	" " "
3	SSW	8	5	3	" " "
4	SSW	8	5	3	" " "
1-1977	SSW	8	5	3	
2	SSW	8	5	3	
3	SSW	8	5	3	
4	SSW	8	4	4	Inactive
1-1978	-	8	4	4	
2-	NCPLX	8	4	4	
3-	NCPLX	8	4	4	
4-	NCPLX	8	4	4	
1-1979	NCPLX	8	4	4	
2-	NCPLX	8	4	4	
3-	NCPLX	8	4	4	
4-	NCPLX	8	4	4	
1-1980	NCPLX	8	4	4	
2-	NCPLX	8	4	4	
3-	NCPLX	9	4	5	New Photo 4/3/80
4-	NCPLX	9	4	5	

9212561300

Waste Status Summary of 204-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	MW	55	---	---	Full in January 1948
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1949	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1950	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1951	MW	55	---	---	
2	MW	55	---	---	
3	MW	55	---	---	
4	MW	55	---	---	
1-1952	MW	54.5	---	--	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	54.5	---	---	

9 2 1 2 5 6 1 3 0 1

Waste Status Summary of 204-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	54.5	---	---	
2	MW	54.5	---	---	
3	MW	54.5	---	---	
4	MW	15.2	---	---	MW removal in progress. Supernatant transferred to 106-C
1-1954	MW	51	40	11	Contains water and initial sludge
2	MW	51	40	11	Contains water and initial sludge
3	MW	51	40	11	Contains water and initial sludge
4	MW	47	36	11	Pumped in November
1-1955	MW	0	0	0	Pumped in January
2	MW	0	0	0	
3	MW	0	0	0	
4	SSW	5	5	0	
1-1956	SSW	5	5	0	
2	SSW	34	34	0	Rec'd SSW in May
3	SSW	34	34	0	
4	SSW	34.5	34.5	0	
1-1957	HOT-SEMI	54	54	---	
2	HOT-SEMI	33	33	---	Latest electrode reading
3	HOT-SEMI	32	32	---	Latest electrode reading
4	HOT-SEMI	32	32	---	
1-1958	HOT-SEMI	34	34	---	Latest electrode reading
2	HOT-SEMI	34	34	---	
3	HOT-SEMI	34	34	---	
4	HOT-SEMI	34	34	---	
1-1959	HOT-SEMI	33	33	---	
2	HOT-SEMI	33	33	---	
3	HOT-SEMI	33	33	---	
4	HOT-SEMI	36	36	---	New electrode installed
1-1960	HOT-SEMI	36	36	---	
2	HOT-SEMI	36	36	---	
3	HOT-SEMI	36	36	---	
4	HOT-SEMI	36	36	---	
1-1961					
2	HOT-SEMI	37	37	---	[6 month report]
3					
4	HOT-SEMI	37	37	---	[6 month report]

Waste Status Summary of 204-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	HOT-SEMI	37	26	11	[6 month report]
3					
4	HOT-SEMI	37	26	11	[6 month report]
1-1963					
2	HOT-SEMI	37	26	11	[6 month report]
3					
4	HOT-SEMI	36	25	11	[6 month report]
1-1964					
2	HOT-SEMI	36	25	11	[6 month report]
3					
4	HOT-SEMI	36	25	11	[6 month report]
1-1965					
2	HS	36	25	11	New elect. [6 month report]
3	HS	36	25	11	New electrode
4	HS	36	25	11	
1-1966	HS	36	25	11	
2	HS	36	25	11	
3	HS	36	25	11	
4	HS	36	25	11	
1-1967	HS	36	25	11	
2	HS	36	25	11	
3	HS	36	25	11	
4	HS	57	46	11	
1-1968	HS	57	46	11	
2	HS	57	46	11	
3	HS	57	46	11	
4	SSW	57	46	11	
1-1969	SSW	57	46	11	
2	SSW	57	46	11	
3	SSW	57	46	11	
4	SSW	57	46	11	
1-1970	SSW	57	55	2	
2	SSW	43	41	2	14 to 104-C
3	SSW	42	40	2	
4	SSw	42	40	2	

9 2 1 2 6 1 3 1 3

Waste Status Summary of 204-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971	SSW	42	40	2	
2	SSW	42	40	2	
3	SSW	42	40	2	
4	SSW	42	40	2	
1-1972	SSW	42	41	1	
2	SSW	42	41	1	
3	SSW	42	41	1	
4	SSW	42	41	1	
1-1973	SSW	42	41	1	
2	SSW	42	41	1	
3	SSW	42	41	1	
4	SSW	44	43	1	
1-1974	SSW	44	43	1	
2	SSW	44	43	1	
3	SSW	44	43	1	
4	SSW	44	44	0	
1-1975	SSW	44	44	0	
2	SSW	44	44	0	
3	SSW	44	44	0	
4	SSW	44	44	0	
1-1976	SSW	44	44	0	
2	SSW	44	44	0	
3	---	44	44	0	
4	---	44	44	0	
1-1977	---	44	44	0	
2	---	44	44	0	
3	---	3	3	0	Inactive Current
4	---	3	3	0	" "

9 2 1 2 6 1 3 1 4

Waste Status Summary of 204-C Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	3	3	0	Inactive
2-	NCPLX	3	3	0	
3-	NCPLX	3	3	0	
4-	NCPLX	3	3	0	
1-1979	NCPLX	3	3	0	Primary Stabilized
2-	NCPLX	3	3	0	
3-	NCPLX	3	3	0	
4-	NCPLX	3	3	0	
1-1980	NCPLX	3	3	0	
2-	NCPLX	3	3	0	
3-	NCPLX	3	2	1	New Photo 4/3/80
4-	NCPLX	3	2	1	

9212561375

Waste Status Summary of 101-S Tank Capacity 750,000 Gallons

Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3	R	---	---	---	
4	R	---	---	---	
1-1953	R	---	---	---	
2	R	---	---	---	
3	R	758	758	0	Cascade receives - salt waste, lab. waste and "hot" condensate.
4	R	772	772	0	Cascade receives salt waste, lab. waste and "hot" condensate.
1-1954	R	719	719	0	Self-evaporating.
2	R	730	730	0	Cascade received coating waste. Self-evaporating.
3	R	759	759	0	
4	R	758	758	0	
1-1955	R	741	741	0	Self-evaporating.
2	R	725	725	0	
3	R	772	772	0	4m self-conc.
4	R	763	763	0	

Waste Status Summary of 101-S Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	761	761	0	Self-concentrating
2	R	757	757	0	1,000 gallons evaporated
3	R	756	756	0	
4	R	756	756	0	
1-1957	R	752	752	0	Latest electrode reading
2	R	752	752	0	
3	R	750	750	0	Latest electrode reading
4	R	750	750	0	
1-1958	R	769	769	0	
2	R	769	769	0	
3	R	766	766	0	Latest electrode reading
4	R	763	763	0	
1-1959	R	763	763	0	
2	R	763	763	0	
3	R	762	762	0	
4	R	761	761	0	Latest electrode reading
1-1960	R	757	757	0	
2	R	757	757	0	
3	R	757	757	0	
4	R	761	761	0	
1-1961					
2	R	758	758	0	6 months report
3					
4	R	758	758	0	6 months report

Waste Status Summary of 101-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					Latest electrode reading
2	R	755	755	0	6 months report
3					
4	R	755	755	0	6 months report
1-1963					
2	R	755	755	0	6 months report
3					
4	R	755	755	0	6 months report
1-1964					
2	R	755	755	0	6 months report
3					
4	R	755	755	0	6 months report
1-1965					
2	R	744	744	0	6 months report
3	R	744	744	0	
4	R	744	744	0	
1-1966	R	744	744	0	
2	R	744	744	0	
3	R	744	744	0	
4	R	744	744	0	
1-1967	R	744	744	0	
2	R	744	744	0	
3	R	744	744	0	
4	R	744	744	0	

9-2-1-2-5-6-1-3-0-8

Waste Status Summary of 101-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	744	744	0	
2	R	745	745	0	
3	R	745	745	0	
4	R	745	745	0	
1-1969	R	744	744	0	
2	R	744	744	0	
3	R	744	744	0	
4	R	744	533	211	
1-1970	R	743	532	211	
2	R	743	532	211	
3	R	743	532	211	
4	R	743	532	211	
1-1971	R	743	532	211	
2	R	743	532	211	
3 *	R	743	532	211	
4	R	743	532	211	
1-1972	R	743	532	211	
	R	743	532	211	
3	R	743	532	211	
4	R	744	533	211	
1-1973	R	744	533	211	
2	R	734	523	211	
3	R	744	533	211	
4	N-BNW-DW-CW-EB	426	99-26-45-4-41	211	273 M from 107-U, 335 from 108-U, 926 M to 102-S

* Dry Well #40-01-01 drilled
Dry Well #40-01-06 drilled
Dry Well #40-01-08 drilled

Waste Status Summary of 101-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	IX	616	372	244	162 from 103-U, 210 from 107-U, 97 from 105-S, 123 from 107-S, 828 from 110-S, 112 H_2O, 1340 to 102-S
2	CW-LW-BNW-N-DW	588	23-59-63-167-32	244	515 from 107-S, 2,192 from 110-S, 2 from 111-S, 2,748 to 102-S, 11 from 105-S
3 *	BNW-N-LW-PL-B-CW	339	19-34-11-8-12-11	244	7 from 105-S, 85 from 107-S, 1215 from 110-S, 339 from 101-SX, 1883 to 102-S, 12 to 107-S
4	EB	519	275	244	257 from 107-S, 345 to 102-S, 242-S bottom and recycle (1)
1-1975	EB	552	308	244	242-S bottom and recycle(1), 5 from 105-S
2	EB	692	360	332	242-S bottom and recycle(1), 4 from 105-S
3	---	332	0	332	242-S bottoms and recycle(1)
4	TL	560	228	332	242-S bottoms and recycle(1)
1-1976	TL	717	385	332	242-S bottoms and recycle(1) 263 from 105-SX
2	EB	717	385	332	242-S bottoms and recycle(1)
3	EVAP	719	387	332	
4	EVAP	725	393	332	Lo-heat EVAP feed
1-1977	EVAP	708	376	332	Lo-heat EVAP feed
2	EVAP	725	393	332	Lo-heat EVAP feed
3	Resid.	703	371	332	Neut. feed, EVAP feed
4	Resid.	706	374	332	Neut. feed, EVAP feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S Farm tanks.

* Dry Well #40-01-04 drilled
Dry Well #40-01-10 drilled

Waste Status Summary of 101-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	703	371	332	Active - Part Neut. Fd.
2-	PNF	703	371	332	New Photo 3/21/78
3-	PNF	700	368	332	
4-	PNF	700	368	332	
1-1979	PNF	678	346	332	
2-	PNF	472	140	332	
3-	PNF	472	140	332	New Photo 7/11/79
4-	PNF	585	253	332	
1-1980	DSSF	711	379	332	New Photo 2/12/80
2-	DSSF	520	188	332	
3-	DSSF	427	12	415	New Liquid Level 9/16/80
4-	DSSF	427	12	415	

9212561311

Waste Status Summary of 102-S Tank Capacity 750,000 Gallons

Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3	R	---	---	---	
4	R	---	---	---	
1-1953	R	---	---	---	
2	R	---	---	---	
3	R	239	239	0	Cascade receives - salt waste, lab. waste and "hot" condensate.
4	R	766	766	0	
1-1954	R	750	750	0	
2	R	747	747	0	
3	R	747	747	0	
4	R	715	715	0	
1-1955	R	715	715	0	
2	R	715	715	0	
3	R	745	745	0	
4	R	745	745	0	

Waste Status Summary of 102-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	745	745	0	
2	R	745	745	0	
3	R	745	745	0	
4	R	745	745	0	
1-1957	R	740	740	0	Latest electrode reading
2	R	740	740	0	
3	R	739	739	0	Latest electrode reading
4	R	739	739	0	
1-1958	R	739	739	0	
2	R	739	739	0	
3	R	739	739	0	
4	R	739	739	0	
1-1959	R	736	736	0	Latest electrode reading
2	R	736	736	0	
3	R	736	736	0	
4	R	736	736	0	
1-1960	R	736	736	0	
	R	736	736	0	
3	R	736	736	0	
4	R	733	733	0	
1-1961					
2	R	733	733	0	6 months report
3					
4	R	733	733	0	6 months report

Waste Status Summary of 102-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	733	733	0]	6 months report
3					
4	R	733	733	0]	6 months report
1-1963					
2	R	733	733	0]	6 months report
3					
4	R	733	733	0]	6 months report
1-1964					
2	R	733	733	0]	6 months report
3					
4	R	733	733	0]	6 months report
1-1965					
2	R	750	750	0]	6 months report
3	R	750	745	5	
4	R	750	745	5	
1966	R	750	745	5	
2	R	750	745	5	
3	R	750	745	5	
4	R	750	745	5	
1-1967	R	750	745	5	
2	R	750	745	5	
3	R	750	745	5	
4	R	750	745	5	

Waste Status Summary of 102-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	750	745	5	
2	R	750	745	5	
3	R	750	745	5	
4	R	750	745	5	
1-1969	R	750	745	5	
2	R	750	745	5	
3	R	750	745	5	
4	R	750	746	4	
1-1970	R	750	746	4	
2	R	750	746	4	
3	R	750	746	4	
4	R	750	746	4	
1-1971	R	750	746	4	
2	R	750	746	4	
3 *	R	750	746	4	
4	R	750	746	4	
1-1972	R	750	746	4	
2	R	750	746	4	
3	R	750	746	4	
4	R	744	740	4	
1-1973	R	743	739	4	
2	R	743	739	4	
3	R	762	758	4	
4	EB	577	526	51	242-S feed tank (1) - (2)

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

(2) 926 M from 101-S, 54 M from 107-S, 428 M H_2O, 1,839 evaporated

* Dry Well #40-02-01 drilled
Dry Well #40-02-07 drilled
Dry Well #40-02-10 drilled

Waste Status Summary of 102-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	634	583	51	
2	EB	685	634	51	242-S feed tank (1) - (2)
3 *	EB	691	588	103	242-S feed tank (1) - (2), 1883 from 101-S, 81 from 101-SX, 598 from 102-SX, 860 from 107-S, 288 from 110-S, 1628 water, 4532 evaporated
4	EB	662	517	145	242-S feed tank (1) - (4)
1-1975	EB	604	459	145	242-S feed tank (1) - (4), 579 from 107-S, 636 from 106-SX, 634 from 103-SX, 902 Water, 2805 evaporated
2	EB	689	544	145	242-S feed tank (1), 1,464 from 106-SX, 1,181 water, 2,599 evaporated
3	EB	464	319	145	242-S feed tank (1), 1319 from 111-U, 1719 from 106-SX, 1103 water, 4016 evaporated
4	EB	554	354	200	242-S feed tank (1), 1245 water, 3750 evaporated
1-1976	EB	477	277	200	242-S feed tank (1), 2 to 107-S, 99 from 107-S, 774 from 106-SX 485 water, 4210 evaporated
2	EB	552	352	200	242-S bottoms and recycle (1)
3	DIL EVAP Feed	543	343	200	
4	EVAP	535	335	200	LO-Heat EVAP feed tank
1-1977	EVAP	211	3	208	Lo-heat EVAP feed tank
2	EVAP	230	22	208	Lo-heat EVAP feed tank
3	EVAP	233	25	208	Lo-heat EVAP feed tank
4	EVAP	246	38	208	Lo-heat EVAP feed tank

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

(2) 2748 from 101-S, 1249 from 107-S, 786 from 110-S, 1660 water, 5864 evaporated.

(4) 345 from 101-S, 274 from 107-S, 739 from 106-SX, 1260 water, 1992 evaporated

* Dry Wells #40-02-03, 40-02-05, 40-02-08 and 40-02-11 drilled.

Waste Status Summary of 102-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	Evap.	266	58	208	
2-	NCPLX	274	66	208	Future Solids Receiver
3-	NCPLX	282	74	208	New Photo 9/14/78
4-	NCPLX	483	275	208	
1-1979	PNF	618	410	208	
2-	PNF	378	170	208	New Photo 4/25/79
3-	PNF	480	272	208	
4-	DSSF	618	108	510	New Solids Level 10/15/79
1-1980	DSSF	609	99	510	
2-	DSSF	561	51	510	
3-	DSSF	555	0	555	Inactive- New Photo & Solids Level 8/21/80
4-	DSSF	555	0	555	

9 2 1 2 3 5 6 1 3 1 7

Waste Status Summary of 103-S Tank Capacity 750,000 Gallons

Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3 *	R	---	---	---	
4	R	---	---	---	
1-1953	R	---	---	---	
2	R	---	---	---	
3	R	0	0	0	
4	R	430	430	0	
1-1954	R	514	514	0	
2	R	549	549	0	Cascade received coating waste.
3	R	549	549	0	
4	R	536	536	0	
1-1955	R	537	537	0	
2	R	752	752	0	Receiving from 106-S.
3	R	752	752	0	
4	R	752	752	0	

* Dry Well 40-03-05 was drilled.

Waste Status Summary of 103-S Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	752	752	0	
2	R	752	752	0	
3	R	752	752	0	
4	R	752	752	0	
1-1957	R	752	752	0	Latest electrode reading
2	R	750	750	0	
3	R	750	750	0	
4	R	750	750	0	
1-1958	R	747	747	0	Latest electrode reading
2	R	750	750	0	Latest electrode reading
3	R	750	750	0	Latest electrode reading
4	R	750	750	0	
1-1959	R	750	750	0	
2	R	750	750	0	
3	R	750	750	0	
4	R	750	750	0	
1-1960	R	747	747	0	
	R	747	747	0	
3	R	747	747	0	
4	R	750	750	0	
1-1961					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report

Waste Status Summary of 103-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report
1-1963					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report
1-1964					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report
1-1965					
2	R	763	763	0]	6 months report
3	R	763	758	5	
4	R	763	758	5	
1-1966	R	763	758	5	
2	R	763	758	5	
3	R	763	758	5	
4	R	763	758	5	
1-1967	R	768	763	5	
2	R	765	760	5	
3	R	765	760	5	
4	R	765	760	5	

Waste Status Summary of 103-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	765	760	5	
2	R	765	760	5	
3	R	765	760	5	
4	R	764	759	5	
1-1969	R	764	759	5	
2	R	764	759	5	
3	R	765	760	5	
4	R	765	756	9	
1-1970	R	764	755	9	
2	R	764	755	9	
3	R	765	756	9	
4	R	764	755	9	
1-1971	R	764	755	9	
2	R	764	755	9	
3 *	R	764	755	9	
4	R	764	755	9	
1-1972	R	763	754	9	
2	R	763	754	9	
3	R	766	757	9	
4	R	767	758	9	
1-1973	R	767	758	9	
2	R	761	752	9	
3	R	773	764	9	
4	R	549	512	37	242-S bottoms and recycle (1) - (3)

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of S farm tanks.

(3) 41 M from 242-S, 29 M to 106-S, 103M to 107-S

* Dry Wells #40-03-01, 40-03-06, and 40-03-09 were drilled.

Waste Status Summary of 103-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	388	351	37	242-S bottoms and recycle (1)
2	EB	640	603	37	242-S bottoms and recycle (1)
3 *	EB	570	533	37	242-S bottoms and recycle (1)
4	EB	513	476	37	242-S bottoms and recycle (1)
1-1975	EB	409	372	37	242-S bottoms and recycle (1)
2	EB	642	605	37	242-S bottoms and recycle (1)
3	EB	403	366	37	242-S bottoms and recycle (1)
4	EB	565	528	37	242-S bottoms and recycle (1)
1-1976	EB	326	289	37	242-S bottoms and recycle (1)
2	EB	337	300	37	242-S bottoms and recycle (1)
3	CON. EVAP	194	157	37	
4	EVAP	439	402	37	Lo-heat Evap. dump tank
1-1977	EVAP	466	409	57	Lo-heat Evap. dump tank
2	EVAP	301	244	57	Lo-heat Evap. dump tank
3	EVAP	257	200	57	Lo-heat Evap. dump tank
4	EVAP	395	327	68	Lo-heat Evap. dump tank

9 2 1 2 5 5 6 1 3 2 2

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

* Dry Wells #40-03-08 and 40-03-11 were drilled.

Waste Status Summary of 103-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	Evap.	459	390	68	Active - Part Neut. Fd.
2-	NCPLX	238	118	120	Evap.-Dump Tank
3-	NCPLX	387	220	167	New Photo 9/20/78 Jet Pump Installed
4-	NCPLX	662	534	128	New Solids Level 11/21/78
1-1979	PNF	440	182	128	
2-	PNF	499	371	128	New Photo 4/26/79
3-	PNF	560	432	128	
4-	DSSF	708	555	153	New Solids Level 10/15/7
1-1980	PNF	675	522	153	
2-	PNF	484	331	153	
3-	PNF	647	494	153	
4-	DSSF	248	17	231	Inactive - New Solids Level 11/20/80

* New Well 40-03-03 in service 6/19/78

9 2 1 2 5 5 6 1 3 2 3

Waste Status Summary of 104-S Tank Capacity 750,000 Gallons

Yr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3	R	---	---	---	
4	R	---	---	---	
1-1953	R	741	741	0	Cascade receives - salt waste, lab. waste; coating waste and hot condensates.
2	R	758	758	0	
3	R	663	663	0	Cascade receives centrifuge cake waste.
4	R	524	524	0	
1-1954	R	458	458	0	Cascade received centrifuge cake waste on 1/13/54. Self-evaporating.
2	R	734	734	0	Self-evaporating.
3	R	667	667	0	
4	R	648	648	0	
1-1955	R	623	623	0	
2	R	725	725	0	
3	R	763	763	0	3m self-conc.
4	R	759	759	0	

Waste Status Summary of 104-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	752	752	0	
2	R	753	753	0	
3	R	753	753	0	
4	R	753	753	0	
1-1957	R	750	750	0	Latest electrode reading
2	R	732	732	0	Latest electrode reading
3	R	732	732	0	
4	R	730	730	0	Latest electrode reading
1-1958	R	725	725	0	Latest electrode reading
2	R	725	725	0	Latest electrode reading
3	R	725	725	0	latest electrode reading
4	R	725	725	0	
1-1959	R	725	725	0	
2	R	725	725	0	
3	R	721	721	0	
4	R	719	719	0	Latest electrode reading
1-1960	R	719	719	0	
2	R	719	719	0	
3	R	719	719	0	
4	R	716	716	0	
1-1961					
2	R	714	714	0]	6 months report
3					
4	R	714	714	0]	6 months report

Waste Status Summary of 104-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	714	714	0]	6 months report
3					
4	R	714	714	0]	6 months report
1-1963					
2	R	711	711	0]	6 months report
3					
4	R	711	711	0]	6 months report
1-1964					
2	R	711	711	0]	6 months report
3					
4	R	711	711	0]	6 months report
1-1965					
2	R	807	807	0]	6 months report, 96 M from 107-S
3	R	807	807	0	
4	R	807	807	0	
1966	R	805	805	0	Latest electrode reading
	R	802	802	0	Latest electrode reading
3	R	799	799	0	Latest electrode reading
4	R	796	796	0	
1-1967	R	796	796	0	
2	R	791	791	0	
3	R	790	790	0	
4	R	789	789	0	

Waste Status Summary of 104-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	787	787	0	
2	R	787	787	0	
3	R	787	787	0	
4	R	785	785	0	
1-1969	R	785	785	0	
2	R	784	784	- 0	
3	R	784	784	---	
4	R	784	543	241	
1-1970	R	783	542	241	
2	R	307	66	241	474 M to 103-TY
3 *	R	304	63	241	
4	R	310	69	241	
1-1971	R	310	69	241	
2	R	309	68	241	
3	R	309	68	241	
4	R	308	67	241	
1-1972	R	308	67	241	
	R	308	67	241	
3	R	308	67	241	
4	R	308	67	241	
1-1973	R	309	68	241	
2	R	307	66	241	
3	R	308	67	241	
4	R	307	66	241	Suspect leaker

* Dry Wells #'s 40-04-01, 40-04-05, 40-04-07, 40-04-08 were drilled.

Waste Status Summary of 104-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	R	307	66	241	Suspect leaker
2	R	307	66	241	Suspect leaker
3	R	309	68	241	Suspect leaker, 1 to 107-S
4	R	301	60	241	Suspect leaker
1-1975	---	299	0	299	Suspect leaker, 2 to 107-S
2	---	299	0	299	Removed from service, 3 to 107-S
3	---	299	0	299	Removed from service, 2 to 107-S
4	---	299	0	299	Removed from service
1-1976	---	299	0	299	Removed from service
2	---	299	0	299	Removed from service
3	---	299	0	299	Salt well pumped
4	---	299	0	299	Salt well pumped
1-1977	---	299	0	299	Salt well pumped
2	---	299	0	299	Salt well pumped
3	---	299	0	299	Inactive current
4	---	299	0	299	Inactive current

9 2 1 2 5 6 7 9

Waste Status Summary of 104-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	299	0	299	Inactive-Salt Well installed
2-	PNF	299	0	299	
3-	PNF	299	0	299	Jet pump installed
4-	PNF	299	0	299	
1-1979	PNF	299	0	299	
2-	PNF	299	0	299	Questionable Integrity Primary Stabilized New Photo 5/30/79
3-	PNF	299	0	299	
4-	PNF	299	0	299	
101980	PNF	299	0	299	
2-	PNF	299	0	299	
3-	PNF	299	0	299	
4-	NCPLX	299	0	299	

9 2 1 2 5 5 6 1 3 2 9

Waste Status Summary of 105-S Tank Capacity 750,000 Gallons

Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3 *	R	---	---	---	
4	R	---	---	---	
1-1953	R	---	---	---	
2	R	758	758	0	Cascade receives - salt waste, lab. waste, coating waste, and hot condensate.
3	R	723	723	0	Cascade receives centrifuge cake waste.
4	R	722	722	0	
1-1954	R	722	722	0	
2	R	734	734	0	
3	R	728	728	0	
4	R	728	728	0	
1-1955	R	728	728	0	
2	R	728	728	0	
3	R	723	723	0	
4	R	723	723	0	

* Dry Well #40-05-05 was drilled.

Waste Status Summary of 105-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	723	723	0	
2	R	723	723	0	
3	R	723	723	0	
4	R	723	723	0	
1-1957	R	754	754	0	Latest electrode reading
2	R	754	754	0	
3	R	752	752	0	Latest electrode reading
4	R	755	755	0	Latest electrode reading
1-1958	R	752	752	0	Latest electrode reading
2	R	752	752	0	
3	R	719	719	0	
4	R	719	719	0	
1-1959	R	719	719	0	
2	R	719	719	0	
3	R	719	719	0	
4	R	717	717	0	Latest electrode reading
1-1960	R	717	717	0	
2	R	717	717	0	
3	R	717	717	0	
4	R	717	717	0	
1-1961					
2	R	717	717	0]	6 months report
3					
4	R	717	717	0]	6 months report

Waste Status Summary of 105-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	717	717	0]	6 months report
3					
4	R	717	717	0]	6 months report
1-1963					
2	R	717	717	0]	6 months report
3					
4	R	717	717	0]	6 months report
1-1964					
2	R	717	717	0]	6 months report
3					
4	R	717	717	0]	6 months report
1-1965					
2	R	763	763	0	6 months report, 46 M from 107-S
3	R	763	763	0	
4	R	763	763	0	
1-1966	R	763	763	0	
	R	763	763	0	
3	R	763	763	0	
4	R	763	763	0	
1-1967	R	763	763	0	
2	R	763	763	0	
3	R	763	763	0	
4	R	763	763	0	

Waste Status Summary of 105-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	763	763	0	
2	R	763	763	0	
3	R	763	763	0	
4	R	763	763	0	
1-1969	R	763	763	0	
2	R	763	763	0	
3	R	763	763	---	
4	R	763	761	2	
1-1970	R	763	761	2	
2	R	763	761	2	
3	R	762	760	2	
4	R	762	760	2	
1-1971	R	762	760	2	
2	R	763	761	2	
3*	R	763	761	2	
4	R	763	761	2	
1-1972	R	762	760	2	
2	R	762	760	2	
3	R	762	760	2	
4	R	763	761	2	
1-1973	R	763	761	2	
2	R	753	751	2	
3	R	767	765	2	
4	EB	365	116	249	(1)

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S Farm tanks.

* Dry Wells #'s 40-05-03, 40-05-07 and 40-05-10 were drilled.

Waste Status Summary of 105-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	730	181	549	242-S bottoms and recycle(1) 97M to 101-S
2	---	549	0	549	242-S bottoms and recycle(1) 11 to 101-S, 12 to 110-S
3	---	549	0	549	242-S bottoms and recycle(1) 7 to 101-S
4	---	541	0	541	Salt filled(1)
1-1975	---	541	0	541	Salt filled(1), 5 to 101-S
2	---	541	0	541	Salt filled(1), 4 to 101-S
3	---	541	0	541	Salt filled(1)
4	---	541	0	541	Salt filled
1-1976	---	541	0	541	Salt filled
2	---	541	0	541	Removed from service, salt filled
3*	---	541	0	541	
4	---	541	0	541	Salt well pumped
1-1977	---	541	0	541	
2	---	541	0	541	
3	---	541	0	541	Inactive current
4	---	541	0	541	Inactive current

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

* Dry Well #40-05-08 was drilled.

9212556134

Waste Status Summary of 105-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	541	0	541	Inactive-Salt Well Installed
2-	PNF	541	0	541	
3-	PNF	541	0	541	Jet Pump Installed
4-	PNF	541	0	541	New Photo 5/12/78
1-1979	PNF	541	0	541	
2-	PNF	541	0	541	Primary Stabilized
3-	PNF	541	0	541	New Photo 5/24/79 New Solids Level 6/28/79
4-	PNF	541	0	541	
1-1980	PNF	488	0	488	
2-	PNF	488	0	488	
3-	PNF	488	0	488	
4-	NCPLX	488	0	488	

9 2 1 2 5 5 6 1 3 3 5

Waste Status Summary of 106-S Tank Capacity 750,000 Gallons

Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3 *	R	---	---	---	
4	R	---	---	---	
1-1953	R	---	---	---	
2	R	426	426	0	Cascade receives - salt waste, lab. waste, coating waste, and hot condensate.
3	R	729	729	0	Cascade receives centrifuge cake waste
4	R	725	725	0	
1954	R	725	725	0	
2	R	733	733	0	
3	R	737	737	0	
4	R	712	712	0	
1-1955	R	711	711	0	
2	R	541	541	0	Pumping to 103-S.
3	R	539	539	0	
4	R	754	754	0	Received from 107-S.

* Dry Well #40-06-05 was drilled.

Waste Status Summary of 106-S Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	754	754	0	
2	R	754	754	0	
3	R	754	754	0	
4	R	754	754	0	
1-1957	R	748	748	0	Latest electrode reading
2	R	748	748	0	
3	R	750	750	0	Latest electrode reading
4	R	750	750	0	
1-1958	R	750	750	0	
2	R	750	750	0	
3	R	747	747	0	Latest electrode reading
4	R	747	747	0	
1-1959	R	739	739	0	Latest electrode reading
2	R	747	747	0	
3	R	747	747	0	
4	R	747	747	0	
1-1960	R	744	744	0	
	R	744	744	0	
3	R	744	744	0	
4	R	747	747	0	
1-1961					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report

Waste Status Summary of 106-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	747	747	0]	6 months report
3					
4	R	747	747	0]	6 months report
1-1963					
2	R	747	747	0]	6 month report
3					
4	R	744	744	0]	6 months report, Latest electrode reading
1-1964					
2	R	744	744	0]	6 months report
3					
4	R	744	744	0]	6 months report
1-1965					
2	R	761	748	13]	6 months report
3	R	761	748	13	
4	R	761	748	13	
1966	R	761	748	13	
2	R	761	748	13	
3	R	761	748	13	
4	R	761	748	13	
1-1967	R	761	748	13	
2	R	761	748	13	
3	R	761	748	13	
4	R	761	748	13	

Waste Status Summary of 106-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	761	748	13	
2	R	761	748	13	
3	R	761	748	13	
4	R	758	745	13	
1-1969	R	759	746	13	
2	R	759	746	13	
3	R	759	746	13	
4	R	759	727	32	
1-1970	R	760	728	32	
2	R	760	728	32	
3	R	760	728	32	
4	R	760	728	32	
1-1971	R	760	728	32	
2	R	759	727	32	
3 *	R	759	727	32	
4	R	759	727	32	
1-1972	R	759	727	32	
2	R	759	727	32	
3	R	759	727	32	
4	R	759	727	32	
1-1973	R	759	727	32	
2	R	753	721	32	
3	R	766	734	32	
4	EB	657	273	384	(1) - (4)

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S Farm tanks.

(4) 29 to 103-S, 1 Water, 7 to 110-S, 298 to 107-U

* Dry Wells #40-06-02, 40-06-06 and 40-06-09 were drilled.

9 2 1 2 5 5 6 1 3 3 9

Waste Status Summary of 106-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	585	149	436	242-S bottoms and recycle(1)
2	EB	584	148	436	242-S bottoms and recycle(1)
3	EB	669	233	436	242-S bottoms and recycle(1)
4	EB	733	176	557	242-S bottoms and recycle(1)
1-1975	EB	684	77	607	242-S bottoms and recycle(1), 57 to 106-SX
2	EB	686	79	607	242-S bottoms and recycle(1)
3	---	673	0	673	Salt filled(1)
4	---	673	0	673	Salt filled(1)
1-1976	EB	692	19	673	Salt filled
2	EB	695	22	673	Removed from service, salt filled
3*	EVAP	700	27	673	Salt well installed
4	EVAP	703	30	673	
1-1977	EVAP	703	121	582	
2	EVAP	703	121	582	
3	Resid.	703	121	582	
4	Resid.	706	124	582	Part neut. feed

9 2 1 2 5 5 6

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

* Dry Well #40-06-08 was drilled.

Waste Status Summary of 106-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	706	124	582	R-Part Neut. Feed Active Restricted
2-	PNF	706	124	582	New Photo 5/12/78
3-	PNF	700	118	582	Jet Pump Installed
* 4-	PNF	700	118	582	
1-1979	PNF	703	121	582	
2-	PNF	612	30	582	
3-	PNF	612	0	612	
4-	PNF	612	0	612	
1-1980	PNF	612	0	612	
2-	PNF	612	0	612	
3-	PNF	612	0	612	
4-	NCPLX	612	0	612	

* New Well 40-06-04 in service 10/16/78

9 2 1 2 5 5 6 1 3 4 1

Waste Status Summary of 107-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	---	---	---	---	
3	R	---	---	---	
4	R	763	763	0	
1-1953	R	763	763	0	Cascade receives centrifuge cake waste as of 2/9/53, 340 gallons centrifuge cake waste sent to Cascade 107-109S
2	R	758	758	0	
3	R	751	751	0	
4	R	748	748	0	
1-1954	R	748	748	0	Cascade started receiving centrifuge cake waste after 1/26/54
2	R	754	754	0	
3	R	722	722	0	
4	R	758	758	0	Cascade received centrifuge waste
1-1955	R	758	758	0	Cascade received coating waste
2	R	758	758	0	
3	R	685	685	0	
4	R	741	741	0	Enough space for coats from 276-T

Waste Status Summary of 107-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	757	757	0	Centrifuge waste to 110-11 on 1/27/75
2	R	757	757	0	
3	R	757	757	0	
4	R	757	757	0	
1-1957	CW	750	750	0	Latest electrode reading
2	CW	750	750	0	
3	CW	596	596	0	S.S. received 55 M CW, 202 M pumped to 107-U
4	CW	689	689	0	93 M CW received
1-1958	CW	653	653	0	49 M CW received, 85 M to 107-U
2	CW	538	538	0	77 M CW received, 192 M to 107-U
3	CW	618	618	0	80 M CW received
4	CW	642	642	0	8 M CW received
1-1959	CW	686	686	0	Received 36 M CW
2	CW	528	528	0	Received 57 M CW, pumped 215 M to U Farm CW
3	CW	562	562	0	Received 34 M CW
	CW	607	607	0	Received 45 M CW
1-1960	CW	637	637	0	Received 22 M Redox CW
2	CW	564	564	0	Received 51 M Redox CW, Pumped 134M to 108-U
3	CW	598	598	0	Received 34 M Redox CW
4	CW	536	536	0	Received 30 M Redox CW, Transferred 104 M to 108-U
1-1961					Received 109 M Redox CW
2	CW	645	645	0]	6 months report
3					201 M to 108-U, received 116 M CW
4	CW	560	560	0]	6 months report

Waste Status Summary of 107-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	CW	659	659	0]	6 months report, received 99 M CW
3					
4	CW	555	555	0]	6 months report, 213 M to 108-U, received 109 M
1-1963					
2	CW	527	527	0]	6 months report, received 142 M, 170 M to 108-U
3					
4	CW	615	615	0]	6 months report, received 88 M CW
1-1964					
2	CW	590	590	0]	6 months report, received 165 M CW, 190M to 108-U
3	CW	628	628	0]	6 months report, received 196 M CW, 158 M to other farms
1-1965				]	6 months report
	CW	508	314	194	Received 164 M, 291 M to other tanks
	CW	587	393	194	79 M from 202-S
4	CW	669	475	194	received 82 M CW
1-1966	CW	565	371	194	received 127 M CW, 231M to T & TX
2	CW	568	374	194	received 157 M CW, 187 M to 115-TX
3	CW	613	419	194	received 45 M CW
4	CW	642	448	194	received 174 M, 145 M to 115-TX
1-1967	CW	656	562	194	received 14 M
2	CW	656	562	194	
3	CW	656	562	194	
4	CW	656	562	194	

Waste Status Summary of 107-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	CW	654	460	194	
2	CW	654	460	194	
3	CW	305	111	194	350 M to 107-U
4	CW-EB	325	111-20	194	20 M from Redox evaporators
1-1969	CW-EB	415	111-110	194	89 M from Redox evaporators
2	CW-EB	476	111-171	194	61 M from Redox evaporators
3	CW-EB	577	111-272	194	101 M from Redox evaporators
4	CW-EB	451	20-146	285	157 M from Redox evaporators, 283 M to 107-U
1-1970	CW-EB	477	20-172	285	28 M from Redox
2	CW-EB	532	20-219	293	54 M from Redox
3	EB	343	50	293	56 M from Redox, 246 M to 103-TY
4	EB	449	156	293	107 M from Redox
1-1971	EB	536	243	293	86 M from Redox
2 *	EB	589	296	293	54 M from Redox
3	R	609	316	293	19 M from Redox
4	R	622	329	293	12 M from Redox
1-1972	R	655	362	293	35 M from Redox
2	EB	756	463	293	100 M from Redox
3	EB	756	463	293	
4	EB	757	464	293	
1-1973	EB	757	464	293	
2	EB	749	456	293	
3	EB	761	468	293	
4	R-EB	686	69-324	293	103 from 103-S, 4 Water, 54 to 102-S 131 to 107-U

* Dry Wells #'s 40-07-01, 40-07-06 and 40-07-10 were drilled.

Waste Status Summary of 107-S Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	IX	731	438	293	310 from 110-S, 12 water, 123 to 101-S, 158 to 102-S
2 *	DW-BL-IX	492	11-32-106	343	358 from 104-C, 277 from 106-BX, 138 from 110-S, 752 from 111-SX (4)
3	BNW-N-LW-PL-B-CW	468	25-44-15-10-16-15	282	(3)
4	BL-IX-PL-BNW-N-LW-CW	519	10-116-8-4-13-14-11	343	393 from 103-BX, 7 from 104-S, 72 from 107-U, 1[illegible] from 302-S catch tank, 92 from 104-BX (5)
1-1975	BNW-N-EB-DW	475	45-6-53-28	343	2 from 104-S, 278 from 104-BX, 3 water, 260 from 107-U, 53 from 110-S
2	BNW-N-EB-DW	477	45-6-55-28	343	3 from 107-S
3	BNW-N-EB-DW	480	45-6-58-28	343	2 from 104-S
4	TL	491	148	343	
1-1976	TL	656	313	343	102 to 109-B
2	EB	703	360	343	49 from 111-S
3	CON-EVAP	700	357	343	Interstitial Liquor Storage
	EVAP	431	88	343	
1-1977	EVAP	455	112	343	
2	EVAP	585	242	343	
3	Resid	717	374	343	
4	Resid	409	66	343	Residual Liquor Storage

(3) 297 from 103-C, 613 from 110-S, 85 to 101-S, 860 to 102-S, 12 from 101-S, 1 from 104-S

(4) 515 to 101-S, 1249 to 102-S

(5) 7 from 103-C, 257 to 101-S, 274 to 102-S

* Dry Wells #'s 40-07-04, 40-07-08, 40-07-11 were drilled.

9 2 1 2 5 6 1 3 4 6

Waste Status Summary of 107-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	422	79	343	Active
2-	DSSF	719	376	343	Crossite SHP TNK
3-	PNF	497	154	343	
4-	PNF	711	368	343	New Solids Level 11/28/78 - Taken with no change
1-1979	PNF	425	82	343	
2-	PNF	692	349	343	New Photo 5/30/79
3-	PNF	684	341	343	
4-	DSSF	692	349	343	
1-1980	DSSF	450	107	343	
2-	CC	476	133	343	
3-	DSSF	346	6	340	Inactive - New Solids level 9/25/80
4-	DSSF	346	6	340	

9 2 1 2 5 5 6 1 3 4 7

Waste Status Summary of 108-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	---	---	---	---	
3	R	---	---	---	
4	R	760	760	0	Filled 12/24/52; cascaded to 109-S active tank, Redox wastes
1-1953	R	760	760	0	
2	R	758	758	0	Cascade receives centrifuge cake waste
3	R	751	751	0	
4	R	747	747	0	
1-1954	R	747	747	0	
2	R	743	743	0	
3	R	740	740	0	
4	R	758	758	0	
1-1955	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	

Waste Status Summary of 108-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1957	R	765	765	0	Latest electrode reading
2	R	763	763	0	Latest electrode reading
3	R	763	763	0	
4	R	763	763	0	
1-1958	R	761	761	0	Latest electrode reading
2	R	761	761	0	
3	R	761	761	0	
4	R	761	761	0	
1-1959	R	761	761	0	
2	R	761	761	0	
3	R	761	761	0	
4	R	761	761	0	
1-1960	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1961					
2	R	755	755	0]	6 months report
3	R	755	755	0]	6 months report

Waste Status Summary of 108-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1963					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1964					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1965					
2	R	758	754	4]	6 months report
3	R	758	754	4	
4	R	758	754	4	
1966	R	758	754	4	
2	R	758	754	4	
3	R	758	754	4	
4	R	758	754	4	
1-1967	R	758	754	4	
2	R	758	754	4	
3	R	758	754	4	
4	R	758	754	4	

Waste Status Summary of 108-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	758	754	4	
2	R	757	753	4	
3	R	757	753	4	
4	R	757	753	4	
1-1969	R	757	753	4	
2	R	757	753	4	
3	R	757	753	4	
4	R	757	752	5	
1-1970	R	756	751	5	
2	R	756	751	5	
3	R	756	751	5	
4	R	756	751	5	
1-1971	R	756	751	5	
2 *	R	756	751	5	
3	R	756	751	5	
4	R	756	751	5	
1-1972	R	756	751	5	
	R	756	751	5	
3	R	756	751	5	
4	R	758	753	5	
1-1973	R	757	752	5	
2	R	748	743	5	
3	R	761	756	5	
4					

* Dry Wells #'s 40-08-06 and 40-08-09 were drilled.

Waste Status Summary of 108-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	704	331	373	242-S bottoms and recycle(1)
2	EB	718	133	585	242-S bottoms and recycle(1)
3	EB	706	4	702	242-S bottoms and recycle(1)
4	EB	719	13	706	Salt filled (1)
1-1975	EB	717	11	706	Salt filled(1), 73 to 101-S, 579 to 102-S
2	EB	722	16	706	Salt filled (1)
3	EB	728	22	706	
4	TL	725	19	706	
1-1976	TL	728	22	706	
2	EB	728	22	706	
3 *	EVAP	730	24	706	
4	EVAP	730	24	706	
1-1977	EVAP	733	63	670	Salt filled, Evap. feed
2	EVAP	733	63	670	Salt filled, Evap. feed
3	Resid	733	63	670	Salt filled, Evap. bottoms
4	Resid	733	63	670	Part neut. feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

* Dry Wells #'s 40-08-01 and 40-08-08 were drilled.

9 2 1 2 5 5 6 4 3 5 2

Waste Status Summary of 108-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	733	63	670	R-Part Neut. Feed
2-	PNF	733	63	670	
3-	PNF	719	49	670	Jet Pumping Supernate
* 4-	PNF	692	22	670	
1-1979	PNF	692	22	670	Inactive
2-	PNF	670	0	670	Primary Stabilized New Photo 4-20-79
3-	PNF	670	0	670	New Photo 7/26/79
4-	PNF	670	58	612	New Solids Level 6/28/79
1-1980	PNF	612	0	612	
2-	PNF	612	0	612	
3-	PNF	612	0	612	
4-	NCPLX	612	0	612	

* New Well 40-08-12 in service 8/16/78

9 2 1 2 5 6 1 3 3

Waste Status Summary of 109-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	---	---	---	---	
3 *	R	---	---	---	
4	R	103	103		
1-1953	R	582	582		340 gallons of centrifuge cake waste was sent to Cascade 107 & 109S
2	R	585	585	0	Cascade receives centrifuge cake waste
3	R	575	575	0	
	R	579	579	0	
1-1954	R	579	579	0	
2	R	576	576	0	
3	R	576	576	0	
4	R	576	576	0	
1-1955	R	704	704	0	
2	R	747	747	0	
3	R	747	747	0	
4	R	747	747	0	

* Dry Well #40-09-05 was drilled.

Waste Status Summary of 109-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	747	747	0	
2	R	747	747	0	
3	R	747	747	0	
4	R	747	747	0	
1-1957	R	764	764	0	Latest electrode reading
2	R	764	764	0	
3	R	763	763	0	Latest electrode reading
4	R	763	763	0	
1-1958	R	763	763	0	
2	R	763	763	0	
3	R	763	763	0	
4	R	763	763	0	
1-1959	R	763	763	0	
2	R	763	763	0	
3	R	763	763	0	
4	R	763	763	0	
1-1960	R	761	761	0	
	R	761	761	0	
3	R	761	761	0	
4	R	763	763	0	
1-1961					
2	R	761	761	0]	6 months report
3					
4	R	761	761	0]	6 months report

Waste Status Summary of 109-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	761	761	0]	6 months report
3					
4	R	761	761	0]	6 months report
1-1963					
2	R	761	761	0]	6 months report
3					
4	R	761	761	0]	6 months report
1-1964					
2	R	761	761	0]	6 months report
3					
4	R	761	761	0]	6 months report
1-1965					
2	R	766	759	7]	6 months report
3	R	766	759	7	
4	R	766	759	7	
1966	R	766	759	7	
2	R	766	759	7	
3	R	766	759	7	
4	R	766	759	7	
1-1967	R	766	759	7	
2	R	766	759	7	
3	R	766	759	7	
4	R	766	759	7	

Waste Status Summary of 109-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	766	759	7	
2	R	766	759	7	
3	R	766	759	7	
4	R	765	758	7	
1-1969	R	765	758	7	
2	R	765	758	7	
3	R	765	758	7	
4	R	765	752	13	
1-1970	R	765	752	13	
2	R	765	752	13	
3	R	765	752	13	
4	R	765	752	13	
1-1971	R	765	752	13	
2	R	765	752	13	
3 *	R	765	752	13	
4	R	765	752	13	
1-1972	R	765	752	13	
	R	765	752	13	
3	R	765	752	13	
4	R	765	752	13	
1-1973	R	765	752	13	
2	R	758	745	13	
3	R	770	757	13	
4	R	771	758	13	

* Dry Wells #'s 40-09-02, 40-09-06 and 40-09-09 were drilled.

Waste Status Summary of 109-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	361	98	263	242-S bottoms and recycle (1)
2	EB	672	184	488	242-S bottoms and recycle (1)
3	EB	700	47	653	242-S bottoms and recycle (1)
4	EB	717	64	653	Salt filled (1)
1-1975	EB	717	64	653	Salt filled (1)
2	EB	719	66	653	Salt filled (1)
3	EB	722	69	653	Salt filled (1)
4	EB	722	69	653	Salt filled (1)
1-1976	TL	725	72	653	Salt filled (1)
2 *	EB	725	72	653	Salt filled (1)
3	EVAP	730	77	653	Salt filled (1)
4	EVAP	728	75	653	Salt filled (1)
1-1977	EVAP	730	162	568	Salt filled (1)
2	EVAP	730	162	568	Salt filled (1)
3	Resid	730	162	568	Evap. bottoms (1)
4	Resid	730	162	568	Part neut. feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of S farm tanks.

* Dry Wells #'s 40-09-01 and 40-09-08 were drilled.

9212156

Waste Status Summary of 109-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	733	165	568	R-Part Neut. Feed Active Restricted
2-	PNF	733	165	568	
3-	PNF	695	127	568	Jet pumping supernate
4-	PNF	689	121	568	
1-1979	PNF	651	83	568	
2-	PNF	568	0	568	Photo taken 5/17/79
3-	PNF	568	0	568	
4-	PNF	568	0	568	
1-1980	PNF	568	0	568	
2-	PNF	568	0	568	
3-	PNF	568	0	568	
4-	NCPLX	568	0	568	

9 2 1 2 1 5 6 1 3 9

Waste Status Summary of 110-S Tank Capacity 750,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	R	681	681	0	
3	R	774	774	0	
4	R	774	774	0	
1-1953	R	774	774	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1954	R	758	758	0	Cascade received centrifuge cake waste from 1/13/54 to 1/26/54. Received catch tank after 1/26/54.
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1955	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	

Waste Status Summary of 110-S Tank Capacity .750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1957	R	781	781	0	Latest electrode reading
2	R	781	781	0	
3	R	780	780	0	Latest electrode reading
4	R	780	780		
1-1958	R	780	780	0	
2	R	780	780	0	
3	R	777	777	0	
4	R	777	777	0	
1-1959	R	777	777	0	
2	R	777	777	0	
3	R	777	777	0	
4	R	777	777	0	
1-1960	R	774	774	0	
2	R	774	774	0	
3	R	774	774	0	
4	R	777	777	0	
1-1961					
2	R	774	774	0	6 months report
3					
4	R	774	774	0	6 months report

Waste Status Summary of 110-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	774	774	0]	6 months report
3					
4	R	774	774	0]	6 months report
1-1963					
2	R	774	774	0]	6 months report
3					
4	R	772	772	0]	6 months report, latest electrode reading
1-1964					
2	R	772	772	0]	6 months report
3					
4	R	772	772	0]	6 months report
1-1965					
2	R	772	666	106]	6 months report
3	R	772	666	106	
4	R	772	666	106	
1-1966	R	772	666	106	
	R	772	666	106	
3	R	772	666	106	
4	R	772	666	106	
1-1967	R	772	666	106	
2	R	772	666	106	
3	R	772	666	106	
4	R	772	666	106	

Waste Status Summary of 110-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	772	666	106	
2	R	776	670	106	
3	R	776	670	106	
4	R	776	670	106	
1-1969	R	776	670	106	
2	R	776	670	106	
3	R	776	670	106	
4	R	776	663	113	
1-1970	R	775	662	113	
2	R	775	662	113	
3 *	R	776	663	113	
4	R	775	662	113	
1-1971	R	775	662	113	
2	R	774	661	113	
3 **	R	775	662	113	
4	R	775	662	113	
1972	R	774	661	113	
	R	774	661	113	
3	R	773	660	113	
4	R	774	661	113	
1-1973	R	773	660	113	
2	R	766	653	113	
3	R	778	665	113	
4	R	786	673	113	7 from 106-S

* Dry Well #40-10-01 was drilled.

** Dry Wells #'s 40-10-03, 40-10-06 and 40-10-09 were drilled.

Waste Status Summary of 110-S Tank Capacity 750,000 Gallons

Qrtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	BL-OWW-RIX	280	35-59-55	131	385 from 107-U, 272 from 103-U, 424 from 105-U, 424 from 106-U, 316 from 107-U (3)
2	DW-CW-BL IX-224	686	118-13-44-107-273	131	475 from 102-T, 354 from 103-T, 425 from 105-T, 366 from 108-T (5)
3	EB	580	449	131	242S bottoms and recycle (1) (4)
4	EB	695	440	255	242-S bottoms and recycle (1)
1-1975	EB	678	264	414	242-S bottoms and recycle (1)
2	EB	739	179	560	242-S bottoms and recycle (1)
3	---	755	0	755	Salt filled (1)
4	---	689	0	689	Salt filled
1-1976	---	689	0	689	Salt filled
2	---	689	0	689	Removed from service, salt filled
3 *	---	689	0	689	Inactive
4	---	623	0	623	Inactive
1-1977	---	623	148	475	Inactive
2	EVAP	700	225	475	Inactive
3	Resid	700	225	475	Inactive
4	Resid	700	225	475	Part neut. feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S-Farm tanks.

(3) 209 from 109-U, 363 from 104-BX, 381 from 105-BX, 678 from 104-TY, 828 to 101-S, 2822 to 102-S, 310 t 107-S.

(4) 516 from 110-SX, 230 from 101-T, 136 from 112-T, 639 from 107-U, 168 water, 1215 to 101-S, 288 to 102-S, 613 to 107-S.

(5) 396 from 109-T, 59 from 110-T, 28 from 111-T, 273 from 112-T, 529 from 104-TX, 605 from 107-U, 12 from 105-S, 2192 to 101-S, 786 to 102-S, 138 to 110-S.

* Dry well numbers 40-10-05 and 40-10-08 were drilled.

9 2 1 2 5 5 6 1 3 6 4

Waste Status Summary of 110-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	700	225	475	R Part Neut. Feed
2-	PNF	700	225	475	
* 3-	PNF	692	217	475	
4-	PNF	692	217	475	
1-1979	PNF	692	0	692	Inactive-Prim. Stabilize New Solids Level 1/31/79 - Solid Level Adjusted
2-	PNF	692	0	692	
3-	PNF	692	0	692	
4-	PNF	692	0	692	
1-1980	PNF	692	0	692	
2-	PNF	692	0	692	
3-	PNF	692	0	692	
4-	NCPLX	692	0	692	

* New well 40-10-13 in service 8/21/78

9 2 1 2 5 5 6 1 3 5 5

Waste Status Summary of 111-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	---	---	---	---	
3	R	755	755	0	Tank cascaded to 112-S 7/25/52
4	R	755	755	0	
1-1953	R	755	755	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
-1954	R	758	758	0	
	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1955	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	

Waste Status Summary of 111-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	758	758	0	
2	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1957	R	761	761	0	Latest electrode reading
2	R	761	761	0	
3	R	761	761	0	
4	R	761	761	0	
1-1958	R	761	761	0	
2	R	761	761	0	
3	R	761	761	0	
4	R	761	761	0	
1-1959	R	761	761	0	
2	R	761	761	0	
3	R	761	761	0	
4	R	761	761	0	
1960	R	758	758	0	
	R	758	758	0	
3	R	758	758	0	
4	R	758	758	0	
1-1961					
2	R	755	755	0	6 months report
3					
4	R	755	755	0	6 months report

Waste Status Summary of 111-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1963					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1964					
2	R	755	755	0]	6 months report
3					
4	R	755	755	0]	6 months report
1-1965					
2	R	761	617	144]	6 months report, 8 M from 107-S
3	R	761	617	144	
4	R	761	617	144	
1-1966	R	761	617	144	
[illegible]	R	761	617	144	
3	R	761	617	144	
4	R	761	617	144	
1-1967	R	761	617	144	
2	R	759	615	144	
3	R	759	615	144	
4	R	759	615	144	

Waste Status Summary of 111-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	759	615	144	
2	R	759	615	144	
3	R	759	615	144	
4	R	759	615	144	
1-1969	R	758	614	144	
2	R	758	614	144	
3	R	758	614	144	
4	R	758	619	139	
1-1970	R	758	619	139	
2	R	758	619	139	
3	R	758	619	139	
4	R	758	619	139	
1-1971	R	758	619	139	
2	R	758	619	139	
3 *	R	758	619	139	
4	R	758	619	139	
1-1972	R	758	619	139	
2	R	758	619	139	
3	R	758	619	139	
4	R	758	619	139	
1-1973	R	759	620	139	
2	R	749	610	139	
3	R	764	625	139	
4	R	766	627	139	

* Dry Wells #'s 40-11-01, 40-11-07 and 40-11-09 were drilled.

Waste Status Summary of 111-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	311	172	139	456 to 102-S
2	EB	689	355	334	242-S bottoms and recycle (1), 2 to 101-S
3	EB	730	228	502	242-S bottoms and recycle (1)
4	EB	692	129	563	242-S bottoms and recycle (1)
1-1975	EB	739	143	596	242-S bottoms and recycle (1)
2	EB	739	143	596	242-S bottoms and recycle (1)
3	---	750	0	750	Salt filled (1)
4	---	750	0	750	Salt filled
1-1976	---	750	0	750	Salt filled
2	---	750	0	750	Removed from service, salt filled
3 *	---	750	0	750	Inactive, salt well pumped
4	---	623	0	623	Salt well pumped
1-1977	---	623	0	623	Salt well, pump phase 2 pumping
2	---	623	0	623	Salt well, pump phase 2 pumping
3	EVAP	623	0	623	Salt well, pump phase 2 pumping
4	EVAP	623	0	623	Salt well, pump phase 2 pumping

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S farm tanks.

* Dry Wells #'s 40-11-05 and 40-11-08 were drilled.

9 2 1 2 5 5 5 7 3 0

Waste Status Summary of 111-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	623	0	623	Inactive-Primary stabilized
2-	PNF	623	0	623	New photo 3/27/78
3-	PNF	623	0	623	Proto Jet Pump
4-	PNF	623	0	623	
1-1979	PNF	623	0	623	
2-	PNF	623	0	623	
3-	PNF	623	0	623	
4-	PNF	623	0	623	
1-1980	PNF	623	0	623	
2-	PNF	623	0	623	
3-	PNF	623	0	623	
4-	NCPLX	623	0	623	New Photo 4/11/80

9212561371

Waste Status Summary of 112-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952	---	---	---	---	Completed in 1951
2	---	---	---	---	
3	R	755	755	0	
4	R	442	442	0	
1-1953	R	442	442	0	
2	R	442	442	0	
3	R	498	498	0	
4	R	640	640	0	
1954	R	656	656	0	
2	R	688	688	0	
3	R	686	686	0	
4	R	675	675	0	
1-1955	R	695	695	0	
2	R	695	695	0	
3	R	695	695	0	
4	R	747	747	0	

Waste Status Summary of 112-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	747	747	0	
2	R	747	747	0	
3	R	747	747	0	
4	R	747	747	0	
1-1957	R	780	780	0	Latest electrode reading
2	R	780	780	0	
3	R	780	780	0	
4	R	780	780	0	
1-1958	R	780	780	0	
2	R	780	780	0	
3	R	780	780	0	
4	R	780	780	0	
1-1959	R	780	780	0	
2	R	780	780	0	
3	R	780	780	0	
4	R	780	780	0	
1-1960	R	777	777	0	
2	R	777	777	0	
3	R	777	777	0	
4	R	780	780	0	
1-1961					
2	R	777	777	0	6 months report
3					
4	R	777	777	0	6 months report

Waste Status Summary of 112-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	777	777	0	6 months report
3					
4	R	777	777	0	6 months report
1-1963					
2	R	777	777	0	6 months report
3					
4	R	777	777	0	6 months report
1-1964					
2	R	777	777	0	6 months report
3					
4	R	777	777	0	6 months report
1-1965					
2	R	785	781	4	6 months report, 8 M from 107-S
3	R	785	781	4	
4	R	785	781	4	
1-1966	R	785	781	4	
2	R	785	781	4	
3	R	785	781	4	
4	R	785	781	4	
1-1967	R	785	781	4	
2	R	788	784	4	
3	R	788	784	4	
4	R	788	784	4	

Waste Status Summary of 112-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	788	784	4	
2	R	788	784	4	
3	R	788	784	4	
4	R	787	783	4	
1-1969	R	787	783	4	
2	R	787	783	4	
3	R	787	783	4	
4	R	787	781	6	
1-1970	R	787	781	6	
2	R	787	781	6	
3	R	787	781	6	
4	R	787	781	6	
1-1971	R	787	781	6	
2	R	787	781	6	
3*	R	787	781	6	
4	R	788	782	6	
1-1972	R	787	781	6	
2	R	787	781	6	
3	R	787	781	6	
4	R	787	781	6	
1-1973	R	787	781	6	
2	R	780	774	6	
3	R	792	786	6	
4	R	792	786	6	

* Dry Wells #'s 40-12-02, 40-12-06, and 40-12-09 were drilled.

Waste Status Summary of 112-S Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB	473	106	367	242-S bottoms and recycle (1)
2	EB	713	115	598	242-S bottoms and recycle (1)
3	EB	732	46	686	242-S bottoms and recycle (1)
4	EB	730	57	673	242-S bottoms and recycle (1)
1-1975	EB	736	22	714	Salt filled (1)
2	EB	736	22	714	Salt filled (1)
3	EB	739	25	714	Salt filled (1)
4	---	706	0	706	
1-1976	---	706	0	706	
2	---	706	0	706	Removed from service, salt filled
3 *	---	706	0	706	Inactive
4	---	706	0	706	Contains salt
1-1977	---	706	33	673	Contains salt
2	EVAP	717	44	673	Contains salt
3	Resid	719	46	673	Inactive, part neut. feed
4	Resid	719	46	673	Inactive, part neut. feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty of the liquid-to-solid ratio of the S farm tanks.

* Dry Well #40-12-07 was drilled.

Waste Status Summary of 112-S Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	719	46	673	Inactive-Part Neut. Fd.
2-	PNF	719	46	673	
* 3-	PNF	675	2	673	Jet Pumping Supernate
4-	PNF	678	5	673	
1-1979	PNF	675	2	673	
2-	PNF	673	0	673	New photo 5/24/79 Liquid Level Adjusted
3-	PNF	673	0	673	
4-	PNF	673	0	673	
1-1980	PNF	673	0	673	
2-	PNF	672	0	672	New Photo 6/28/80
3-	PNF	672	0	672	
4-	NCPLX	672	0	672	

* New Well 40-12-04 in service 8/21/78

9212561377

Waste Status Summary of 101-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Completed constructing 1954.
[illegible]	R	303	303	0	Received combined centrifuge cake waste and concentrated salt waste.
3	R	1000	1000	0	
4	R	1000	1000	0	
1-1955	R	Est 888	888	0	
2	R	653	653	0	
3	R	892	892	0	Receiving salt waste. Self evaporating.
4	R	785	785	0	

9212556137 8

Waste Status Summary of 101-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	696	696	0	
2	R	634	634	0	
3	R	594	594	0	40m self-concentrating.
4	R	571	571	0	25m self-concentrating.
1-1957	R	544	544	0	27m self-concentrating volume estimated.
2	R	516	516	0	27m self-concentrating.
3*	R	549	549	0	8m self-concentrating 50m water added.
4	R	521	521	0	18m water boiled off.
1-1958	R	510	510	0	14m water boiled off.
2	R	494	494	0	14m - self-concentrating.
3	R	494	494	0	6m - self-concentrating.
4	R	488	488	0	6m - self-concentrating
1-1959	R	480	480	0	8m - self-concentrating.
2	R	484	484	0	Latest electrode reading.
3	R	475	475	0	9m self-concentrating.
4	R	475	475	0	
1-1960	R	459	459	0	New electrode being installed.
	R	450	450	0	New electrode.
3	R	447	447	0	Latest electrode reading.
4	R	445	445	0	Boiled off 2m.
1-1961					6 months report.
2	R	439	439	0	
3					6 months report.
4	R	442	442	0	

* Leak detection dry well 41-01-07 drilled.

9212556137 9

Waste Status Summary of 101-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	442	442	0	6 months report.
3					
4	R	442	442	0	6 months report.
1-1963					
2	R	442	442	0	6 months report.
3					
4	R	447	447	0	6 months report.
1-1964					
2	R	447	447	0	6 months report.
3					
4	R	465	465	0	6 months report.
1-1965					
2	R	464	17	447	6 months report.
3	R	464	17	447	
4	R	466	19	447	
1-1966	R	466	19	447	
2	R	466	19	447	
3	R	466	19	447	
4	R	466	19	447	
1-1967	R	466	19	447	
2	R	466	19	447	
3	R	466	19	447	
4	R	466	19	447	

9 2 1 2 5 5 6 1 3 8 0

Waste Status Summary of 101-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	466	19	447	(1) NB
2	R	465	18	447	(1) NB
3	R	467	20	447	
4	R	467	20	447	
1-1969	R	469	22	447	
2	R	469	22	447	
3	R	470	6	464	
4	R	470	5	465	
1-1970	R	469	4	465	
2	R	468	3	465	
3	R	467	1	466	
4	R	467	1	466	
1-1971	R	466	0	466	
2	R	466	0	466	
3 *	R	466	0	466	
4	EB-RIX	891	19-406	466	424 M from 101-BX
-1972	EB-RIX	891	19-406	466	
2	EB-RIX	915	20-429	466	24S-151 catch tank
3	EB-RIX	915	20-429	466	
4 **	EB-RIX	915	20-429	466	
1-1973	EB-RIX	903	19-418	466	
2	EB-RIX	901	19-416	466	
3	EB-RIX	916	20-430	466	
4	EB-RIX	913	20-427	466	

(1) NB - Tank not equipped for boiling waste.

* Leak detection dry wells installed 41-01-06 and 41-01-08.
** Leak detection dry well installed 41-01-01.

9 2 1 2 5 5 6 1 3 8 1

Waste Status Summary of 101-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	926	21-439	466	14 from 302A catch tank.
2 *	EB-RIX	923	21-436	466	
3	EB	922	456	466	242-S bottoms and recylce (1) 339 to 101-S.
4	EB	923	457	466	242-S Bottoms and recycle (1).
1-1975	EB	926	460	466	242-S Bottoms and recycle (1).
2	EB	934	468	466	242-S Bottoms and recycle (1).
3	EB	934	468	466	242-S Bottoms and recycle (1).
4	TL	931	465	466	242-S Bottoms and recycle (1).
1-1976	TL	931	465	466	242-S Bottoms and recycle (1).
2	TL	931	465	466	Terminal liquor.
3	Resid.	931	465	466	Residual liquor.
4	Resid.	931	465	466	Residual liquor.
1-1977	Resid.	934	468	466	(128 sludge & 338 salt cake)
2	Resid.	931	465	466	(128 sludge & 338 salt cake)
3	Resid.	931	465	466	(128 sludge & 338 salt cake)
4	Resid.	934	468	466	(128 sludge & 338 salt cake)

9212556138 2

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the SX Tank Farm.

* Leak detection dry wells installed: 41-01-04, 41-01-10, 41-01-11.

Waste Status Summary of 101-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	937	534	403	Active Photo taken 2/1/78
2-	PNF	934	531	403	Solids Level Taken 5/21/78
3-	PNF	937	534	403	Caustic for HLSW
4-	PNF	937	534	403	
1-1979	PNF	937	534	403	
2-	CPLX	708	305	403	Photo taken 4/27/79
3-	CPLX	887	484	403	Photo taken 7/25/79
4-	CPLX	546	143	403	
1-1980	CPLX	744	341	403	Cross-site transfer
2-	CPLX	803	400	403	
3-	CPLX	593	146	447	New Solids Level 8/15/80
4-	NCPLX	471	16	455	Adj. salt cake - Inactive

9 2 1 2 5 5 6 1 3 8 3

Waste Status Summary of 102-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Completed constructing 1954.
*	R	0	0	0	
3	R	303	303	0	
4	R	1000	1000	0	
1-1955	R	1000	1000	0	
2	R	980	980	0	
3	R	983	983	0	Receiving salt waste.
4	R	983	983	0	

* Leak detection dry well 41-01-07 drilled.

9 2 1 2 5 5 6 1 3 8 4

Waste Status Summary of 102-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	983	983	0	
2	R	983	983	0	
3	R	980	980	0	
4	R	978	978	0	
1-1957	R	978	978	0	
2	R	978	978	0	
3	R	978	978	26	
4	R	978	978	26	
1-1958	R	986	986	26	
2	R	986	986	---	
3	R	989	989	26	
4	R	552	552	26	432m to 102 and 103-U, 16m decrease - air sparging.
1-1959	R	549	549	0	Latest electrode reading.
2	R	546	546	0	1m self-concentrating latest electrode reading.
3	R	273	273	0	272m to 105-TX, latest electrode reading.
4	R	271	271	0	Latest electrode reading.
1-1960	R	267	267	0	Latest electrode reading.
2	R	266	266	0	
3	R	265	265	0	
4	R	261	261	0	
1-1961					Received 351m from 103-SX
2	R	612	612	0	6 months report.
3					Received 122m from 103-SX
4	R	645	645	0	90m to 115-SX 6 months report.

Waste Status Summary of 102-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]532m out, 738m from 103-SX.
2	R	850	850	0	]6 months report.
3					]6 months report.
4	R	755	755	0	]984m to TX, 578m from 107-SX.
1-1963					]6 months report.
2	R	791	791	0	]Received 46m condensate.
3					]6 months report.
4	R	140	140	0	]651m to 101-TX.
1-1964					]6 months report.
2	R	792	792	0	]
3					]6 months report.
4	R	795	795	0	]
1-1965					]6 months report.
2	R	805	721	84	]
3	R	805	721	84	
4	R	312	228	84	493m to 105-TX.
1966	R	733	649	84	388m from 112-SX.
2	R	744	660	84	
3	R	758	674	84	
4	R	758	674	84	
1-1967	R	758	674	84	
2	R	759	675	84	
3	R	761	677	84	
4	R	760	677	84	

Waste Status Summary of 102-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	757	673	84	(1) NB
2	R	754	670	84	
3	R	750	666	84	
4	R	744	660	84	
1-1969	R	739	655	84	
2	R	735	651	84	
3	R	733	687	46	
4	R	730	679	51	
1-1970	R	728	677	51	
2	R	726	675	51	
3	R	725	666	59	
4	R	723	664	59	
1-1971	R	720	661	59	
2	R	636	577	59	
3	R	862	803	59	116 M from 110-SX, 564 M from 111-SX, 492 M from 104-SX, 1,014 M to 104-BX 65 M dilution
	R	843	784	59	376 M from 111-SX, 55 M from 109-SX, 492 M from 114-SX, 62 H_2O, 1,005 to 104-BX
1-1972	R	369	310	59	171 M from 114-SX, 11 M H_2O, 13 M from 241-SX, 670 M to 104-BX
2	EB-RIX	908	142-707	59	742 M from 101-BX, 203 M to 104-BX
3	EB-RIX	908	142-707	59	
4 *	EB-RIX	908	142-707	59	
1-1973	EB-RIX	912	143-710	59	
2	EB-RIX	912	143-710	59	
3	EB-RIX	927	146-722	59	
4	EB-RIX	927	146-722	59	

(1) NB - Tank not equipped for boiling waste.

* Leak detection dry well 41-02-02 and 41-02-08 drilled.

Waste Status Summary of 102-SX Tank-Capacity 1.000.000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	927	146-722	59	
2 *	EB-RIX	956	152-745	59	30 from 106-SX
3	EB-RIX	363	52-252	59	598 to 102-S
4	EB	609	492	117	242-S bottom and recycle (1)
1-1975	EB	978	828	150	242-S bottom and recycle (1), 307 from 106-SX
2	EB	747	135	612	242-S bottom and recycle (1)
3	EB	967	355	612	242-S bottom and recycle (1), 221 from 110-SX
4	EB	576	77	499	242-S bottom and recycle (1), 1,215 from 110-SX
1-1976	EB	640	165	475	242-S bottom and recycle (1), 778 from 110-SX
2	EB	827	352	475	242-S bottom and recycle (1), 442 from 110-SX
3	EVAP	931	456	475	Conc. EVAP Feed
4	RESID	851	360	491	Residual Liquor
1-1977	RESID	975	478	497	(117 sludge & 380 salt cake)
2	RESID	967	470	497	(117 sludge & 380 salt cake)
3	RESID	961	464	497	(117 sludge & 380 salt cake)
4	RESID	967	470	497	(117 sludge & 380 salt cake) Part Neut. Feed

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the SX farm tanks.

* Leak detection dry well 41-02-11 drilled.

9 2 1 2 5 5 6 1 3 8 8

Waste Status Summary of 102-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	799	302	497	Active
* 2-	PNF	799	302	497	Salt well receiver Photo taken 3/21/78
3-	PNF	796	299	497	
4-	PNF	794	297	497	
1-1979	PNF	796	299	497	
2-	PNF	796	299	497	
3-	PNF	865	368	497	
4-	PNF	868	371	497	
1-1980	PNF	846	349	497	
2-	PNF	849	352	497	
3-	DSSF	538	20	518	Inactive - New Solid Level 8/15/80
4-	DSSF	538	20	518	

* 410205 New Well in service 5/20/78

9212561339

Waste Status Summary of 103-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Completed constructing in 1954.
[illegible]	R	0	0	0	
[illegible]	R	0	0	0	
4	R	637	637	0	
1-1955	R	827	827	0	
2	R	824	824	0	
3	R	943	943	0	Receiving salt waste.
4	R	943	943	0	

9 2 1 2 5 5 6 1 3 9 0

Waste Status Summary of 103-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	943	943	0	
2	R	943	943	0	
3	R	941	941	0	
4	R	941	941	0	
1-1957	R	941	941	0	
2	R	941	941	0	
3	R	941	941	10	
4	R	941	941	10	
1-1958	R	941	941	10	
2	R	450	450	---	448 to 101-U, 43 to 101-U.
3	R	752	752	---	305m from 113-SX.
4	R	697	697	10	55m decrease - air sparging.
1-1959	R	664	664	0	33m decrease - air sparging.
2	R	645	645	0	19m decrease - air sparging.
3	R	625	625	0	20m decrease - air sparging.
4	R	610	610	0	15m decrease - air sparging.
1-1960	R	595	595	0	15m decrease - air sparging.
2	R	590	590	0	5m decrease - air sparging.
3	R	582	582	0	8m decrease - air sparging.
4	R	580	580	0	Latest electrode reading.
1-1961					] 351m to 102-SX.
2	R	222	222	0	] 6 months report.
3					] Received 724m from 114-SX,
4	R	813	813	0	] 112m to 102-SX. 6 months report.

Waste Status Summary of 103-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	740	740	0	]
3					]6 months report.
4	R	731	731	0	]
1-1963					]6 months report.
2	R	722	722	0	]
3					]6 months report.
4	R	126	126	0	]660m to 101-TX, received 64m water.
1-1964					]6 months report.
2	R	658	658	0	]Received 484m from 111-SX.
3					]6 months report.
4	R	660	660	0	]
1-1965					]6 months report.
2	R	659	586	73	]529m to 101-TX, 514m from 110-SX.
3	R	668	595	73	Received 9m condensate.
4	R	675	602	73	
-1966	R	681	608	73	Received 6m condensate.
2	R	692	619	73	
3	R	167	94	73	525m to 101-TX.
4	R	505	432	73	320m from 105-SX.
1-1967	R	530	457	73	492m to 101-TY, 388m from 108-SX.
2	R	532	459	73	
3	R	536	463	73	
4	R	554	326	128	

9212556139 2

Waste Status Summary of 103-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	686	558	128	(1) NB, Received 132 M from 108-SX
2	R	685	558	127	(1) NB
3	R	684	559	125	
4	R	700	574	126	
1-1969	R	681	556	125	
2	R	680	555	125	
3	R	678	553	125	
4	R	675	550	125	
1-1970	R	674	549	125	
2	R	671	546	125	
3	R	670	545	125	
4	R	669	544	125	
1-1971	R	292	167	125	376 to 104-BX
2	R	160	35	125	132 M to 104-BX
3	CW-OWW-R	946	375-411-35	125	426 M from 103-BX, 360 M from 101-BX
4	CW-OWW-R	948	376-412-35	125	
1-1972	CW-OWW-R	948	376-412-35	125	
2	CW-OWW-R	948	376-412-35	125	
3	CW-OWW-R	948	376-412-35	125	
4 *	CW-OWW-R	948	376-412-35	125	
1-1973	CW-OWW-R	920	363-398-34	125	
2	CW-OWW-R	918	372-397-34	125	
3	CW-OWW-R	930	367-403-35	125	
4	CW-OWW-R	929	367-402-35	125	

(1) NB - Tank not equipped for boiling waste.

* Leak detection dry wells 41-03-06, 41-03-09 and 41-03-12 drilled.

Waste Status Summary of 103-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	CW-OWW-R	928	367-401-35	125	
2 *	CW-OWW-R	927	367-400-35	125	
3	CW-OWW-R	928	367-401-35	125	
4	CW-OWW-R	928	388-424-37	79	Awaiting solidification
1-1975	CW-OWW-R	293	83-90-8	112	634 to 102-S
2	EB	945	696	249	242-S bottoms and recycle (1)
3	EB	961	712	249	242-S bottoms and recycle (1)
4	EB	810	561	249	242-S bottoms and recycle (1)
1-1976	EB	640	391	249	242-S bottoms and recycle (1)
2	EB	912	663	249	242-S bottoms and recycle (1)
3	EVAP	967	718	249	Conc. Feed
4	RESID	656	407	249	Residual Liquor
1-1977	RESID	981	358	623	(112 sludge & 511 salt cake)
2	RESID	967	344	623	(112 sludge & 511 salt cake)
3	RESID	961	338	623	(112 sludge & 511 salt cake)
4	RESID	961	338	623	(112 sludge & 511 salt cake) Part Neut. Feed

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the SX farm tanks.

* Leak detection dry wells 41-03-02, 41-03-05 and 41-03-10 drilled.

9 2 1 2 5 5 6 1 3 9 4

Waste Status Summary of 103-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	761	3	758	Active
2-	PNF	758	0	758	
3-	PNF	758	0	758	Inactive-Primary Stabilized Solids Level Taken 9/10/78
4-	PNF	758	0	758	
1-1979	PNF	758	0	758	
2-	PNF	758	0	758	
3-	PNF	758	0	758	
4-	PNF	829	71	758	Active
1-1980	PNF	736	22	714	New Photo 2/19/80
2-	PNF	743	29	714	
3-	DSSF	666	32	634	New Photo 8/29/80 New Solids Level 8/27/80 - Inactive
4-	DSSF	666	32	634	

9 2 1 2 5 5 6 1 3 9 5

Waste Status Summary of 104-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	R	---	---	---	Completed construction in 1954.
*	R	0	0	0	
3	R	0	0	0	
4	R	0	0	0	
1-1955	R	507	507	0	Active receiver, Redox waste.
2	R	994	994	0	Started evaporating this month.
3	R	960	960	0	Self-evaporating.
4	R	901	901	0	Received concentrated salt waste for 10 days.

* Leak detection dry well 41-04-07 drilled.

9212556139 6

Waste Status Summary of 104-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	872	872	0	Received salt waste for 3 days self-evaporating tank.
2	R	899	899	0	Salt waste diverted to 109-SX on 1/23/56
3	R	851	851	0	73m self-concentrating.
4	R	832	832	0	66m self-concentrating.
1-1957	R	792	792	0	40m self-concentrating.
2	R	810	810	0	27m self-concentrating, 25m from 106-SX, 20m received from catch tanks.
3	R	821	821	0	8m self-concentrating, 16m water boiled off, 27m condensate added.
4	R	835	835	0	9m water boiled off, 13m condensate added, latest electrode reading.
1-1958	R	821	821	0	14m water boiled off.
2	R	816	816	0	8m self-concentrating.
3	R	814	814	0	9m self-concentrating.
4	R	794	794	0	20m self-concentrating.
1-1959	R	786	786	0	8m self-concentrating.
	R	780	780	0	6m self-concentrating.
3	R	769	769	0	11m self-concentrating.
4	R	764	764	0	5m self-concentrating.
1-1960	R	767	767	0	7m self-concentrating.
2	R	765	765	0	
3	R	752	752	0	13m boiled off.
4	R	749	749	0	Boiled off 3m.
1-1961					
2	R	739	739	0	6 months report.
3					
4	R	730	730	0	6 months report.

9212556139 7

Waste Status Summary of 104-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	726	726	0	]
3					]6 months report.
4	R	726	726	0	]
1-1963					]6 months report.
2	R	719	719	0	]
3					]6 months report.
4	R	718	718	0	]
1-1964					]6 months report.
2	R	713	713	0	]
3					]6 months report.
4	R	719	719	0	]
1-1965					]6 months report.
2	R	730	539	191	]
3	R	737	546	191	Received 7m condensate.
4	R	741	550	191	
1-1966	R	741	550	191	
2	R	750	559	191	
3	R	761	570	191	
4	R	774	583	191	
1-1967	R	780	589	191	
2	R	788	598	191	
3	R	794	603	191	
4	R	792	601	191	

9 2 1 2 5 6 1 3 9 8

Waste Status Summary of 104-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	791	600	191	(1) NB
2	R	789	598	191	(1) NB
3	R	786	786	0	(1) NB
4	R	784	593	191	
1-1969	R	781	590	191	
2	R	779	588	191	
3	R	777	613	164	
4	R	775	610	165	
1-1970	R	774	609	165	
2	R	772	607	165	
3	R	771	602	169	
4	R	769	600	169	
1-1971	R	766	597	169	
2	R	764	595	169	
3	R	269	100	169	496 M to 102-SX
4	EB-RIX	943	90-684	169	669 M from 105-SX
-1972	EB-RIX	942	90-683	169	
2	EB-RIX	942	90-683	169	
3 *	EB-RIX	942	90-683	169	
4	EB-RIX	942	90-683	169	
1-1973	EB-RIX	924	88-667	169	
2	EB-RIX	922	88-665	169	
3	EB-RIX	939	90-680	169	
4	EB-RIX	937	90-678	169	

(1) NB - Tank not equipped for boiling waste.

* Leak detection dry wells 41-04-01 and 41-04-11 drilled.

9 2 1 2 5 5 6 1 3 9 9

Waste Status Summary of 104-SX Tank-Capacity 1,000,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	934	89-676	169	
2	EB-RIX	931	88-674	169	
3 *	EB-RIX	927	87-671	169	
4	EB-RIX	926	90-697	139	Awaiting solidification
1-1975	EB-RIX	923	86-668	169	
2	EB-RIX	708	190-349	169	206 from 105-SX, 418 to 102-S
3	EB	917	635	282	242-S bottoms and recycle (1)
4	EB	763	244	519	242-S bottoms and recycle (1)
1-1976	EB	664	101	563	242-S bottoms and recycle (1), 174 to 102-S
2	EB	681	118	563	242-S bottoms and recycle (1)
3	EVAP	972	409	563	Conc. Feed
4	RESID	758	195	563	Residual Liquor
1-1977	RESID	772	99	673	(169 sludge & 504 salt cake)
2	RESID	945	272	673	(169 sludge & 504 salt cake)
3	RESID	953	146	807	(169 sludge & 504 salt cake) Slurry receive
4	RESID	964	157	807	(169 sludge & 504 salt cake) Part Neut. Feed

9212556140 0

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S and SX farm tanks

* Leak detection dry wells 41-04-03 and 41-04-05 drilled.

Waste Status Summary of 104-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	972	165	807	Active
* 2-	PNF	970	163	807	Photo Taken 4/21/78
3-	PNF	970	163	807	
4-	PNF	967	160	807	
1-1979	PNF	972	165	807	
2-	PNF	970	163	807	Photo taken 4/27/79
3-	PNF	917	110	807	
4-	PNF	917	110	807	
1-1980	DSSF	950	195	755	New Photo 1/15/80
2-	DSSF	958	203	755	
3-	DSSF	763	50	713	Inactive - New Photo & Solids Level 8/18/80
4-	DSSF	763	50	713	

* New well 410408 in service on 6/20/78

9212561401

Waste Status Summary of 105-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	R	---	---	---	Completed construction in 1954.
	R	0	0	0	
3	R	0	0	0	
4	R	0	0	0	
1-1955	R	0	0	0	
2	R	142	142	0	Condensate.
3	R	963	963	0	
4	R	963	963	0	

Waste Status Summary of 105-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	963	963	0	
2	R	963	963	0	
3	R	960	960	0	
4	R	960	960	0	Condensate collector.
1-1957	R	952	952	0	Latest electrode reading.
2	R	937	937	0	Latest electrode reading.
3	R	931	931	15	Latest electrode reading.
4	R	923	923	15	Latest electrode reading.
1-1958	R	920	920	15	Latest electrode reading.
2	R	920	920	---	Latest electrode reading.
3	R	920	920	15	Latest electrode reading.
4	R	920	920	15	
1-1959	R	920	920	0	
2	R	919	919	0	1m self-concentrating.
3	R	916	916	0	1m self-concentrating, latest electrode reading.
4	R	915	915	0	Latest electrode reading.
1-1960	R	910	910	0	5m decrease.
2	R	911	911	0	
3	R	906	906	0	
4	R	908	908	0	
1-1961					6 months report.
2	R	904	904	---	
3					6 months report.
4	R	901	901	0	

Waste Status Summary of 105-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	898	898	0	]
3					]6 months report.
4	R	340	340	0	]327m to 108-SX, 234m to 109-SX.
1-1963					]6 months report.
2	R	695	695	0	]230m to 101TX, 619m from 114.
3					]6 months report.
4	R	627	627	0	]
1-1964					]6 months report.
2	R	708	708	0	]120m sod.nitrite to 202-S dissolvers.
3					]6 months report.
4	R	796	796	0	]120m sod. nitrite to 202-S, 208m from 115SX.
1-1965					]6 months report.
2	R	714	671	43	]132m sod. nitrite to 202-S, 52m from 115-S.
	R	662	619	43	52m sod. nitrite to 202-S.
	R	604	561	43	59m sod. nitrite to 202-S.
1-1966	R	541	498	43	63m sod. nitrite to 202-S.
2	R	480	437	43	61m sod. nitrite to 202-S.
3	R	442	399	43	36m sod. nitrite to 202-S.
4	R	412	379	43	Rec'd. 261m, 320m to 103-SX.
1-1967	R	428	385	43	Rec'd. 65m.
2	R	474	431	43	Rec'd. 46m.
3	R-HLO	450	398-9	43	Rec'd. 9m HLO concentrate.
4	R-HLO-EB	450	362-9-36	43	Rec'd. 36m Redox Evap. bottoms.

Waste Status Summary of 105-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R-EB	542	92-407	43	Received 196 M from Redox Evap. (2)(3)
2	R-EB	629	92-482	55	Received 86 M from Redox Evap. (2)
3	R-EB	787	92-425	57	Received 158 M from Redox Evap.
4	R-EB	878	92-729	57	91 M from Redox Evap.
1-1969	R-EB	735	92-584	59	134 M to 107-U
2	R	113	54	59	(Spare) 615 to 107-U
3	R	301	243	58	(Spare) 196 from Redox Evap.
4	R	293	235	58	(Spare)
1-1970	R	286	228	58	(Spare)
2	R	279	211	68	(Spare)
3	R	274	208	66	(Spare)
4	R	267	201	66	(Spare)
1-1971	R	262	196	66	(Spare)
2	R	263	197	66	(Spare)
3	RIX	909	843	66	1,375 M from 101-BX, 734 M to 110-SX
4	EB-RIX	647	68-513	66	1,196 M from 101-BX, 669 M to 104-SX, 790 M to 111-SX
1-1972	EB-RIX	945	182-697	66	1,127 M from 101-BX, 760 M Redox Evap.
2	EB-RIX	940	181-693	66	390 M from 101-BX, 394 M to 106-SX
3 *	EB-RIX	948	182-700	66	1 from 302-R catch tank
4	EB-RIX	946	182-698	66	
1-1973	EB-RIX	938	180-692	66	
2 **	EB-RIX	937	180-691	66	
3	EB-RIX	945	182-697	66	
4	EB-RIX	944	182-696	66	

(2) Tank equipped for boiling waste.

(3) Bottoms from concentration of BNW and DUN (100-N) waste.

* Leak detection dry wells 41-05-02, 41-05-03, 41-05-07, 41-05-08, 41-05-10 and 41-05-12 were drilled.

** Leak detection dry well 41-05-05 drilled.

Waste Status Summary of 105-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	944	182-696	66	
2	EB-RIX	942	182-694	66	2 from 111-SX
3	EB-RIX	940	182-692	66	
4	EB-RIX	937	187-713	37	Awaiting solidification
1-1975	EB-RIX	934	179-682	73	
2	EB	252	179	73	242-S bottoms and recycle (1), 206 to 104-SX
3	EB	956	693	263	242-S bottoms and recycle (1)
4	EB	865	401	464	242-S bottoms and recycle (1)
1-1976	EB	978	487	491	242-S bottoms and recycle (1), 263 to 101-S, 66 to 107-S
2	EB	744	253	491	242-S bottoms and recycle (1)
3	EVAP	769	278	491	Conc. Feed
4	RESID	972	492	480	Residual Liquor
1-1977	RESID	978	239	739	(73 sludge & 666 salt cake)
2	RESID	942	203	739	(73 sludge & 666 salt cake)
3	RESID	961	222	739	(73 sludge & 666 salt cake) Slurry receiver
4	RESID	747	8	739	(73 sludge & 666 salt cake) Part Neut. Feed

9 2 1 2 5 5 6 1 4 0 6

(1) Due to characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of the S and SX farm tanks

Waste Status Summary of 105-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	PNF	747	8	739	Active
2-	PNF	747	8	739	
3-	PNF	741	0	741	Inactive-Primary Stab. Solids Level 9/10/78
4-	PNF	744	3	741	
1-1979	PNF	744	3	741	
2-	PNF	750	9	741	
3-	PNF	750	9	741	
4-	PNF	805	64	741	New Photo 12/20/79
1-1980	DSSF	884	143	741	
2-	DSSF	884	143	741	
3-	DSSF	688	15	673	Inactive - New Photo & Solids Level 8/29/80
4-	DSSF	688	15	673	

9212561407

Waste Status Summary of 106-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	R	0	0	0	Completed construction in 1954.
	R	0	0	0	Fume header condensate receiver pumps to underground cavern.
3 *	R	18	18	0	Condensate.
4	R	97	97	0	Condensate.
1-1955	R	71	71	0	Condensate and deiversion box flush material.
2	R	142	142	0	Condensate.
3	R	127	127	0	Condensate collector.
4	R	187	187	0	

* Leak detection dry well 41-06-11 drilled.

9 2 1 2 5 6 1 4 0 8

Waste Status Summary of 106-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	351	351	0	Condensate collector.
2	R	323	323	0	Condensate collector.
3	R	417	417	0	Condensate collector.
4	R	367	367	0	Condensate collector.
1-1957	R	252	252	0	Condensate collector.
2	R	103	103	0	Condensate collector.
3	R	197	197	0	Condensate collector.
4	R	315	315	0	Condensate collector.
1-1958	R	238	238	0	Condensate collector.
2	R	183	183	0	Condensate collector.
3	R	95	95	0	Condensate collector.
4	R	175	175	0	Condensate collector.
1-1959	R	634	634	0	69m condensate collected 36m pumped to 107 and 108-SX 19m to 108-SX, 5m water boiled off.
2	R	206	206	0	54m pumped to 108-SX, 52m to 107 and 114-SX.
3	R	71	71	0	160m pumped out, 25m received.
4	R	130	130	0	30m condensate received, 29 pumped.
1-1960	R	150	150	0	31 pumped 108-SX, 40m pumped 114-SX, received 53m condensate.
2	R	54	54	0	Received 29m, 186m pumped to 108 and 111 and 114-SX.
3	R	54	54	0	Received 61m, pumped out 53m.
4	R	44	44	0	Received 26m, pumped 105m to 114-SX and 115-SX, pumped 15m water to 106-SX.
1-1961					6 months report.
2	R	321	321	0	
3					6 months report.
4	R	150	150	0	

9 2 1 2 5 5 6 1 4 0 9

Waste Status Summary of 106-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	110	110	0	]
3					]6 months report.
4	R	81	81	0	]
1-1963					]25m to 202-S dissolvers.
2	R	279	279	0	]6 months report.
3					]6 months report.
4	R	297	297	0	]
1-1964					]6 months report.
2	R	399	399	0	]
3					]6 months report.
4	R	481	481	0	]
1-1965					]6 months report.
2	R	447	447	0	]Condensate collector
3	R	343	343	0	Condensate collector.
4	R	461	461	0	Condensate collector.
1966	R	516	516	0	Condensate collector.
2	R	400	400	0	Condensate collector.
3	R	357	357	0	Condensate collector.
4	R	389	389	0	
1-1967	R	409	409	0	
2	R-HLO	213	198-15	0	Rec'd. 15m HLO.
3	R-HLO	228	213-15	0	
4	R	224	224	0	

9 2 1 2 5 6 1 1 0

Waste Status Summary of 106-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	172	172	0	(1) NB
2	R	129	129	0	(1) NB
3	R	165	165	0	
4	R	306	306	0	
1-1969	R	444	444	0	Received 100 M BNW Waste
2	R	399	399	0	
3	R	374	373	1	
4	R	369	368	1	
1-1970	R	363	362	1	
2	R	362	361	1	
3	R	373	372	1	
4	R	412	411	1	
1-1971	R	449	448	1	
2	R	493	492	1	
3	R	472	471	1	
4	R	340	339	1	
-1972	EB-RIX	937	194-742	1	760 M from 105-SX, 192 M to 114-SX
2	EB-RIX	937	194-742	1	394 M from 105-SX, 392 M to 114-SX
3 *	EB-RIX	907	188-718	1	
4	EB-RIX	932	193-738	1	
1-1973	EB-RIX	893	185-707	1	
2	EB-RIX	919	190-728	1	
3	EB-RIX	959	198-760	1	
4	EB-RIX	936	193-742	1	

(1) (NB) - Tank not equipped for boiling waste.

* Leak detection dry wells 41-06-02, 41-06-05 and 41-06-09 drilled.

9212556141

Waste Status Summary of 106-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	963	199-763	1	
2	EB-RIX	952	197-754	1	30 to 102-SX
3	Water	966	965	1	
4	Water	238	237	1	Awaiting solidification, 739 to 102-S
1-1975	CW-IX-EB (4)	466	12-115-11(4)	9	242-S feed receiver tank; 349 from 103-C (3)
2	IX-EB-BL	854	377-435-33	9	297 from 102-B, 426 from 103-C (5)
3	EB	777	768	9	1,044 from 103-C, 618 from 103-BX, 7 water, 1,719 to 102-S
4	CW-R-IX-OWW-N-BNW-LW-TBP-DW	219	31-20-41-62-10-7-4-5-13	26	711 from 103-C, 7 water, received slurry, pumped to 102-S
1-1976	PL-B	43	1-16	26	483 from 104-C, 774 to 102-S
2	PSS-B-PL-BL	970	99-671-26-148	26	932 from 104-C
3	EVAP-DIL	453	427	26	Feed Receiver
4	EVAP	945	916	29	Lo-Heat High Sr. Waste Conc.
-1977	RESID	945	572	373	(12 sludge & 361 salt cake)
2	RESID	942	569	373	(12 sludge & 361 salt cake)
3	RESID	948	575	373	(12 sludge & 361 salt cake) Hi SR.
4	RESID	950	577	373	(12 sludge & 361 salt cake) Waste Cone Stabilized Phase I

(2) 1,464 from 106-SX, 1,181 water, 2,599 evaporated

(3) 114 from 103-BX, 230 from 101-T, 418 from 107-TX, 57 from 106-S, 307 to 102-SX, 636 to 102-S

(4) BL-RIX-R-N-DW-BNW-LW-PL → 229-39-12-7-3-16-8-5

(5) 703 from 103-BX, 413 from 106-BX, 16 from 154-UX C.T., 1,464 to 102-S

9212556141 2

Waste Status Summary of 106-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	CCPLX	279	129	150	Active
2-	CCPLX	150	0	150	Photo Taken 3/22/78
3-	NCPLX	516	366	150	
4-	NCPLX	205	118	87	New Solid Level Adj. 12/18/79 Future Slurry Receiver
1-1979	CPLX	816	729	87	
2-	CPLX	967	880	87	New Photo 5/1/79
3-	CPLX	967	880	87	
4-	PNF	832	745	87	
1-1980	PNF	260	173	87	
2-	PNF	671	584	87	
3-	PNF	890	803	87	
4-	DSSF	477	0	477	New Photo 10/28/80 New Solids Level 10/23/80 - Inactive

9 2 1 2 5 6 1 4 1 3

Waste Status Summary of 107-SX Tank-Capacity 1,000,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.

9 2 1 2 5 5 6 1 4 1 4

Waste Status Summary of 107-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	R	548	548	0	SS High MWD received 92m gallons.
3	R	493	493	0	133m self-concentrating.
4	R	399	399	0	94m self-concentrating.
1-1957	R	324	324	0	107m self-concentrating, estimated volume.
2	R	543	543	0	287m received, 67m self-concentrating.
3	R	612	612	0	168m self-concentrating, received 237m plus 56m condensate.
4	R	623	623	0	168m self-concentrating, received 182m.
1-1958	R	612	612	0	69m self-concentrating, 69m H_2O added under total reflux.
2	R	640	640	0	36m self-concentrating, 70m - boiled off.
3	R	714	714	2	102m from 241-S, 50m - boiled off.
4	R	656	656	---	6m self-concentrating, 41m water boiled off.
-1959	R	634	634	---	43m boiled off, 26m received.
2	R	626	626	---	Received 22m condensate from 106-SX, 30m boiled off.
3	R	620	620	---	Received 14m from 240-S catch tank, 20m water boiled off.
4	R	623	623	---	Received 24m water, 23m boiled off.
1-1960	R	646	646	---	28m cooling water added.
2	R	645	645	---	
3	R	629	629	---	Boiling.
4	R	626	626	---	Boiled off 3m.
1-1961					
2	R	626	626	---	6 months report.
3					
4	R	651	651	---	6 months report.

9 2 1 2 5 5 6 1 4 1 5

Waste Status Summary of 107-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	648	648	0	]
3					]578m to 102-SX.
4	R	332	332	0	]6 months report.
1-1963					]6 months report.
2	R	494	494	0	]Rec'd. 536m, 219m to 114-SX.
3 *					]6 months report.
4	R	418	418	0	]Rec'd. 291m water.
1-1964					]6 months report.
2	R	495	495	0	]559m rec'd.
3					]6 months report.
4	R	517	517	0	]
1-1965					]6 months report.
2	R	472	459	13	]
3	R	472	459	13	
4	R	425	412	13	Rec'd. 6m condensate.
-1966	R	519	506	13	Rec'd. 127m water.
	R	491	478	13	Rec'd. 8m water.
3	R	477	464	13	Rec'd. 17m water.
4	R	461	448	13	Rec'd. 10m water.
-1967	R	447	434	13	
2	R	441	428	13	
3	R	491	478	13	
4	R	477	376	101	Suspect leaker

* Leak detection dry wells 41-07-02, 41-07-03, 41-07-05, 41-07-07, 41-07-08, 41-07-10, 41-07-12 drilled.

Waste Status Summary of 107-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	466	365	101	Possible leaker (2) (B)
2	R	473	375	98	Possible leaker (2) (B)
3	R	178	32	146	New evidence of tank leakage 127 M to 110-SX, 145 to 111-SX
4	R	147	0	147	Tank leaks: Air drying of sludge initiated 12/19/68
1-1969	R	136	0	136	Tank leaks, air cooling sludge
2	R	135	0	135	Tank leaks, air cooling sludge
3	R	135	0	135	Tank leaks, air cooling sludge
4	R	134	0	134	Tank leaks, air cooling sludge
1-1970	---	134	0	134	Tank leaks, air cooling sludge
2	---	131	0	131	Tank leaks, air cooling sludge
3	---	131	0	131	Tank leaks, air cooling sludge
4	---	131	0	131	Tank leaks, air cooling sludge
1-1971	---	131	0	131	Tank leaks, air cooling sludge
2	---	131	0	131	Tank leaks, air cooling sludge
3	---	131	0	131	Tank leaks, air cooling sludge
4	---	110	0	110	Tank leaks
1-1972	---	110	0	110	Tank leaks
2	---	110	0	110	Tank leaks
3	---	110	0	110	Tank leaks
4	---	110	0	110	Tank leaks
1-1973	---	110	0	110	Tank leaks
2	---	110	0	110	Tank leaks
3	---	110	0	110	Tank leaks
4	---	110	0	110	Tank leaks

(2) (B) - Tank equipped for boiling waste.

107-SX-6

Waste Status Summary of 107-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	109	0	109	Primary Stabilized
2-	—	109	0	109	
3-	—	109	0	109	Air Cooled
4-	—	109	0	109	
1-1979	—	109	0	109	
2-1979	—	109	0	109	
3-1979	—	109	0	109	
4-1979	—	109	0	109	PHOTO Taken 11-9-79 Interim Stabilized
1-1980	—	109	0	109	
2-	—	109	0	109	
3-	—	109	0	109	
4-	—	109	0	109	

9212565614 13

Waste Status Summary of 107-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	110	0	110	Tank leaks
2	---	110	0	110	Tank leaks
3	---	110	0	110	Tank leaks
4	---	109	0	109	Tank leaks
1-1975	---	109	0	109	Tank leaks
2	---	109	0	109	Tank leaks
3	---	109	0	109	Tank leaks
4	---	109	0	109	Tank leaks
1-1976	---	109	0	109	Tank leaks
2	---	109	0	109	Tank leaks
3	---	109	0	109	Tank leaks, air-cooled
4	---	109	0	109	Tank leaks, air-cooled
1-1977	---	109	0	109	Tank leaks, air cooled
2	---	109	0	109	Tank leaks, air cooled
3	---	109	0	109	Tank leaks, stabilized Phase I
4	---	109	0	109	Tank leaks, stabilized Phase I
1-1978	-	109	0	109	Primary Stabilized
2-	-	109	0	109	
3-	-	109	0	109	Air Cooled
4-	-	109	0	109	
1-1979	-	109	0	109	
2-	-	109	0	109	
3-	-	109	0	109	
4-	-	109	0	109	Photo taken 11/9/79, Interim Stabilized
1-1980	-	109	0	109	
2-	-	109	0	109	
3-	-	109	0	109	
4-	-	109	0	109	

9 2 1 2 5 5 6 1 4 1 9

Waste Status Summary of 108-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	R	564	564	---	To receive high MWD waste.

9 2 1 2 5 6 1 4 0

Waste Status Summary of 108-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	466	466	0	High MWD waste - self-evaporating.
2	R	481	481	0	High MWD waste - self-evaporating.
3	R	527	527	0	51m self-concentrating.
4	R	470	470	0	57m self-concentrating.
1-1957	R	703	703	0	Received 78m, 115m self-concentrating (Received 145m during the month of Feb.)
2	R	574	574	0	129m self-concentrating.
3	R	494	494	0	100m self-concentrating.
4	R	623	623	0	128m self-concentrating, 257m received.
1-1958	R	541	541	0	88m self-concentrating, under total reflux.
2	R	596	596	0	16m self-concentrating, 52m boiled off.
3	R	593	593	3	9m self-concentrating, 42m boiled off, received 4m.
4	R	785	785	---	12m self-concentrating, 20m boiled off, received 106m.
1-1959	R	763	763	---	40m self-concentrating, received 62m.
	R	754	754	---	Received 51m from 106-SX, 57m boiled off, 9m self-concentrating.
3	R	764	764	---	Received 69m, 59m boiled off.
4	R	722	722	---	32m self-concentrating.
1-1960	R	717	717	---	5m self-concentrating.
2	R	718	718	---	Received 20m from 106-SX, 1m self-concentrating.
3	R	739	739	0	Received 49m, boiled off 18m.
4	R	756	756	0	Received 42m H_2O and 15m condensate, boiled off 43m.
1-1961					6 months report.
2	R	728	728	0	
3					6 months report.
4	R	700	700	0	

9 2 1 2 5 5 6 1 4 2 1

Waste Status Summary of 108-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	315	315	0	]665m to 103SX.
3 *					]6 months report.
4	R	714	714	0	]Rec'd. 397m, 205m to 114SX, 327 from 105SX.
1-1963					]6 months report.
2	R	524	524	0	]Rec'd. 185m.
3					]6 months report
4	R	633	633	0	]Rec'd. 550m waste, 132m water.
1-1964					]6months report.
2	R	660	660	0	]Rec'd. 43m.
3					]6 months report.
4	R	678	678	0	]
1-1965					]6 months report.
2	R	637	621	16	]
3	R	637	621	16	
	R	653	637	16	Rec'd. 27m condensate.
1-1966	R	653	637	16	
2	R	640	624	16	
3	R	626	610	16	
4	R	601	585	16	
1-1967	R	213	197	16	Tank leaks. 388m to 103SX.
2	R	216	200	16	
3	R	213	213	0	
4	R	211	91	120	

* Leak detection dry wells 41-08-02, 41-08-03, 41-08-04, 41-08-06, 41-08-07, 41-08-10 drilled.

Waste Status Summary of 108-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	130	10	120	(2) (B), Tank leaks
2	R	135	5	130	Tank leaks
3	R	126	0	126	Tank leaks
4	R	126	0	126	Tank leaks, air drying sludge
1-1969	R	145	0	145	Tank leaks, air cooling sludge (new electrode tape)
2	R	143	0	143	Tank leaks, air cooling sludge
3	R	143	0	143	Tank leaks, air cooling sludge
4	R	142	0	142	Tank leaks, air cooling sludge
1-1970	---	142	0	142	Tank leaks, air cooling sludge
2	---	142	0	142	Tank leaks, air cooling sludge
3	---	142	0	142	Tank leaks, air cooling sludge
4	---	142	0	142	Tank leaks, air cooling sludge
1-1971	---	142	0	142	Tank leaks, air cooling sludge
2	---	142	0	142	Tank leaks, air cooling sludge
3	---	142	0	142	Tank leaks, air cooling sludge
4	---	142	0	142	Tank leaks
1-1972	---	142	0	142	Tank leaks
2	---	142	0	142	Tank leaks
3	---	142	0	142	Tank leaks
4	---	142	0	142	Tank leaks
1-1973	---	142	0	142	Tank leaks
2	---	142	0	142	Tank leaks
3 *	---	142	0	142	Tank leaks
4	---	142	0	142	Tank leaks

(2) (B) - Tank equipped for boiling waste.

* Leak detection dry well 41-08-06 deepened.

Waste Status Summary of 108-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	142	0	142	Tank leaks
2	---	142	0	142	Tank leaks
3	---	142	0	142	Tank leaks
4	---	87	0	87	Tank leaks
1-1975	---	87	0	87	Tank leaks
2	---	87	0	87	Tank leaks
3	---	87	0	87	Tank leaks
4	---	87	0	87	Tank leaks
1-1976	---	87	0	87	Tank leaks
2	---	87	0	87	Tank leaks
3	---	87	0	87	Tank leaks, air-cooled
4	---	87	0	87	Tank leaks, air-cooled
1-1977	---	87	0	87	Tank leaks, air-cooled
2	---	87	0	87	Tank leaks, air-cooled
3	---	87	0	87	Tank leaks, air-cooled
4	---	87	0	87	Tank leaks, stabilized Phase I
1-1978	-	87	0	87	Primary Stabilized
2-	-	87	0	87	Air cooled
3-	-	87	0	87	
4-	-	87	0	87	
1-1979	-	87	0	87	
2-	-	87	0	87	
3-	-	87	0	87	
4-	-	87	0	87	Interim Stab. 8/79
1-1980	-	87	0	87	New Photo 1/24/80
2-	-	87	0	87	
3-	-	87	0	87	
4-	-	87	0	87	

9212356142

Waste Status Summary of 109-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	R	520	520	---	Receiving concentrated salt waste.
4	R	662	662	---	Receiving concentrated salt waste. Stopped on eleventh.

Waste Status Summary of 109-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	956	956	0	Low MWD Waste, self-evaporating.
2	R	908	908	0	Low MWD Waste, self-evaporating.
3	R	890	890	0	19m self-concentrating.
4	R	981	981	0	11m self-concentrating.
1-1957	R	969	969	0	12m self-concentrating.
2	R	961	961	0	8m self-concentrating.
3	R	959	959	0	2m self-concentrating.
4	R	956	956	0	
1-1958	R	956	956	0	
2	R	959	950	0	
3	R	967	967	0	
4	R	964	964	0	3m self-concentrating.
1-1959	R	961	961	0	3m water boiled off.
2	R	959	959	0	2m water boiled off.
3	R	960	960	0	Latest electrode reading.
4	R	959	959	0	
-1960	R	953	953	0	New electrode installed.
2	R	951	951	0	Latest electrode reading.
3	R	667	667	0	Pumped out 284m.
4	R	665	665		
1-1961					
2	R	659	659	0	6 months report.
3					Received 58m, 386m to 110-SX,
4	R	337	337	0	6 months report.

9 2 1 2 5 6 1 4 2 6

Waste Status Summary of 109-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					]6 months report.
2	R	486	486	0	]Rec'd. 507m, 89m from 102-SX.
3 *					]6 months report.
4	R	676	676	0	]Rec'd. 147m, 234m from 105-SX.
1-1963					]
2	R	733	733	0	]6 months report.
3					]6 months report.
4	R	722	722	0	]
1-1964					]6 months report.
2	R	710	710	0	]
3					]6 months report.
4	R	676	676	0	]
1-1965					]6 months report.
2	R	670	602	68	]
3	R	665	597	68	
4	R	631	563	68	
-1966	R	612	544	68	
2	R	576	508	68	
3	R	565	497	68	
4	R	557	489	68	
1-1967	R	546	478	68	
2	R	544	475	68	
3	R	541	473	68	
4	R	538	374	164	Suspect leaker.

* Leak detection dry wells 41-09-02, 41-09-03, 41-09-04, 41-09-06, 41-09-07, 41-09-11 drilled.

Waste Status Summary of 109-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	530	366	164	(2) (B), Possible leaker
2	R	524	344	180	(2) (B), Possible leaker
3	R	519	323	186	Possible leaker
4	R	510	323	187	Possible leaker
1-1969	R	511	320	191	Possible leaker
2	R	508	321	187	Possible leaker
3	R	352	174	178	Possible leaker, 196 M to 105-SX
4	R	346	170	176	Possible leaker
1-1970	R	342	166	176	Possible leaker
2	R	341	147	194	Possible leaker
3	R	343	150	193	Possible leaker
4	R	341	152	189	Possible leaker
1-1971	R	337	148	189	Possible leaker
2	R	333	144	189	Possible leaker
3	R	333	144	189	Possible leaker
4	R	277	88	189	Possible leaker
1-1972	R	274	85	189	Possible leaker
2	R	275	86	35	Tank leaks
3	R	273	84	189	Possible leaker
4	R	270	81	189	Possible leaker
1-1973	R	268	79	189	Tank leaks
2 *	R	268	79	189	Tank leaks
3	R	257	68	189	Tank leaks
4	R	256	67	189	Tank leaks

(2) (B) - Tank equipped for boiling waste.

* Leak detection dry well 41-09-11 deepened.

Waste Status Summary of 109-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	257	0	257	Tank leaks
2	---	257	0	257	Tank leaks
3	---	257	0	257	Tank leaks
4	---	257	0	257	Tank leaks
1-1975	---	257	0	257	Tank leaks
2	---	257	0	257	Tank leaks
3	---	257	0	257	Tank leaks
4	---	257	0	257	Tank leaks
1-1976	---	257	0	257	Tank leaks
2	---	257	0	257	Tank leaks
3	---	257	0	257	Tank leaks, air-cooled
4	---	257	0	257	Tank leaks, air-cooled
1-1977	---	257	0	257	Tank leaks, air-cooled
2	---	257	0	257	Tank leaks, air-cooled
3	---	257	0	257	Tank leaks, air-cooled
4	---	257	0	257	Tank leaks, air-cooled
-1978	-	257	0	257	Air cooled
2-	-	257	0	257	
3-	-	257	0	257	
4-	-	257	0	257	
1-1979	-	257	0	257	
2-	-	257	0	257	
3-	-	257	0	257	
4-	-	257	0	257	
1-1980	-	257	0	257	
2-	-	257	0	257	
3-	-	257	0	257	
4-	-	257	0	257	

9 2 1 2 5 5 6 1 4 2 9

Waste Status Summary of 110-SX Tank-Capacity 1,000,000 Gallons

Qtr. Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	
	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.

9212361430

Waste Status Summary of 110-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1957	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3 *	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1958	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1959	---	---	---	---	
2	R	MT	MT	---	
3	R	9	9	---	Latest electrode reading.
4	R	9	9	---	
-1960	R	9	9		
2	R	176	176	---	Received 136m from 112-SX, Received 33m from 106-SX.
3	R	175	175		
4	R	297	297	---	Received 109m, Redox SW receiving end of December.
1-1961					] Received 535m.
2	R	642	642		] 6 months report.
3					
4	R	678	678	---	Received 50m, received 386m from 109-SX.

* Leak detection dry wells 41-10-02 and 41-10-10 drilled.

9 2 1 2 5 5 6 1 4 3 1

Waste Status Summary of 110-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					] 6 months report
2 *	R	706	706	0	] 113m from 102-SX
3					] 6 months report
4	R	720	720	0	]
1-1963					] 6 months report
2	R	711	711	0	]
3					] 6 months report
4	R	719	719	0	] Received 58m water.
1-1964					] 6 months report
2	R	702	702	0	]
3					] 6 months report
4	R	672	672	0	]
1-1965					] 6 months report
2	R	158	101	51	] 514m to 103-SX; back-up tank in event of failure.
3	R	188	137	51	Received 30m condensate; back-up tank in event of failure.
4	R	420	369	51	Received 274m; receiving at end of December.
1-1966	R	554	503	51	Received 434m from 202-S; receiving at end of March.
2	R	631	580	51	Received 202m from 202-S and 222m water.
3	R	631	580	51	
4	R	623	572	51	Received 220m water.
1-1967	R	620	569	51	
2	R	628	577	51	
3	R	640	589	51	
4	R	634	602	32	

* Leak detection dry wells 41-10-03, 41-10-05, 41-10-06, 41-10-08, 41-10-11 drilled.

9214256

Waste Status Summary of 110-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	641	609	32	(2) (B)
2	R	640	582	58	(2) (B)
3	R	776	726	50	127 M from 107-SX
4	R	789	747	42	
1-1969	R	932	890	42	Received 139 M from 112-SX
2	R	942	934	8	Lower sludge level due to increase in agitation
3	R	952	944	8	
4	R	945	921	24	
1-1970	R	944	920	24	
2	R	943	911	32	
3	R	948	916	32	
4	R	959	927	32	
1-1971	R	958	926	32	
2	R	294	262	32	663 M to 102-SX
3	RIX-R	930	683-215	32	734 M from 105-SX, 116 M to 102-SX
4	RIX-R	936	688-216	32	
1-1972	RIX-R	931	683-216	32	
2	RIX-R	927	680-215	32	
3	RIX-R	916	672-212	32	
4	RIX-R	906	665-209	32	
1-1973	RIX-R	934	686-216	32	
2	RIX-R	926	680-214	32	
3 *	RIX-R	924	678-214	32	
4	RIX-R	969	712-225	32	

(2) (B) - Tank equipped for boiling waste.

* Leak detection drywell 41-10-01 drilled.

9 2 1 2 5 6 1 4 3

Waste Status Summary of 110-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	RIX-R	963	707-224	32	
2	RIX-R	951	698-221	32	
3	RIX-R	432	304-96	32	516 to 110-S
4	RIX-R	420	295-93	32	
1-1975	RIX-R	411	288-91	32	
2	RIX-R	406	284-90	32	
3	RIX-R	183	115-36	32	221 to 102-SX
4	EB-IX-BL-224-BNW	527	211-195-5-31-53	32	669 from 103-B, 603 from 103-BX, 283 from 105-BX, 1,215 to 102-SX
1-1976	EB-IX-224-BNW	95	4-57-1-1	32	322 from 103-BX, 778 to 102-SX, 23 from 241-302B
2	224-IX-EB-BL	334	12-104-177-9	32	367 from 103-B, 305 from 103-BX 442 to 102-SX
3	EVAP	65	33	32	Inactive
4	---	32	0	32	Questionable integrity - air-cooled
1-1977	---	32	0	32	Inactive air-cooled
2	---	32	0	32	Inactive air-cooled
3	---	32	0	32	Inactive air-cooled
4	---	32	0	32	Inactive air-cooled
1-1978	-	32	0	32	Primary Stabilized - Air Cooled
2-	-	32	0	32	
3-	-	32	0	32	
4-	-	32	0	32	
1-1979	-	32	0	32	
2-	-	32	0	32	
3-	-	32	0	32	Interim Stabilized
4-	-	62	0	62	Photo taken 11/6/79
1-1980	-	62	0	62	
2-	-	62	0	62	
3-	-	62	0	62	
4-	-	62	0	62	

Waste Status Summary of 111-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954					
	R	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.

Waste Status Summary of 111-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	---	---	---	---	
3	R	640	640	0	SS 578m gallons concentrating waste received.
4 *	R	895	895	0	Started cascading 10/27/56. 123m self-concentrating.
1-1957	R	807	807	0	88m self-concentrating.
2	R	741	741	0	66m self-concentrating.
3	R	700	700	0	41m self-concentrating.
4	R	675	675	0	22m self-concentrating.
1-1958	R	656	656	0	
2	R	642	642	0	14m self-concentrating.
3	R	631	631	29	16m self-concentrating.
4	R	105	105	29	1m to 103-U, 465m to 102 and 103-U, 60m to 102-U.
1-1959	R	285	285	0	Received 181m.
2	R	439	439	0	Received 243m, 89m self-concentrating.
	R	468	468	0	Received 257m, 156m self-concentrating.
4	R	555	555	0	Received 292m, 149m self-concentrating.
1-1960	R	632	632	0	Received 223m from 112-SX, 146m self-concentrating.
2	R	683	683	0	Received 60m condensate from 106-SX, also 43m water, 64m boiled off.
3	R	703	703	0	Received 76m, 16m boiled off.
4	R	703	703	0	Received 33m water boiled off 33m.
1-1961					6 months report.
2	R	659	659	0	
3					6 months report.
4	R	634	634	0	

* Leak detection drywell 41-11-10 drilled.

Waste Status Summary of 111-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					] 6 months report
2	R	686	686	0	]
3 *					] 6 months report
4	R	659	659	0	]
1-1963					] 6 months report
2	R	637	637	0	]
3					] 6 months report
4	R	616	616	0	]
1-1964					] 6 months report
2	R	123	123	0	] 202m sodium nitrite to 105-SX
3					] 6 months report
4	R	212	212	0	] Received 89m
1-1965					] 6 months report
2	R	519	495	24	] Received 548m; receiving at end end of June.
[illegible]	R	566	542	24	Received 275m.
[illegible]	R	631	607	24	Received 105m.
1-1966	R	651	627	24	
2	R	650	626	24	Received 123m water.
3	R	653	629	24	Received 199m water.
4	R	559	535	24	Received 179m water.
1-1967	R	640	616	24	
2	R	658	634	24	
3	R	651	627	24	
4	R	663	579	84	

* Leak detection dry wells 41-11-02, 41-11-03, 41-11-05, 41-11-06, 41-11-09 drilled.

Waste Status Summary of 111-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	647	563	84	(2) (B)
2	R	642	540	102	(2) (B)
3	R	810	722	88	145 M from 107-SX
4	R	807	717	90	
1-1969	R	944	854	90	Received 111 M from 112-SX
2	R	938	866	72	
3	R	938	866	72	
4	R	941	864	77	
1-1970	R	942	865	77	
2	R	942	871	77	
3	R	948	871	77	
4	R	957	880	77	
1-1971	R	944	867	77	
2	R	943	866	77	
3	R	372	295	77	564 M to 102-SX
4	EB-RIX	944	91-776	77	790 from 105-SX, 170 M from 106-SX, 376 M to 102-SX
1-1972	EB-RIX	939	90-772	77	
2	EB-RIX	944	91-776	77	
3	EB-RIX	920	88-755	77	
4	EB-RIX	908	87-744	77	
1-1973	EB-RIX	924	89-758	77	
2	EB-RIX	913	87-749	77	
3 *	EB-RIX	905	86-742	77	
4	EB-RIX	895	85-733	77	

(2) (B) Tank equipped for boiling waste.

* Leak detection dry well 41-11-08 drilled. Also 41-11-05 deepened.

Waste Status Summary of 111-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	EB-RIX	885	84-724	77	
2	EB-RIX	128	5-40	83	Tank leaks, 2 to 105-SX, (6)
3	---	128	0	128	Tank leaks
4	---	125	0	125	Tank leaks
1-1975	---	125	0	125	Tank leaks
2	---	125	0	125	Tank leaks
3	---	125	0	125	Tank leaks
4	---	125	0	125	Tank leaks
1-1976	---	125	0	125	Tank leaks
2	---	125	0	125	Tank leaks
3	---	125	0	125	Tank leaks, air-cooled
4	---	125	0	125	Tank leaks, air-cooled
1-1977	---	125	0	125	Tank leaks, air-cooled
2	---	125	0	125	Tank leaks, air-cooled
3	---	125	0	125	Tank leaks, air-cooled
4	---	125	0	125	Tank leaks stabilized Phase I

(6) 752 to 105-S

1-1978	-	125	0	125	Primary Stabilized - Air Cooled
2-	-	125	0	125	
3-	-	125	0	125	
4-	-	125	0	125	
1-1979	-	125	0	125	Photo taken 1/3/79
2-	-	125	0	125	
3-	-	125	0	125	Interim Stabilized
4-	-	125	0	125	New Photo 11/9/79
1-1980	-	125	0	125	
2-	-	125	0	125	
[illegible]-	-	125	0	125	
[illegible]-	-	125	0	125	

9212156149

Waste Status Summary of 112-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954					
	R	---	---	---	Tank not released to operations.
3	R	---	---	---	Tank not released to operations.
4	R	---	---	---	Tank not released to operations.
1-1955	R	---	---	---	Tank not released to operations.
2	R	---	---	---	Tank not released to operations.
3	R	---	---	---	Tank not released to operations.
4	R	---	---	---	Tank not released to operations.

9212561410

Waste Status Summary of 112-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	R	556	556	0	Self-evaporating, low MWD received for 28 days.
2	R	586	586	0	Self-evaporating, low MWD received for 28 days.
3 *	R	589	589	0	
4	R	977	977	0	7m self-concentrating.
1-1957	R	933	933	0	Received 10m, 54m self-concentrating.
2	R	893	893	0	40m self-concentrating.
3	R	876	876	0	17m self-concentrating.
4	R	865	865	0	11m self-concentrating.
1-1958	R	860	860	0	5m self-concentrating.
2	R	857	857	0	3m self-concentrating.
3	R	860	812	48	6m self-concentrating.
4	R	854	806	48	
1-1959	R	846	846	---	8m self-concentrating.
2	R	838	838	---	8m self-concentrating.
3	R	838	838	---	
	R	635	635	---	206m pumped to 111-SX, 3m self-concentrating.
1-1960	R	411	411	---	223m pumped to 111-SX.
2	R	241	241	---	Pumped 199m to 110-SX.
3	R	444	444	0	Received 201-M.
4	R	564	564	0	Received 169m, Redox SW, 49m self-concentrating.
1-1961					] 6 months report.
2	R	469	469	0	
3					] Received 437m.
4	R	472	472		] 6 months report.

* Leak detection dry well 41-12-04 drilled.

Waste Status Summary of 112-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					6 months report
2	R	719	719	0	331 M from 102-SX
3 *					6 months report
4	R	722	722	0	
1-1963					6 months report
2	R	717	717	0	
3					6 months report
4	R	723	723	0	
1-1964					6 months report
2	R	699	699	0	
3					6 months report
4	R	670	670	0	
1-1965					6 months report
2	R	637	564	73	
3	R	629	556	73	
4	R	629	556	73	
5 -1966	R	241	168	73	388 M to 102-SX
2	R	524	451	73	Received 281 M water from 202-S
3	R	596	523	73	Received 292 M from 202-S
4	R	626	553	73	Received 65 M plus 300 M water
1-1967	R	634	561	73	
2	R	623	550	73	
3	R	627	554	73	
4	R	647	604	43	

* Leak detection dry wells 41-12-02, 41-12-03, 41-12-06, 41-12-07, 41-12-09, 41-12-12 drilled.

9 2 1 2 5 5 6 1 4 4 2

Waste Status Summary of 112-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	628	565	43	(2) (B)
2	R	643	585	58	(2) (B)
3	R	646	582	54	
4	R	682	636	46	21 from 107SX
1-1969	R	121	82	39	Started leaking: Supernatant to 110SX, 111SX and 114SX
2	R	119	77	42	Tank leaks
3	R	120	85	35	Tank leaks
4	R	118	83	35	Tank leaks
1-1970	R	120	85	35	Tank leaks
2	R	120	85	35	Tank leaks
3	R	119	84	35	Tank leaks
4	R	117	82	35	Tank leaks
1-1971	R	119	84	35	Tank leaks
2	R	117	82	35	Tank leaks
3	R	118	83	35	Tank leaks
4	R	118	83	35	Tank leaks
1-1972	R	120	85	35	Tank leaks
2	R	121	86	35	Tank leaks
3	R	124	89	35	Tank leaks
4	R	121	86	35	Tank leaks
1-1973	R	125	90	35	Tank leaks
2	R	114	79	35	Tank leaks
3	R	119	84	35	Tank leaks
4	R	108	73	35	Tank leaks

(2) (B) Tank equipped for boiling waste.

Waste Status Summary of 112-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	R	108	73	35	Tank leaks
2	R	108	73	35	Tank leaks
3	---	112	0	112	Tank leaks
4	---	106	0	106	Tank leaks
1-1975	---	106	0	106	Tank leaks
2	---	106	0	106	Tank leaks
3	---	106	0	106	Tank leaks
4	---	106	-	106	Tank leaks
1-1976	---	106	0	106	Tank leaks
2	---	106	0	106	Tank leaks
3	---	106	0	106	Tank leaks, air-cooled
4	---	106	0	106	Tank leaks, air-cooled
1-1977	---	106	0	106	Tank leaks, air-cooled
2	---	106	0	106	Tank leaks, air-cooled
3	---	106	0	106	Tank leaks, air-cooled
4	---	106	0	106	Tank leaks, stabilized Phase I
1-1978	-	106	0	106	Primary Stabilized - Air Cooled
2-	-	106	0	106	
3-	-	106	0	106	
4-	-	106	0	106	
1-1979	-	106	0	106	
2-	-	106	0	106	
3-	-	106	0	106	Interim Stabilized
4-	-	106	0	106	
1-1980	-	106	0	106	
2-	-	106	0	106	
3-	-	106	0	106	
4-	-	106	0	106	

9 2 1 2 5 5 6 1 4 4 4

Waste Status Summary of 113-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	R	---	---	---	Tanks not released to operations.
1-1955	R	---	---	---	Tanks not released to operations.
2	R	---	---	---	Tanks not released to operations.
3	R	---	---	---	Tanks not released to operations.
4	R	---	---	---	Tanks not released to operations.

9 2 1 2 5 5 6 1 4 4 5

Waste Status Summary of 113-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1957	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1958	R	191	191	---	191m received.
2 *	R	321	321	---	292m received, 62m (est.) self-concentrating.
3	R	3	3	---	305m to 108-SX, 13m (est.) self-concentrating. Tank bulged.
4	R	1	1	---	
1-1959	R	0	0	---	Tank bulged.
2	R	0	0	---	Tank bulged.
3	R	0	0	---	Tank bulged.
	R	0	0	---	Tank bulged.
1-1960	R	0	0	---	Tank bulged.
2	R	0	0	---	Tank bulged.
3	R	0	0	---	Tank bulged.
4	R	0	0	---	Tank bulged.
1-1961					6 months report.
2	R	0	0	---	
3					6 months report.
4	R	0	0	---	

* Leak detection dry well 41-13-10 drilled.

9 2 1 2 5 5 6 1 4 4 4 6

Waste Status Summary of 113-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					] 6 months report
2	R	0	0	0	] Tank leaks
3					] 6 months report
4	R	11	11	0	] Tank leaks
1-1963					] 6 months report
2	R	11	11	0	] Tank leaks
3					] 6 months report
4	R	9	9	0	] Tank leaks
1-1964					] 6 months report
2	R	9	9	0	] Tank leaks
3					] 6 months report
4	R	9	9	0	] Tank leaks
1-1965					] 6 months report
2	R	26	23	3	] Tank leaks
3	R	26	23	3	Tank leaks
4	R	26	23	3	Tank leaks
-1966	R	26	23	3	Tank leaks
2	R	26	23	3	Tank leaks
3	R	26	23	3	Tank leaks
4	R	37	34	3	Tank leaks
1-1967	R	37	34	3	Tank leaks
2	R	37	34	3	Tank leaks
3	R	36	33	3	Tank leaks
4	R	32	29	3	Tank leaks

9 2 1 2 5 6 1 1 4 7

Waste Status Summary of 113-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	29	26	3	(2) (B) Tank leaks
2	R	26	23	3	(2) (B) Tank leaks
3	R	25	21	3	Tank leaks
4	R	24	21	3	Tank leaks
1-1969	R	24	21	3	Tank leaks
2	R	21	18	3	Tank leaks
3	R	20	17	3	Tank leaks
4	R	20	18	2	Tank leaks
1-1970	R	18	16	2	Tank leaks
2	R	18	16	2	Tank leaks
3	R	17	15	2	Tank leaks
4	R	17	15	2	Tank leaks
1-1971	R	17	15	2	Tank leaks
2	R	2	0	2	Tank leaks
3	R	2	0	2	Tank leaks
4	----	2	0	2	Tank leaks
1-1972	----	2	0	2	Tank leaks approximately 24 tons of diatomaceous earth added 113SX
2	----	2	0	2	
3	----	2	0	2	Tank leaks. Contains diatomaceous earth
4	----	2	0	2	Tank leaks. Contains diatomaceous earth
1-1973	----	2	0	2	Tank leaks. Contains diatomaceous earth
2	----	2	0	2	Tank leaks. Contains diatomaceous earth
3	----	2	0	2	Tank leaks. Contains diatomaceous earth
4	----	2	0	2	Tank leaks. Contains diatomaceous earth

(2) (B) - Tank equipped for boiling waste.

Waste Status Summary of 113-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	2	0	2	Tank leaks, contains diatomaceous earth
2	---	2	0	2	Tank leaks, contains diatomaceous earth
3	---	2	0	2	Tank leaks, contains diatomaceous earth
4	---	6	0	6	Tank leaks, contains diatomaceous earth
1-1975	---	6	0	6	Tank leaks, contains diatomaceous earth
2	---	6	0	6	Tank leaks, contains diatomaceous earth
3	---	6	0	6	Tank leaks, contains diatomaceous earth
4	---	6	0	6	Tank leaks, contains diatomaceous earth
1-1976	---	6	0	6	Tank leaks, contains diatomaceous earth
2	---	6	0	6	Tank leaks, contains diatomaceous earth
3	---	10	0	10	Leaker cont. deseccant
4	---	10	0	10	Leaker cont. deseccant
1-1977	---	10	0	10	Tank leaks, desiccant addition complete
2	---	10	0	10	Isolated & stabilized, tank leaks
3	---	10	0	10	Tank leaks, isolated Phase A stabilized Phase I
4	---	10	0	10	Tank leaks, isolated Phase A stabilized Phase I
1-1978	-	10	0	10	Primary Stabilized- Partizlly Interim Stabilized
2-	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	
1-1979	-	10	0	10	
2-	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	
1-1980	-	10	0	10	New Photo 1/24/80
20	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	

9 2 1 2 5 5 6 1 4 4 9

Waste Status Summary of 114-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	R	---	---	---	Tanks not released to operations.
2	R	---	---	---	Tanks not released to operations.
3	R	---	---	---	Tanks not released to operations.
4	R	---	---	---	Tanks not released to operations.

9 2 1 2 5 5 6 1 4 5 0

Waste Status Summary of 114-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3 *	---	---	---	---	Tank not released to operations.
4	---	---	---	--	Tank not released to operations.
1-1957	R	220	220	0	Received 43m and was receiving end of March.
2	R	370	370	0	Received 194m, 36m self-concentrating.
3	R	675	675	0	Received 368m, 63m self-concentrating.
4	R	623	623	0	Received 206m, 258m self-concentrating.
1-1958	R	579	579	0	Received 194m, 238m self-concentrating.
2	R	601	601	0	Received 198m, 179m self-concentrating receiving at end of month.
3	R	722	721	1	Received 188m, 252m self-concentrating, 76m boiled off.
4	R	733	732	1	64m water received, receiving at end of September, 254m water boiled off.
-1959	R	761	761	---	Received 185m, 157m water boiled off.
2	R	783	783	0	Received 80m, 58m water boiled off.
3	R	804	804	0	Received 142m, 32m self-concentrating, 89m water boiled off.
4	R	796	796	0	Received 20m, 20m water boiled off.
1-1960	R	797	797	0	40m received, 12m water added, 51m boiled off.
2	R	801	801	0	Received 54m condensate, 33m boiled off.
3	R	793	793	0	Received 8m water.
4	R	820	820	0	Received 104m,boiled off 83m.
1-1961					] 6 months report.
2	R	807	806	0	
3					] 6 months report.
4	R	326	326	0	] 724m to 103-SX.

* Leak detection dry well 41-14-04 drilled.

9 2 1 2 5 5 6 1 4 5 1

Waste Status Summary of 114-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					] 6 months report
2	R	312	312	0	]
3 *					] 6 months report
4	R	480	480	0	] Several transfers during period
1-1963					] 6 months report
2	R	16	16	0	] 219 M from 107-SX, 619 M to 105-SX
3					] 6 months report
4		11	11	0	
1-1964					] 6 months report
2	R	388	388	0	] Received 285 M
3					] 6 months report
4	R	708	708	0	] Received 975 M
1-1965					] 6 months report
2	R	645	624	21	] Received 321 M
3	R	645	624	21	
4	R	664	643	21	Received 345 M water
-1966	R	651	630	21	
2	R	631	610	21	Received 91 M water
3	R	631	610	21	
4	R	645	624	21	Received 193 M water
1-1967	R	648	627	21	
2	R	650	629	21	
3	R	648	627	21	
4	R	654	597	57	

* Leak detection dry wells 41-14-02, 41-14-03, 41-14-06, 41-14-08, 41-14-09 and 41-14-11 drille

9 2 1 2 5 5 6 1 4 5 2

Waste Status Summary of 114-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	638	581	57	(2) (B)
2	R	638	511	127	
3	R	671	587	84	
4	R	676	596	80	
1-1969	R	935	855	80	Received 248 from 112-SX
2	R	941	758	183	
3	R	948	744	204	
4	R	943	739	204	
1-1970	R	944	740	204	
2	R	947	743	204	
3	R	942	738	204	
4	R	950	746	204	
1-1971	R	945	741	204	
2	R	942	742	200	
3	R	950	750	200	
4	R	449	249	200	492 M to 102-SX
1-1972	EB-RIX-R	527	38-144-145	200	67 M from 105-SX, 192 M from 106-SX, 171 M to 113-SX
2	EB-RIX-R	937	123-465-149	200	392 M from 106-SX
3	EB-RIX-R	480	47-177-56	200	437 M to 101-T
4	EB-RIX-R	204	1-2-1	200	254 M to 101-T
1-1973	---	200	0	200	
2	---	200	0	200	
3	---	200	0	200	
4	---	200	0	200	

(2) (B) Tank equipped for boiling waste.

9 2 1 2 5 5 6 1 4 5 3

Waste Status Summary of 114-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Fol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	200	0	200	Suspect leaker
2	---	200	0	200	Suspect leaker
3	---	200	0	200	Suspect leaker
4	---	200	0	200	Suspect leaker
1-1975	---	200	0	200	Suspect leaker
2	---	200	0	200	Suspect leaker
3	---	200	0	200	Removed from service
4	---	200	0	200	Removed from service
1-1976	---	200	0	200	Removed from service
2	---	200	0	200	Removed from service
3	---	200	0	200	Air-cooled
4	---	200	0	200	Questionable integrity, air-cooled
1-1977	---	200	0	200	Inactive, air-cooled
2	---	200	0	200	Inactive, air-cooled
3	---	200	0	200	Inactive, air-cooled
4	---	200	0	200	Inactive, air-cooled stabilized Phase
1-1978	-	200	0	200	Primary Stabilized - Air Cooled
2-	-	200	0	200	
3-	-	200	0	200	
4-	-	200	0	200	
1-1979	-	200	0	200	Photo taken 1/3/79
2-	-	200	0	200	
3-	-	200	0	200	Interim Stabilized
4-	-	200	0	200	
1-1980	-	200	0	200	
2-	-	200	0	200	
3-	-	200	0	200	
4-	-	200	0	200	

9 2 1 2 5 5 6 1 4 5 4

Waste Status Summary of 115-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2					
3					
4					
1-1953					
2					
3					
4					
1-1954	---	---	---	---	Tanks not released to operations.
	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.
1-1955	---	---	---	---	Tanks not released to operations.
2	---	---	---	---	Tanks not released to operations.
3	---	---	---	---	Tanks not released to operations.
4	---	---	---	---	Tanks not released to operations.

9 2 1 2 5 5 6 1 4 5 5

Waste Status Summary of 115-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1956	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1957	---	---	---	---	Tank not released to operations.
2	---	---	---	---	Tank not released to operations.
3	---	---	---	---	Tank not released to operations.
4	---	---	---	---	Tank not released to operations.
1-1958	---	---	---	---	Tank not released to operations.
2	---	---	--	---	Tank not released to operations.
3	R	200	200	---	147m received and 51m water.
4	R	263	263	---	Latest electrode reading.
1-1959	R	243	243	---	20m decreased from air sparging.
2	R	234	234	---	9m decreased from air sparging.
3	R	227	227	---	7m decreased from air sparging.
4	R	439	439	---	Received 212m and was receiving at end of December.
1-1960	R	475	475	---	Received 246m salt waste, 210m boiled off.
2	R	547	547	---	Received 309m salt waste, 240m boiled off.
3	R	631	631	---	Received 244m from 106 and 109-SX, 160m boiled off.
4	R	643	643	---	Received 122m, boiled off 87m.
1-1961					6 months report.
2	R	645	645	---	
3					6 months report.
4	R	667	667	---	Received 90m from 102-SX.

9212556145 6

Waste Status Summary of 115-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1962					6 months report
2	R	675	675	0	
3					6 months report
4 *	R	684	684	0	
1-1963 **					6 months report
2	R	700	700	0	65 M to 202-S dissolvers
3					6 months report
4	R	702	702	0	Received 23 M water
1-1964					6 months report
2	R	192	192	0	574 M to 102-SX
3					6 months report
4	R	117	117	0	208 M to 105-SX
1-1965					6 months report
2	R	8	5	3	52 M to 105-SX, Tank leaks
3	R	8	5	3	Tank leaks
4	R	8	5	3	Tank leaks
.-1966	R	8	5	3	Tank leaks
2	R	6	3	3	Tank leaks
3	R	6	3	3	Tank leaks
4	R	14	11	3	Tank leaks
1-1967	R	14	11	3	Tank leaks
2	R	19	16	3	Tank leaks
3	R	19	16	3	Tank leaks
4	R	19	16	3	Tank leaks

* Leak detection dry wells 41-15-02, 41-15-03, 41-15-05, 41-15-07, 41-15-09 drilled.

** Leak detection dry well 41-15-10 drilled.

9212556145 7

Waste Status Summary of 115-SX Tank Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	R	6	3	3	(2) (B) Tank leaks
2	R	6	3	3	(2) (B) Tank leaks
3	R	6	3	3	Tank leaks
4	R	6	3	3	Tank leaks
1-1969	R	6	3	3	Tank leaks
2	R	5	2	3	Tank leaks
3	R	6	0	6	Tank leaks
4	R	6	0	6	Tank leaks
1-1970	R	6	0	6	Tank leaks
2	R	6	0	6	Tank leaks
3	---	6	0	6	Tank leaks
4	---	6	0	6	Tank leaks
1-1971	---	6	0	6	Tank leaks
2	---	6	0	6	Tank leaks
3	---	6	0	6	Tank leaks
4	---	6	0	6	Tank leaks
-1972	---	6	0	6	Tank leaks
2	---	6	0	6	Tank leaks
3	---	6	0	6	Tank leaks
4	---	6	0	6	Tank leaks
1-1973	---	6	0	6	Tank leaks
2	---	6	0	6	Tank leaks
3	---	6	0	6	Tank leaks
4	---	6	0	6	Tank leaks

(2) (B) Tank equipped for boiling waste.

9 2 1 2 5 5 6 1 4 5 8

Waste Status Summary of 115-SX Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1974	---	6	0	6	Tank leaks
2	---	8	0	8	Tank leaks
3	---	8	0	8	Tank leaks
4	---	6	0	6	Tank leaks
1-1975	---	6	0	6	Tank leaks
2	---	6	0	6	Tank leaks
3	---	6	0	6	Tank leaks
4	---	6	0	6	Tank leaks
1-1976	---	6	0	6	Tank leaks
2	---	6	0	6	Tank leaks
3	---	10	0	10	Tank leaks, air-cooled
4	---	10	0	10	Tank leaks, air-cooled
1-1977	---	10	0	10	Tank leaks, air-cooled
2	---	10	0	10	Isolated & stabilized
3	---	10	0	10	Tank leaks, isolated & stabilized
4	---	10	0	10	Tank leaks, stabilized Phase I air-cooled
1-1978	-	10	0	10	Primary Stabilized-Partially Interim Isolated
2-	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	
1-1979	-	10	0	10	
2-	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	
1-1980	-	10	0	10	
2-	-	10	0	10	
3-	-	10	0	10	
4-	-	10	0	10	

9212556145 9

Waste Status Summary of SY-101 Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	0	0	0	0	Under construction
2-	RESID	263	250	13	Slurry Receiver
3-	RESID	271	245	26	Slurry Receiver
4-	REDIS	653	539	114	DLB Shell slurry
1-1978	HDRL	662	548	114	Double Shell Slurry
2-	DSS	802	688	114	
3-	DSS	877	742	135	
4-	DSS	869	734	135	Photo taken 12-18-78
1-1979	DSS	872	737	135	
2-	DSS	872	737	135	
3-	CCPLX	897	201	*696	
4-	CCPLX	872	176	*696	
1-1980	DSS	913	217	*696	New Photo 2-11-80
2-	DSS	889	193	*696	
3-	CCPLX	890	194	*696	
4-	CCPLX	1131	435	*696	

* 561,000 gals. of the solids is DSS but must be considered a solid since it represents an Interim Product form.

9212556146 0

Waste Status Summary of 102-SY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	0	0	0	0	Under Construction
2-	EVAP	216	216	0	EVAP Feed Tank
3-	EVAP	51	51	0	EVAP Feed Tank
4-	EVAP	505	484	21	EVAP Feed Tank
1-1978	PNF	499	412	87	Photo taken 2-8-78
2-	NCPLX	414	327	87	Evap. Feed Tank
3-	NCPLX	616	539	77	Solid Level Adjusted
4-	MC°:X	99	16	83	Solid Level Determination 11/21/78
1-1979	NCPLX	195	112	83	
2-	NCPLX	971	888	83	Photo taken 6/13/79
3-	PNF	154	49	105	
4-	NCPLX	971	888	83	
1-1980	PNF	701	596	105	
2-	PNF	398	293	105	
3-	PNF	459	354	105	
4-	DSSF	659	554	105	

9 2 1 2 5 5 6 1 4 6 1

Waste Status Summary of 103-SY Tank-Capacity 1,000,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	0	0	0	0	Under Construction
2-	RESID	274	274	0	HI SR Waste Conc.
3-	RESID	274	274	0	" " "
4-	RESID	274	274	0	" " "
1-1978	CCPLX	937	937	0	
2-	CCPLX	937	937	0	
3-	CCPLX	960	960	0	
4-	CCPLX	963	963	0	
1-1979	CCPLX	954	954	0	
2-	CCPLX	954	954	0	Photo taken 6-13-79
3-	CCPLX	960	960	0	
4-	CCPLX	954	954	0	
1-1980	CCPLX	960	960	0	
2-	CCPLX	837	837	0	
3-	CCPLX	123	123	0	
4-	DSS	543	410	*135	

* 135,000 gals. of the solids is Double Shell Slurry, but must be considered a solid since it represents an Interim Product Form.

9 2 1 2 5 5 6 1 4 6 2

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	MW	135	---	---	101,102,103 in Cascade, began filling Dec. 44.
2	MW	317	---	---	101,102,103 in Cascade.
3	MW	527	---	---	101,102,103 in Cascade, began overflow to 102 in Sept.
4	MW	528	---	---	Cascade began overflow to 103 in Nov.
1-1946	MW	528	---	---	Cascade 103 full in Feb. 46.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	Cascade full.
4	MW	528	---	---	Cascade full.
1-1947	MW	528	---	---	Cascade full.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	Cascade full.
4	MW	528	---	---	Cascade full.
1-1948	MW	528	---	---	Cascade full.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	Cascade full.
4	MW	528	---	---	Cascade full.
1-1949	MW	528	---	---	Cascade full.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	Cascade full.
4	MW	528	---	---	Cascade full.
1-1950	MW	528	---	---	Cascade full.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	Cascade full.
4	MW	528	---	---	Cascade full.
1-1951	MW	528	---	---	Cascade full.
2	MW	528	---	---	Cascade full.
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 5 5 5 6 1 4 6 3

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1952	---	---	---	---	
2	MW	530	---	---	
3	MW	530	---	---	
4	MW	530	---	---	
1-1953	MW	530	---	---	
2	MW	169	169	---	Metal waste removal in process.
3	---	---	---	---	
4	TBP	20	20	---	Unconcentrated, scavenged TBP waste for test. 256,000 gallons cribbed. Remainder except heel pumped to 107-T. Flushed 3 times to 107-T.
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	MW	417	417	---	Rec'd T Plant metal waste.
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	
1-1956	MW	530	530	---	To be sluiced soon.
2	MW	20	10	10	Sluicing began this month.
3					Sluicing continued.
3	MW	3	1	2	Heel to be sluiced.
4	---	---	---	---	Active sluicing.
1-1957	---	---	---	---	
2	CW	59	59	---	New electrode reading.
3	CW	57	57	---	Latest electrode reading.
4	CW	57	57	---	
1-1958	CW	57	57	---	
2	CW	57	57	---	
3	CW	57	57	----	
4	CW	46	46	---	New electrode reading.
1-1959	CW	45	45	---	
2	CW	45	45	---	
3	CW	45	45	---	
4	CW	45	45	---	

9 2 1 2 5 5 6 1 4 6 4

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1960	CW	45	45	---	
2	CW	45	45	---	
3	CW	45	45	---	
4	CW	48	48	---	
1-1961	---	---	---	---	
2	CW	51	51	---	
3	---	---	---	---	
4	CW	51	51	---	
1-1962	---	---	---	---	
2	CW	51	51	---	
3	---	---	---	---	
4	CW	51	51	---	
1-1963	---	---	---	---	
2	CW	507	507	---	432M from 108-U.
3	---	---	---	---	
4	CW	507	507	---	
1-1964	---	---	---	---	
2	CW	507	507	---	
3	---	---	---	---	
4	CW	532	532	---	
1-1965	---	---	---	---	
2	CW	535	535	---	
3	CW	535	535	---	
4	CW	535	535	---	
1-1966	CW	535	535	---	
2	CW	535	535	---	
3	CW	535	535	---	
4	CW	535	535	---	
1-1967	CW	535	535	---	
2	CW	535	535	---	
3	CW	535	535	---	
4	CW	535	535	---	
1-1968	CW	537	537	---	
2	CW	536	536	---	
3	CW	536	536	---	
4	CW	538	538	---	

9 2 1 2 5 5 6 1 4 6 5

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	CW	539	539	---	
2	CW	92	92	---	447 to 103-T.
3	CW	94	94	---	
4	CW	94	57	37	
1-1970	CW	96	59	37	
2	CW	96	59	37	
3	CW	96	59	37	
4	CW	96	59	37	
1-1971	CW	97	60	37	
2	CW	96	59	37	
3	CW	97	60	37	
4	CW	98	61	37	
1-1972	CW	98	61	37	
2	CW	98	61	37	
3	BL-IX-EB-RIX-R	243	24-14-7-26-8	37	498 from 101-BX, 437 from 114-SX, 3 flush water, 489 to 102-T, 305 to 103-T.
4	BL-IX-EB-RIX-R	312	2-14-44-163-52	37	254 from 114-SX, 182 to 103-T.
1-1973	BL-IX-EB-RIX-R	312	2-14-44-163-52	37	
2 *	BL-IX-EB-RIX-R	340	2-15-48-180-58	37	
3	BL-IX-EB-RIX-R	311	2-14-43-163-52	37	
4	BL-IX-EB-RIX-R	312	2-14-43-164-52	37	
1-1974	BL-IX-EB-RIX-R	313	2-14-43-165-52	37	
2	BL-IX-EB-RIX-R	313	2-14-43-165-52	37	
3	CW-IX-EB-RIX-R-DW BL	259	11-84-18-65-20-5-19	37	139 from 103-T, 37 from 106-T, 230 to 110-S.
4	CW-IX-EB-RIX-R-DW BL	260	11-85-18-65-20-5-19	37	

* Dry Wells No.s 50-01-02, 50-01-04, 50-01-06, 50-01-09 and 50-01-12 were drilled.

9 2 1 2 5 5 6 1 4 6 6

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1975	CW-IX-EB-BL-RIX-R-DW-BNW	189	4-63-7-33-26-8-2-9	37	122 from 108-T, 41 from 109-T, 230 from 106-SX.
2	CW-IX-EB-BL-RIX-R-DW-BNW	208	4-68-7-38-26-8-2-18	37	6 from 108-T, 12 from 109-T.
3	CW-IX-EB-BL-RIX-R-DW-BNW	208	4-68-7-38-26-8-2-18	37	
4	CW-IX-EB-BL-RIX-R-DW-BNW	208	4-68-7-38-26-8-2-18	37	
1-1976	224-CW-IX-EB-BL-RIX-R-DW-BNW	337	67-5-114-8-43-29-9-2-23	37	2 from 102-T, 15 from 104-T, 1 from 105-T, 31 from 107-T, 2 from 109-T, 9 from 110-T, 8 from 111-T, 21 from 201-T, 27 from 202-T, 1 from 203-T, 15 from Ct, 241-T-301-8 1 from 204T.
2	IX-224	329	209-83	37	2 from 102-T, 189 from 107-T, 3 from 109-T, 8 from 110-T, 5 from 111-T, 1 from 201-T, 1 from 202-T, 8 from 203-T, 5 from 204-T.
3	Evap.	387	350	37	
4	Evap.	403	366	37	Int. liquid storage.
1-1977	Evap.	156	116	40	" " " "
2	Evap.	161	121	40	" " " "
3	Evap.	222	160	62	" " " "
4	Evap.	249	146	103	" " " "

9 2 1 2 5 5 6 1 4 6 7

Waste Status Summary of 101-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NCPLX	252	149	103	Active - Salt Well Recvr. Photo taken 3-15-78
2-	NCPLX	268	165	103	
3-	NCPLX	220	129	91	Solid Level Adjusted 9-10-78
4-	NCPLX	244	141	103	
1-1979	NCPLX	208	105	103	
2-	NPCLX	246	143	103	Photo taken 6-1-79
3-	NCPLX	246	143	103	Inactive
4-	NCPLX	246	143	103	
1-1980	NCPLX	131	28	103	
2-	NCPLX	131	28	103	
3-	NCPLX	131	28	103	
4-	NCPLX	131	28	103	

9 2 1 2 5 5 6 1 4 6 8

Waste Status Summary of 102-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	MW	130	---	---	Began overflow in Sept.
4	MW	528	---	---	Began overflow to 103 in Nov.
1-1946	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1947	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1948	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1949	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1950	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1951	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	-0-	
3	MW	530	530	---	
4	MW	530	530	---	

9 2 1 2 5 5 6 1 4 6 9

Waste Status Summary of 102-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	MW	530	---	---	
2	MW	436	436	---	Metal waste removal in process.
3	---	1	-0-	1	Metal waste removal in process.
4	---	---	---	---	Declared empty on 12-10-53
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	MW	530	530	---	Started receiving 4-22.
3	MW	530	530	---	
4	MW	530	530	---	
1-1956	MW	530	530	---	
2	MW	30	20	10	Supernatant pumped to 115-TX. Sluicing initiated.
3	MW	3	1	2	Heel to be sluiced.
4	---	---	---	---	Active sluicing, sluiced mt.
1-1957	---	---	---	---	
2	CW	38	38	---	New electrode reading.
3	CW	26	26	---	Latest electrode reading.
4	CW	26	26	---	
1-1958	---	---	---	---	New electrode reading.
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1959	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1960	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1961	---	---	---	---	Installed new electrode.
2	CW	40	40	---	
3	---	---	---	---	
4	---	---	---	---	Latest electrode reading.

9 2 1 2 5 5 6 1 4 7 0

Waste Status Summary of 102-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1963	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1964	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	CW	90	90	---	
1-1965	---	---	---	---	
2	CW	535	535	---	445m CW from 102-C.
3	CW	535	535	---	
4	CW	535	535	---	
1-1966	CW	535	535	---	
2	CW	535	535	---	
3	CW	535	535	---	
4	CW	535	535	---	
1-1967	CW	535	535	---	
2	CW	535	535	---	
3	CW	535	535	---	
4	CW	535	535	---	
1-1968	CW	536	536	---	
2	CW	536	536	---	
3	CW	536	536	---	
4	CW	537	537	---	
1-1969	CW	538	538	---	
2	CW	538	538	---	
3	CW	42	42	---	497 to 103-T.
4	CW	43	19	24	
1-1970	CW	44	20	24	
2	CW	44	20	24	
3	CW	44	20	24	
4	CW	44	20	24	

9 2 1 2 5 5 6 1 4 7 1

Waste Status Summary of 102-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	CW	46	22	24	
2	CW	44	20	24	
3	CW	46	22	24	
4	CW	46	22	24	
1-1972	CW	46	22	24	
2	CW	46	22	24	
3	BL-IX-EB-RIX--R-CW	524	29-167-40-147-45-83	13	489 from 101-T.
4	BL-IX-EB-RIX-R-CW	533	29-166-40-146-45-83	24	
1-1973	BL-IX-EB-RIX-R-CW	534	29-167-40-146-45-83	24	
2 *	BL-IX-EB-RIX-R-CW	536	29-168-40-147-45-83	24	
3	BL-IX-EB-RIX-R-CW	532	29-166-40-146-45-82	24	
4	BL-IX-EB-RIX-R-CW	534	29-167-40-147-45-82	24	
1-1974	BL-IX-EB-RIX-R-CW	534	29-167-40-147-45-82	24	
2 **	BL-IX-EB-RIX-R-CW	60	2-12-3-10-3-6	24	475 to 110-S.
3	IX	60	1	59	
4	---	59	0	59	
1-1975	IX	62	3	59	
2	IX	62	3	59	
3	IX	62	3	59	
4	IX	62	3	59	
1-1976	IX	62	3	59	Removed from service 2 to 101-T.
2	---	62	0	62	Removed from service 2 to 101-T.
3	---	62	0	62	Inactive salt well pumping.
4	---	62	0	62	
1-1977	---	62	0	62	Salt well, pump
2	---	62	0	62	" " "
3	---	62	0	62	Inactive cur
4	---	62	0	62	Salt well installed

* Dry Wells No. 50-02-08 and 50-02-09 were drilled.

** Dry Wells No. 50-02-02, 50-02-05, 50-02-10 and 50-02-12 were drilled.

9 2 1 2 5 5 6 1 4 7 2

Waste Status Summary of 102-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	62	0	62	Inactive-Salt Well Instld
2-	-	62	0	62	
3-	-	50	0	50	
4-	-	15	0	15	Solids Level Adj. 11-30-78, Liquid Pool Photo taken 10-17-78
1-1979	-	15	0	15	Primary stabilized
2-	-	15	0	15	
3-	-	15	0	15	
4-	-	15	0	15	
1-1980	-	15	0	15	
2-	-	15	0	15	New photo 4-30-80 (liq. pool)
3-	-	15	0	15	
4-	0	15	0	15	

9 2 1 2 1 5 6 1 4 7 3

Waste Status Summary of 103-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	----	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	268	---	---	Began Cascade in Nov.
1-1946	MW	528	---	---	Full in Feb. 46.
2	MW	528	---	---	Cascade full.
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1947	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1948	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1949	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1950	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	MW	528	---	---	" "
4	MW	528	---	---	" "
1-1951	MW	528	---	---	Cascade full.
2	MW	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	519	---	---	
3	MW	519	---	---	
4	MW	519	---	---	

9212561474

Waste Status Summary of 103-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	MW	519	---	---	
2	MW	519	519	---	Metal waste removal in process.
3	MW	241	241	---	Metal waste removal in process.
4	---	---	---	---	Declared empty on 12-15-53.
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	MW	521	521	---	Filled on 6-20-55.
3	MW	521	521	---	
4	MW	521	521	---	Enough for 106-TU.
1-1956	MW	521	521	---	
2	MW	40	35	5	Supernatant pumped to 115-TX
3	MW	40	39	1	Heel to be sluiced.
4	MW	46	46	---	Heel to be sluiced. Active sluicing. H_2O soaking sludge.
1-1957	MW	24	24	---	H_2O soaking sludge to be declared mt. - sluicing water.
2	CW	15	15	---	New electrode reading.
3	CW	15	15	---	Latest electrode reading.
4	CW	15	15	---	
1-1958	CW	15	15	---	
2	CW	15	15	---	
3	CW	15	15	---	
4	CW	15	15	---	
1-1959	---	---	---	---	Latest electrode reading.
2	CW	18	18	---	
3	CW	18	18	---	
4	CW	18	18	---	
1-1960	CW	18	18	---	
2	CW	18	18	---	
3	CW	18	18	---	
4	CW	18	18	---	
1-1961	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	CW	18	18	---	Latest electrode reading.

9212556147 5

Waste Status Summary of 103-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1962	---	---	---	---	
2	CW	18	18	---	
3	---	---	---	---	
4	CW	18	18	---	
1-1963	---	---	---	---	
2	CW	18	18	---	
3	---	---	---	---	
4	CW	18	18	---	
1-1964	---	---	---	---	
2	CW	18	18	---	
3	---	---	---	---	
4	CW	18	18	---	
1-1965	---	---	---	---	
2	CW	345	345	---	327m CW from 102-C.
3	CW	532	532	---	187m from 102-C.
4	CW	524	524	---	Latest electrode reading.
1-1966	CW	524	524	---	
2	CW	521	521	---	Latest electrode reading.
3	CW	521	521	---	
4	CW	521	521	---	
1-1967	CW	521	521	---	
2	CW	519	519	---	
3	CW	519	519	---	
4	CW	519	519	---	
1-1968	CW	518	518	---	
2	CW	516	516	---	
3	CW	516	516	---	
4	CW	515	515	---	
1-1969	CW	515	515	---	
2	CW	497	497	---	447 from 101-T; 465 to 103-TY.
3	CW	50	50	---	497 from 102-T; 945 to 103-TY.
4	CW	50	32	18	
1-1970	CW	50	32	18	
2	CW	50	32	18	
3	CW	50	32	18	
4	CW	51	33	18	

9 2 1 2 5 5 6 1 4 7 6

Waste Status Summary of 103-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1971	CW	51	33	18	
2	CW	52	34	18	
3	CW	51	33	18	
4	CW	51	33	18	
1-1972	CW	51	33	18	
2	CW	51	33	18	
3	BL-IX-EB-RIX-R-CW	356	20-120-28-105-32-33	18	305 from 101-T.
4	BL-IX-EB RIX-R-CW	538	41-245-34-128-39-33	18	182 from 101-T.
1-1973	BL-IX-EB-RIX-R-CW	536	41-243-34-128-39-33	18	
2 *	BL-IX-EB-RIX-R-CW	556	43-252-35-133-41-34	18	
3	BL-IX-EB-RIX-R-CW	520	40-235-33-124-38-32	18	32 to 107-U.
4	BL-IX-EB-RIX-R-CW	519	40-234-33-124-38-32	18	
1-1974	BL-IX-EB-RIX-R-CW	516	40-232-33-123-38-32	18	
2 **	BL-IX-EB-RIX-R-CW	165	12-69-10-36-11-9	18	354 to 110-S.
3	BL-IX-RIX	26	1-4-3	18	139 to 101-T.
4	---	35	0	35	Removed from service.
1-1975	---	35	0	35	Removed from service.
2	---	35	0	35	" " "
3 ***	---	35	0	35	" " "
4	---	35	0	35	" " "
1-1976	---	35	0	35	Removed from service.
2	---	35	0	35	" " "
3	---	35	0	35	Inactive.
4	---	35	0	35	
1-1977	---	35	0	35	Inactive
2	---	35	0	35	"
3	---	35	0	35	"
4	---	35	0	35	"

* Dry Wells No.s 50-03-04 and 50-03-05 were drilled.

**Dry Wells No.s 50-03-01, 50-03-08 and 50-03-10 were drilled.

***Dry Well No. 50-03-06 was drilled.

9 2 1 2 5 5 6 1 4 7 7

Waste Status Summary of 103-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	35	0	35	Inactive - Prim. Stab.
2-	-	35	0	35	
3-	-	22	0	22	
4-	-	35	0	35	
1-1979	-	35	0	35	
2-	-	35	0	35	Questionable Integrity
3-	-	35	0	35	
4	-	35	0	35	
1-1980	-	35	0	35	
2-	-	35	0	35	
3-	-	35	0	35	
4-	-	35	0	35	

9212556147 3

Waste Status Summary of 104-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	104,105,106 in Cascade.
2	---	---	---	---	" " " " "
3	---	---	---	---	" " " " "
4	---	---	---	---	" " " " "
1-1946	IC	49	---	---	Cascade filling March 46.
2	IC	49	---	---	" " " "
3	IC	528	---	---	Full in August.
4	IC	528	---	---	Full Cascade.
1-1947	IC	528	---	---	Full Cascade.
2	IC	528	---	---	" "
3	IC	528	---	---	" "
4	IC	528	---	---	" "
1-1948	IC	528	---	---	Full Cascade.
2	IC	528	---	---	" "
3	IC	528	---	---	" "
4	IC	528	---	---	" "
1-1949	IC	528	---	---	Full Cascade.
2	IC	528	---	---	" "
3	IC	528	---	---	" "
4	IC	528	---	---	" "
1-1950	IC	528	---	---	Full Cascade.
2	IC	528	---	---	" "
3	IC	528	---	---	" "
4	IC	528	---	---	" "
1-1951	IC	528	---	---	Full Cascade.
2	IC	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 3 5 6 1 4 7 9

Waste Status Summary of 104-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1952	---	---	---	---	
2	1C	530	530	---	Cascade filled 3-31-52. Next and last cascade of 1st cycle waste to evaporate in West Area. To take place after sufficient allowance for aging.
3	1C	530	530	---	Content of cascade will be aged 1 yr. 3-31-53 - after which time evaporation may be started.
4	1C	530	530	---	1 year decay complete 3-31-53 - evap. scheduled to start 4-1-53.
1-1953	1C	530	168	372	Sludge measurements of 1-29-53 taken.
2	1C	530	168	372	
3	1C	530	168	372	
4	1C	530	168	372	
1-1954	1C	546	169	377	Sent to crib - T Plant active 1C waste filled approx. 6" above overflow. Started cascading to 105-T.
2	1C	546	38	508	T Plant active first cycle waste cascade.
3	1C	530	5	525	T Plant active first cycle waste cascade.
4	1C	530	5	525	To be pumped to 118-TX pumping to 118-TX.
1-1955	1C	530	5	525	
2	1C	530	5	525	
3	1C	530	5	525	
4	1C	530	5	525	
1-1956	1C	530	5	525	
2	1C	530	5	525	
3	1C	530	5	525	
4	1C	530	5	525	

9 2 1 2 5 6 1 4 1 0

Waste Status Summary of 104-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1957	1C	541	16	525	Latest electrode reading.
2	1C	538	13	525	
3	1C	538	13	525	
4	1C	538	13	525	
1-1958	1C	538	13	525	
2	1C	538	13	525	
3	1C	538	13	525	
4	1C	538	13	525	
1-1959	1C	538	13	525	
2	1C	538	13	525	
3	1C	538	13	525	
4	1C	538	13	525	
1-1960	1C	538	13	525	
2	1C	538	13	525	
3	1C	538	13	525	
4	1C	538	13	525	
1-1961	---	---	---	---	
2	1C	538	13	525	[6 month report
3	---	---	---	---	
4	1C	538	13	525	[6 month report
1-1962	---	---	---	---	
2	1C	535	10	525	Latest electrode reading.
3	---	---	---	---	[6 month report
4	1C	535	10	525	
1-1963	---	---	---	---	
2	1C	535	10	525	[6 month report
3	---	---	---	---	
4	1C	535	10	525	[6 month report
1-1964	---	---	---	---	
2	1C	535	10	525	[6 month report
3	---	---	---	---	
4	1C	535	10	525	[6 month report
1-1965	---	---	---	---	
2	1C	532	44	488	[6 month report
3	1C	532	44	488	
4	1C	532	44	488	

Waste Status Summary of 104-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1966	1C	532	44	488	
2	1C	532	44	488	
3	1C	532	44	488	
4	1C	532	44	488	
1-1967	1C	532	44	488	
2	1C	532	44	488	
3	1C	532	44	488	
4	1C	532	44	488	
1-1968	1C	532	44	488	
2	1C	532	44	488	
3	1C	532	44	488	
4	1C	532	44	488	
1-1969	1C	531	43	488	
2	1C	531	43	488	
3	---	483	0	483	48 to 103-TY.
4	---	483	0	483	
1-1970	---	483	0	483	
2	---	483	0	483	
3	---	482	0	482	
4	---	483	0	483	
1-1971	---	482	0	482	
2	---	483	0	483	
3	---	483	0	483	
4	---	483	0	483	
1-1972	---	483	0	483	
2	---	483	0	483	
3	---	483	0	483	
4	---	483	0	483	
1-1973	---	483	0	483	
2	---	483	0	483	
3	---	483	0	483	
4	---	483	0	483	
1-1974	---	483	0	483	
2	---	483	0	483	
3 *	---	483	0	483	
4	---	483	0	483	Salt filled.

* Dry Wells No.s 50-04-05 and 50-04-10 were drilled.

9 2 1 2 5 5 6 1 4 8 2

Waste Status Summary of 104-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1975	---	483	0	483	Salt filled.
2	---	483	0	483	
3 *	---	483	0	483	Salt filled.
4	---	483	0	483	Salt filled.
1-1976	---	483	0	483	Salt filled 15 to 101-T.
2	---	483	0	483	Salt filled - removed from service.
3	---	483	0	483	Salt filled.
4	---	483	0	483	
1-1977	---	483	0	483	Salt well, pump
2	---	483	0	483	" " " "
3	---	483	0	483	" " " " Inactive cur
4	---	483	0	483	" " installed
1-1978	-	483	0	483	Inactive Prim. Stab.
2-	-	483	0	483	
3-	-	470	0	470	
4-	-	483	0	483	
1-1979	-	483	0	483	
2-	-	483	0	483	
3-	-	483	0	483	
4-	-	483	0	483	
1-1980	-	483	0	483	New Photo 3-28-80
2-	-	483	0	483	
3-	-	483	0	483	
4-	-	483	0	483	

* Dry Wells No.s 50-04-03, 50-04-07 and 50-04-08 were drilled.

Waste Status Summary of 105-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	2C	43	---	---	Cascade began filling July '46.
4	2C	190	---	---	Cascade.
1-1947	2C	363	---	---	Cascade.
2	2C	528	---	---	Cascade full.
3	2C	528	---	---	" "
4	2C	528	---	---	" "
1-1948	2C	528	---	---	Cascade full.
2	1C & 2C	180	---	---	New cascade April received 13 of 1C, 360 of 2C to crib.
3	1C & 2C	528	---	---	New cascade.
4	1C & 2C	528	---	---	Cascade.
1-1949	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1950	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1951	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	530	---	---	
3	1C	530	---	---	
4	1C	530	---	---	

9 2 1 2 3 5 6 1 4 3 4

Waste Status Summary of 105-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	1C	530	---	149	Sludge measurements of 1/29/53 taken.
2	1C	530	381	149	
3	1C	530	381	149	
4	1C	530	381	149	
1-1954	1C	183	34	149	Sent to crib.
2	1C	543	394	149	
3	1C	530	333	197	
4		188	0	188	To receive coating waste on 1/1/55.
1-1955	1C-CW	285	97	188	Received coating waste.
2	1C-CW	387	199	188	Received coating waste, coating waste receiver.
3	1C-CW	468	39-280	149	
4	1C-CW	510	0-322	188	Enough for 77 Total Units
1-1956	1C-CW	508	0-320	188	Enough for 68 Total Units Corrected electrode reading.
2	1C-CW	508	320	188	
3	1C-CW	530	342	188	S.S.
4	1C-CW	530	342	188	
1-1957	1C-CW	540	352	188	Latest electrode reading.
2	1C-CW	524	336	188	
3	1C-CW	524	336	188	
4	1C-CW	524	336	188	
1-1958	1C-CW	524	336	188	
2	1C-CW	524	336	188	
3	1C-CW	524	336	188	Latest electrode readings.
4	1C-CW	521	333	188	
1-1959	1C-CW	521	333	188	
2	1C-CW	519	331	188	
3	1C-CW	519	331	188	
4	1C-CW	519	331	188	
1-1960	1C-CW	519	331	188	
2	1C-CW	519	331	188	
3	1C-CW	519	331	188	
4	1C-CW	519	331	188	

Waste Status Summary of 105-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	---	---	---	---	
2	1C-CW	516	328	188	[6 month report
3	—	---	---	---	
4	1C-CW	516	328	188	
1-1962	- -	---	---	---	
2	- -	516	328	188	
3	- -	---	---	---	[6 month report
4	1C-CW	516	328	188	
1-1963	- -	---	---	---	
2	1C-CW	516	328	188	
3	- -	---	---	---	[6 month report
4	1C-CW	516	328	188	
1-1964	- -	---	---	---	
2	1C-CW	516	328	188	
3	- -	---	---	---	[6 month report
4	1C-CW	516	328	188	
1-1965	- -	---	---	---	[6months report
2	1C-CW	538	126-350	62	22m from 107-S.
3	1C-CW	538	126-350	62	
4	1C-CW	535	126-347	62	
1-1966	1C-CW	535	126-347	62	
2	1C-CW	535	126-347	62	
3	1C-CW	535	126-347	62	
4	1C-CW	535	126-347	62	
1-1967	1C-HLO	183	66-55	62	407 to 118TX; received 55m.
2	1C-HLO	524	66-396	62	Received 341m from HLO.
3	1C-HLO	524	66-396	62	
4	1C-HLO	128	31-35	62	396m to Redox Evaporator.
1-1968	1C-HLO-DW	269	31-35-141	62	Received 141m from 221-T.
2	1C-HLO-DW	388	31-35-260	62	127 from 221-T; 9 to Redox Evap.
3	DW	109	47	62	279 to Redox Conc.
4	CW	110	48	62	

Waste Status Summary of 105-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	DW	107	45	62	
2	DW	164	102	62	57 from 221-T.
3	DW	163	101	62	
4	DW	163	64	99	
1-1970	DW	163	64	99	
2	DW	163	64	99	
3	DW	163	64	99	
4	DW	163	64	99	
1-1971	DW	163	64	99	
2	DW	163	63	100	
3	DW	163	63	100	
4	DW	164	64	100	
1-1972	DW	164	64	100	
2	DW	163	63	100	
3	DW	164	64	100	
4	DW-BL-IX	479	64-82-233	100	316 from 104-BX.
1-1973	DW-BL-IX	540	64-110-266	100	63 from 104-BX, 4 to 106-T.
2	DW-BL-IX	539	33-96-310	100	452 from 107-T, 451 to 106-T.
3 *	DW-BL-IX	536	33-95-309	100	
4	DW-BL-IX	537	33-95-309	100	
1-1974	DW-BL-IX	537	33-95-309	100	
2	DW-BL-IX	113	1-3-9	100	425 to 110-S.
3	DW-BL-IX	113	1-3-9	100	
4	DW-BL-IX	114	1-3-9	101	
1-1975	DW-BL-IX	114	1-3-9	101	
2	DW-BL-IX	114	1-3-9	101	
3 **	DW-BL-IX	114	1-3-9	101	
4	DW-BL-IX	114	1-3-9	101	
1-1976	DW-BL-IX	114	1-3-9	101	Removed from service 1 to 101-T.
2	---	114	0	114	Removed from service.
3	---	114	0	114	Inactive salt well pumped.
4	---	114	0	114	
1-1977	---	114	0	114	Salt Well Pump
2	---	114	0	114	" " " "
3	---	114	0	114	Inactive
4	---	114	0	114	Salt Well Installed

* Dry Wells No.s 50-05-06 and 50-05-11 were drilled.

** Dry Well No. 50-05-07 was drilled.

9 2 1 2 3 5 6 1 4 1 3 7

Waste Status Summary of 105-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	114	0	114	Salt Well Installed
2-	-	114	0	114	
3-	-	102	0	102	
4-	-	114	0	114	
1-1979	-	114	0	114	
2-	-	114	0	114	
3-	-	114	0	114	
4-	-	114	0	114	
1-1980	-	114	0	114	
2-	-	99	0	99	Prim. Stab., New Solids Level 6-13-80, isolated small pools
3-	-	99	0	99	
4-	-	99	0	99	

9 2 1 2 5 5 6 1 4 8 8

Waste Status Summary of 106-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	2C	5	---	---	Starting filling in June.
3	2C	37	---	---	
4	2C	192	---	---	
1-1948	2C	528	---	---	Full in March.
2	2C	528	---	---	New Cascade.
3	1C & 2C	117	---	---	New Cascade jetted 2C to crib.
4	1C & 2C	434	---	---	Cascade July & August.
1-1949	1C	528	---	---	Cascade full in Jan.
2	1C	528	---	---	Cascade full.
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1950	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1951	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	528	---	---	
3	1C	528	---	---	
4	1C	529	---	---	

9 2 1 2 5 5 6 1 4 8 9

Waste Status Summary of 106-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	1C	528	---	10	Sludge measurements of 1/29/58 taken.
2	1C	528	518	10	
3	1C	528	518	10	
4	1C	528	518	10	
1-1954	1C	150	140	10	Pump to crib has broken shaft and requires repair.
2	1C	127	117	10	Scheduled to be pumped to crib. Started receiving waste 6/17/54.
3	1C	519	509	10	Received 1C waste during month.
4	1C	519	509	10	
1-1955	---	10	0	10	
2	---	10	0	10	
3	---	10	0	10	
4	---	10	0	10	
1-1956	---	10	0	10	
2	CW	231	221	10	Received CW from 110-U.
3	CW	231	221	10	
4	CW	231	221	10	
1-1957	CW	202	192	10	Latest electrode reading.
2	CW	224	214	10	New electrode reading.
3	CW	219	209	10	New electrode reading.
4	CW	219	209	10	
1-1958	CW	219	209	10	
2	CW	219	209	10	
3	CW	219	209	10	
4	CW	222	212	10	New electrode reading.
1-1959	CW	222	212	10	
2	CW	222	212	10	
3	CW	221	211	10	
4	CW	221	211	10	
1-1960	CW	221	211	10	
2	CW	221	211	10	
3	CW	221	211	10	
4	CW	221	211	10	

9 2 1 2 5 5 6 1 4 9 0

Waste Status Summary of 106-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	---	---	---	---	
2	CW	221	211	10	[6 month report
3	---	---	---	---	
4	CW	221	211	10	[6 month report
1-1962	---	---	---	---	
2	CW	221	211	10	[6 month report
3	---	---	---	---	
4	CW	221	211	10	[6 month report
1-1963	---	---	---	---	
2	CW	221	211	10	[6 month report
3	---	---	---	---	
4	CW	221	211	10	[6 month report
1-1964	---	---	---	---	
2	CW	221	211	10	[6 month report
3	---	---	---	---	
4	CW	221	211	10	[6 month report
1-1965	---	---	---	---	
2	CW	442	416	26	221m from 107-S.[6 month report]
3	CW	442	416	26	
4	CW	442	416	26	
1-1966	CW	532	506	26	90m CW from 107-S.
2	CW	532	506	26	
3	CW	532	506	26	
4	CW	532	506	26	
1-1967	CW	532	506	26	
2	CW	532	506	26	
3	CW	532	506	26	
4	CW	532	506	26	
1-1968	CW	532	506	26	
2	CW	532	506	26	
3	CW	532	506	26	
4	CW	532	506	26	
1-1969	CW	531	505	26	
2	CW	531	505	26	
3	CW	68	42	26	463 to 103-TY.
4	CW	65	26	39	

9 2 1 2 5 5 6 1 4 9 1

Waste Status Summary of 106-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1970	CW	66	27	39	
2	CW	65	26	39	
3	CW	66	27	39	
4	CW	66	27	39	
1-1971	CW	66	27	39	
2	CW	66	27	39	
3	CW	74	35	39	
4	CW	74	35	39	
1-1972	CW	75	36	39	
2	CW	74	35	39	
3	CW	74	35	39	
4	CW	74	35	39	
1-1973	CW-BL-IX-CW	78	1-1-2-35	39	4 from 105-T.
2	CW-DW-BL-IX	64	2-2-5-16	39	Tank leaks. 451 from 105-T, 350 to 112-T, 115 to ground.
3 *	CW-DW-BL-IX	65	2-2-5-17	39	Tank leaks.
4	CW-DW-BL-IX	64	2-2-5-16	39	Tank leaks.
1-1974	CW-DW-BL-IX	60	2-2-4-13	39	Tank leaks
2	CW-DW-BL-IX	60	2-2-4-13	39	" "
3	---	23	0	23	" " , 37 to 101-T.
4	IX	26	2	24	" "
1-1975	IX	26	2	24	Tank leaks.
2	IX	26	2	24	" "
3 **	IX	26	2	24	" "
4	IX	26	2	24	" "
1-1976	IX	26	2	24	Tank leaks.
2	---	26	0	26	" "
3	---	26	0	26	" " , inactive.
4	---	26	0	26	
1-1977	---	26	0	26	Leaker
2	---	26	0	26	"
3	---	26	0	26	" Phase 1 Complete
4	---	26	0	26	" Phase 1 Complete

* Dry Wells No.s 50-06-02, 50-06-03, 50-06-04, 50-06-05, 50-06-06, 50-06-08, and 50-06-11 were drilled.

** Dry Wells No.s 50-06-16 and 50-06-17 were drilled.

9 2 1 2 5 5 6 1 4 9 2

Waste Status Summary of 106-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1979	-	26	0	26	Primary Stab.-Leaker
2-	-	26	0	26	
3-	-	14	0	14	New Photo 6-20-78
4-	-	26	0	26	
1-1979	-	26	0	26	New Photo 1-5-79
2-	-	26	0	26	
3-	-	26	0	26	
4-	-	26	0	26	
1-1980	-	26	0	26	
2-	-	26	0	26	500 Gal. Pool
3-	-	26	0	26	
4-	-	26	0	26	

9212561493

Waste Status Summary of 107-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	1C	125	---	---	107,108,109 in Cascade. Began filling Dec. '44.
2	1C	287	---	---	107,108,109 in Cascade.
3	1C	527	---	---	" " " " " Began overflow to 108 in Sept.
4	1C	528	---	---	Cascade, began overflow to 109 in Dec.
1-1946	1C	528	---	---	Cascade full. 109 full in March '46.
2	1C	528	---	---	Cascade full.
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1947	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1948	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1949	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1950	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1951	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 5 5 6 1 4 9 4

Waste Status Summary of 107-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1952	---	---	---	---	
2	1C	245	---	---	Reserved for TBP. TBP-waste-active cascade.
3	1C	245	---	---	Space allocated to TBP waste.
4	1C-TBP	530	---	---	Full 11/26/52. Start filling with TBP 11/17/52, because of plug in 110-111-112C cascade
1-1953	1C-TBP	536	---	201	Sludge measurement of 1/29/53 taken, cascade filled with TBP waste on 1/2/53.
2	1C-TBP	536	44-291	201	
3	1C	234	33	201	Supernatant sent to the 118-TX tank to feed the 200-W evaporator.
4	TBP	476	275	201	Received unconcentrated scavenged TBP waste from 101-T.
1-1954	TBP	524	323	201	Received flushes from 101-T.
2	TBP	524	323	201	
3	TBP	524	323	201	
4	TBP	524	323	201	
1-1955	TBP	524	323	201	
2	TBP	524	323	201	
3	TBP	524	323	201	
4	TBP	524	323	201	
1-1956	TBP	524	323	201	
2	TBP	524	323	201	
3	TBP	524	323	201	
4	TBP	524	323	201	
1-1957	TBP	523	323	201	Latest electrode reading.
2	TBP	521	320	201	Latest electrode reading.
3	TBP	521	320	201	
4	TBP	521	320	201	
1-1958	TBP	521	320	201	
2	TBP	521	320	201	
3	TBP	521	320	201	
4	TBP	521	320	201	

9 2 1 2 3 5 6 1 4 9 5

Waste Status Summary of 107-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1959	TBP	519	318	201	
2	TBP	519	318	201	
3	TBP	519	318	201	
4	TBP	519	318	201	
1-1960	TBP	519	318	201	
2	TBP	519	318	201	
3	TBP	519	318	201	
4	TBP	519	318	201	
1-1961	---	---	---	---	
2	TBP	519	318	201	[6 months report
3	---	---	---	---	
4	TBP	519	318	201	[6 months report
1-1962	---	---	---	---	
2	TBP	519	318	201	[6 months report
3	---	---	---	---	
4	TBP	519	318	201	[6 months report
1-1963	---	---	---	---	
2	TBP	519	318	201	[6 months report
3	---	----	---	---	
4	TBP	519	318	201	[6 months report
1-1964	---	---	---	---	
2	TBP	519	318	201	[6 months report
3	---	---	---	---	
4	TBP	519	318	201	[6 months report
1-1965	---	---	---	---	
2	1C-TBP	527	201-140	186	[6 months report
3	1C-TBP	527	201-140	186	
4	1C-TBP	527	201-140	186	
1-1966	1C-TBP	527	201-140	186	
2	1C-TBP	519	201-132	186	8m to 118-TX.
3	1C-TBP	519	201-132	186	
4	1C	208	22	186	311m to 118-TX.
1-1967	1C-CW	376	22-168	186	168m from 102-C.
2	1C-CW	505	22-297	186	Received 129m from 102-C.
3	1C-CW	505	22-297	186	
4	1C-CW	505	22-297	186	

9 2 1 2 5 5 6 1 4 9 6

Waste Status Summary of 107-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1968	1C-CW	504	22-296	186	
2	1C-CW	503	22-295	186	
3	1C-CW	503	22-295	186	
4	1C-CW	503	22-295	186	
1-1969	1C-CW	503	22-295	186	
2	1C-CW	503	22-295	186	
3	1C-CW	503	22-295	186	
4	CW	228	119	109	275 to 103-TY.
1-1970	CW	228	119	109	
2	CW	228	119	109	
3	CW	228	119	109	
4	CW	228	119	109	
1-1971	CW	228	119	109	
2	CW	228	119	109	
3	CW	228	119	109	
4	CW	228	119	109	
1-1972	CW	227	118	109	
2	CW	228	119	109	
3	CW	228	119	109	
4	CW	228	119	109	
1-1973	BL-IX	282	78-95	109	684 from 104-BX, 13 flush water, 645 to 108-T
2	IX	402	293	109	573 from 104-BX, 452 to 105-T, 2 to 108-T.
3	IX	399	290	109	
4	IX	399	290	109	
1-1974	IX	399	290	109	
2	IX	399	290	109	
3 *	IX	400	291	109	
4	IX	398	289	109	
1-1975	IX	398	289	109	
2	IX	398	289	109	
3 **	IX	398	289	109	
4	IX	398	289	109	
1-1976	IX	370	261	109	Removed from service 31 to 101-T.
2	IX	178	47	131	" " " 189 to 101-T
3	Evap.	178	47	131	Inactive. Salt well pumping.
4	Evap.	178	47	131	

* Dry Well No. 50-07-07 was drilled.
** Dry Wells No.s 50-07-03 and 50-07-08 were drilled.

9 2 1 2 5 5 6 1 4 9 7

Waste Status Summary of 107-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	EVAP.	131	0	131	Salt Well Pumped
2-1977	EVAP.	178	47	131	
3-1977	EVAP.	178	28	150	Solids Level Adjusted Inactive Current
4-1977	EVAP.	178	28	150	
1-1978	-	178	28	150	
2-	NCPLX	178	28	150	Questionable Integrity
3-	NCPLX	165	27	138	
4-	NCPLX	178	28	150	
1-1979	NCPLX	178	28	150	Photo taken 1-9-79
2-	NCPLX	178	28	150	
3-	NCPLX	178	28	150	
4-	NCPLX	178	28	150	
1-1980	NCPLX	178	11	167	New Solids Level 2-1-80
2-	NCPLX	178	11	167	
30	NCPLX	178	11	167	
4-	NCPLX	178	11	167	

9 2 1 2 5 6 1 4 0 3

Waste Status Summary of 108-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	1C	79	---	---	Began filling in Sept.
4	1C	528	---	---	Cascade full.
1-1946	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1947	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1948	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1949	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1950	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1951	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	73	---	---	
3	1C	73	---	---	Space allocated to TBP waste.
4	IC-TBP	530	--- ---	---	Tank filled 12/11/52.

* Dry Well No. 50-08-11 was drilled.

9 2 1 2 5 5 1 4 9 9

Waste Status Summary of 108-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	1C-TBP	531	--- ---	21	Sludge measurement of 1/29/53 taken.
2	1C-TBP	531	73-437	21	
3	1C	81	60-0	21	Supernatant sent to the 118-TX tank to feed the 200-W evaporator.
4	1C	81	60-0	21	
1-1954	1C-TBP-EB	532	52-8-451	21	Received EB from 117-TX.
2	1C-TBP-EB	532	52-8-451	21	
3	1C-TBP-EB	532	52-8-451	21	
4	1C-TBP-EB	532	52-8-451	21	
1-1955	1C-TBP-EB	532	52-8-451	21	
2	1C-TBP-EB	532	52-8-451	21	
3	1C-TBP-EB	532	52-8-451	21	
4	1C-TBP-EB	532	52-8-451	21	
1-1956	1C-TBP-EB	532	52-8-451	21	
2	1C-TBP-EB	532	52-8-451	21	
3	1C-TBP-EB	532	52-8-451	21	
4	1C-TBP-EB	532	0-8-451	73	
1-1957	1C-TBP-EB	518	52-8-437	21	Latest electrode reading.
2	1C-TBP-EB	524	44-8-443	29	Latest electrode reading.
3	1C-TBP-EB	529	49-8-443	29	Latest electrode reading.
4	1C-TBP-EB	524	44-8-443	29	
1-1958	1C-TBP-EB	524	44-8-443	29	
2	1C-TBP-EB	524	44-8-443	29	
3	1C-TBP-EB	524	44-8-443	29	
4	1C-TBP-EB	529	48-4-443	29	
1-1959	1C-TBP-EB	524	44-8-443	29	
2	1C-TBP-EB	524	44-8-443	29	
3	1C-TBP-EB	524	44-8-443	29	
4	1C-TBP-EB	524	44-8-443	29	
1-1960	1C-TBP-EB	524	44-8-443	29	
2	1C-TBP-EB	524	44-8-443	29	
3	1C-TBP-EB	524	44-8-443	29	
4	1C-TBP-EB	522	44-8-441	29	

9 2 1 2 5 5 6 1 5 0 0

Waste Status Summary of 108-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	---	---	---	---	
2	1C-TBP-EB	522	44-8-441	29	[6 months report
3	---	---	---	---	
4	1C-TBP-EB	524	44-8-443	29	[6 months report
1-1962	---	---	---	---	
2	10-EB	522	52-441	29	[6 months report
3	---	---	---	---	
4	1C-EB	522	52-441	29	[6 months report
1-1963	---	---	---	---	
2	1C-EB	522	52-441	29	[6months report
3	---	---	---	---	
4	1C-EB	522	52-441	29	[6 months report
1-1964	---	---	---	---	
2	1C-EB	522	52-441	29	[6 months report
3	---	---	---	---	
4	1C-EB	522	52-441	29	[6 months report
1-1965	---	---	---	---	
2	1C-EB	535	19-454	62	[6 months report
3	1C-EB	535	19-454	62	
4	1C-EB	535	19-454	62	
1-1966	1C-EB	535	19-454	62	
2	1C-EB	535	19-454	62	
3	1C-EB	535	19-454	62	
4	1C-EB	535	19-454	62	
1-1967	1C-EB	535	19-454	62	
2	1C-EB-HLO	158	19-31-46	62	206m to 118-TX; 46m from HLO.
3	1C-EB-HLO	178	19-31-66	62	Received 20m from HLO.
4	1C-EB-HLO	178	19-31-66	62	
1-1968	1C-EB-HLO*	294	19-31-182*	62	Received 116m from DUN (100N) HLO. *Includes waste from 100-N Area.
2	1C-EB-HLO	294	19-31-182	62	
3	1C-EB-HLO	294	19-31-182	62	
4	1C-EB-BNW	294	19-31-182	62	

9 2 1 2 5 5 6 1 5 0 1

Waste Status Summary of 108-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	1C-EB-BNW	294	19-31-182	62	
2	1C-EB-BNW	294	19-31-182	62	
3	1C-EB-BNW	294	19-31-182	62	
4	BNW	294	188	106	
1-1970	BNW	294	188	106	
2	BNW	294	188	106	
3	BNW	294	188	106	
4	BNW	294	188	106	
1-1971	BNW	294	188	106	
2	BNW	294	188	106	
3	BNW	294	188	106	
4	BNW	294	188	106	
1-1972	BNW	293	187	106	
2	BNW	293	187	106	
3	BNW	293	187	106	
4	BNW	293	187	106	
1-1973	BL-IX	560	204-250	106	645 from 107-T; 378 to 109-T.
2	BL-IX	540	195-239	106	2 from 107-T; 22 to 109-T.
3 *	BL-IX	535	193-236	106	
4	BL-IX	535	193-236	106	
1-1974	BL-IX	535	193-236	106	
2	BL-IX	168	28-34	106	366 to 110-S.
3 **	BL-IX	170	29-35	106	
4	BL-IX	169	30-36	103	Removed from service.
1-1975	BL-IX	87	4-4	79	Removed from service; 122 to 101-
2	BL-IX	35	10-10	15	Removed from service; 12 to 101-T
3	---	51	0	51	Removed from service.
4	BL-IX	51	8-8	35	Removed from service.
1-1976	---	35	0	35	Removed from service.
2	---	35	0	35	" " "
3	---	35	0	35	Inactive.
4	---	35	0	35	
1-1977	---	35	0	35	Salt Well, Completed
2	---	35	0	35	" " " "
3	---	35	0	35	Phase 1 Complete
4	---	35	0	35	Phase 1 Complete

* Dry Well No. 50-08-09 was drilled.
** Dry Wells No.'s 50-08-05 and 50-08-07 were drilled.

9 2 1 2 5 5 6 1 5 0 2

Waste Status Summary of 108-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	46	0	46	Inactive, Prim. Stab. Solids Level Taken 1-19-78
* 2-	-	46	0	46	
3-	-	33	0	33	
4-	-	46	0	46	
1-1979	-	46	0	46	Interim Stabilized
2-	-	46	0	46	Questionable Integrity
* 3-	-	46	0	46	New Photo 8-9-79
4-	-	46	0	46	
1-1980	-	46	0	46	100 Gal. Pool
2-	-	46	0	46	
3-	-	46	0	46	
4-	-	46	0	46	

* New well 50 08 08 in service 4-27-78
50 08 19 in service 8-1-79

9 2 1 2 5 5 6 1 5 0 3

Waste Status Summary of 109-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	1C	208	---	---	Cascade began in Dec.
1-1946	1C	528	---	---	Cascade full in March '46.
2	1C	528	---	---	Cascade full.
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1947	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1948	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1949	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1950	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	1C	528	---	---	" "
4	1C	528	---	---	" "
1-1951	1C	528	---	---	Cascade full.
2	1C	528	---	---	" "
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	4	---	---	Supernate tank.
3	1C	4	---	---	Space allocated to TBP waste.
4	1C-TBP	462	---	---	Tank now filling with TBP waste.

9212561574

Waste Status Summary of 109-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	1C-TBP	524	---	---	Sludge measurement of 1/29/53 taken.
2	1C-TBP	524	4-520	---	
3	1C-TBP	88	4-84	---	Supernatant sent to the 118-TX tank to feed the 200-W evaporator.
4	1C-TBP-EB	508	4-84-420	---	
1-1954	1C-TBP-EB	543	4-84-455	---	
2	1C-TBP-EB	543	4-84-455	---	
3	1C-TBP-EB	543	4-84-455	---	
4	1C-TBP-EB	543	4-84-455		
1-1955	1C-TBP-EB	543	4-84-455	---	
2	1C-TBP-EB	543	4-84-455	---	
3	1C-TBP-EB	543	4-84-455	---	
4	1C-TBP-EB	543	4-84-455	---	
1-1956	1C-TBP-EB	543	4-84-455	---	
2	1C-TBP-EB	543	4-84-455	---	
3	1C-TBP-EB	543	4-84-455	---	
4	1C-TBP-EB	543	4-84-455	---	
1-1957	EB	541	541	---	Latest electrode reading.
2	EB	532	478	54	" " "
3	EB	541	541	---	New electrode reading.
4	EB	541	487	54	
1-1958	EB	541	487	54	
2	EB	541	487	54	
3	EB	541	487	54	
4	EB	541	487	54	
1-1959	EB	541	487	54	
2	EB	541	487	54	
3	EB	541	487	54	
4	EB	541	487	54	
1-1960	EB	541	487	54	
2	EB	541	487	54	
3	EB	541	487	54	
4	EB	541	487	54	

9 2 1 2 5 5 6 1 5 0 5

Waste Status Summary of 109-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	---	---	---	---	
2	EB	541	487	54	[illegible] months r[illegible]
3	---	---	---	---	
4	EB	541	487	54	[6 months report
1-1962	---	---	---	---	
2	EB	541	487	54	[6 months report
3	---	---	---	---	
4	EB	541	487	54	[6 months report
1-1963	---	---	---	---	
2	EB	541	487	54	[6 months report
3	---	---	---	---	
4	EB	541	487	54	[6 months report
1-1964	---	---	---	---	
2	EB	541	487	54	[6 months report
3	---	---	---	---	
4	EB	541	487	54	[6 months report
1-1965	---	---	---	---	[6 months report
2	EB	552	424	128	
3	EB	552	424	128	
4	EB	552	424	128	
1-1966	EB	552	424	128	
2	EB	552	424	128	
3	EB	552	424	128	
4	EB	552	424	128	
1-1967	EB	552	424	128	
2	EB	552	424	128	
3	EB	552	424	128	
4	EB	552	424	128	
1-1968	EB	551	423	128	
2	EB	551	423	128	
3	EB	551	423	128	
4	EB	551	423	128	
1-1969	EB	551	423	128	
2	EB	551	423	128	
3	EB	551	423	128	
4	---	134	0	134	415 to 103-TY.

9212556150 6

Waste Status Summary of 109-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1970	---	134	0	134	
2	---	134	0	134	
3	---	134	0	134	
4	---	135	0	135	
1-1971	---	135	0	135	
2	---	136	0	136	
3	---	136	0	136	
4	---	136	0	136	
1-1972	---	136	0	136	
2	---	136	0	136	
3	---	136	0	136	
4	---	138	0	138	
1-1973	BL-IX-BNW	516	86-105-187	138	378 from 108-T.
2	BL-IX-BNW	539	96-118-187	138	22 from 108-T.
3 *	BL-IX-BNW	536	95-117-186	138	
4	BL-IX-BNW	537	95-117-187	138	
1-1974	BL-IX-BNW	538	95-117-188	138	14 from 111-T; 396 to 110-S.
2 **	BL-IX-BNW	147	2-2-5	138	
3	BL-IX-BNW	156	2-2-5	147	Removed from service.
4	BL-IX-BNW	147	2-2-5	132	
1-1975	BL-IX-BNW	147	1-1-3	142	Removed from service 41 to 101-T.
2	BL-IX-BNW	147	1-1-3	142	Removed from service 12 to 101-T.
3 ***	BL-IX-BNW	147	1-1-3	142	" " "
4	BL-IX-BNW	147	1-1-3	142	" " "
1-1976	BL-IX-BNW	147	1-1-3	142	Removed from service 2 to 101-T.
2	---	147	0	147	" " " 3 to 101-T.
3	---	147	0	147	Inactive salt well pumping.
4	---	147	0	147	
1-1977	---	147	0	147	Salt Well, Pump
2	---	147	0	147	" " "
3	---	147	0	147	Inactive current
4	---	147	0	147	" " " Salt well installed

* Dry Wells No. 50-09-09 and 50-09-10 were drilled.
** Dry Wells No. 50-09-05 and 50-09-07 were drilled.
*** Dry Wells No. 50-09-01 and 50-09-02 were drilled.

9 2 1 2 5 5 6 1 5 0 7

Waste Status Summary of 109-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	147	0	147	Prim. Stabilized
2-	-	147	0	147	
3-	-	135	0	135	
4-	-	147	0	147	
1-1979	-	147	0	147	
2-	-	147	0	147	Questionable Integrity
3-	-	147	0	147	
4-	-	147	0	147	
1-1980	-	147	0	147	100 Gal. Pool, New photo 3-28-80
2-	-	147	0	147	
3-	-	147	0	147	
4-	-	147	0	147	

9212561673

Waste Status Summary of 110-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	2C	154	---	---	110,111,112 in cascade. Began filling in Dec. 1944.
2	2C	279	---	---	110,111,112 in cascade.
3	2C	516	---	---	110,111,112 in cascade.
4	2C	528	---	---	Cascade. Began overflow to 111 in Oct.
1-1946	2C	528	---	---	Cascade. Began filling 112 in Jan. '46.
2	2C	528	---	---	Cascade.
3	2C	528	---	---	Cascade. Finished filling 112 in July '46.
4	2C	528	---	---	Full.
1-1947	2C	528	---	---	Full.
2	2C	528	---	---	Cascade full.
3	2C	528	---	---	Full.
4	2C	528	---	---	Full.
1-1948	2C	528	---	---	Full.
2	2C	528	---	---	"
3	2C	528	---	---	"
4	2C	528	---	---	"
1-1949	2C	528	---	---	Full.
2	2C	528	---	---	"
3	2C	528	---	---	"
4	2C	528	---	---	"
1-1950	2C	528	---	---	Full.
2	2C	528	---	---	"
3	2C	528	---	---	"
4	2C	528	---	---	"
1-1951	2C	528	---	---	Cascade full.
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	

9212556150 9

Waste Status Summary of 110-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1952	----	---	---	---	
2	224 & 2C	530	---	---	Active cascade - T Plant.
3	224 & 2C	530	---	---	Active cascade - T Plant - 2nd cycle, 224 & sect. 5 waste.
4	224 & 2C	530	---	---	Active cascade - T Plant.
1-1953	---	530	---	530	Active cascade - T Plant - 112-T cascades to crib.
2	---	530	0	530	3 tanks cascade to crib.
3	224&2C	530	9	521	3 tanks cascade to crib. T Plant active 2nd cycle waste.
4	---	530	0	530	T Plant active 2nd cycle and 224 waste. 3 tank cascade to crib.
1-1954	---	530	0	530	
2	---	530	0	530	
3	---	530	0	530	T Plant active 2nd cycle & 224 waste cascade to crib.
4	---	530	0	530	T Plant active 2nd cycle & 224 waste cascade to crib. Full of sludge.
1-1955	---	530	0	530	
2	---	530	0	530	
3	---	530	0	530	
4	---	530	0	530	
1-1956	---	530	0	530	
2	---	530	0	530	
3	---	530	0	530	
4	---	530	0	530	
1-1957	224&2C	530		530	Latest electrode reading.
2	224&2C	530		530	" " "
3	224&2C	527	481	46	
4	---	527	481	46	
1-1958	224&2C	527	481	46	
2	224&2C	527	481	46	
3	224&2C	527	481	46	
4	224&2C	527	481	46	

9212556150

Waste Status Summary of 110-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1959	224 & 2C	524	478	46	Latest electrode reading.
2	224 & 2C	524	478	46	
3	224 & 2C	524	478	46	
4	224 & 2C	524	478	46	
1-1960	224 & 2C	524	478	46	
2	224 & 2C	524	478	46	
3	224 & 2C	524	478	46	
4	224 & 2C	524	478	46	
1-1961	---	---	---	---	
2	224 & 2C	524	478	46	[6 months report
3	---	---	---	---	
4	224 & 2C	524	478	46	[6months report
1-1962	---	---	---	---	
2	224 & 2C	524	478	46	[6 months report
3	---	---	---	---	
4	224 & 2C	524	478	46	[6 months report
1-1963	---	---	---	---	
2	224 & 2C	524	478	46	[6 months report
3	---	---	---	---	
4	224 & 2C	524	478	46	[6 months report
1-1964	---	---	---	---	
2	224 & 2C	524	478	46	[6 months report
3	---	---	---	---	
4	224 & 2C	524	478	46	[6 months report
1-1965	---	---	---	---	
2	224-2C	532	24	508	[6 months report
3	224-2C	532	24	508	
4	224-2C	532	24	508	
1-1966	224-2C	532	24	508	
2	224-2C	532	24	508	
3	224-2C	532	24	508	
4	224-2C	532	24	508	
1-1967	224-2C	532	24	508	
2	224-2C	534	26	508	
3	224-2C	534	26	508	
4	224-2C	534	26	508	

9 2 1 2 5 5 6 1 5 1 1

Waste Status Summary of 110-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1968	224-2C	535	27	508	
2	224-2C	534	26	508	
3	224-2C	534	26	508	
4	224-2C	534	26	508	
1-1969	224-2C	534	26	508	
2	224-2C	534	26	508	
3	224-2C	534	26	508	
4	224-2C	534	241	293	
1-1970	224-2C	534	241	293	
2	224-2C	534	241	293	
3	224-2C	534	241	293	
4	224-2C	534	241	293	
1-1971	224-2C	534	241	293	
2	224-2C	534	241	293	
3	224-2C	534	241	293	
4	224-2C	534	241	293	
1-1972	224-2C	535	242	293	
2	224-2C	535	242	293	
3	224-2C	535	242	293	
4	224-2C	535	242	293	
1-1973	224-2C	536	243	293	
2	224-2C	536	243	293	
3	224-2C	531	238	293	
4	224-2C	531	238	293	
1-1974	224-2C	531	238	293	
2	224-2C	475	182	293	59 to 110-S.
3 *	224-2C	483	190	293	8 Water.
4	224-2C	483	17	466	Awaiting solidification.
1-1975	224-2C	483	17	466	Awaiting solidification.
2	224-2C	483	17	466	
3 **	224-2C	483	17	466	
4	224-2C	483	17	466	
1-1976	224	472	6	466	Removed from service 9 to 101-T.
2	---	466	0	466	" " " 8 to 101-T.
3	---	466	0	466	Inactive salt well pumping.
4	---	466	0	466	
1-1977	---	466	0	466	Salt Well, Pump
2	---	466	0	466	
3	---	466	0	466	Inactive current
4	---	466	0	466	Salt Well Installed " "

* Dry Wells No.s 50-10-05, 50-10-07 and 50-10-10 were drilled.
** Dry Well No. 50-10-08 was drilled.

9 2 1 2 5 5 6 1 5 1 2

Waste Status Summary of 110-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	466	0	466	Inactive, Prim. Stab.
2-	-	466	0	466	
3-	-	454	0	454	
4-	-	466	0	466	
1-1979	-	466	0	466	
2-	-	466	0	466	
3-	-	466	0	466	
4-	-	466	0	466	
1-1980	-	466	0	466	
2-	-	466	0	466	New Photo 4-30-80
3-	-	466	0	466	
4-	-	466	0	466	

9 2 1 2 5 5 6 1 5 1 3

Waste Status Summary of 111-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	2C	400	---	---	
1-1946	2C	528	---	---	
2	2C	528	---	---	
3	2C	528	---	---	
4	2C	528	---	---	Full.
1-1947	2C	528	---	---	Full.
2	2C	528	---	---	Cascade full.
3	2C	70	---	---	Jetted to crib in September.
4	2C	22	---	---	Jetted to crib in October
1-1948	2C	82	---	---	Receiving waste in March.
2	2C	293	---	---	Receiving.
3	2C	528	---	---	Cascade full.
4	2C	528	---	---	
1-1949	2C	528	---	---	Cascade full.
2	2C	528	---	---	
3	2C	528	---	---	
4	2C	528	---	---	
1-1950	2C	528	---	---	Cascade full.
2	2C	528	---	---	
3	2C	528	---	---	
4	2C	528	---	---	
1-1951	2C	528	---	---	Cascade full.
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224 & 2C	530	---	---	
3	224 & 2C	530	---	---	
4	224 & 2C	530	---	---	

9212556114

Waste Status Summary of 111-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1953	224 & 2C	530	---	191	Active cascade T Plant - 112-T cascades to crib.
2	224 & 2C	530	284	246	3 tank cascade to crib.
3	224 & 2C	530	317	213	3 tank cascade to crib, T Plant active. 2nd cycle waste.
4	224 & 2C	530	300	230	T plant active 2nd cycle and 224 waste 3 tank cascade to crib.
1-1954	224 & 2C	530	231	299	T Plant active 2nd cycle & 224 waste cascade to crib.
2	224 & 2C	530	218	312	T Plant active 2nd cycle & 224 waste cascade to crib.
3	224 & 2C	530	530	377	T Plant active 2nd cycle & 224 waste cascade to crib.
4		530	91	439	
1-1955	224 & 2C	530	43	487	T Plant active 2nd cycle & 224 waste cascade to crib.
2	224 & 2C	530	128	402	Pumping to 112-T at 833,000 gals supernate pumped to open ditch
3	224 & 2C	530	100	430	
4	224 & 2C	530	65	465	
1-1956	224 & 2C	530	27	507	
2	224 & 2C	530	20	510	SS receives from T Plant.
3	224 & 2C	530	20	510	S.S.
4	224 & 2C	530	20	510	S.S.
1-1957	224 & 2C	560	50	510	S.S.
2	224 & 2C	560	50	510	S.S.
3	224 & 2C	557	47	510	S.S.
4	224 & 2C	557	47	510	
1-1958	224 & 2C	557	47	510	
2	224 & 2C	524	14	510	Corrected calculation.
3	224 & 2C	527	17	510	
4	224 & 2C	527	17	510	New electrode reading.
1-1959	224 & 2C	524	14	510	
2	224 & 2C	524	14	510	
3	224 & 2C	524	14	510	
4	224 & 2C	524	14	510	Receiving 221-T waste.
1-1960	224 & 2C	527	17	510	
2	224 & 2C	527	17	510	
3	224 & 2C	527	17	510	
4	224 & 2C	529	19	510	

9 2 1 2 5 5 6 1 5 1 5

Waste Status Summary of 111-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1961	---	---	---	---	
2	224 - 2C	527	17	510	6 Month Report
3	---	---	---	---	
4	224 - 2C	527	17	510	6 Month Report
1-1962	---	---	---	---	
2	224 - 2C	524	14	510	6 Month Report
3	----	---	---	---	
4	224 - 2C	524	14	510	221-T waste cascades from 111-T to 112-T and then pumped to TY crib.
1-1963	---	---	---	---	
2	224 - 2C	524	14	510	
3	---	---	---	---	
4	224 - 2C	524	14	510	
1-1964	---	---	---	---	
2	224 - 2C	524	14	510	
3	---	-- -	---	---	
4	224 - 2C	524	14	510	
1-1965	---	---	---	---	
2	224 - 2C	541	501	40	221-T waste cascades from 111-T to 112-T & then pumped to cribs
3	224 - 2C	538	96	442	
4	224 - 2C	546	104	442	
1-1966	224 - 2C	543	101	442	
2	224 - 2C	538	96	442	
3	224 - 2C	538	96	442	
4	224 - 2C	538	96	442	
1-1967	224 - 2C	538	96	442	
2	224 - 2C	538	96	442	
3	224 - 2C	538	96	442	
4	224 - 2C	540	98	442	
1-1968	224 - 2C	538	96	442	
2	224 - 2C	538	96	442	
3	224 - 2C	538	96	442	
4	224 - 2C	538	91	447	

9 2 1 2 5 5 6 1 5 1 6

Waste Status Summary of 111-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	224-2C	538	91	447	
2	224-2C	538	91	447	
3	224-2C	538	91	447	
4	224-2C	537	304	233	
1-1970	224-2C	539	306	233	
2	224-2C	538	305	233	
3	224-2C	539	306	233	
4	224-2C	539	306	233	
1-1971	224-2C	540	307	233	
2	224-2C	545	312	233	
3	224-2C	539	306	233	
4	224-2C	541	308	233	
1-1972	224-2C	538	305	233	
2	224-2C	540	307	233	
3	224-2C	539	306	233	
4	224-2C	539	306	233	
1-1973	224-2C	536	303	233	
2	224-2C	536	303	233	
3	224-2C	535	302	233	
4	224-2C	534	301	233	
1-1974	224-2C	534	301	233	
2	224-2C	490	257	233	28 to 110-S, 14 to 109-T.
3 *	---	485	0	485	
4	---	488	0	488	Removed from service.
1-1975	---	488	0	488	Removed from service.
2	---	488	0	488	
3	---	488	0	488	
4	---	488	0	488	
1-1976	---	488	0	488	Removed from service 8 to 101-T.
2	---	488	0	488	5 to 101-T.
3	---	488	0	488	Inactive salt well pumping.
4	---	488	0	488	
1-1977	---	488	0	488	Salt well, pump
2	---	488	0	488	
3	---	488	0	488	Inactive current
4	---	488	0	488	" " " Salt well installe

* Dry Wells No. 50-11-05 and 50-11-08 were drilled.
** Dry Wells No. 50-11-07 and 50-11-10 were drilled.

9 2 1 2 5 5 6 1 5 1 7

Waste Status Summary of 111-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	488	0	488	Salt Well Installed
2-	-	488	0	488	
3-	-	476	0	476	
4-	-	488	0	488	
1-1979	-	488	0	488	Photo taken 1-8-79
2-	-	488	0	488	Questionable Integrity
* 3-	-	488	0	488	Prim. Stab.
4-	-	488	0	488	
1-1980	-	488	0	488	12' Pool
2-	-	488	0	488	
3-	-	488	0	488	
4-	-	488	0	488	

* New well 50 11 11 in service 7-26-79

9 2 1 2 5 6 1 5 1 3

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	2C	187	---	---	
2	2C	489	---	---	
3	2C	528	---	---	
4	2C	528	---	---	Full.
1-1947	2C	528	---	---	Full.
2	2C	528	---	---	Cascade full.
3	2C	528	---	---	Full.
4	2C	508	---	---	Jetted to crib in Nov.
1-1948	2C	508	---	---	
2	2C	508	---	---	
3	0	0	---	---	Jetted 450,000 gal. to crib in Aug. & Sept., including receipts for month.
4	2C	109	---	---	Started receiving in Oct.
1-1949	2C	326	---	---	151,200 gal. to crib in March, including receipts for month.
2	2C	326	---	---	373,000 gal. to crib during April & May.
3	2C	310	---	---	Unknown quantity sent to crib during quarter.
4	2C	44	---	---	528,000 gal. to crib in Nov. & Dec.
1-1950	2C&BNW	369	---	---	Includes 27,300 of BPW from 300 Area.
2	2C	66	---	---	591,000 gal. to crib during quarter.
3	2C	485	---	---	Cascade receiving.
4	2C	0	---	---	975,150 gal. to crib during quarter.

9212356159

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1951	2C	412	---	---	Unknown quantity to crib during quarter. More than 143,000 ga
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224&2C	569	---	---	Cascading to crib.
3	224&2C	569	---	---	112-T cascades to crib.
4	224&2C	569	---	---	112-T cascades to crib.
1-1953	224&2C	569	---	28	Active cascade - T Plant 112-T cascades to crib.
2	224&2C	569	524	45	3 tank cascade to crib.
3	224&2C	569	567	2	T Plant active 2nd cycle waste 3 tank cascade to crib.
4	224&2C	569	562	7	T Plant active 2nd cycle and 224 waste, 3 tank cascade to crib.
1-1954	224&2C	569	536	33	
2	224&2C	569	536	33	
3	224&2C	569	536	33	T Plant active 2nd cycle & 224 waste cascade to crib.
4	224&2C	569	536	33	
1-1955	224&2C	569	536	33	
2	224&2C	569	399	170	Cascades to crib.
3	224&2C	569	399	170	
4	224&2C	569	399	170	Pumps to crib at intervals.
1-1956	224&2C	439	269	170	Pumps to crib at intervals.
2	224&2C	429	259	170	
3	224&2C	429	259	170	140m free space.
4	224&2C	470	300	170	
1-1957	224&2C	422	252	170	Estimated reading.
2	224&2C	448	278	170	
3	224&2C	417	247	170	Latest electrode reading.
4	224&2C	417	247	170	
1-1958	224&2C	420	250	170	Latest electrode reading.
2	224&2C	420	250	170	
3	224&2C	420	250	170	
4	224&2C	425	255	170	Latest electrode reading.

9 2 1 2 5 5 6 1 5 2 0

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1959	224 & 2C	439	269	170	New electrode reading.
2	224 & 2C	444	274	170	Latest electrode reading.
3	224 & 2C	442	272	170	" " "
4	224 & 2C	442	272	170	
1-1960	224 & 2C	450	280	170	Received 3m 281-T waste.
2	224 & 2C	429	259	170	Received 16m waste from 221-T pumped out to TY crib 44m.
3	224 & 2C	429	259	170	
4	224 & 2C	403	233	170	Jetted 58m to TY crib.
1-1961	----	---	---	---	6 month report
2	224 & 2C	395	225	170	Received 221-T waste and pumped to TY crib.
3	---	---	---	---	
4	224 & 2C	395	225	170	6 Month Report
1-1962	---	---	---	---	
2	224 & 2C	442	272	170	6 Month Report
3	---	---	---	---	
4	224 & 2C	395	225	170	221-T waste cascades from 111-T to 112-T, and then pumped to TY cribs. 6 month report
1-1963	---	---	---	---	
2	224 & 2C	395	225	170	221-T waste cascades from 111-T to 112-T, and then pumped to TY cribs. 6 month report
3	---	---	---	---	
4	224 & 2C	430	260	170	6 month report
1-1964	---	---	---	---	
2	224 & 2C	430	260	170	6 month report
3	---	----	---	---	
4	224 & 2C	433	263	170	6 month report
1-1965	---	---	---	---	
2	DW	442	402	40	221-T waste cascades from 111-T to 112-T & then pumped to cribs
3	DW	447	407	40	6 month report
4	DW	431	391	40	

9 2 1 2 5 5 6 1 5 2 1

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1966	DW	524	484	40	221-T waste cascades from 111-T to 112-T & then pumped to crib
2	DW	458	418	40	
3	DW	392	352	40	
4	DW	392	352	40	
1-1967	DW	392	352	40	
2	DW	362	322	40	146m to 118-TX.
3	DW	72	33	40	289m to 118-TX.
4	DW	371	201	170	Received 298m from T Plant.
1-1968	DW	508	468	40	Received 141m from 221-T.
2	DW	237	197	40	382 to Redox; 111 from 221-T.
3	DW	365	325	40	252 from 221-T; 125 to Redox con
4	DW	266	242	24	255 from 221-T; 354 to Redox Eva
1-1969	DW	406	382	24	226 from 221-T; 86 to Redox.
2	DW	165	141	24	227 from 221-T; 20 to Redox.
3	DW	354	330	24	189 from T Plant.
4	DW	174	141	33	232 from T Plant; 413 to Redox Evap.
1-1970	DW	290	257	33	228 from T Plant; 111 to Redox Evap.
2	DW	343	311	32	161 from T Plant; 109 to Redox Evap.
3	DW	351	319	32	140 from T Plant; 132 to Redox Evap.
4	DW	370	338	32	138 from T Plant; 119 to Redox.
1-1971	DW	395	363	32	100 from T Plant; 76 to Redox.
2	DW	298	266	32	147 from T; 244 to Redox.
3	DW	342	310	32	160 from T; 116 to Redox.
4	DW	399	367	32	144 from T; 87 to Redox.
1-1972	DW	378	346	32	237 from T Plant; 260 to Redox.
2	DW	403	371	32	174 from T Plant; 146 to Redox.
3	DW	468	436	32	136 from T Plant; 71 to 107-U.
4	DW	329	297	32	148 from T Plant; 286 to 107-U.
1-1973	DW	217	185	32	199 from T Plant; 20 from 301-T catch tank; 332 to 107-U.
2	DW-CW-BL-IX	508	207-22-59-188	32	120 from T Plant; 350 from 106-T; 180 to 107-U.
3	DW-CW-BL-IX	505	205-22-59-187	32	
4	DW-CW-BL-IX	505	205-22-59-187	32	

9 2 1 2 5 5 6 1 5 2 2

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1974	DW-CW-BL-IX	505	205-22-59-187	32	
2	DW-CW-BL-IX	236	89-9-25-81	32	273 to 110-S.
3 *	DW-CW-BL-IX	101	31-3-8-27	32	136 to 110-S.
4	DW-CW-BL-IX	101	31-3-8-27	32	
1-1975	DW-CW-BL-IX	101	31-3-8-27	32	
2	" " " "	"	" " " "	"	
3 **	" " " "	"	" " " "	"	
4	" " " "	"	" " " "	"	
1-1976	DW-CW-BL-IX	101	31-3-8-27	32	
2	" " " "	"	" " " "	"	
3	Evap.	101	69	32	Inactive salt well pumping.
4	Evap.	101	69	32	
1-1977	Evap.	101	69	32	Space-lo Heat
2	Evap.	101	69	32	" " "
3	Evap.	70	8	62	Current Minimum Heel
4	Evap.	68	6	62	Inactive Spare Current

* Dry Wells No. 50-12-07 and 50-12-10 were drilled.

** Dry Well No. 50-12-05 was drilled.

9 2 1 2 1 5 6 1 5 2 3

Waste Status Summary of 112-T Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	68	6	62	Inactive
2-	-	68	6	62	
3-	-	55	5	50	
4-	-	68	6	62	Photo taken 7-12-78
1-1979	NCPLX	68	6	62	
2-	NCPLX	68	6	62	
3-	NCPLX	68	6	62	
4-	NCPLX	68	6	62	
1-1980	NCPLX	68	6	62	
2-	NCPLX	68	6	62	
3-	NCPLX	68	6	62	
4-	NCPLX	68	6	62	

9 2 1 2 1 5 6 1 5 2 4

Waste Status Summary of 201-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224	54.5	---	---	These 4 tanks out of service 5/29/52.
3	224	54.5	---	---	
4	224	54.5	---	---	
1-1953	---	54.5	---	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1954	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1955	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1956	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1957	---	54.5	0	54.5	Estimated reading.
2	---	54.5	0	54.5	New electrode reading.
3	---	54		54.5	
4	---	54		54.5	
1-1958	224	54	.5	54.5	
2	224	54	.5	54.5	
3	224	54	.5	54.5	
4	224	54	.5	54.5	
1-1959	224	54	.5	54.5	
2	224	54	.5	54.5	
3	224	54	.5	54.5	
4	224	54	.5	54.5	

9212156125

Waste Status Summary of 201-T Tank-Capacity 55,0000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1960	224	54	.5	54.5	
2	224	54	.5	54.5	
3	224	54	.5	54.5	
4	224	54	.5	54.5	
1-1961	---	---	---	---	6 Month Report
2	224	54	.5	54.5	
3	---	---	---	---	
4	224	54	.5	54.5	6 Month Report
1-1962	---	---	---	---	
2	224	53	---	53	6 Month Report
3	---	---	---	---	
4	224	52	2	50	Latest electrode readings.
1-1963	---	---	---	---	6 Month Report
2	224	54	4	50	New electrode reading.
3	---	---	---	---	
4	224	54	4	50	6 Month Report
1-1964	---	---	---	---	
2	224	54	4	50	6 Month Report
3	---	---	---	---	
4	224	54	4	50	6 Month Report
1-1965	---	---	---	---	6 Month Report
2	224	53	20	33	
3	224	53	20	33	
4	224	53	20	33	
1-1966	224	53	20	33	
2	224	53	20	33	
3	224	53	20	33	
4	224	53	20	33	
1-1967	224	53	20	33	
2	224	53	20	33	
3	224	53	20	33	
4	224	53	20	33	
1-1968	224	48	15	33	
2	224	48	15	33	
3	224	48	15	33	
4	224	49	16	33	

9 2 1 2 5 5 6 1 5 2 6

Waste Status Summary of 201-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	224	53	20	33	
2	224	54	21	33	
3	224	54	21	33	
4	224	54	21	33	
1-1970	224	54	21	33	
2	224	54	21	33	
3	224	54	21	33	
4	224	54	23	31	
1-1971	224	54	23	31	
2	224	54	23	31	
3	224	54	23	31	
4	224	54	23	31	
1-1972	224	54	23	31	
2	224	54	23	31	
3	224	54	23	31	
4	224	54	23	31	
1-1973	224	54	23	31	
2	224	54	23	31	
3	224	54	23	31	
4	224	54	23	31	
1-1974	224	54	23	31	
2	224	54	23	31	
3	224	54	23	31	
4	224	54	23	31	
1-1975	224	54	23	31	
2	224	54	23	31	
3	224	54	23	31	
4	224	54	23	31	
1-1976	224	34	3	31	Removed from service 21 to 101-T.
2	224	33	2	31	" " " 1 to 101-T.
3	Evap.	31	0	31	Inactive salt well pumping.
4	---	31	0	31	
1-1977	---	31	0	31	Salt Well, Pump
2	---	31	0	31	Salt Well, Pump
3	---	31	0	31	Inactive Current
4	---	31	0	31	" " " Salt Well installed

9 2 1 2 5 5 6 1 5 2 7

Waste Status Summary of 201-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	28	0	28	Photo taken 2-27-78 Prim. Stabilized
2-	-	27	0	27	New Solids Level Adj. 5-31-78
4-	-	27	0	27	
1-1979	-	27	0	27	
2-	-	27	0	27	
3-	-	27	0	27	
4-	-	27	0	27	
1-1980	-	27	0	27	New Photo 3-10-80
2-	-	27	0	27	
3-	-	28	0	28	
4-	-	28	0	28	

9 2 1 2 5 5 6 1 5 2 3

Waste Status Summary of 202-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224	54.5	---	---	
3	224	54.5	---	---	
4	224	54.5	---	---	
1-1953	---	54.5	---	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1954	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1955	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1956	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1957	---	54.5	0	54.5	Estimated reading.
2	---	54.5	0	54.5	New electrode reading.
3	224	55	.5	54.5	Latest electrode reading.
4	224	55	.5	54.5	
1-1958	224	55	.5	54.5	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	
1-1959	224	56	1.5	54.5	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	

9 2 1 2 5 5 6 1 5 2 9

Waste Status Summary of 202-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1960	224	55	.5	54.5	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	
1-1961	---	---	---	---	
2	224	55	.5	54.5	6 Month Report
3	---	---	---	---	" " "
4	224	55	.5	54.5	
1-1962	---	---	---	---	" " "
2	224	54	---	54	
3	---	---	---	---	
4	224	53	3	50	Latest electrode readings.
1-1963	---	---	---	---	
2	224	53	3	50	New electrode reading.
3	---	---	---	---	6 Month Report
4	224	53	3	50	
1-1964	---	---	---	---	" " " "
2	224	53	3	50	
3	---	---	---	---	" " " "
4	224	53	3	50	
					" " " "
1-1965	---	---	---	---	
2	224	52	22	30	
3	224	52	22	30	
4	224	52	22	30	
1-1966	224	52	22	30	
2	224	52	22	30	
3	224	52	22	30	
4	224	52	22	30	
1-1967	224	52	22	30	
2	224	52	22	30	
3	224	52	22	30	
4	224	52	22	30	
1-1968	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	

9 2 1 2 5 5 6 1 5 3 0

Waste Status Summary of 202-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1970	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1971	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1972	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1973	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1974	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1975	224	51	21	30	
2	224	51	21	30	
3	224	51	21	30	
4	224	51	21	30	
1-1976	---	25	0	25	Removed from service 27 to 101-T.
2	---	25	0	25	" " " 1 to 101-T.
3	---	25	0	25	Inactive salt well pumping.
4	---	25	0	25	
1-1977	---	25	0	25	Salt Well, Pump
2	---	25	0	25	Inactive, current
3	---	25	0	25	" " "
4	---	25	0	25	" " " Salt Well Installed

9212556153 1

Waste Status Summary of 202-T Tank-Capacity 50,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	20	0	20	Prim. Stabl., Photo taken 2-27-78
2-	-	20	0	20	Solids Level taken 1-31-
3-	-	20	0	20	
4-	-	20	0	20	
1-1979	-	20	0	20	
2-	-	20	0	20	
3-	-	20	0	20	
4-	-	20	0	20	New Photo 10-12-79
1-1980	-	20	0	20	
2-	-	20	0	20	
3-	-	21	0	21	
4-	-	21	0	21	

9 2 1 2 5 5 6 1 5 3 2

Waste Status Summary of 203-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224	54.5	---	---	
3	224	54.5	---	---	
4	224	54.5	---	---	
1-1953	---	54.5	---	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1954	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1955	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1956	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1957	---	54.5	0	54.5	Estimated reading.
2	---	54.5	0	54.5	New electrode reading.
3	224	55	.5	54.5	Latest electrode reading.
4	224	55	.5	54.5	
1-1958	224	55	.5	54.5	
2	224	55	.5	54.5	
3	224	55	0	55	
4	224	55	.5	54.5	
1-1959	224	55	.5	54.5	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	

9 2 1 2 5 6 1 5 3 3

Waste Status Summary of 203-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1960	224	55	.5	54.5	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	
1-1961	---	---	---	---	
2	224	55	.5	54.5	6 Month Report
3	---	---	---	---	" " " "
4	224	55	.5	54.5	
1-1962	---	---	---	---	" " " "
2	224	54	---	54	
3	---	---	---	---	" " " "
4	224	53	3	50	Latest electrode reading.
1-1963	---	---	---	---	
2	224	53	3	50	New electrode reading.
3	---	---	---	---	
4	224	53	3	50	6 Month Report
1-1964	---	---	---	---	" " " "
2	224	53	3	50	
3	---	---	---	---	" " " "
4	224	53	3	50	
1-1965	---	---	---	---	" " " "
2	224	52	17	35	
3	224	52	17	35	
4	224	52	17	35	
1-1966	224	52	17	35	
2	224	52	17	35	
3	224	52	17	35	
4	224	52	17	35	
1-1967	224	52	17	35	
2	224	52	17	35	
3	224	52	17	35	
4	224	51	16	35	
1-1968	224	47	12	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	

9 2 1 2 5 5 6 1 5 3 4

Waste Status Summary of 203-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1969	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1970	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1971	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1972	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1973	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1974	224	51	16	35	
2	224	51	16	35	
3	224	51	16	35	
4	224	51	16	35	
1-1975	224	51	17	35	
2	224	51	17	35	
3	224	51	17	35	
4	224	51	17	35	
1-1976	224	50	15	35	Removed from service 1 to 101-T.
2	224	42	7	35	" " " 1 to 101-T.
3	Evap.	41	6	35	Inactive salt well pumping.
4	Evap.	40	5	35	
1-1977	Evap.	39	4	35	Salt Well, Pumping
2	Evap.	38	3	35	" " " "
3	Evap.	36	3	35	" " " "
4	Evap.	36	1	35	Salt Well Installed

9 2 1 2 5 6 1 3 3 3

Waste Status Summary of 203-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	37	0	37	Salt Well Installed New Solids Level 1-31-78
2-	-	36	0	36	
3-	-	36	0	36	
4-	-	36	0	36	
1-1979	-	36	0	36	Inactive Primary Stab.
2-	-	36	0	36	
3-	-	36	0	36	
4-	-	36	0	36	
1-1980	-	36	0	36	New Photo 3-18-80
2-	-	36	0	36	
3-	-	37	0	37	
4-	-	37	0	37	

9 2 1 2 1 5 6 1 5 5 5 6

Waste Status Summary of 204-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	224	54.5	---	---	
3	224	54.5	---	---	
4	224	54.5	---	---	
1-1953	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1954	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1955	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1956	---	54.5	0	54.5	
2	---	54.5	0	54.5	
3	---	54.5	0	54.5	
4	---	54.5	0	54.5	
1-1957	---	54.5	0	54.5	Estimated reading.
2	---	54.5	0	54.5	New electrode reading.
3	224	56	1.5	54.5	Latest electrode reading.
4	224	56	1.5	54.5	
1-1958	224	56	1.5	54.5	
2	224	56	1.5	54.5	
3	224	56	1.5	54.5	
4	224	56	1.5	54.5	
1-1959	224	56	1.5	545	
2	224	55	.5	54.5	
3	224	55	.5	54.5	
4	224	55	.5	54.5	

9 2 1 2 5 5 6 1 5 3 7

Waste Status Summary of 204-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1960	224	54	.5	54.5	
2	224	54	.5	54.5	
3	224	54	.5	54.5	
4	224	54	.5	54.5	
1-1961	---	---	---	---	
2	224	52	2.5	54.5	6 Month Report
3	---	---	---	---	
4	224	52	2.5	54.5	6 Month Report
1-1962	---	---	---	---	
2	224	54	---	54	6 Month Report
3	---	----	---	---	
4	224	52	2	50	6 Month Report Latest electrode reading.
1-1963	---	---	---	---	
2	224	52	2	50	6 Month Report New electrode reading.
3	---	---	---	---	
4	224	52	2	50	6 Month Report
1-1964	---	---	---	---	
2	224	52	2	50	6 Month Report
3	---	---	---	---	
4	224	52	2	50	6 Month Report
1-1965	---	---	---	---	
2	224	52	8	44	6 Month Report
3	224	52	8	44	
4	224	52	8	44	
1-1966	224	52	8	44	
2	224	52	8	44	
3	224	52	8	44	
4	224	52	8	44	
1-1967	224	52	8	44	
2	224	52	8	44	
3	224	52	8	44	
4	224	52	8	44	
1-1968	224	52	8	44	
2	224	51	7	44	
3	224	51	7	44	
4	224	51	7	44	
1-1969	224	51	7	44	
2	224	51	7	44	
3	224	51	7	44	
4	224	51	7	44	

9212556153 8

Waste Status Summary of 204-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid In Storage	Solids In Storage	Remarks
1-1970	224	51	7	44	
2	224	51	7	44	
3	224	51	7	44	
4	224	51	7	44	
1-1971	224	51	7	44	
2	224	51	7	44	
3	224	51	7	44	
4	224	51	7	44	
1-1972	224	51	7	44	
2	224	51	7	44	
3	224	51	7	44	
4	224	51	7	44	
1-1973	224	51	7	44	
2	224	50	6	44	
3	224	50	6	44	
4	224	50	6	44	
1-1974	224	50	6	44	
2	224	50	6	44	
3	224	50	6	44	
4	224	50	6	44	
1-1975	224	50	6	44	
2	224	50	6	44	
3	224	50	6	44	
4	224	50	6	44	
1-1976	224	49	5	44	Removed from service 1 to 101-T.
2	---	44	0	44	Removed from service 5 to 101-T.
3	---	44	0	44	Inactive salt well pumping.
4	---	44	0	44	
1-1977	---	44	0	44	Salt well, pump
2	---	44	0	44	
3	---	44	0	44	Inactive current
4	---	44	0	44	Inactive current

9212561539

Waste Status Summary of 204-T Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	37	0	37	Prim. Stab. New Solids Level 1-31-78
2-	-	37	0	37	
3-	-	37	0	37	
4-	-	37	0	37	
1-1979	-	37	0	37	
2-	-	37	0	37	
3-	-	37	0	37	
4-	-	37	0	37	
1-1980	-	37	0	37	New Photo 3-18-80
2-	-	37	0	37	
3-	-	38	0	38	
4-	-	38	0	38	

9212256150

Waste Status Summary of 101-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2-					
3-					
4-					
1-1945					
2-					
3-					
4-					
1-1946					
2-					
3-					
4-					
1-1947					
2-					
3-					
4-					
1-1948					
2-					
3-					
4-					
1-1949					
2-					
3-	Metal	281			Began Filling in July
4-	Metal	658			
1-1950	Metal	741			Cascade filled in January
2-	Metal	741			Cascade
3-	Metal	741			Cascade
4-	Metal	741			Cascade

9212156154

Waste Status Summary of 101-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	* Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-	Metal Waste	758			
3-	" "	758			
4-	"	758			
1-1953	Metal Waste	758			
2-	" "	758			
3-	" "	758			
4-	" "	270			Supernatant transferred to 106-TX & 115-TX in preparation for sluicing
1-1954	Metal Waste	20			Sluicing metal waste removal in progress
2-	" "	8			Metal waste removal in progress
3-	" "	3			1) sluicing, 2) active sluicing tank 1st part of month 3) MW in 12-24-54
4-	" "	323			
1-1955	Metal Waste	707			Overflow partially plugged
2-	" "	707			" " "
3-	" "	707			" " "
4-	" "	20		15	Sluicing Tank
1-1956	" "	45		5	Water soaking sludge
2-	" "	10		5	MW Heel
3-	" "	5		3	Heel
4-	" "	3		3	Sluicing
1-1957	" "	0			Declared MT Sluicing Heel
2-	R	24			New electrode rdg
3-	R	24			
4-	R	24			

* (1) (2) (3) designates month in each quarter action occurred.

9212561542

Waste Status Summary of 101-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	29			Latest electrode rdg
2-	R	4			New electrode rdg
3-	R	4			
4-	R	4			
1-1959	R	5			Latest electrode rdg
2-	R	5			
3-	R	5			
4-	R	5			
1-1960	R	5			
2-	R	10			Receiving flush water fro 153 RX Div. box catch tank
3-	R	10			
4-	R	10			
1-1961	R	10			6 Months
2-					
3-	R				6 Months
4-	R	10			
1-1962	R	10			6 Months
2-					
3-					
4-	R	524			6 Months 514M from 102-SX
1-1963	R	112			649M to 101 TX 230M from 105-SX 6 months
2-					
3-					
4-	R	758			649M from 103 SX 6 months
1-1964	R	756			6 Months
2-					
3-					
4-	R	150			608M to 106 TX 6 months

9 2 1 2 5 6 1 5 4 3

Waste Status Summary of 101-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	R	728		51	578M from 103-SX
2-					6 months
3-	R	728		51	
4-	R	758		51	
1-1966	R	755		51	Latest electrode rdg
2-	R	758		51	
3-	R	747		51	626M from 103-SX
4-	R	681		51	66M to 108 TX
1-1967	R	678		51	
2-	R	676		51	
3-	R	676		51	
4-	R	670		51	
1-1968	R	672		51	
2-	R	681		51	9 from 153-TX & 154-TXR catch tank
3-	R	681		51	
4-	R	669	618	51	
1-1969	R	669	618	51	
2-	R	670	619	51	
3-	R	670	619	51	
4-	R	669	659	10	
1-1970	R	668	658	10	
2-	R	668	658	10	
3-	R	235	225	10	Rec'd 21 flush water 454 + 87 dilution water to 105-C
4-	R	143	133	10	366 from 105-TX; 8 from catch tank; 10 from dilution water; 26 from 102-TX (drain back) 502 to 105-C
1-1971	R	151	141	10	8 drainage from 106-TX to 105-C transfer
2-	EB-CW-OWW-RIX	527	11-45-89-154	128	1205 from 106 BX, 829 to 118T
3-	R-TBP	597	237-232	128	200 from 101 BX, 412 from 102 TX, 517 from 103-TX 527 from 104-TX, 328 from 106 TX, 1914 to 118-TX
4-	EB-RIX	515	82-335	98	419 from 102-B, 824 from 103-B, 1325 to 118-TX

9 2 1 2 5 5 6 1 5 4 4

Waste Status Summary of 101-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	BL-IX-CW-EB	497	15-60-39-310	73	553 from 103-B, 349 from 107-921 to 118-TX
2-	EB-SIX-CW	342	211-44-14	73	165 from 101-BX, 439 from 108U, 758 to 118-TX
3-	BL-IX	499	62-364	73	907 from 101-BX, 15 from 302-R catch tank, 765 to 118-TX
4-	BL-IX	719	168-478	73	686 from 101-BX, 582 from 104-BX, 1048 to 118-TX
1-1973	BL-IX	690	277-340	73	558 from 104-BX, 588 to 118TX
2-	BL-IX	570	223-274	73	15 from 302-B, 128to 118TX
3- *	BL-IX	581	228-280	73	
4-	BL-IX	482	184-225	73	101 to 118-TX
1-1974	BL-IX-IC-TBP	720	187-230-222-8	73	12 from 302-B catch tank, 226 from 109-TX
2- **	BL-IX-IC-TBP	720	187-230-222-8	73	
3-	BL-IX-IC-TBP	427	102-127-121-4	73	294 to 118-TX
4-	BL-IX-IC-TBP	601	3-5-2-2-238-2	73	281 from 103-C 5 from 302-A catch tank, 118 to 118TX
1-1975	BNW-N-LW-PL-BL-CW (3)	461	2-4-1-1-250-1- (3)	73	135 to 118-TX
2-	BNW-N-LW-CW=DW (3)	684	24-41-5-10-4-1 (3)	73	37 from 234-5 Z, 584 from 103-C; 13 from 302-A,CT; 29 from 302-B,C,T; 3 water 441 to 118-TX
3-	B-BL	530	420-37	73	1044 from 104-C; 40 from 002-TXR; 1237 to 118-TX
4-	PL-BL-B	439	12-195-159	73	193 from 104-C; 15 from 001-TXR, 297 to 118-TX
1-1976	EB-BL-OWW-RIX-R-PL-B	164	19-36-3-3-1-2-27	73	466 to 118-TX, 24 from CT 302-B, 6 from TY 302-A, 162 from 102-TY
2-	EB-BL-OWW-RIX-R-PL-B	169	20-39-3-3-1-2-28	73	5 from TX-302 CT
3-	Evap. Feed	172	99	73	Evap. Feed dil.
4-	Evap. Feed	172	99	73	Evap. Feed dil.
1-1977	Evap. Feed	172	99	73	
2-	Evap. Feed	172	99	73	Evap. Feed dil.
3-	Evap. Feed	90	17	73	Inactive Current
4-	Evap. Feed	90	17	73	Inactive Current, Salt Well installed

(3) IX-IC-TBP 65-62-2

* Leak detection dry wells 51-01-04 and 51-01-09 drilled

** Leak detection dry wells 51-01-02, 51-01-06 and 51-01-08 drilled

9 2 1 2 5 5 6 1 5 4 5

Waste Status Summary of 101-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NCPLX	90	17	73	
2-	NCPLX	90	17	73	
3-	NCPLX	92	19	73	
4-	NCPLX	92	19	73	Neut. Liq. Storage
1-1979	NCPLX	95	22	73	
2-	NCPLX	271	198	73	
3-	PNF	488	415	73	
4-	PNF	169	96	73	New Photo 12-19-79
1-1980	PNF	175	102	73	
2-	NCPLX	107	1	106	Inactive - New Solids 6-30-80
3-	NCPLX	107	1	106	
4-	NPCLX	107	1	106	

9212356154 6

Waste Status Summary of 102-TXTank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2-					
3-					
4-					
1-1945					
2-					
3-					
4-					
1-1946					
2-					
3-					
4-					
1-1947					
2-					
3-					
4-					
1-1948					
2-					
3-					
4-					
1-1949					
2-					
3-					
4-					
1-1950	Metal	302			Cascade began filling in Jan.
2-	Metal	697			Cascade
3-	Metal	741			Cascade filled in July
4-	Metal	741			Cascade

9 2 1 2 5 5 6 1 5 4 7

Waste Status Summary of 102-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	*Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-	Metal Waste	758			
3-	" "	758			
4-	" "	758			
2-1953	" "	758			
2-	" "	758			
3-	" "	758			
4-	" "	758			
1-1954	Metal Waste	175			Supernatant used for blending
2-	" "	103			
3-	" "	0			Emptied to 103-TX 7-19
4-	" "	0			
1-1955	Metal Waste	758			
2-	" "	758			
3-	" "	758			
4-	" "	758			
1-1956	Metal Waste	15		10	Pumped to 104-TX, sluicing
2-	" "	5		2	1) sluicing doscontinued 2) to be visually inspected 3) MW Heel
3-	" "	5		2	Heel
4-	" "	10		2	Sluicing heel
1-1957	Metal Waste	0			Declared MT Sluicing heel
2-	R	12			New electrode rdg.
3-	R	15			New electrode rdg.
4-	R	15			

* (1) (2) (3) designates month in each quarter that transferred occurred.

9212156158

Waste Status Summary of 102-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	15			
2-	R	15			
3-	R	15			
4-	R	15			
1-1959	R	18			Latest electrode rdg.
2-	R	18			
3-	R	18			
4-	R	18			
1-1960	R	18			
2-	R	18			
3-	R	18			
4-	R	21			
1-1961	R	23			Latest electrode rdg.
2-					6 month report
3-					
4-	R	21			6 month report
1-1962	R	23			6 month report
2-					
3-					
4-	R	23			6 month report
1-1963	R	23			6 month report
2-					
3-					
4-	R	755			732M from 101-TX
					6 month report
1-1964	R	752			Latest electrode rdg.
2-					6 month report
3-					
4-	R	752			6 month report

9212056159

Waste Status Summary of 102-TX Tank Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Liquid in Storage	Remarks
1-1965	R	750		8	6 month report
2-					
3-	R	750		8	
4-	R	750		8	
1-1966	R	750		8	
2-	R	750		8	
3-	R	750		8	
4-	R	750		8	
1-1967	R	750		8	
2-	R	750		8	
3-	R	750		8	
4-	R	750		8	
1-1968	R	750		8	
2-	R	750		8	
3-	R	750		8	
4-	R	750	742	8	
1-1969	R	750	742	8	
2-	R	750	742	8	
3-	R	749	741	8	
4-	R	748	736	12	
1-1970	R	748	736	12	
2-	R	750	738	12	
3-	R	752	740	12	
4-	R	50	38	12	681 M to 105-C 26 M to 101-TX
1- 1971	R	48	36	12	542 M from 105-TX
2-	EB-CW-OWW-RIX	591	160-65-128-223	15	412 M to 101-TX
3- *	EB-CW-OWW-RIX	179	46-18-36-64	15	242-T bottom and Recycle
4-	EB	723	650	73	(1)

(1) Due to the characteristics of solids in bottom tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tank 102-TX

* Leak detection dry wells 51-02-05, 51-02-09 and 51-02-12 drilled

9 2 1 2 5 5 6 1 5 0

Waste Status Summary of 102-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	689	616	73	242T bottom & Recycle (1)
2-	EB	689	616	73	" " "
3-	EB	700	616	84	" " "
4-	EB	700	514	186	" " "
1-1973	EB	697	511	186	242T bottom & Recycle
2-	EB	7-6	520	186	" " "
3-	EB	700	514	186	" " "
4-	EB	695	509	186	" " "
1-1974	EB	703	517	186	242T bottom & Recycle (1)
2- *	EB	693	507	186	" " "
3-	EB	700	514	186	" " "
4-	EB	711	517	194	" " "
1-1975	EB	700	506	194	242T bottom & recycle (1)
2-	EB	697	503	194	" " "
3-	EB	706	512	194	" " " removed from service due to crusting problems
4-	EB	708	514	194	Removed from service due to crusting
1-1976	EB	719	525	194	10 H_2O
2-	EB	719	525	194	242T bottoms & recycle
3-	Evap Feed	719	525	194	contains salt evap feed btms.
4-	Evap Feed	719	525	194	" "
1-1977	Evap Feed	455	0	455	Salt well pumping
2-	Evap Feed	455	0	455	Inactive salt well pumping
3-	Evap Feed	455	0	455	Inactive - salt well pumping
4-	Evap Feed	455	0	455	Inactive current-salt well installed

(1) Due to the characteristics of the solids in bottoms tanks and the inability to measure them precisely, there is a sigificant degree of uncertainty in the liquid-to solid ratio of tank 102-TX.

* Leak detection dry wells 51-02-02 and 51-02-07 drilled

9 2 1 2 5 5 6 1 5 5 1

Waste Status Summary of 102-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	455	0	455	Inactive - Prim. Stab.
2-	-	455	0	455	New Photo 3-17-78
3-	-	455	0	455	
4-	-	334	0	334	Solid Level Adj. 10-31-78
1-1979	-	334	0	334	
2-	-	334	0	334	
3-	-	334	0	334	
4-	-	334	0	334	
1-1980	-	334	0	334	
2-	-	334	0	334	
3-	-	334	0	334	
4-	-	334	0	334	

9212356152

Waste Status Summary of 103-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2-					
3-					
4-					
1-1945					
2-					
3-					
4-					
1-1946					
2-					
3-					
4-					
1-1947					
2-					
3-					
4-					
1-1948					
2-					
3-					
4-					
1-1949					
2-					
3- *					
4-					
1-1950					
2-					
3-	Metal	439			Cascade began filling in July
4-	Metal	741			Cascade filled in Nov.

* Leak detection dry well 51-03-02 drilled

9 2 1 2 5 6 1 5 3 3

Waste Status Summary of 103-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-	Metal Waste	758			
3-	" "	758			
4-	" "	758			
1-1953	Metal Waste	758			
2-	" "	758			
3-	" "	758			
4-	" "	758			
1-1954	Metal Waste	117			Supernatant used in blending metal removal waste in prog.
2-	" "	147			
3-	" "	0			emptied to 104-TX 7-28
4-	TBP	682			
1-1955	TBP	682			
2-	TBP	682			
3-	TBP	682			
4-	TBP	682			
1-1956	TBP	682			
2-	TBP	682			To be scvg. @ 242T
3-	TBP	682			To be scvg. @ 242T
4-	TBP	682			To be scvg. @ 242T
1-1957	TBP	675(E)			To be scvg. @ 242T
2-	TBP	675			To be scvg. @ 242T
3-	TBP	675			
4-	TBP	675			

9 2 1 2 5 6 1 5 1 d

Waste Status Summary of 103-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	TBP	675			
2-	TBP	675			
3-	TBP	675			
4-	TBP	675			
1-1959	TBP	675			
2-	TBP	675			
3-	TBP	675			
4-	TBP	675			
1-1960	TBP	675			
2-	TBP	675			
3-	TBP	675			
4-	TBP	675			
1-1961	TBP	681			Latest electrode rdg.
2-	TBP				6 mo. Report
3-	TBP				
4-	TBP	678			6 mo. Report
1-1962	TBP	681			Latest electrode rdg.
2-					6 mo. Report
3-					
4-	TBP	681			6 mo. Report
1-1963	TBP	681			6 mo. Report
2-					
3-					
4-	TBP	686			Latest electrode rdg. 6 mo. Report
1-1964	TBP	686			6 mo. Report
2-					
3-					
4-	TBP	686			6 mo. Report

9 2 1 2 5 6 1 5 5 5

Waste Status Summary of 103-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	TBP	686	6 months	4	
2-					
3-	TBP	686		4	
4-	TBP	686		4	
1-1966	TBP	686		4	
2-	TBP	686		4	
3-	TBP	686		4	
4-	TBP	686		4	
1-1967	TBP	686		4	
2-	TBP	689		4	
3-	TBP	689		4	
4-	TBP	689		4	
1-1968	TBP	689		4	
2-	TBP	689		4	
3-	TBP	689		4	
4-	TBP	690	686	4	
1-1969	TBP	690	686	4	
2-	TBP	691	687	4	
3-	TBP	691	687	4	
4-	TBP	691	688	3	
1-1970	TBP	692	689	3	
2-	TBP	692	689	3	
3-	TBP	692	689	3	
4-	TBP	693	690	3	
1-1971	TBP	693	690	3	
2-	TBP	693	690	3	
3- *	TBP	178	175	3	517 to 101-TX
4-	TBP-H_2O	184	174-7	3	7 Flush H_2O

* Leak detection dry wells 51-03-06, 51-03-09 and 51-03-12 drilled.

9 2 1 2 1 5 6 1 5 5 6

Waste Status Summary of 103-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	TBP-H_2O	187	177-7	3	
2-	" "	186	176-7	3	
3-	EB	232	229	3	242 bottoms & recycle *
4-	EB	488	485	3	" " " *
1-1973	EB	645	642	3	242 bottoms & recycle *
2-	EB	722	719	3	" " " *
3-	EB	723	720	3	" " " *
4-	EB	726	723	3	" " " *
1-1974	EB	727	724	3	242 bottoms & recycle *
2-	EB	729	726	3	" " " *
3-	EB	728	725	3	" " " *
4-	EB	728	725	3	" " " *
1-1975	EB	728	725	3	242 bottoms & recycle *
2-	EB	730	727	3	" " " *
3-	EB	730	727	3	" " " *
4-	EB	730	727	3	" " " *
1-1976	EB	730	727	3	242 bottoms & recycle *
2-	EB	730	727	3	" " " *
3-	Evap Feed	730	724	6	Evap feed-con. evap feed btms
4-	Evap Feed	609	603	6	" " " " " "
1-1977	Evap Feed	450	330	120	Interstitial liquor storage
2-*	Evap Feed	222	102	120	Interstitial liquor storage
3-	Evap Feed	260	140	120	Interstitial liquor storage
4-	Evap Feed	307	162	145	Salt well recovery, interstitial liquor storage

*Due to the characteristics of solids in bottoms tanks & the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks.

* Leak detection dry wells 51-03-01 and 51-03-11 drilled.

9212556157

Waste Status Summary of 103-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	307	162	145	Active Salt Well. Recvt.
2-	NCPLX	329	184	145	
3-	NCPLX	587	442	145	
4-	NCPLX	706	561	145	
1-1979	NCPLX	497	352	147	Solid Level Adj.
2-	NCPLX	497	352	145	
3-	PNF	612	467	145	
4-	PNF	612	467	145	
1-1980	PNF	629	484	145	
2-	PNF	226	81	145	
3-	PNF	204	47	157	Inactive
4-	NCPLX	204	47	157	New Solids Level 8-14-80

9 2 1 2 5 5 6 1 5 5 8

Waste Status Summary of 104-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2-					
3-					
4-					
1-1945					
2-					
3-					
4-					
1-1946					
2-					
3-					
4-					
1-1947					
2-					
3-					
4-					
1-1948					
2-					
3-					
4-					
1-1949					
2-					
3-					
4-					
1-1950					
2-					
3-					
4-	Metal	397			Cascade began filling in Nov

9212561579

Waste Status Summary of 104-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2-					
3-					
4-					
1-1952					
2-	Metal Waste	750			
3-	" "	750			
4-	" "	750			
1-1953	Metal Waste	750			
2-	" "	750			
3-	" "	750			
4-	" "	750			
1-1954	Metal Waste	750			
2-	" "	389			Supernatant used for blendin
3-	" "	700			Supernatant used for blendin overflow to 106 partially plugged.
4-	" "	422			Supernatant used for blendin
1-1955	Metal Waste	96			Supernatant used for blendin
2-	" "	96			" " " "
3-	" "	96			" " " "
4-	" "	504			" " " " supernatant supply tank
1-1956	Metal Waste	15			
2-	" "	15			
3-	" "	5			SS receives from T plant pump fell into tank
4-		0			Declared MT
1-1957	Metal Waste	15			Sluicing water
2-	R	29			New electrode rdg.
3-	R	29			
4-	R	29			

9212361360

Waste Status Summary of 104-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	29			
2-	R	29			
3-	R	29			
4-	R	29			
1-1959	R	29			
2-	R	29			
3-	R	29			
4-	R	29			
1-1960	R	29			
2-	R	29			
3-	R	29			
4-	R	29			
1-1961	R	32			Latest electrode rdg.
2-					6 mo. Report
3-	R	29			
4-					6 mo. Report
1-1962	R	32			Latest electrode rdg.
2-					6 mo. Report
3-					
4-	R	32			
1-1963	R	681			649M from 101-TX
2-					6 mo. Report
3-					
4-	R	747			66M from 101-TX
1-1964	R	747			6 mo. Report
2-					
3-					
4-	R	747			

9 2 1 2 3 5 6 1 3 3 1

Waste Status Summary of 104-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	R	761	6 months	0	
2-					
3-	R	761		0	
4-	R	761		0	
1-1966	R	761		0	
2-	R	95		0	666M to 118-TX
3-	R	732		0	637M from 101-TX
4-	R	732		0	
1-1967	R	732		0	
2-	R	732		0	
3-	R	732		0	
4-	R	732		0	
1-1968	R	731		8	
2-	R	731		8	
3-	R	731		8	
4-	R	731	723	8	
1-1969	R	731	723	8	
2-	R	730	722	8	
3-	R	730	722	8	
4-	R	730	719	11	
1-1970	R	729	718	11	
2-	R	729	718	11	
3-	R	729	718	11	
4-	R	728	717	11	
1-1971	R	728	717	11	
2-	R	727	709	18	
3- *	R	200	182	18	527 to 101-TX
4-	R-H_2O	211	182-11	18	11 flush H_2O

* Leak detection dry wells 51-04-05, 51-04-08 and 51-04-12 drilled.

Waste Status Summary of 104- TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	R-Water	211	182-11	18	
2-	R	211	193	18	
3-	R	219	201	18	
4-	R	207	189	18	
1-1973	R	201	183	18	
2-	R	218	200	18	
3-	BL-OWW-RIX-R-TBP	660	46-94-87-375-40	18	213 from 101-TY, 227 from 103-TY
4-	BL-OWW-RIX-R-TBP	661	46-94-87-376-40	18	
1-1974	BL-OWW -RIX -R-TBP	660	46-94-87-375-40	18	
2-	" " "	136	8-17-16-70-7	18	529 to 110-S
3-	" " "	132	8-16-15-68-7	18	
4-	" " "	134	8-16-15-70-7	18	
1-1975	BL-OWW-RIX- (2)	543	8-16-15-70-7-409	18	409 to 109-TX
2	EB	689	671	18	242-T bottoms & recycle *
3-	EB	607	589	18	" " " *
4-	EB	579	561	18	" " " *
1-1976	EB	728	710	18	242-T bottoms & recycle *
2- **	EB	725	707	18	" " " *
3-	Evap Feed	725	707	18	Evap feed con. evap feed btr
4-	Evap Feed	722	704	18	Evap feed con. chelated Sr waste
1-1977	Evap Feed	65	25	40	Inactive Chelated Sr. Waste
2-	Evap Feed	68	28	40	Inactive Chelated Sr. Waste
3-	Evap Feed	68	28	40	Inactive Current, Chelated Sr. Waste
4-	Evap. Feed	68	28	40	Inactive Current, Chelated Sr. Waste

*Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is significant degree of uncertainty in the liquid of solid ratio of tank

** Leak detection dry wells 51-04-02, 51-04-06 and 51-04-10 drilled.

(2) BL-OWW-RIX

9 2 1 2 5 5 6 1 5 6 3

Waste Status Summary of 104-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	68	28	40	Open Hold Salt Well
2-	CPLX	68	28	40	
3-	CPLX	68	28	40	
4-	CPLX	68	28	40	
1-1979	CPLX	48	8	40	
2-	CPLX	48	8	40	
3-	CPLX	48	8	40	Interim Stabilized
4-	CPLX	48	8	40	
1-1980	CPLX	48	8	40	
2-	CPLX	48	8	40	
3-	CPLX	48	8	40	
4-	CPLX	68	0	68	New Solids Level 9-18-80, 1400 Gal. pool

9 2 1 2 5 5 6 1 5 5 4

Waste Status Summary of 105-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 5 6 1 5 6 5

Waste Status Summary of 105-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	Metal	758			Cascade set up to receive high TBP
3	Metal	758			Cascade now receiving high TBP waste in addition to T Plant metal wastes
4	Metal	766			Overflow to 106-TX plugged @ month end → plugged 11/8/52
1-1953	Metal	766			Replugged on 2/53 Unplugged 2/53 Overflow to 106-TX
2	Metal	758			
3	Metal	758			
4	Metal	758			
1-1954	Metal	758			
2	Metal	758			Overflow to 106-TX partially plugged
3	Metal	758			
4	Metal	758			
1-1955	Metal	758			
2	Metal	55		55	Sluicing tank
3	Metal	1		1	Sluicing tank
4	Metal	5		1	
1-1956	Metal	387			Receives T Plant MW
2	Metal	439			S.S. received from T Plant
3	Metal	444			S.S. received from T Plant
4	Metal	5		3	Sluicing
1-1957	R	0			Declared MT
2	R	12			New electrode reading
3	R	13			New electrode reading
4	R	13			

9 2 1 2 5 5 6 1 5 6 6

Waste Status Report of 105-TX Tank-Farm Capacity (750,000 gals.)

Quar.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	13			
2-	R	13			
3-	R	13			
4-	R	13			
1-1959	R	15			Latest electrode rdg.
2-	R	15			
3-	R	301			1) From 102-SX rec'd 264M Salt Waste 2) 15M rec'd from 102-SX 7M flush H_2O rec'd
4-	R	301			
1-1960	R	301			
2-	R	301			
3-	R	301			
4-	R	301			
1-1961	R	301			Six months
2-					
3-	R	301			Six months
4-					
1-1962	R	301			Six months
2-					
3-	R	771			Six months 470 M from 102-SX
4-					
1-1963	R	769			Six months
2-					
3-	R	772			Six months Latest electrode reading
4-					
1-1964	R	769			Six months Latest electrode reading
2-					
3-	R	769			Six months
4-					

9212156167

Waste Storage Summary of 105-TX Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	R	142		8	Six months
2-					627 M to 103-SX
3-	R	142		8	
4-	R	673		8	493 M from 102-SX
1-1966	R	689		8	Latest electrode reading
2-	R	689		8	
3-	R	689		8	
4-	R	689		8	
1-1967	R	689		8	
2-	R	688		8	
3-	R	688		8	
4-	R	685		8	
1-1968	R	685		8	
2-	R	685		8	
3-	R	683		8	
4-	R	684	676	8	
1-1969	R	685	677	8	
2-	R	686	678	8	
3-	R	685	677	8	
4-	R	685	672	11	
1-1970	R	687	674	13	
2-	R	700	687	13	Received 13 flush water
3-	R	703	690	13	
4-	R	109	96	13	228 to 105-C, 366 to 101-TX
1-1971	R	111	98	13	
2-	EB-CW-OWW-RIX	176	45-18-36-64	13	966 from 106-BX flush water, 542 to 102-TX, 412 to 106-TK
3- *	EB	656	643	13	242-T bottoms and recycle
4-	EB	712	544	168	242-T bottoms and recycle (1)

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainity in the liquid-to-solid ratio of tank

* Leak detection dry wells 51-05-05, 51-05-08 and 51-05-10 drilled

9 2 1 2 5 5 6 1 5 6 8

105-TX (750,000 gals.)

Year	Type Waste	Total Vol.	Solids in Storage	Liquids in Storage	Remarks
1-1972	EB	721	417	304	242-T bottoms and recycle (1
2-	EB	723	372	351	242-T bottoms and recycle (1
3-	EB	719	289	430	242-T bottoms and recycle (1
4-	EB	708	278	430	242-T bottoms and recycle (1 3 flush water
1-1973	EB	716	217	499	242-T bottoms and recycle (1
2-	EB	721	222	499	242-T bottoms and recycle (1
3-	EB	714	215	499	242-T bottoms and recycle (1
4-	EB	717	218	499	242-T bottoms and recycle (1
1-1974	EB	712	213	499	242-T bottoms and recycle (1
2-	EB	710	211	499	242-T bottoms and recycle (1
3-*	EB	722	223	499	242-T bottoms and recycle (1
4-	EB	733	231	502	242-T bottoms and recycle (1
1-1975	EB	714	212	502	242-T bottoms and recycle (1
2-	EB	717	215	502	242-T bottoms and recycle (1
3-	EB	695	193	502	242-T bottoms and recycle (1 Salt filled
4-	EB	706	204	502	Salt filled
1-1976	EB	711	209	502	Salt filled, 6 water
2-	EB	708	206	502	RFS - Salt filled
3-	Evap. Feed	708	206	502	Active restricted
4-	Evap. Feed	708	206	502	Restricted
1-1977	Evap Feed	692	190	502	Restricted
2	Evap Feed	629	127	502	Restricted
3	Evap Feed	609	0	609	Inactive current
4	Evap Feed	609	0	609	Inactive current-salt well installed

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks.

* Leak detection dry wells 51-05-01, 51-05-03 and 51-05-07 drilled.

9 2 1 2 5 5 6 1 5 6 9

Waste Status Summary of 105 TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	609	0	609	Questionable Integrity Prim. Stab.
2-	-	609	0	609	New Photo 3-17-78
3-	-	609	0	609	
4-	-	609	0	609	
1-1979	-	609	0	609	
2-	-	609	0	609	
3-	-	609	0	609	
4-	-	609	0	609	
1-1980	-	609	0	609	
2-	-	609	0	609	Shallow Pools
3-	-	609	0	609	
4-	-	609	0	609	

9 2 1 2 5 5 6 1 5 7 0

106-TX Tank Capacity (750,000 gals.)

Year	Month	Total Vol.	Change	Change
1-1944				
2				
3				
4				
1-1945				
2				
3				
4				
1-1946				
2				
3				
4				
1-1947				
2				
3				
4				
1-1948				
2				
3				
4				
1-1949				
2				
3				
4				
1-1950				
2				
3				
4				

9 2 1 2 5 5 6 1 5 7 1

Waste Status Summary of 106-TX Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	Metal	758			
3	Metal	95			Started pumping to 114-TX on 8-29-52, Pumped 114-TX on 9-6-52 overground
4	Metal	292			Active cascade 221-T metal waste
1-1953	Metal	523			105-TX overflow
2	Metal	633			
3	Metal	635			
4	Metal	758			Received from 101-TX
1-1954	Metal	758			
2	Metal	758			
3	Metal	758			
4	Metal	758			
1-1955	Metal	758			
2	Metal	710			
3	Metal	15		15	Supernatant for blending sluicing
4	Metal	6		1	
1-1956	Metal	5		1	
2	Metal	5		1	
3	Metal	3			
4	Metal	3			
1-1957	R	0			To be declared MT
2	R	34			New electrode reading
3	R	35			New electrode reading
4	R	35			

9 2 1 2 5 5 6 1 5 7 2

Waste Stat[illegible] 106-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	35			
2	R	35			
3	R	35			
4	R	35			
1-1959	R	35			
2	R	35			
3	R	35			
4	R	35			
1-1960	R	35			
2	R	35			
3	R	35			
4	R	29			
1-1961	R	29			Six months
2					
3	R	29			Six months
4					
1-1962	R	29			Six months
2					
3	R	29			Six months
4					
1-1963	R	29			Six months
2					
3	R	29			Six months
4					
1-1964	R	29			Six months
2					
3	R	642			Six months, 613 M from 101-TX
4					

9 2 1 2 5 5 6 1 5 7 3

[illegible] 106-TX Tank-Capacity (750,000 gals.)

[illegible]	Type Waste	Total Vol.	[illegible] in Storage	[illegible] in Storage	[illegible]
1-1965	R	645		5	Six months
2					
3	R	645		5	
4	R	645		5	
1-1966	R	645		5	
2	R	645		5	
3	R	642		5	
4	R	642		5	
1-1967	R	642		5	
2	R	641		5	
3	R	641		5	
4	R	641		5	
1-1968	R	640		5	
2	R	638		5	
3	R	638		5	
4	R	638	633	5	
1-1969	R	637	632	5	
2	R	637	632	5	
3	R	637	632	5	
4	R	637	622	15	
1-1970	R	638	623	15	
2	R	641	626	15	
3	R	641	626	15	
4	R	641	626	15	
1-1971	R	71	56	15	561 to 105-C, 8 to 101-TX
2 *	EB-CW-OWW-RIX	490	130-53-105-181	21	412 from 105-TX, 7 flush water
3	EB	623	602	21	242-T bottoms and recycle 328 to 101-TX
4	EB	716	574	142	(1)

(1) Due to characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks.

* Leak detection dry wells 51-06-02, 51-06-04 and 51-06-10 drilled.

9 2 1 2 5 5 6 1 5 7 4

Waste Status Summary of 106-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	677	494	183	242-T bottoms and recycle (1)
2	EB	686	418	268	242-T bottoms and recycle (1)
3	EB	722	454	268	242-T bottoms and recycle (1)
4	EB	714	446	268	242-T bottoms and recycle (1)
1-1973	EB	686	418	268	242-T bottoms and recycle (1)
2	EB	707	439	268	242-T bottoms and recycle (1)
3	EB	690	422	268	242-T bottoms and recycle (1
4	EB	688	420	268	242-T bottoms and recycle (1)
1-1974	EB	710	442	268	242-T bottoms and recycle (1)
2	EB	693	425	268	242-T bottoms and recycle (1)
3 *	EB	690	422	268	242-T bottoms and recycle (1)
4	EB	692	435	257	242-T bottoms and recycle (1)
1-1975	EB	722	465	257	242-T bottoms and recycle (1)
2	EB	521	264	257	242-T bottoms and recycle (1)
3	EB	527	270	257	242-T bottoms and recycle (1) Salt filled
4	EB	532	275	257	242-T bottoms and recycle (1)
1-1976	EB	530	273	257	242-T bottoms and recycle (1)
2	EB	527	270	257	242-T bottoms and recycle (1)
3 **	Evap. Feed	527	270	257	Evap. Feed Con., Evap Feed bottoms
4	Evap. Feed	609	352	257	Evap. Feed Con., Chetated Sr. Waste
1-1977	Evap Feed	615	358	257	Evap. Feed Con., Chelated Sr. Waste
2	Evap Feed	612	355	257	Evap. Feed Con., Chelated Sr. Waste
3	Evap Feed	453	0	453	Inactive Current
4	Evap Feed	453	0	453	Inactive Current

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tank.

* Leak detection dry well 51-06-08 drilled.

** Lead detection dry well 51-06-12 drilled.

9 2 1 2 5 5 6 1 5 7 5

Waste Status Summary of 106-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	453	0	453	Inactive
2-	-	453	0	453	New Photo 3-17-78
3-	-	453	0	453	
4-	-	453	0	453	
1-1979	-	453	0	453	
2-	-	453	0	453	
3-	-	453	0	453	
4-	-	453	0	453	
1-1980	-	453	0	453	
2-	-	453	0	453	Aux-SW-Receiver
3-	-	453	0	453	
4-	-	453	0	453	

9 2 1 2 5 6 1 5 7 6

Waste Status Summary of 107-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 5 6 1 5 7 7

Waste Status Summary of 107-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	*Remarks
1-1971					
2					
3					
4					
1-1952					
2	Metal	758			
3	Metal	758			
4	Metal	766			Supernate Temp. 213°F 10-31-52
1-1953	Metal	766			
2	Metal	758			
3	Metal	758			
4	Metal	758			
1-1954	Metal	758			
2	Metal	758			
3	Metal	30		30	Active sluicing tank
4	Metal	23			Active sluicing tank
1-1955	Metal	10		10	Active sluicing tank next for T Plant metal waste
2	Metal	244			
3	Metal	758			Tank filled 9/26 with T Plant MW
4	Metal	758			
1-1956	Metal	758			
2	Metal	758			
3	Metal	15		10	Sluicing
4	Metal	2		1	Sluicing
1-1957	Metal	0			(1) to be declared MT (2) sluicing, (3) declared MT
2	R	12			New electrode reading
3	R	13			New electrode reading
4	R	0			New electrode reading

* (1) (2) (3) designates month in each quarter that transfer occurred.

9 2 1 2 5 5 6 1 5 7 8

Waste Status Summary of 107-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	0			
2	R	0			
3	R	0			
4	R	2			
1-1959	R	2			
2	R	2			
3	R	2			
4	R	2			
1-1960	R	2			
2	R	2			
3	R	2			
4	R	3			
1-1961	R	9			Six months
2					
3	R	9			Six months
4					
1-1962	R	9			Six months
2					
3	R	9			Six months
4					
1-1963	R	7			Six months, Received 3 M water flush
2					
3	R	7			Six months
4					
1-1964	R	7			Six months
2					
3	R	7			Six months
4					

9 2 1 2 5 5 6 1 5 7 9

Waste Status Summary of 107-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	R	659		8	Six months, 627 M from 105-TX
2					
3	R	659		8	
4	R	662		8	
1-1966	R	662		8	
2	R	662		8	
3	R	662		8	
4	R	662		8	
1-1967	R	662		8	
2	R	663		8	
3	R	663		8	
4	R	663		8	
1-1968	R	663		8	
2	R	662		8	
3	R	662		8	
4	R	663	655	8	
1-1969	R	664	656	8	
2	R	664	656	8	
3	R	664	656	8	
4	R	664	658	6	
1-1970	R	664	658	6	
2	R	666	660	6	
3	R	665	659	6	
4	R	665	659	6	
1-1971	R	666	660	6	
2	R	666	642	24	
3 *	R	666	642	24	
4	R	666	642	24	

* Leak detection dry wells 51-07-04, 51-07-09 and 51-07-11 drilled.

9 2 1 2 5 5 6 1 5 8 0

Waste Status Summary of 107-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	R	675	651	24	
2	R	673	649	24	
3	R	673	649	24	
4	R	673	649	24	
1-1973	R	673	649	24	
2	R	674	650	24	
3	R	674	650	24	
4	R	675	651	24	
1-1974	R	675	651	24	
2 *	R	675	651	24	
3	R	675	651	24	
4	R	675	651	24	Awaiting solidification
1-1975	ER-R	274	18-232	24	18 from 109-TX, 418 to 106-SX
2	EB	725	701	24	242-T bottoms and recycle (1)
3	EB	725	701	24	242-T bottoms and recycle (1)
4	EB	700	676	24	242-T bottoms and recycle (1)
1-1976	EB	719	695	24	242-T bottoms and recycle (1)
2 **	EB	714	690	24	242-T bottoms and recycle (1)
3	Evap. Feed	717	693	24	Evap. Feed con., Evap. Feed bottoms
4	Evap. Feed	717	693	24	Evap. Feed Con., Chelated Sr. waste
1-1977	Evap Feed	711	687	24	Evap. Feed Con., Chelated Sr. Waste
2 ***	Evap Feed	95	71	24	Evap. Feed Con., Chelated Sr. Waste
3	Evap Feed	24	0	24	Inactive Current, Chelated Sr Waste
4	Evap Feed	24	0	24	Inactive Current, Open Hole Salt Well

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks.

* Leak detection dry well 51-07-01 drilled.
** Leak detection dry well 51-07-03 drilled.
*** Leak detection dry wells 51-07-07 and 51-07-18 drilled.

9 2 1 2 5 5 6 1 5 8 1

Waste Status Summary of 107-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	40	0	40	Prim. Stab., New Solids Level 1-19-78
2-	-	40	0	40	
3-	-	40	0	40	
4-	-	40	0	40	
1-1979	-	40	0	40	New Photo 3-15-79
2-	-	40	0	40	Questionable Integrity
3-	-	40	0	40	
4-	-	40	0	40	
1-1980	-	40	0	40	New Photo 2-13-80
2-	-	40	0	40	1 K Pool
3-	-	40	0	40	
4-	-	40	0	40	

9212561532

Waste Status Summary of 108TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					
1-1951					
2					
3					
4					
1-1952					
2	Metal Waste	461			MW tank now filling T plant via 107TX
3	Metal Waste	718			Active MW tank T plant acti tank 221-T-metal waste
4	Metal Waste	751			

9 2 1 2 1 5 6 1 5 5 3

Waste Status Summary of 108TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	*Remarks
1-1953	Metal Waste	751			
2	Metal Waste	751			
3	Metal Waste	751			
4	Metal Waste	751			
1-1954	Metal Waste	758			
2	Metal Waste	758			
3	Metal Waste	758			
4	Metal Waste	758			
1-1955	Metal Waste	222			Supernatant for blending
2	Metal Waste	10			Supernatant for blending sluicing
3	Metal Waste	722			
4	Metal Waste	758			
1-1956	Metal Waste	758			
2	Metal Waste	758			
3	Metal Waste	758			
4	Metal Waste	3		2	(1) incorrect rdg. last mont sluicing
1-1957	Metal Waste	0			Declared MT
2	R	13			New electrode rdg.
3	R	13			New electrode rdg.
4	R	13			
1-1958	R	13			
2	R	13			
3	R	15			Latest electrode rdg.
4	R	15			
1-1959	R	15			
2	R	15			
3	R	15			
4	R	15			
1-1960	R	15			
2	R	15			
3	R	15			
4	R	15-119			(1) Rec'd 93M waste from 105TY (3) Rec'd 24M H_2O 102TY

* (1) (3) designates month in each quarter that transfer occurred.

9 2 1 2 5 5 6 1 5 8 4

Waste Status Summary of 108TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961	TBP	428			Rec'd 294M from 105TY
2					6 month report
3	TBP	428			6 month report
4					
1-1962	TBP	428			6 month report
2					
3	TBP	428			6 month report
4					
1-1963	TBP	428			6 month report
2					
3					
4	TBP	428			6 month report
1-1964	TBP	431			Latest electrode rdg.
2					6 month report
3					
4	TBP-DW	431-112			112M from 118TX
1-1965	TBP-DW	431-143		6	6 month report
2					
3	TBP-DW	431-143		6	
4	TBP-DW	431-143		6	
1-1966	TBP	128		6	446M to 118TX
2	TBP	73		6	55M to 118TX
3	EB	543		63	470M from 117TX
4	EB	697		63	66M from 101-TX
1-1967	EB	695		63	
2	EB	695		63	
3	EB	695		63	
4	EB	695		63	
1-1968	EB	695		81	
2	EB	692		81	
3	EB	692		81	
4	EB	692	611	81	
1-1969	EB	693	612	81	
2	EB	694	613	81	
3	EB	694	613	81	
4	EB	694	584	110	
1-1970	EB	694	584	110	
2	EB	694	584	110	
3	EB	694	584	110	
4	EB	693	583	110	
1-1971	EB	693	583	110	
2	EB	693	581	112	
3 *	EB	693	581	112	
4	EB	697	616	81	4 flush H_2O

* Leak detection dry wells 51-08-05, 51-08-09 and 51-08-11 drilled.

9 2 1 2 5 5 6 1 5 8 5

Waste Status Summary of 108TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	703	622	81	
2	EB	703	622	81	
3	EB	703	622	81	
4	EB	650	569	81	
1-1973	EB	650	569	81	
2	EB	676	595	81	
3	EB	720	639	81	242T bottom & recycle (1)
4	EB	721	640	81	242T bottom & recycle (1)
1-1974	EB	721	640	81	242T bottom & recycle (1)
2	EB	721	640	81	242T bottom & recycle (1)
3	EB	721	640	81	242T bottom & recycle (1)
4	EB	719	638	81	242 bottom & recycle (1)
1-1975	EB	722	641	81	242T bottom & recycle (1)
2	EB	719	638	81	242T bottom & recycle (1)
3	EB	719	638	81	" " " " " " " "
4	EB	719	638	81	" " " " " " " "
1-1976	EB	719	638	81	" " " " " " " "
2	EB	395	314	81	" " " " " " " "
3	Evap feed	109	28	81	323 to 102-U, 1 to 103U Evap feed Con. evap feed btm
4	Evap feed	106	25	81	" " " " " "
1-1977	Evap Feed	81	0	81	Inactive Salt Well Pumping
2	Evap Feed	81	0	81	Inactive Salt Well Pumping
3	Evap Feed	81	0	81	Inactive Current
4	Evap Feed	81	0	81	Inactive Current - Salt Well Installed

(1) Due to the characteristic of solids in bottom tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio.

9 2 1 2 5 5 6 1 5 8 6

Waste Status Summary of 108-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	81	0	81	Inactive
2-	-	81	0	81	Primary Stabilized
3-	-	81	0	81	
4-	-	131	0	131	Solid Level Adj. 10-22-78
1-1979	-	131	0	131	
2-	-	131	0	131	
3-	-	131	0	131	
4-	-	131	0	131	
1-1980	-	131	0	131	
2-	-	131	0	131	New Photo 5-12-80
3-	-	131	0	131	
4-	-	131	0	131	

9 2 1 2 5 5 6 1 5 8 7

Waste Status Summary of 109TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949	1C	335			Began filling in January
2	1C	537			
3	1C	741			Cascade filled in September
4	1C	741			Cascade
1-1950	1C	741			Cascade
2	1C	741			Cascade
3	1C	741			Cascade
4	1C -TBP	722-33		722	New electrode
1-1951					
2					
3					
4					
1-1952					
2	1C	673			1C tank now filling T-plant
3	1C	758			Tank filled on run 7-12-07-DR-18 7/25/52
4	1C	758			Active cascade 221T first cycle
1-1953	1C	758		415	
2	1C	758		415	T-plant active
3	1C	758		622	
4	1C	758		630	T-plant active 1st cycle wast cascade

9 2 1 2 5 6 1 5 3 8

Waste Status Summary Of 109-TX Tank-Capacity 750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C	758		630	T-plant active 1st cycle waste cascade when waste was discharged to the 104T tank
2	1C	758			
3		664		640	Purged 1C waste to 110TX tank because of plugged overflow
4	1C	722		650	Purged 1C waste to 110TX tank because of plugged overflow
1-1955	1C TBP	722-36		650	Rec'd TBP waste
2	1C -TBP	722-36		650	
3	1C -TBP	722-36		650	
4	1C -TBP	722-36		650	
1-1956	1C -TBP	722-36		650	
2	1C -TBP	722-36		650	
3	1C -TBP	722-36		630	
4	1C -TBP	722-32		630	
1-1957	1C -TBP	722-28		722	Latest electrode rdg
2	1C -TBP	722-33		722	
3	1C -TBP	722-33		722	
4	1C -TBP	722-33		722	
1-1958	1C -TBP	722-33		722	
2	1C -TBP	722-33		722	
3	1C -TBP	722-33		722	
4	1C -TBP	722-33		722	
1-1959	1C -TBP	722-33		722	
2	1C -TBP	722-33		722	
3	1C -TBP	722-33		722	
4	1C -TBP	722-30		722	Latest electrode rdg.
1-1960	1C -TBP	722-30		722	
2	1C -TBP	722-30		722	
3	1C -TBP	722-30		722	
4	1C	722-30		722	
1-1961	1C -TBP	722-25		722]	Latest electrode rdg
2					6 month report
3					
4	1C -TBP	722-28		722]	6 month report
1-1962					Latest electrode rdg
2	1C -TBP	722-25		722]	6 month report
3					
4	1C -TBP	722-25		722]	6 month report

9 2 1 2 5 5 6 1 5 8 9

Waste Status Summary of 109TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963	1C -TBP	722-25		722]	6 month report
2					
3					
4	1C -TBP	722-25		722]	6 month report
1-1964	1C -TBP	722-25		722]	6 month report
2					
3					
4	1C -TBP	722-25		722]	6 month report
1-1965	1C -TBP	722-22		590]	6 month report
2					
3	1C -TBP	722-22		590	
4	1C -TBP	722-22		590	
1-1966	1C -TBP	722-22		590	
2	1C -TBP	722-22		590	
3	1C -TBP	722-22		590	
4	1C -TBP	722-22		590	
1-1967	1C -TBP	722-22		590	
2	1C -TBP	722-21		590	
3	1C -TBP	722-21		590	
4	1C -TBP	722-21		590	
1-1968	1C -TBP	722-21		590	
2	1C -TBP	722-21		590	
3	1C -TBP	722-21		590	
4	1C -TBP	743	132-21	590	
1-1969	1C -TBP	743	132-21	590	
2	1C -TBP	743	132-21	590	
3	1C -TBP	743	599-21	123	
4	1C -TBP	743	599-21	123	
1-1970	1C -TBP	743	599-21	123	
2	1C -TBP	743	599-21	123	
3	1C -TBP	743	599-21	123	
4	1C -TBP	743	599-21	123	
1-1971	1C -TBP	743	599-21	123	
2	1C -TBP	743	599-21	123	
3 *	1C -TBP	743	599-21	123	(1)
4	1C -TBP	744	600-21	123	

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tank.

* Leak detection dry wells 51-09-03, 51-09-08 and 51-09-12 drilled.

9 2 1 2 5 5 6 1 5 9 0

Waste Status Summary of 109TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	1C -TBP	744	600-21	123	
2	1C -TBP	744	600-21	123	
3	1C -TBP	741	597-21	123	
4	1C -TBP	736	592-21	123	
1-1973	1C -TBP	737	593-21	123	
2	1C -TBP	734	590-21	123	
3	1C -TBP	735	591-21	123	
4	1C -TBP	733	589-21	123	
1-1974	EB-1C-TBP	694	166-390-15	123	158 from 118TX, 27 H_2O, 226 t 101TX
2	EB	688	565	123	8 from 111-T
3	EB	717	594	123	
4	EB	700	577	123	242T bottoms and recycle (1)
1-1975	EB	697	574	123	242T bottoms and recycle (1)
2	EB	582	459	123	242T bottoms and recycle (1)
3	EB	719	596	123	242T bottoms and recycle (1)
4	EB	703	580	123	242T bottoms and recycle (1)
1-1976	EB	673	550	123	242T bottoms and recycle (1)
2 *	EB	692	569	123	242T bottoms and recycle (1)
3	Evap feed	678	555	123	Evap feed - con. evap feed bt
4	Evap feed	673	550	123	Evap feed chelated sr. waste
1-1977	Evap Feed	670	547	123	Evap feed chelated sr. waste
2	Evap Feed	670	547	123	Evap feed chelated sr. waste
3	Evap Feed	450	0	450	Inactive current, solid level adj.
4	Evap Feed	450	0	450	Inactive current, solid level adj.

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks.

* Leak detection dry wells 51-09-04 and 51-09-10 drilled.

9212556159 1

Waste Status Summary of 109-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	450	0	450	
2-	-	450	0	450	
3-	-	450	0	450	
4-	-	450	0	450	
1-1979	-	450	0	450	
2-	-	450	0	450	
3-	-	450	0	450	
4-	-	450	0	450	
1-1980	-	450	0	450	
2-	-	450	0	450	
3-	-	450	0	450	
4-	-	450	0	450	

9 2 1 2 3 5 6 1 5 9 2

Waste Status Summary of 110TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3	1C	59			Began filling in Sept.
4	1C	409			Cascade
1-1950	1C	741			Cascade filled in March
2	1C	741			Cascade
3	1C	741			Cascade filled in August
4					
1-1951					
2					
3					
4					
1-1952					
2	1C	9			
3	1C	178			Tank now filling T-plant 1st. cycle
4	1C	398			
1-1953	1C	634		9	Active 1st cycle waste tank T Plant
2	1C	758		9	First cycle
3	1C	758		1	
4	1C	758		1	

9 2 1 2 5 6 1 5 9 3

Waste Status Summary of 110TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C	758		1	
2	1C	758		1	Scheduled to be pumped to ditch
3	1C	497		10	
4	1C	497		10	
1-1955	1C -TBP	113-645		10	Rec'd TBP
2	1C "	113-645		10	
3	1C "	113-645		10	
4	1C "	113-645		10	
1-1956	1C -TBP	113-645		10	
2	1C- "	113-645		10	
3	1C- "	113-645		1	
4	1C- "	113-645		1	
1-1957	1C -TBP	113-648		1	
2	1C "	113-650		1	New electrode rdg.
3	1C "	113-650			New electrode rdg.
4	1C "	113-650			
1-1958	1C -TBP	113-650		1	
2	1C "	113-650		1	
3	1C "	113-647		1	Latest electrode rdg.
4	1C "	113-647		1	
1-1959	1C -TBP	113-649		1	Latest electrode rdg
2	1C "	113-649		1	
3	1C "	'113-649		1	
4	1C "	113-649		1	
1-1960	1C -TBP	113-649		1	
2	1C -TBP	113-649		1	
3	1C "	113-649		1	
4	1C "	113-649		1	
1-1961	1C -TBP	113-649		1	6 month report
2					
3					
4	1C -TBP	113-649		1	6 month report
1-1962					
2	1C -TBP	113-649		1	6 month report
3					
4	1C -TBP	113-649		1	6 month report
1-1963	1C -TBP	113-649			6 month report
2					
3					
4	1C -TBP	113-645			Latest electrode rdg. 6 month report

9 2 1 2 5 5 6 1 5 9 4

Waste Status Summary of 110TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964	1C-TBP	113-645			6 month report
2					
3					
4	1C-TBP	113-649			Latest electrode rdg. 6 month report
1-1965	1C-TBP	113-639		40	6 month report
2					
3	1C-TBP	113-639		40	
4	1C "	113-639		40	
1-1966	1C-TBP	113-639		40	
2	1C "	113-639		40	
3	1C "	113-639		40	
4	1C "	113-639		40	
1-1967	1C-TBP	113-639		40	
2	1C-"	113-641		40	
3	1C-"	113-641		40	
4	1C-"	113-641		40	
1-1968	1C-TBP	113-641		40	
2	1C-"	113-641		40	
3	1C-"	113-641		40	
4	1C-"	754	73-641	40	
1-1969	1C-TBP	759	73-641	40	
2	1C-"	754	73-641	40	
3	1C-"	754	73-641	40	
4	1C-"	755	73-679	3	
1-1970	1C-TBP	754	73-644	37	
2 *	EB	696	634	62	Placed in bottoms service 4/14/70
3	EB	682	590	92	242T bottoms and recycle
4	EB	701	576	125	"
1-1971	EB	706	548(1)	158(1)	242T bottoms and recycle
2	EB	712	548	164	"
3	EB	697	453	244	"
4	EB	688	288	400	(1)
1-1972	EB	719	319	400	242T bottoms and recycle (1)
2	EB	722	322	400	"
3	EB	685	213	472	"
4	EB	688	216	472	"

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks 110TX through 118TX

* Leak detection dry wells 51-10-04, 51-10-08 and 51-10-12 drilled.

9 2 1 2 5 5 6 1 5 9 5

Waste Status Summary of 110TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973	EB	700	267	433	242T bottoms and recycle (1)
2	EB	686	253	433	"
3	EB	696	262	433	"
4	EB	684	251	433	"
1-1974	EB	682	249	433	242T bottoms and recycle (1)
2	EB	681	248	433	"
3 *	EB	722	289	433	"
4	EB	697	277	420	"
1-1975	EB	717	297	420	242T bottoms and recycle (1)
2	EB	695	275	420	"
3	EB	692	272	420	"
4	EB	590	170	420	"
1-1976	EB	719	299	420	242T bottoms and recycle (1)
2	EB	719	299	420	"
3	Evap feed	722	302	420	Evap feed-con. Evap feed btms
4	Evap feed	706	286	420	" " " chelated sr. wast
1-1977	Evap feed	708	288	420	Evap feed-con. chelated sr. waste
2 **	Evap feed	585	165	420	Evap feed-con. chelated sr. waste
3	Evap feed	568	0	568	Inactive current, solid level adj.
4	Evap feed	568	0	568	Inactive current, solid level adj.

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks 110TX through 118TX

*Leak detection dry well 51-10-01 drilled.
**Leak detection dry well 51-10-13 drilled third quarter 1977.

9212556159 6

Waste Status Summary of 110-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	568	0	568	Prim. Stab.
2-	-	568	0	568	
3-	-	568	0	568	
4-	-	568	0	568	Pump Removed
1-1979	-	568	0	568	New Photo 3-26-79
2-	-	568	0	568	Questionable Integrity
3-	-	568	0	568	
4-	-	530	0	530	
1-1980	-	530	0	530	
* 2-	-	530	0	530	500 Gal. Pool
3-	-	530	0	530	
4-	-	530	0	530	

* New Well 5 1 - 10-25 in service 3-23-78

9 2 1 2 1 5 6 1 3 9 7

Waste Status Summary of 111TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949 *					
2					
3					
4					
1-1950	1C	42			Cascade began filling in Marc
2	1C	421			Cascade
3	1C	741			Cascade filled in August
4					
1-1951					
2					
3					
4					
1-1952					
2	1C	---			
3	1C	---			
4	1C	---			
1-1953	1C	---			
2	1C	0			Waste
3	1C	224			Waste
4	1C	474			Waste

* Leak detection dry well 51-11-02 drilled.

9 2 1 2 3 6 1 3 9 3

Waste Status Summary of 111TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C	747			
2	1C	747			
3	1C	134			
4	1C-TBP	103-627			Rec'd from 103TX
1-1955	1C-TBP	103-655		88	Rec'd TBP waste
2	1C-TBP	103-655		88	
3	1C-TBP	103-655		88	
4	1C-TBP	103-655		88	
1-1956	1C-TBP	103-655		88	
2	1C-TBP	103-655		88	
3	1C-TBP	103-655			
4	1C-TBP	103-655			
1-1957	1C-TBP	103-622(E)			No electrode
2	1C-TBP	103-655			Latest electrode rdg.
3	1C-TBP	103-655			
4	1C-TBP	103-658			
1-1958	1C-TBP	103-658			
2	1C-TBP	103-658			
3	1C-TBP	103-658			
4	1C-TBP	103-655			Latest electrode rdg.
1-1959	1C-TBP	103-655			
2	1C-TBP	103-655			
3	1C-TBP	103-655			
4	1C-TBP	103-655			
1-1960	1C-TBP	103-655			
2	1C-TBP	103-655			
3	1C-TBP	103-655			
4	1C-TBP	103-655			
1-1961	1C-TBP	103-655			6 month report
2					
3					
4	1C-TBP	103-655			6 month report
1-1962	1C-TBP	103-652			6 month report
2					
3					
4	1C-TBP	103-652			6 month report
1-1963	1C-TBP	103-652			6 month report
2					
3					
4	1C-TBP	103-652			6 month report

Waste Status Summary of 111TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964	1C-TBP	103-652			6 month report
2					
3					
4	1C-TBP	103-652			6 month report
1-1965	1C-TBP	103-647		4	6 month report
2					
3	1C-TBP	103-647		4	
4	1C-TBP	103-647		4	
1-1966	1C-TBP	103-647		4	
2	1C-TBP	103-647		4	
3	1C-TBP	103-647		4	
4	1C-TBP	103-647		4	
1-1967	1C-TBP	103-647		4	
2	1C-TBP	103-649		4	
3	1C-TBP	103-649		4	
4	1C-TBP	103-649		4	
1-1968	1C-TBP	103-649		4	
2	1C-TBP	103-648		4	
3	1C-TBP	103-649		4	
4	1C-TBP	752	99-649	4	
1-1969	1C-TBP	752	99-649	4	
2	1C-TBP	751	99-648	4	
3	1C-TBP	752	99-649	4	
4	1C-TBP	752	99-650	4	
1-1970	1C-TBP	752	99-610	43	
2	EB	685	619	66	Placed in bottoms service 4/19/70
3*	EB	718	609	109	242T bottoms and recycle
4	EB	668	435	233	242T bottoms and recycle
1-1971	EB	699	414	285	242T bottoms and recycle
2	EB	699	357	51	242T bottoms and recycle
3	EB	689	291	398	242T bottoms and recycle
4	EB	689	359	330	(1)
1-1972	EB	693	304	389	242T bottoms and recycle (1)
2	EB	732	343	389	242T bottoms and recycle (1)
3	EB	723	334	389	242T bottoms and recycle (1)
4	EB	689	300	389	242T bottoms and recycle (1)

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks 110TX through 118TX

* Leak detection dry wells 51-11-03, 51-11-07 and 51-11-10 drilled.

9212556160 0

Waste Status Summary of 111TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973	EB	725	336	389	242T bottoms and recycle (1)
2	EB	699	310	389	"
3	EB	690	301	389	"
4	EB	728	339	389	"
1-1974	EB	724	335	389	242T bottoms and recycle (1)
2 *	EB	722	333	389	"
3	EB	697	308	389	"
4	EB	708	319	389	"
1-1975	EB	719	330	389	242T bottoms and recycle (1)
2	EB	703	314	389	"
3	EB	590	201	389	"
4	EB	719	330	389	"
1-1976	EB	722	333	389	242T bottoms and recycle (1)
2	EB	708	319	389	" 14 to 118TX
3	Evap feed	717	328	389	Evap feed con evap feed btms
4	Evap feed	719	330	389	Evap feed chelated sr. waste
1-1977	Evap feed	722	333	389	Evap feed-con. chelated sr. waste
2	Evap feed	593	204	389	Evap feed-con. chelated sr waste
3	Evap feed	403	14	389	Inactive current chelated sr. waste
4	Evap feed	403	33	370	Inactive current, salt well installed.

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degeee of uncertainty in the liquid to solid ratio of tanks 110TX through 118TX

* Leak detection dry well 51-11-01 drilled.

9212556160 1

Waste Status Summary of 111-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NCPLX	403	33	370	Salt Well Installed
2-	NCPLX	403	33	370	
3-	NCPLX	403	33	370	
4-	NCPLX	403	33	370	
1-1979	NCPLX	403	33	370	New Photo3-26-79
2-	NCPLX	403	33	370	
3-	NCPLX	403	33	370	
4-	NCPLX	403	33	370	
1-1980	NCPLX	403	33	370	
2-	NCPLX	403	33	370	
3-	NCPLX	403	33	370	
4-	NCPLX	403	33	370	

9 2 1 2 5 6 1 6 7 2

Waste Status Summary of 112TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3	1C	228			Began filling in August
4					
1-1951					
2					
3					
4					
1-1952					
2	1C	---			
3	1C	---			
4	1C	---			Tank to be held for recouplex waste
1-1953	1C	---			112TX no longer held for recouplex Cascade
2	1C	---			
3	1C	0			
4	1C	0			

9 2 1 2 5 6 1 6 7 3

Waste Status Summary of 112TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C	0			
2	EB	752			Rec'd from 117TX
3	EB	752			
4	EB	752			
1-1955	EB	752			
2	EB	752			
3	EB	752			
4	EB	752			
1-1956	EB	752			
2	EB	752			
3	EB	752			
4	EB	752			
1-1957	EB	761			Latest electrode rdg.
2	EB	747			Latest electrode rdg.
3	EB	750			
4	EB	750			
1-1958	EB	750			
2	EB	750			
3	EB	750			
4	EB	750			
1-1959	EB	750			
2	EB	750			
3	EB	750			
4	EB	750			
1-1960	EB	750			
2	EB	750			
3	EB	750			
4	EB	747			
1-1961	EB	747			6 month report
2					
3					
4	EB	747			6 month report
1-1962					
2	EB	750			6 month report
3					
4	EB	750			6 month report
1-1963	EB	750			6 month report
2					
3					
4	EB	750			6 month report

9 2 1 2 5 5 6 1 6 0 4

Waste Status Summary of 112TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1964	EB	750	6 months		
2					
3					
4	EB	750	6 months		
1-1965	EB	747	6 months	24	
2					
3	EB	747		24	
4	EB	747		24	
1-1966	EB	747		24	
2	EB	747		24	
3	EB	747		24	
4	EB	747		24	
1-1967	EB	747		24	
2	EB	747		24	
3	EB	747		24	
4	EB	747		24	
1-1968	EB	747		24	
2	EB	747		24	
3	EB	747		24	
4	EB	748	724	24	
1-1969	EB	747	723	24	
2	EB	748	724	28	
3	EB	748	724	24	
4	EB	749	716	33	
1-1970	EB	747	708	39	
2 *	EB	747	708	39	
3	EB	722	566	156	To bottoms and recycle in July
4	EB	723	460	262	"
1-1971	EB	721	351	370	To bottoms and recycle in July
2	EB	719	332	387	"
3	EB	726	339	387	"
4	EB	711	224	487	(1)
1-1972	EB	688	236	452	242T bottoms and recycle (1)
2	EB	686	234	452	"
3	EB	690	238	452	"
4	EB	755	239	516	" 34 flush water

(1) due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks.

* Leak detection dry wells 51-12-04, 51-12-07 and 51-12-11 drilled.

9212556160 5

Waste Status Summary of 112TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1973 *	EB	711	52	659	242T bottoms and recycle (1)
2	EB	722	63	659	"
3	EB	723	64	659	"
4	EB	707	48	659	"
1-1974	EB	723	64	659	242T bottoms and recycle (1)
2	EB	682	23	659	"
3 **	EB	685	26	659	"
4	EB	711	47	664	"
1-1975	EB	711	47	664	242T bottoms and recycle (1)
2	EB	714	50	664	"
3	EB	717	53	664	"
4	EB	711	47	664	Salt filled
1-1976	EB	711	47	664	Salt filled
2	EB	711	47	664	RFS - salt filled
3	Evap feed	714	50	664	Demo cooler
4	Evap feed	714	50	664	Inactive demo cooler
1-1977	Evap feed	714	50	664	Inactive demo cooler
2	Evap feed	714	50	664	Inactive demo cooler
3	Evap feed	684	20	664	Inactive demo cooler
4	Evap feed	673	9	664	Inactive salt well installed

* Leak detection dry well 51-12-01 drilled.
** Leak detection dry well 51-12-05 drilled.

(1) due to the characteristics of solids in tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks 110TX through 118TX

9 2 1 2 5 5 6 1 6 0 6

Waste Status Summary of 112-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NCPLX	673	9	664	Salt Well Installed
2-	NCPLX	673	9	664	
3-	NCPLX	673	9	664	
4-	NCPLX	673	9	664	
1-1979	NCPLX	673	9	664	
2-	NCPLX	673	9	664	
3-	NCPLX	673	9	664	
4-	NCPLX	673	9	664	
1-1980	NCPLX	673	9	664	
2-	NCPLX	673	9	664	
3-	NCPLX	673	9	664	
4-	NCPLX	673	9	664	

9 2 1 2 5 5 6 1 6 0 7

Waste Status Summary of 113-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9212156108

Waste Status Summary of 113-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	EB	532			Active bottoms tank - West Area
3	EB	750			Active bottoms tank - West Area
4	EB	748			
1-1953	EB	748			
2	EB	290			EB & 1st cycle sludge
3	EB	758		252	Filled with TBP, Bottoms
4	EB	758		252	1C sludge & TBP Evap. bottoms
1-1954	EB	758		252	1C sludge & TBP Evap. bottoms
2	EB	748		252	1-C sludge & TBP waste evaporator bottoms
3	EB	748		252	1-C sludge & TBP waste evaporator bottoms
4	EB	748		252	
1-1955	EB	748		252	
2	EB	753		252	
3	EB	753		252	
4	EB	753		252	
1-1956	EB	753		252	
2	EB	753		252	
3	EB	753		252	
4	EB	753		252	
1-1957	1C-EB	252-509		252	Latest electrode reading
2	1C-EB	252-511		142	Latest electrode reading
3	1C-EB	252-514		142	Latest electrode reading
4	1C-EB	252-514		142	

9 2 1 2 5 5 6 1 6 0 9

Waste Status Summary of 113-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	1C-EB	252-514		142	
2	1C-EB	252-514		142	
3	1C-EB	252-514		142	
4	1C-EB	252-514		142	
1-1959	1C-EB	252-514		142	
2	1C-EB	252-514		142	
3	1C-EB	252-514		142	
4	1C-EB	252-514		142	
1-1960	1C-EB	252-511		142	
2	1C-EB	252-511		142	
3	1C-EB	252-511		142	
4	1C-EB	252-508		142	
1-1961	1C-EB	252-508		142	Six months
2					
3	1C-EB	252-508		142	Six months
4					
1-1962	1C-EB	252-508		142	Six months
2					
3	1C-EB	252-508		142	Six months
4					
1-1963	1C-EB	252-508		142	Six months
2					
3	1C-EB	252-508		142	Six months
4					
1-1964	1C-EB	252-508		142	Six months
2					
3	1C-EB	252-508		142	Six months
4					

9212556160

Waste Status Summary of 113-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	1C-EB	252-509		183	Six months
2					
3	1C-EB	252-509		183	
4	1C-EB	252-509		183	
1-1966	EB	524		183	Receiver for EB
2	EB	744		183	Receiver for EB
3	EB	733		171	Receiver for EB
4	EB	733		171	Receiver for EB
1-1967	EB	728		171	
2	EB	722		171	
3	EB	725		171	
4	EB	725		222	
1-1968	EB	725		211	
2	EB	720		215	5M evaporated
3	EB	720		213	
4	EB	609	319	290	242-T bottoms and recyle
1-1969	EB	585	267	318	242-T bottoms and recycle
2	EB	609	231	378	242-T bottoms and recycle
3	EB	677	293	384	242-T bottoms and recycle
4	EB	653	255	398	242-T bottoms and recycle
1-1970	EB	704	323	381	242-T bottoms and recycle
2	EB	693	213	480	242-T bottoms and recycle
3 *	EB	692	168	524	242-T bottoms and recycle
4	EB	688	153	535	242-T bottoms and recycle
1-1971	EB	721	175	546	242-T bottoms and recycle
2	EB	723	125	598	242-T bottoms and recycle, 80 from 116-TX
3	EB	725	44	681	242-T bottoms and recycle, 8 from 116-TX
4	EB	715	59	656	(1), 22 from 116-TX

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks.

* Leak detection dry wells 51-13-05, 51-13-08 and 51-13-12 drilled.

9 2 1 2 5 5 6 1 6 1 1

Waste Status Summary of 113-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	714	58	656	242-T bottoms and recycle (1
2	EB	708	52	656	242-T bottoms and recycle (1
3	EB	714	58	656	242-T bottoms and recycle (1
4	EB	719	63	656	242-T bottoms and recycle, 4 from 116-TX, (1)
1-1973	EB	704	48	656	242-T bottoms and recycle (1
2	EB	706	50	656	242-T bottoms and recycle (1
3	EB	706	50	656	242-T bottoms and recycle (1
4	EB	703	47	656	242-T bottoms and recycle (1
1-1974	EB	701	45	656	242-T bottoms and recycle (1
2	EB	703	47	656	242-T bottoms and recycle (1
3	EB	712	56	656	242-T bottoms and recycle (1
4	EB	697	41	656	Salt filled, 21 to 115-TX (1
1-1975	---	681	0	681	Salt filled, 122 to 115-TX
2	---	681	0	681	Removed from service, 15 to 115-TX
3	---	681	0	681	Removed from service
4	---	681	0	681	Removed from service
1-1976	---	681	0	681	Removed from service, 29 to 115-TX
2	---	681	0	681	RFS
3	---	681	0	681	Salt well pump, inactive salt well pumping
4	---	681	0	681	Salt well pump
1-1977	---	681	0	681	Salt well pumping
2	---	681	0	681	Salt well pumping
3	---	681	0	681	Inactive current
4	---	681	0	681	Inactive current salt well installed.

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks.

9 2 1 2 5 5 6 1 6 1 2

Waste Status Summary of 113-TXTank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	681	0	681	Primary Stabil.
2-	-	681	0	681	
3-	-	681	0	681	
4-	-	681	0	681	
1-1979	-	681	0	681	
2-	-	681	0	681	P-10 PMP Removed, Question. Integrity
3-	-	681	0	681	
4-	-	681	0	681	
1-1980	-	681	0	681	New Photo 1-29-80
2-	-	681	0	681	
3-	-	681	0	681	
4-	-	681	0	681	

9 2 1 2 1 5 6 1 6 1 3

Waste Status Summary of 114-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 3 5 6 1 6 1 4

Waste Status Summary of 114-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	1C	558			Tank now pumping reclaimed space
3	1C	666			Pumping stopped 7/11/52 Received from 106-TX 9/6/52
4	1C	666			
1-1953	1C	666			
2	1C	666			
3	1C	666		4	
4	1C	666		4	Supernatant
1-1954	1C	700		4	
2	MW	411		4	Transferred to 104-TX
3	EB	739		4	
4	EB	739		4	
1-1955	EB	739		4	
2	EB	739		4	
3	EB	739		4	
4	EB	739		4	
1-1956	EB	739		4	
2	EB	739		4	
3	EB	739		4	
4	EB	739		4	
1-1957	EB	741		4	
2	EB	741		15	Latest electrode reading
3	EB	741		15	
4	EB	741		15	

9 2 1 2 5 5 6 1 6 1 5

Waste Status Summary of 114-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	EB	741		15	
2	EB	741		15	
3	EB	741		15	
4	EB	741		15	
1-1959	EB	741		15	
2	EB	741		15	
3	EB	741		15	
4	EB	741		15	
1-1960	EB	741		15	
2	EB	741		15	
3	EB	741		15	
4	EB	741		15	
1-1961	EB	741		15	Six months
2					
3	EB	741		15	Six months
4					
1-1962	EB	741		15	Six months
2					
3	EB	741		15	Six months
4					
1-1963	EB	741		15	Six months
2					
3	EB	741		15	Six months
4					
1-1964	EB	741		15	Six months
2					
3	EB	741		15	Six months
4					

9 2 1 2 5 5 6 1 6 1 6

Waste Status Summary of 114-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	EB	774		62	Six months
2					
3	EB	774		62	
4	EB	774		62	
1-1966	EB	774		62	
2	EB	774		62	
3	EB	774		62	
4	EB	772		62	
1-1967	EB	755		62	
2	EB	722		62	33 M evaporation
3	EB	677		62	45 M evaporation
4	EB	558		140	242-T bottoms and recycle
1-1968	EB	631		103	242-T bottoms and recycle
2	EB	565		139	242-T bottoms and recycle
3	EB	673		128	242-T bottoms and recycle
4	EB	651	528	123	Bottoms receiver changed (11/21) to 113-TX
1-1969	EB	651	424	227	
2	EB	653	407	246	
3	EB	629	385	244	
4	EB	725	462	263	242-T bottoms
1-1970	EB	717	423	294	242-T bottoms
2*	EB	667	322	345	242-T bottoms and recycle
3	EB	718	323	395	242-T bottoms and recycle
4	EB	728	165	563	242-T bottoms and recycle
1-1971	EB	670	146	524	242-T bottoms and recycle
2	EB	695	187	508	242-T bottoms and recycle
3	EB	692	102	590	242-T bottoms and recycle
4	EB	715	53	662	(1)

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

* Leak detection dry wells 51-14-04, 51-14-08 and 51-14-11 drilled.

9 2 1 2 5 5 6 1 6 1 7

Waste Status Summary of 114-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	707	21	686	242-T bottoms and recycle (1)
2	EB	693	7	686	242-T bottoms and recycle (1)
3	EB	722	36	686	242-T bottoms and recycle (1)
4	EB	688	2	686	242-T bottoms and recycle (1)
1-1973	EB	712	56	656	242-T bottoms and recycle (1)
2	EB	723	67	656	242-T bottoms and recycle (1)
3	EB	734	78	656	242-T bottoms and recycle (1)
4	EB	730	74	656	242-T bottoms and recycle (1)
1-1974	EB	729	73	656	242-T bottoms and recycle (1)
2	EB	729	73	656	242-T bottoms and recycle (1)
3	EB	732	76	656	242-T bottoms and recycle (1)
4	EB	684	22	662	Salt filled, 55 to 115-TX (1)
1-1975	---	678	0	678	Salt filled, 35 to 115-TX
2	---	678	0	678	Removed from service, 10 to 115-TX
3	---	678	0	678	Removed from service
4	---	678	0	678	Removed from service
1-1976	---	678	0	678	Removed from service, 23 to 115-TX
2	---	678	0	678	RFS
3	---	678	0	678	Salt well pumped, Inactive S.W. pumping
4	---	678	0	678	Salt well pumped
1-1977	---	678	0	678	Inactive - salt well pump
2	---	678	0	678	Inactive - salt well pump
3	---	645	0	645	Inactive current-solid level adj.
4	---	645	0	645	Inactive current-solid level adj.

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

9 2 1 2 5 5 6 1 6 1 8

Waste Status Summary of 114-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	645	0	645	
2-	-	645	0	645	
3-	-	645	0	645	
4-	-	645	0	645	
1-1979	-	645	0	645	
2-	-	645	0	645	Questionable Integrity
3-	-	645	0	645	
4-	-	645	0	645	
1-1980	-	645	0	645	
2-	-	645	0	645	
3-	-	645	0	645	
4-	-	645	0	645	

9 2 1 2 5 5 6 1 6 1 9

Waste Status Summary of 115-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 5 5 6 1 6 2 0

Waste Status Summary of 115-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	TBP	---			Active TBP supernate; be designated as EB
3	TBP	758			TBP supernate tank - 200 West Area
4	TBP	759			TBP supernate tank - 200 West Area
1-1953	TBP	733		0	TBP supernate tank - 200 West Area, Removal operations
2	MW	487		0	Supernatant
3	MW	366		0	Supernatant
4	MW	476		0	Received MW supernate from 101-TX
1-1954	MW	384		0	Transferred to 109-U
2	MW	46		0	Transferred to 109-U
3	MW	667		0	Received from 114-TX, Received 107-TX
4	MW	667		0	
1-1955	MW	292		0	
2	MW	332		0	Supernatant hold-up tank
3	MW	250		0	Supernatant hold-up tank
4	MW	51		0	
1-1956	MW	180			Pumps to 001-TXR for blends, Received from 102-TX supernatant blend tank
2	MW	442			Received from 101-T, received 102-T, supernatant from 103-T
3	MW	483			Supernatant received from 107-TX, no supernatant rec'd, 484 M gals transferred from 108-TX
4	MW	56			Rec'd from 108-BX, Rec'd from 105-TX
1-1957	MW	0			Active jetting to 107-TX. Declared MT
2	R	13		0	Latest electrode reading
3	R	13		0	
4	R	13		0	

9212556162 1

Waste Status Summary of 115-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	R	15		0	
2	R	15		0	
3	R	15		0	
4	R	15		0	
1-1959	R	15		0	
2	R	15		0	
3	R	15		0	
4	R	15		0	
1-1960	R	15		0	
2	R	15		0	
3	R	15		0	
4	R	15		0	
1-1961	R	18		0	Six months
2					
3	R	18		0	Six months
4					
1-1962	R	18		0	Six months
2					
3	R	18		8	Six months
4					
1-1963	R	18			Six months
2					
3	R	18			Six months
4					
1-1964	R	18			Six months
2					
3	R	20			Six months
4					Latest electrode reading

9 2 1 2 5 5 6 1 6 2 2

Waste Status Summary of 115-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	R	18		20	Six months
2					
3	R	18		20	Req'd for 242-T Evap. Opr.
4	R	18		20	
1-1966	DW-CW	33-227		20	209 M from 107-S, 33 M from 221-T
2	DW-CW	36-447		20	220 M from 107-S, 3 M from 221-T
3	DW-CW	39-447		20	Received 3 M from 221-T
4	DW-CW	39-669		20	145 M from 107-S
1-1967	DW-CW	39-667		20	
2	DW-CW	67-667		20	Rec'd 137 M from 221-T, 109 M to 104-TX
3	DW-CW	67-669		20	Rec'd 200 M from 221-T, 198 M to 104-TX
4	DW-CW	35-350		20	351 M to 104-TX
1-1968	DW-CW	35-349		20	
2	EB	571		25	242-T bottoms and recycle
3	EB	627		40	242-T bottoms and recycle
4	EB	634	539	95	242-T bottoms and recycle
1-1969	EB	648	418	230	242-T bottoms and recycle
2	EB	607	253	354	242-T bottoms and recycle
3	EB	686	309	377	242-T bottoms and recycle
4	EB	685	296	389	242-T bottoms and recycle
1-1970	EB	703	279	424	242-T bottoms and recycle
2	EB	689	212	477	242-T bottoms and recycle
3 *	EB	722	148	574	242-T bottoms and recycle
4	EB	658	49	609	242-T bottoms and recycle
1-1971	EB	673	44	629	242-T bottoms and recycle
2	EB	721	103	618	242-T bottoms and recycle
3	EB	697	74	623	242-T bottoms and recycle
4	EB	710	68	642	(1)

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

* Leak detection dry wells 51-15-04, 51-15-07 and 51-15-11 drilled.

9 2 1 2 5 5 6 1 6 2 3

Waste Status Summary of 115-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	690	48	642	242-T bottoms and recycle (1)
2	EB	642	0	642	242-T bottoms and recycle (1)
3	EB	689	47	642	242-T bottoms and recycle (1)
4	EB	725	83	642	242-T bottoms and recycle (1)
1-1973	EB	706	64	642	242-T bottoms and recycle (1)
2	EB	704	62	642	242-T bottoms and recycle (1)
3	EB	711	69	642	242-T bottoms and recycle (1)
4	EB	696	54	642	242-T bottoms and recycle (1)
1-1974	EB	699	57	642	242-T bottoms and recycle (1)
2	EB	699	57	642	242-T bottoms and recycle (1)
3	EB	701	59	642	242-T bottoms and recycle (1)
4	EB	730	90		Salt filled, 21 from 113-TX, 55 from 114-TX, 95 to 118-TX (1)
1-1975	EB	700	60	640	122 from 113-TX, 35 from 114-TX
2	EB	692	52	640	242-T bottoms and recycle (1)
3	EB	692	52	640	242-T bottoms and recycle (1) Salt filled
4	EB	700	60	640	Salt filled
1-1976	EB	684	44	640	Salt filled, 69 to 118-TX; 29 from 113-TX, 23 from 114-TX
2	EB	686	46	640	
3	Evap. Feed	689	49	640	Questionable integ. Evap. Feed
4	Evap. Feed	653	13	640	Questionable integ. Evap. Feed
1-1977	Evap Feed	662	22	640	Restricted
2	Evap Feed	678	38	640	Restricted Evap Feed other
3	Evap Feed	640	0	640	Inactive Current, Evap Feed other.
4	Evap Feed	640	0	640	Inactive Current, Salt Well Installed.

* Leak detection dry well 51-15-09 drilled.

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid to solid ratio of tanks 110-TX through 118-TX.

9 2 1 2 5 5 6 1 6 2 4

Waste Status Summary of 115-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	640	0	640	Primary Stabilized
2-	-	640	0	640	
3-	-	640	0	640	
4-	-	640	0	640	
1-1979	-	640	0	640	
2-	-	640	0	640	Questionable Integrity New Photo 5-8-79
3-	-	640	0	640	New Photo 7-13-79
4-	-	640	0	640	
1-1980	-	640	0	640	
2-	-	640	0	640	
3-	-	640	0	640	
4-	-	640	0	640	

9 2 1 2 5 5 6 1 6 2 5

Waste Status Summary of 116-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 5 5 6 1 6 2 6

Waste Status Summary of 116-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	EB	758			
3	EB	46			Pumped to 118-TX for starting re-evaporation
4	EB	92			Active bottoms tank 200 West Area
1-1953	EB	662			
2	EB	758			Re-evaporated bottoms
3	EB	758			Re-evaporated bottoms first cycle
4	EB	462			Active bottoms tank 1C and TBP bottoms, Transferred 1st cycle evap. bottoms to 101, 102-TY
1-1954	EB	758			
2	EB	755			
3	EB	758			
4	EB	758			
1-1955	EB	758			
2	EB	758			
3	EB	758			
4	EB	758			
1-1956	EB	758			
2	EB	758			
3	EB	758			
4	EB	758			
1-1957	EB	739			Latest electrode reading
2	EB	739		386	Latest electrode reading
3	EB	744		386	Latest electrode reading
4	EB	744		386	

9212556162 7

Waste Status Summary of 116-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	EB	744		386	
2	EB	772		386	Latest electrode reading
3	EB	769		386	New electrode reading
4	EB	769		386	
1-1959	EB	769		386	
2	EB	769		386	
3	EB	769		386	
4	EB	769		386	
1-1960	EB	769		386	
2	EB	769		386	
3	EB	769		386	
4	EB	769		386	
1-1961	EB	769		386	Six months
2					
3	EB	769		386	Six months
4					
1-1962	EB	769		386	Six months
2					
3	EB	769		386	Six months
4					
1-1963	EB	769		386	Six months
2					
3	EB	769		386	Six months
4					
1-1964	EB	769		386	Six months
2					
3	EB	769		386	Six months
4					

9 2 1 2 5 5 6 1 6 2 8

Waste Status Summary of 116-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	EB	741		323	Six months
2					
3	EB	741		323	
4	EB	722		323	Receives 242-T bottoms
1-1966	EB	573		323	Receiver for EB
2	EB	733		323	Received 154 M EB
3	EB	657		414	76 M to 118-TX
4	EB	601		414	56 M to 118-TX
1-1967	EB	637		414	
2	EB	659		414	242-T bottoms and recycle
3	EB	667		528	242-T bottoms and recycle
4	EB	635		561	
1-1968	EB	651		578	
2	EB	659		576	Received 8 M condensate from 242-T recycle tanks
3	EB	633		574	21 to 117-TX
4	EB	626	12	614	
1-1969	EB	721	107	614	Received 96 condensate from 242-T
2	EB	607	9	598	114 M to 117-TX
3	EB	601	19	582	solidifying
4	EB	733	143	590	242-T bottoms
1-1970	EB	730	54	676	242-T bottoms and recycle
2	EB	728	53	675	242-T bottoms and recycle
3	EB	668	1	667	242-T bottoms and recycle
4	EB	705	0	705	242-T bottoms and recycle (2)
1-1971	EB	705	0	705	242-T bottoms and recycle
2	EB	705	0	705	242-T bottoms, 80 to 113-TX, 80,000 gals. of interstitial supernatant was pumped from 116-TX to 113-TX & it is not known at this time if the solids level dropped.
3	EB	705	0	705	8 to 113-TX
4	EB	667	0	667	22 to 113-TX, 12 to 118-TX (1)

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

(2) Added 128 tons of diatomaceous earth (Oct. 19 - Nov. 5)

9 2 1 2 5 5 6 1 6 2 9

Waste Status Summary of 116-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	631	0	631	242-T bottoms and recycle, 46 M to 118-TX, (1)
2	EB	631	0	631	contains diatomaceous earth
3	EB	631	0	631	contains diatomaceous earth, 9 to 118-TX
4	---	631	0	631	contains diatomaceous earth, 2 flush H_2O, 4 to 113-TX
1-1973	---	631	0	631	contains diatomaceous earth
2	---	631	0	631	contains diatomaceous earth
3	---	631	0	631	contains diatomaceous earth
4	---	631	0	631	contains diatomaceous earth
1-1974	---	631	0	631	contains diatomaceous earth
2	---	631	0	631	contains diatomaceous earth
3	---	631	0	631	contains diatomaceous earth
4	---	631	0	631	contains diatomaceous earth
1-1975	---	631	0	631	contains diatomaceous earth
2	---	631	0	631	contains diatomaceous earth
3	---	631	0	631	contains diatomaceous earth, salt filled
4	---	631	0	631	contains diatomaceous earth, salt filled
1-1976	---	631	0	631	contains diatomaceous earth, salt filled
2	---	631	0	631	contains diatomaceous earth, salt filled, RFS
3	---	631	0	631	Cont. Desiccant
4	---	631	0	631	Inactive Desiccant added
1-1977	---	631	0	631	Inactive-Isolated & stabilized
2	---	631	0	631	Inactive-Isolated & stabilized
3	---	631	0	631	Inactive current, desiccant added
4	---	631	0	631	Inactive current, desiccant added.

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

* Leak detection dry wells 51-16-04, 51-16-07 and 51-16-11 drilled.

9 2 1 2 5 5 6 1 6 3 0

Waste Status Summary of 116-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	631	0	631	Primary Stabilized
2-	-	631	0	631	
3-	-	631	0	631	
4-	-	631	0	631	
1-1979	-	631	0	631	
2-	-	631	0	631	Questionable Integrity
3-	-	631	0	631	
4-	-	631	0	631	
1-1980	-	631	0	631	New Photo 1-29-80
2-	-	631	0	631	
3-	-	631	0	631	
4-	-	631	0	631	

9212556163 1

Waste Status Summary of 117-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2 *					
3					
4					
1-1950					
2					
3					
4					

* Leak detection dry well 51-17-03 drilled.

9 2 1 2 5 5 6 1 6 3 2

Waste Status Summary of 117-TXTank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	EB	756			
3	EB	756			
4	EB	756			
1-1953	EB	1			
2	EB	653			Re-evaporated bottoms
3	EB	420			
4	EB	751			Received TBP evaporator bottoms, Bottoms transferred to 109-T
1-1954	EB	640			Receives overflow from 116-TX
2	EB	626			Pumped to 112-TX Receives evaporated bottoms from 242
3	EB	754			Received evap. bottoms
4	EB-ICEB	46-114			Active 1-C bottoms tank
1-1955	EB-ICEB	46-571			
2	1C-EB	46-429			Bottoms tank
3	EB-ICEB	46-677			To be decant tank for scavenging waste
4	EB-1CEB	46-677			
1-1956	EB-1CEB	46-677			
2	EB-1CEB	46-677			
3	EB-1CEB	46-677			
4	EB-1CEB	46-677			
1-1957	EB-1CEB	46-646			Latest electrode reading
2	EB-1CEB	46-657			Latest electrode reading
3	EB-1CEB	46-660			Latest electrode reading
4	EB-1CEB	46-660			Latest electrode reading

9 2 1 2 5 6 1 6 3 3

Waste Status Summary of 117-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1958	EB-1CEB	46-660			
2	EB-1CEB	46-660			
3	EB-1CEB	46-660			
4	EB-1CEB	46-660			
1-1959	EB-1CEB	46-660			
2	EB-1CEB	46-660			
3	EB-1CEB	46-660			
4	EB-1CEB	46-660			
1-1960	EB-1CEB	46-660			
2	EB	706			
3	EB	706			
4	EB	703			
1-1961	EB	700			Six months
2					
3	EB	700			Six months
4					
1-1962	EB	700			Six months
2					
3	EB	700			Six months
4					
1-1963	EB	700			Six months
2					
3	EB	700			Six months
4					
1-1964	EB	700			Six months
2					
3	EB	700			Six months
4					

9 2 1 2 5 5 6 1 6 3 4

Waste Status Summary of 117-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	EB	700		197	Six months
2					
3	EB	739		197	39 M flush from 242-T
4	EB	752		197	Supernatant to 118-TX
1-1966	EB	689		197	Settling tank for 242-T
2	EB	700		197	Received 11 M EB
3	EB	715		253	470 M to 108-TX, received 485 M
4	EB	715		253	
1-1967	EB	609		253	
2	EB	652		253	242-T bottoms and recycle
3	EB	579		388	242-T bottoms and recycle
4	EB	571		484	242-T bottoms and recycle
1-1968	EB	590		501	242-T bottoms and recycle
2	EB	590		554	Removed from 242-T recycle
3	EB	623		525	99 received, 66 to 118-TX
4	EB	668	132	536	
1-1969	EB	634	98	536	Received condensate from TX tanks exhauster
2	EB	631	93	538	Added to 242-T bottoms and recycle
3	EB	717	127	590	242-T bottoms and recycle
4	EB	702	71	631	242-T bottoms and recycle
1-1970	EB	673	2	671	242-T bottoms and recycle
2	EB	697	24	673	242-T bottoms and recycle
3 *	EB	671	3	668	242-T bottoms and recycle
4	EB	649	427	222	(2)
1-1971	EB	700	0	700	242-T bottoms, 106 to 118-TX (2)
2	EB	700	0	700	242-T bottoms, 27 to 118-TX, 27,000 gals. of interstitial supernatant was pumped from 117-TX to 118-TX without a corresponding drop in the level of the solids
3	EB	700	0	700	
4	EB	626	0	626	(1)

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

(2) Added 43 tons of diatomaceous earth (Dec. 7 - Dec. 28)

* Leak detection dry wells 51-17-02 and 51-17-10 drilled.

9 2 1 2 5 5 6 1 6 3 5

Waste Status Summary of 117-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1972	EB	626	0	626	242-T bottoms and recycle, (1
2	EB	626	0	626	contains diatomaceous earth
3	EB	626	0	626	contains diatomaceous earth
4	EB	626	0	626	contains diatomaceous earth
1-1973	EB	626	0	626	contains diatomaceous earth
2 *	EB	626	0	626	contains diatomaceous earth
3	---	626	0	626	contains diatomaceous earth
4	---	626	0	626	contains diatomaceous earth
1-1974	---	626	0	626	contains diatomaceous earth
2	---	626	0	626	contains diatomaceous earth
3	---	626	0	626	contains diatomaceous earth
4	---	626	0	626	contains diatomaceous earth
1-1975	---	626	0	626	contains diatomaceous earth
2	---	626	0	626	contains diatomaceous earth
3	---	626	0	626	contains diatomaceous earth, salt filled
4	---	626	0	626	contains diatomaceous earth, salt filled
1-1976	---	626	0	626	contains diatomaceous earth, salt filled
2	---	626	0	626	RFS, contains diatomaceous earth, salt filled
3	---	626	0	626	contains salt, cont. desiccant
4	---	626	0		contains salt, desiccant addec
1-1977	---	626	0	626	Contains salt, isolated & stabilized.
2	---	626	0	626	Contains salt, isolated
3	---	626	0	626	Inactive current-Iso-A
4	---	626	0	626	Inactive current-Iso-A

(1) Due to the characteristics of solids in bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of tanks 110-TX through 118-TX.

* Leak detection dry well 51-17-11 drilled.

9 2 1 2 5 5 6 1 6 3 6

Waste Status Summary of 117-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	626	0	626	Partially Interim Isolated, Prim. Stab.
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	
1-1979	-	626	0	626	
2-	-	626	0	626	Questionable Integrity
3-	-	626	0	626	
4-	-	626	0	626	
1-1980	-	626	0	626	
2-	-	626	0	626	
3-	-	626	0	626	
4-	-	626	0	626	

9 2 1 2 5 6 1 6 3 7

Waste Status Summary of 118-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944					
2					
3					
4					
1-1945					
2					
3					
4					
1-1946					
2					
3					
4					
1-1947					
2					
3					
4					
1-1948					
2					
3					
4					
1-1949					
2					
3					
4					
1-1950					
2					
3					
4					

9 2 1 2 5 6 1 6 3 3

Waste Status Summary of 118-TXTank-Capacity (750,000 gals)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951					
2					
3					
4					
1-1952					
2	1C	205			Evaporator feed tank 200 West
3	1C	735			Evaporator feed tank 200 West
4	1C	718			Evaporator feed tank 200 West
1-1953	1C	688			Evaporator feed tank 200 West
2	1C	47			Evaporator feed tank 200 West
3	TBP	732			200-W evaporator feed tank filled with TBP waste from 106-TY
4	TBP	233			
1-1954	TBP	612			Receives from 106-TY tank
2	TBP	624			Receives from 106-TY tank
3	TBP	645			Receives from 106-TY tank
4	1C	281			Pumped to 103-TX →received from 111-TX and 105-T, *23.7% sludge from production test
1-1955	1C	617			Received from 106-T, rec'd from 110-TX, rec'd from 101-TY
2	1C	323			Re-evaporating 1CEB
3	1CEB	70			To be feed tank for scavenging waste
4	1CEB	70			To be feed tank for scavenging waste
1-1956	1CEB	70			
2	1CEB	70			
3	1CEB	70			
4	1CEB	70			
1-1957	1CEB	92			Latest electrode reading
2	1CEB	92			Latest electrode reading
3	1CEB	95		6	
4	EB-TBP	95-50		6	Received 25 M from 221-U

9 2 1 2 5 6 1 6 9

Waste Status Summary of 118-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	*Remarks
1-1958	EB-TBP	95-143		6	(1) rec'd 41 M from 221-U (2) rec'd 14 M from 221-U (3) rec'd 38 M from 221-U
2	EB-TBP	95-182			(1) rec'd 25 M from 221-U (2) rec'd 8 M from 221-U (3) rec'd 6 M from 221-U
3	EB-TBP	95-256			(1) rec'd 49 M from 221-U (3) rec'd 25 M from 221-U
4	EB-TBP	95-349			(1) rec'd 30 M from 221-U (2) rec'd 30 M from 221-U (3) rec'd 25 M from 221-U
1-1959	TBP	95-424			(1) rec'd 38 M from 221-U (2) rec'd 29 M from 221-U (3) rec'd 12 M from 221-U
2	EB-TBP	95-447			(2) rec'd 33 M 221-U (3) rec'd 20 M from 221-U
3	EB-TBP	95-446			(1) rec'd 81 M from 221-U (2) rec'd 39 M from 221-U Pumped 109 M to 104-TY
4	EB-TBP	95-493			(1) rec'd 19 M from 221-U (2) rec'd 20 M from 221-U 221-U waste received
1-1960	EB-TBP	95-586			(2) 221-U waste receiver-33 M (3) rec'd 35 M from 221-U
2	EB-TBP	95-407			
3	EB-TBP	95-452			(3) rec'd 45 M from 221-T
4	EB-TBP	95-543			(1) rec'd 30 M from 221-T (2) rec'd 20 M from 221-T (3) rec'd 41 M from 221-T
1-1961	EB-DW	95-569			Six months report
2					rec'd 186 M from 221-T
3	EB-DW	95-369			Six months report
4					311 M to TY, rec'd 111 M
1-1962	EB-DW	95-481			Six months report
2					rec'd 112 M
3	EB-DW	95-528			Six months report
4					rec'd 47 M from 221-T
1-1963	EB-DW	95-539			Six months report
2					rec'd 11 M from 221-T
3	EB-DW	95-547			Six months report
4					rec'd 8 M from 221-T
1-1964	EB-DW	95-564			Six months report
2					rec'd 17 M
3	EB-DW	95-514			Six months report
4					rec'd 29 M, 112 M to 108-TX

* (1) (2) (3) designates month in each quarter that receeipt occurred.

9 2 1 2 5 5 6 1 6 4 0

Waste Status Summary of 118-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1965	EB-DW	95-536		8	Six months report
2					22 M from 221-T
3	EB-DW	95-613		8	77 M from 221-T
4	EB-DW	95-327		8	Feed for 242-T, 374 M boil-off
1-1966	TBP	604		8	Feed for 242-T, 706 M boil-off
2	TBP	640		8	Feed for 242-T, 308 M boil-off
3	TBP	349		5	Feed for 242-T, 443 M boil-off
4	TBP	453		5	Feed for 242-T, 637 M boil-off
1-1967	CW	593		5	Feed for 242-T, 576 M space reclaimed
2	CW	626		5	Feed for 242-T, 254 M space reclaimed
3	CW	549		35	Feed from 242-T evap., 615 M space reclaimed
4	CW	646		58	Feed for 242-T evap., 436 M space reclaimed
1-1968	CW	560		51	Feed from 242-T evap., 22 M space loss due to flushes for modification
2	CW	587		85	Feed from 242-T evap., 693 M reclaimed by 242-T
3	CW	619		91	242-T evap. feed tank 1, 121 reclaimed by 242-T
4	CW	682	590	92	242-T evap. feed tank, 734 reclaimed by 242-T
1-1969	EB	697	532	165	Rec'd 990 : 924 reclaimed by 242-T
2	EB	711	533	178	Rec'd 1,295 : 1,298 evaporated by 242-T
3	EB	631	455	176	Rec'd 1,314 : 1,184 evaporated by 242-T
4	EB	684	497	189	663 from 103-TY & 104-TY, 78 from 242-T decont. : 500 evaporated by 242-T
1-1970	EB	703	528	175	578 from 103 & 104-TY : 530 evaporated by 242-T
2	EB	675	502	173	397 from 103-TY, 498 from 104-TY, 1,099 evap. by 242-T
3 *	EB	501	339	162	349 from 103-TY, 194 from 102-TY, 727 evap. by 242-T
4	EB	649	427	222	823 from 102-TY, 791 evap. by 242-T

*Leak detection dry wells 51-18-03 and 51-18-07 drilled.

9 2 1 2 5 5 6 1 6 4 1

Waste Status Summary of 118-TX Tank-Capacity (750,000 gals.)

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1971*	EB	576	327	249	94 from 103-TY, 798 from 106-BX, 106 from 117-TX, 1,048 evap. by 242-T
2	EB	647	395	252	829 from 101-TX, 27 from 117-TX, 787 evap. by 242-T
3	EB	712	460	252	1,914 from 101-TX, 226 flush water, 1,180 evaporated
4	EB	464	223	241	1,325 from 101-TX, 12 116-TX 138 flush water, 1,144 evap. degree of uncertainty in liquid to solid ratio of tanks 102-TX, 105-TX, 106-TX and 110-TX through 118-TX
1-1972	EB	534	293	241	349 from 101-TX, 46 from 116-TX, 247 flush water, 1,175 evaporated
2	EB	649	408	241	758 from 101-TX, 15 from 116-TX, 295 flush water, 1,054 evaporated
3	EB	575	286	289	765 from 101-TX, 9 from 116-TX, 350 water 1,078 evaporated
4	EB	574	285	289	1,048 from 101-TX, 306 flush water, 1,077 evaporated
1-1973	EB	565	304	261	588 from 101-TX, 439 water, 715 evaporated
2 **	EB	623	362	261	148 from 234-5, 128 M rec'd
3	EB	640	379	261	247 from 234-5, 33 from 101-TY 78 from 103-TY, 230 water, 591 evaporated
4	EB	711	450	261	86 from 234-5, 101 from 101-TX 9 from 103-TY, 217 water, 302 evaporated
1-1974	EB	700	439	261	622 from 234-5, 78 from 101-TY 89 water, 158 to 109-TX, 27 evaporated
2 ***	EB	629	368	261	138 from 234-5, 62 from 102-TY 10 from 103-TY, 147 water, 491 evaporated
3	EB	616	355	261	73 from 234-5, 294 from 101-TX 121 from 102-TY, 136 water, 632 evaporated
4	EB	634	374	260	93 from 234-5, 118 101-TX 123 from 102-TY, 95 from 115-T 163 water, 605 evaporated

* Leak detection dry well 51-18-10 drilled.
** Leak detection dry well 51-18-11 drilled.
*** Leak detection dry wells 51-18-01, 51-18-05 and 51-18-09 drilled.

9 2 1 2 5 5 6 1 6 4 2

Waste Status Summary of 118-TX Tank Capacity 750,000 Gallons

Qrtr Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1975	EB	626	366	260	56 from 234-5, 135 from 101-TX, 137 water, 70 evaporated
2	EB	552	292	260	97 from 234-5, 414 from 101-TX, 15 from 113-TX, 10 from 114-TX, 31 from 102-TY, 17 water, 169 Evap.
3	EB	631	371	260	79 from 234-5, 1237 from 101-TX, 592 evaporated
4	EB	530	270	260	75 from 234-5, 297 from 101-TX, 480 evaporated
1-1976	EB	469	209	260	48 from 234-5, 69 from 116-TX, 466 from 101-TX, 40 water, 364 evaporated
2	EB-Z	527	267	260	
3	EB-Z	563	303	260	
4	EB-Z	436	137	299	
1-1977	Evap Feed	281	170	299	Acid neutralized tank
2	Evap Feed	354	55	299	Acid neutralized tank
3	Evap Feed	499	200	299	A-Evap Feed con. acid neutralized tank
4	Evap Feed	568	269	299	Evap Feed con. acid neutralized tank

9 2 1 2 5 5 6 1 6 4 3

Waste Status Summary of 118-TX Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	612	313	299	EVAP. Feed - Con Acid Neutral Tk.
2-	PNF	675	371	304	HLSW Acid Neut.
3-	PNF	615	190	425	Solids Level Adj. 9-10-78
4-	PNF	659	319	340	Solid Level Adj. 11-21-78
1-1979	NCPLX	571	231	340	
2-	NCPLX	615	275	340	
3-	PNF	662	322	340	
4-	PNF	601	261	340	New Photo 12-19-79
1-1980	PNF	615	275	340	
2-	PNF	642	302	340	
3-	PNF	412	72	340	
4-	NCPLX	360	13	347	New Solids Level 11-17-80, Inactive

9212161644

Waste Status Summary of 101-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	EB	758	758	---	
1-1954	EB	758	758	---	
2	EB	758	758	---	1st cycle reevaporated bottoms. Scheduled to be pumped to ditch
3	EB	46	46	---	Reevaporated bottoms pumped to ditch
4	1C	739	---	164	Started receiving scvg. waste I-C on 10-24-54
1-1955	1C	175	---	164	Pumped 564,000 gallons supernatant to 118-TY
2	1C	326	---	195	For I-C scvg waste
3	1C	729	---	195	
4	1C	576	276	200	
1-1956	1C	752	552	200	Receives T-Plant I-C waste settling for decanting.
2	1C	752	552	200	Non-cribbable due to excessive cobalt 60
3	1C	752	552	200	OK for normal cribbing
4	1C	183	---	183	569M gals to #1 TY cavern
1-1957	1C	178	---	178	Latest electrode reading
2	1C	213	35	178	Latest electrode reading
3	1C	219	41	178	Latest electrode reading
4	1C	219	41	178	
1-1958	1C	219	41	178	
2	1C	219	41	178	
3	1C	219	41	178	
4	1C	219	41	178	

9212556164 5

Waste Status Summary of 101-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1959	1C	219	41	178	
2	1C	219	41	178	
3	1C-TBP	695	115-402	178	74M rec'd from 106-TY; rec'd 402M waste from 106-TY
4	1C-TBP	695	115-402	178	
1-1960	1C-TBP	695	115-402	178	
2	1C-TBP	695	115-402	178	
3	1C-TBP	695	115-402	178	
4	1C-TBP	695	115-402	178	
1-1961	---	---	---	---	6 month report
2	1C-TBP	695	115-402	178	Latest electrode reading
3	---	---	---	---	
4	1C-TBP	695	115-402	178	6 month report
1-1962	---	---	---	---	6 month report
2	1C-TBP	697	115-404	178	Latest electrode reading
3	---	---	---	---	
4	1C-TBP	697	115-404	178	6 month report
1-1963	---	---	---	---	
2	1C-TBP	697	115-404	178	6 month report
3	---	---	---	---	
4	1C-TBP	697	115-404	178	6 month report
1-1964	---	---	---	---	
2	1C-TBP	697	115-404	178	6 month report
3	---	---	---	---	
4	1C-TBP	697	115-404	178	6 month report
1-1965	---	---	---	---	
2	1C-TBP	662	293-362	7	6 month report
3	1C-TBP	662	293-362	7	
4	1C-TBP	662	293-362	7	
1-1966	1C-TBP	662	293-369	7	
2	1C-TBP	662	293-369	7	
3	1C	263	256	7	
4	1C	263	256	7	
1-1967	TBP-R	755	256-492	7	492M from 103-SX
2	TBP-R	755	256-492	7	
3	TBP-R	755	256-492	7	
4	TBP-R	755	256-492	7	

9 2 1 2 5 5 6 1 6 4 6

Waste Status Summary of 101-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1968	TBP-R	756	256-493	7	
2	TBP-R	754	256-491	7	
3	TBP-R	754	263-484	7	
4	TBP-R	755	256-492	7	
1-1969	TBP-R	754	256-491	7	
2	TBP-R	754	256-491	7	
3	TBP-R	755	256-492	7	
4	TBP-R	755	114-492	149	
1-1970	TBP-R	755	114-492	149	
2	TBP-R	755	114-492	149	
3	TBP-R	754	114-491	149	
4	TBP-R	754	114-491	149	
1-1971	TBP-R	753	114-490	149	
2	TBP-R	752	114-489	149	
3 *	TBP-R	755	115-491	149	
4	TBP-R	752	114-489	149	
1-1972	TBP-R	751	114-488	149	
2	TBP-R	751	114-488	149	
3	TBP-R	751	114-488	149	
4	TBP-R	751	114-488	149	
1-1973	TBP-R	750	114-487	149	
2	TBP-R	748	113-486	149	
3	TBP-R	284	25-110	149	1 water; 222 to 104-C, 213 to 104-T 33 to 118-TX
4	TBP-R	282	25-108	149	
1-1974	TBP-R	208	11-48	149	Suspect leaker, 78 to 118-TX
2	---	202	0	202	Suspect leaker, 27 to 102-TY
3	---	184	0	184	Suspect leaker, 6 to 102-TY
4	---	169	0	169	Suspect leaker, 9 to 102-TY
1-1975	---	169	0	169	Suspect leaker, 6 to 102-TY
2	---	169	0	169	Suspect leaker, removed from service 1 to 102-TY
3	---	169	0	169	Suspect leaker, removed from service
4	---	169	0	169	Suspect leaker, removed from service
1-1976	---	169	0	169	Suspect leaker, removed from service
2	---	169	0	169	Suspect leaker, removed from service
3	---	169	0	169	Suspect leaker, removed from service
4	---	169	0	169	Suspect leaker, SW pump completed

* Dry Wells No.s 52-01-01, 52-01-05 and 52-01-09 were drilled.

9 2 1 2 5 5 6 1 6 4 7

101-TY-4

Waste Status Summary of 101-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	169	0	169	Primary Stabilized
2-	—	169	0	169	
3 -	—	169	0	169	
4 -	-	169	0	169	Solids Level Taken 10-31-78
1-1979	—	169	0	169	
2-1979	—	169	0	169	Questionable Integrity
3-1979	—	169	0	169	
4-1979	—	169	0	169	
1-1980		169	0	169	
2-		169	0	169	
3-		169	0	169	
4-		169	0	169	

9212561613

Waste Status Summary of 101-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	Stabilized	169	0	169	Suspect leaker, SW pump completed
2	Stabilized	169	0	169	Suspect leaker, SW pump completed
3	Stabilized	169	0	169	Inaction cur. - stabilized
4	Stabilized	169	0	169	Inactive cur. - stabilized
1-1978	-	169	0	169	Prim. Stabilized
2-	-	169	0	169	
3-	-	169	0	169	
4-	-	169	0	169	Solids Level Taken 10-31-78
1-1979	-	169	0	169	
2-	-	169	0	169	Questionable Integrity
3-	-	169	0	169	
4-	-	169	0	169	
1-1980	-	169	0	169	
2-	-	169	0	169	
3-	-	169	0	169	
4-	-	169	0	169	

9 2 1 2 5 5 6 1 6 4 9

Waste Status Summary of 102-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	EB	140	140	---	
1-1954	EB	138	138	---	
2	EB	138	138	---	
3	EB	23	23	---	
4	1C-EB	696	10-686	10	
1-1955	1C-EB	696	10-686	10	
2	1C-EB	748	748	---	
3	1C-EB	758	10-748	---	
4	1C-EB	758	10-748	---	
1-1956	1C-EB	758	10-748	---	
2	1C-EB	758	10-748	---	
3	1C-EB	758	10-748	---	
4	1C-EB	758	10-748	---	
1-1957	1C-EB	705	10-685	10	Latest electrode reading
2	1C-EB	769	10-697	62	
3	1C-EB	772	10-700	62	
4	1C-EB	772	10-700	62	
1-1958	1C-EB	772	10-700	62	
2	1C-EB	772	10-700	62	
3	1C-EB	772	10-700	62	
4	1C-EB	772	10-700	62	
1-1959	1C-EB	772	10-700	62	
2	1C-EB	772	10-700	62	
3	1C-EB	772	10-700	62	
4	1C-EB	769	10-749	10	Latest electrode reading

9212556160

Waste Status Summary of 102-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	1C-EB	769	10-749	10	
2	1C-EB	769	10-749	10	
3	1C-EB	769	10-749	10	
4	1C-EB	769	10-749	10	
1-1961					
2	EB	769	759	10	6 month report
3					
4	EB	769	759	10	6 month report
1-1962					
2	EB	769	759	10	6 month report
3					
4	EB	769	759	10	6 month report
1-1963					
2	EB	769	759	10	6 month report
3					
4	EB	769	759	10	6 month report
1-1964					
2	EB	769	759	10	6 month report
3					
4	EB	769	759	10	6 month report
1-1965					
2	EB	755	698	57	6 month report
3	EB	755	698	57	
4	EB	755	698	57	
1-1966	EB	755	698	57	
2	EB	755	698	57	
3	EB	755	698	57	
4	EB	755	698	57	
1-1967	EB	755	698	57	
2	EB	755	698	57	
3	EB	755	698	57	
4	EB	755	698	57	
1-1968	EB	756	698	57	
2	EB	756	698	57	
3	EB	756	698	57	
4	EB	759	699	57	

9 2 1 2 5 5 6 1 6 5 1

Waste Status Summary of 102-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	EB	756	699	57	
2	EB	756	699	57	
3	EB	756	699	57	
4	EB	756	726	30	
1-1970	EB	756	726	30	
2	EB	756	726	30	
3	EB	562	532	30	194 to 118-TX
4	EB	530	500	30	33 to 118-TX
1-1971	EB	530	500	30	
2	EB	530	500	30	
3 *	EB	530	500	30	
4	EB	531	501	30	
1-1972	EB	530	500	30	
2	EB	530	500	30	
3	EB	531	501	30	
4	EB	532	502	30	
1-1973	EB	531	501	30	
2	EB-BL-OWW-RIX	733	501-41-84-77	30	202 from 103-TY
3	EB-BL OWW-RIX	738	504-41-85 78	30	
4	EB-BL-OWW-RIX	739	505-41-85-78	30	
1-1974	EB-BL OWW-RIX	739	505-41-85-78	30	
2	EB-BL-OWW-RIX-TBP-R	706	464-38-78-72-4-20	30	27 from 101-TY, 62 to 118-TX
3	EB-BL-OWW-RIX-TBP-R	602	393-32-66-61-3-17	30	6 from 101-TY, 5 from 103-TY, 2 from 104-TY, 3 from 105-TY, 121 to 118-TX
4	EB-BL-OWW-RIX-TBP-R	494	319-26-54-50-2-14	29	9 from 101-TY, 6 from 103-TY, 1 from 104-TY, 123 to 118-TX
1-1975	EB-BL-OWW-RIX-TBP-R	499	322-26-55-51-2-14	29	5 from 101-TY
2	EB-BL-OWW-RIX-TBP-R	469	302-24-51-48-2-13	29	1 from 101-TY, 31 to 118-TX
3	EB-BL-OWW-RIX-TBP-R	469	302-24-51-48-2-13	29	
4	EB-BL-OWW-RIX-TBP-R		302-24-51-48-2-13	29	

* Dry Wells No.s 52-02-01, 52-02-05 and 52-02-09 were drilled.

9 2 1 2 5 5 6 1 6 5 2

102-TY-4

Waste Status Summary of 102-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	68	3	65	Active Salt well RECVR INT LIQ. STORAGE
2-	NCPLX	68	3	65	
3-	NCPLX	73	8	65	
4-	NCPLX	73	8	65	
1-1979	NCPLX	73	5	68	New Solids level 2-28-79 Inactive
2-1979	NCPLX	73	5	68	
3-1979	NCPLX	73	5	68	Interim stabilized
4-1979	NCPLX	73	5	68	
1-1980	NCPLX	73	3	70	New Photo 1-30-80 *
2-	NCPLX	73	3	70	
3-	NCPLX	73	3	70	
4-	NCPLX	73	3	70	

* [illegible] 53-(3) [illegible]
52-(3) [illegible]

9212556165 3

Waste Status Summary of 102-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1976	EB-BL-OWW-RIX-TBP-R	312	193-16-31-31-2-10	29	162 to 101-TX, 3 from 103-TY
2	EB-BL-OWW-RIX-TBP-R	312	193-16-31-31-2-10	29	
3	Evap. Feed Dil.	315	286	29	Space low heat
4	Evap. Feed Dil.	315	386	29	
1-1977	Evap. Feed Dil.	81	35	46	Int. liquor storage
2	Evap. Feed Dil.	81	35	46	Int. liquor storage
3 *	Evap.	68	22	46	A salt well receiver
4	Evap.	68	3	65	A salt well receiver
1-1978	-	68	3	65	Active Salt Well Receiver, int Liquid Storage
2-	NCPLX	68	3	65	
3-	NCPLX	73	8	65	
4-	NCPLX	73	8	65	
1-1979	NCPLX	73	5	68	New Solids Level 2-28-79, Inactive
2-	NCPLX	73	5	68	
3-	NCPLX	73	5	68	Interim Stabilized
4-	NPCLX	73	5	68	
1-1980	NCPLX	73	3	70	New Photo 1-30-80
2-	NCPLX	73	3	70	
3-	NCPLX	73	3	70	
4-	NCPLX	73	3	70	

* Dry Wells No.'s 52-02-06 and 52-02-11 were drilled.

9 2 1 2 5 5 6 1 6 5 4

Waste Status Summary of 103-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	---	---	---	---	
3	TBP	758	758	---	Receiving TBP waste
4	TBP	758	758	---	
1-1954	TBP	752	752	---	
2	TBP	755	755	---	
3	TBP	755	755	---	
4	TBP	131	131	---	To be pumped 111-TX reserve capacity for 10 scvgd waste
1-1955	1C	208	84	124	For 1C scvg waste
2	1C	759	563	196	
3	1C	590	390	200	
4	1C	758	553	205	Settling for decanting
1-1956	1C	428	218	210	Pumped to TY #1 cavern
2	1C	524	303	221	S.S. receives 1C from T-Plant
3	1C	546	325	221	S.S. receives 1C from T-Plant
4	1C	188		188	S.S. 358 gals to #1 TY cavern
1-1957	1C	233	13	220	Latest electrode reading
2	1C	290	70	220	Latest electrode reading
3	1C	293	73	220	Latest electrode reading
4	1C	293	73	220	
1-1958	1C	293	73	220	
2	1C	293	73	220	
3	1C	293	73	220	
4	1C	293	73	220	
1-1959	1C	293	73	220	
2	1C	290	64	226	
3	1C	309	70-19	220	Rec'd 19M waste from 106-TY
4	1C-TBP	516	290-6	220	207M from 106-TY

9 2 1 2 5 5 6 1 6 5 5

Waste Status Summary of 103-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	1C-TBP	516	290-6	220	
2	1C-TBP	516	290-6	220	
3	1C	516	290-6	220	
4	1C-TBP	516	290-6	220	
1-1961	1C-TBP-DW	510	290	220	6 month report
2					
3	1C-TBP-DW	741	290-0-231	220	231M from 118-TX
4					6 month report
1-1962	1C-TBP-DW	739	290-0-229	220	Latest electrode rdg.
2					6 month report
3	1C-TBP-DW	739	290-0-229	220	6 month report
4					
1-1963	1C-TBP-DW	739	290-0-229	220	6 month report
2					
3	1C-TBP-DW	739	290-0-229	220	6 month report
4					
1-1964	1C-TBP-DW	739	290-0-229	220	6 month report
2					
3	1C-TBP-DW	739	290-0-229	220	6 month report
4					
1-1965	1C-TBP-DW	730	290-119-220	101	6 month report
2					
3	1C-TBP-DW	730	290-119-220	101	
4	1C-TBP-DW	730	290-119-220	101	
1-1966	1C-TBP-DW	730	290-119-220	101	
2	1C-TBP-DW	730	290-119-220	101	
3	1C-TBP-DW	730	290-119-220	101	
4	1C-TBP-DW	730	290-119-220	101	
1-1967	1C-TBP-DW	730	290-119-220	101	
2	1C-TBP-DW	730	290-119-220	101	
3	1C-TBP-DW	546	290-119-36	101	184M to 118-TX
4	1C-TBP-DW	184	83	101	362M to 118-TX
1-1968	1C-TBP-OWW	730	629	101	Rec'd 546M from 102-AX
2	OWW	190	89	101	540M to 118-TX
3	CW-OWW	499	398	101	1075 from 102-BX & 103-BX 765 to 118-TX
4	CW-OWW	609	280-195	134	481 from 103-BX, 371 to 118-TX

9212556165 6

Waste Status Summary of 103-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	CW-OWW	180	18-28	134	413 from 103-BX, 843 to 118-TX
2	CW	362	231	131	448M from 112-T, 465 from 103-T, 11 from 115-TXC.T, 741 to 118-TX
3	CW	505	266	239	1457 from T Farm, 1314 to 118-TX
4	CW	541	302	239	415 from 109-T, 275 from 107-T, 653 to 118-TX
1-1970	R	420	181	239	418 from 112-U, 207 to 118-TX, 333 to 104-TY
2	R	497	300	197	474 from 104-S, 397 to 118-TX
3	EB	395	198	197	246 from 107-X, 349 to 118-TX
4	BL-OWW-RIX	459	52-110-100	197	382 to 111-U, 1048 from 106-BX, 823 to 118-TX, 542 to 104-TY
1-1971	BL-OWW-RIX	722	105-220-200	197	356 from 106-BX, 94 to 118-TX
2	BL-OWW-RIX	723	105-221-200	197	
3 *	BL-OWW-RIX	723	105-221-200	197	
4	BL-OWW-RIX	722	105-220-200	197	
1-1972	BL-OWW-RIX	721	105-219-200	197	
2	BL-OWW-RIX	720	105-218-200	197	
3	BL-OWW-RIX	715	104-216-198	197	
4	BL-OWW-RIX	712	103-215-197	197	
1-1973	BL-OWW-RIX	723	106-219-201	197	
2	BL-OWW-RIX	520	65-134-124	197	202 to 102-TY
3	BL-OWW-RIX	215	4-7-7	197	Tank leaks, 2 water, 78 to 118-TX, 227 to 104-TX
4	BL-OWW-RIX	206	1-4-4	197	Tank leaks, 9 to 118-TX
1-1974	OWW-RIX	202	2-3	197	Tank leaks
2	---	197	0	197	Tank leaks, 10 to 118-TX
3	---	215	0	215	Tank leaks, 5 to 102-TY
4	---	219	0	219	Tank leaks, 6 to 102-TY
1-1975	---	219	0	219	Tank leaks
2	---	219	0	219	Tank leaks
3	---	219	0	219	Tank leaks
4	---	219	0	219	Tank leaks
1-1976	---	219	0	219	Tank leaks, 3 to 102-TX
2	---	219	0	219	
3	---	219	0	219	Inactive leaker
4	---	219	0	219	Inactive leaker

* Dry Wells No.'s 52-03-03, 52-03-06 and 52-03-12 were drilled.

9212556165 7

103-TY-4

Waste Status Summary of 703-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	[illegible]	[illegible]	219	Leaker
2-	—	219	0	219	Primary Stabilized
3-	—	219	0	219	
4-	—	172	0	172	Solid Level Adjusted 11/6/78
1-1979	—	172	0	172	
2-1979	—	172	0	172	
3-1979	—	172	0	172	
4-1979	—	172	0	172	
1-1980	—	172	0	172	New Photo 1-31-80
2-	—	172	0	172	
3-	—	172	0	172	
4-	—	172	0	172	

9212561659

Waste Status Summary of 103-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	---	219	0	219	Inactive leaker
2	---	219	0	219	Inactive leaker
3	---	219	0	219	Inactive leaker
4	---	219	0	219	Inactive leaker, salt well installed
1-1978	-	219	0	219	Leaker, Primary Stabilized
2-	-	219	0	219	
3-	-	219	0	219	
4-	-	172	0	172	Solid Level Adjusted 11-6-78
1-1979	-	172	0	172	
2-	-	172	0	172	
3-	-	172	0	172	
4-	-	172	0	172	
1-1980	-	172	0	172	New Photo 1-31-08
2-	-	172	0	172	
3-	-	172	0	172	
4-	-	172	0	172	

9 2 1 2 5 5 6 1 6 5 9

Waste Status Summary of 104-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	---	---	---	---	
3	TBP	176	176	---	
4	TBP	141	141	---	Transferred to 118-TX
1-1954	TBP	688	688	---	
2	TBP	770	770	---	Filled approx 1 1/3 ft above normal capacity
3	TBP	770	770	---	Filled approx 1 1/3 ft above normal capacity
4	TBP	770	770	---	
1-1955	TBP-1C	758	20-664	74	Rec'd from 103-TY
2	TBP-1C	758	20-664	74	
3	TBP-1C	83		74	To be pumped to TY #1 cavern
4	TBP-1C	83	20-63	74	
1-1956	TBP-1C	83	20-63	74	
2	TBP-1C	83	20-63	74	
3	TBP-1C	83	20-63	74	
4	TBP-1C	83	20-63	74	
1-1957	TBP-1C	100	26	74	
2	TBP-1C	112	20-18	74	
3	TBP-1C	112	20-18	74	
4	TBP-1C	112	20-18	74	
1-1958	TBP-1C	112	20-18	74	
2	TBP-1C	112	20-18	74	
3	TBP-1C	112	20-18	74	
4	TBP-1C	112	20-18	74	
1-1959	TBP-1C	112	20-18	74	
2	TBP-1C	112	20-18	74	Rec'd 80M waste from 118-TX, Rec'd 109M waste from 118-TX
3	TBP-1C	301	129-98	74	
4	TBP-1C	301	129-98	74	

* Dry Wells No.s 52-04-03 and 52-04-10 were drilled.

9 2 1 2 5 5 6 1 6 6 0

Waste Status Summary of 104-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	TBP-1C	301	129-98	74	
2	TBP-1C	498	238-186	74	Rec'd waste from 118-TX
3	TBP-1C	498	238-186	74	
4	TBP-1C	496	238-184	74	
1-1961	TBP-1C-DW	456	238-258-86	74	Rec'd 160M from 118-TX
2					
3	TBP-1C-DW	736	238-258-166	74	80M from 118-TX
4					
1-1962	TBP-1C-DW	736	238-258-166	74	
2					
3	TBP-1C-DW	736	238-258-166	74	
4					
1-1963	TBP-1C-DW	736	238-258-166	74	
2					
3	TBP-1C-DW	736	238-258-166	74	
4					
1-1964	TBP-1C-DW	736	238-258-166	74	
2					
3	TBP-1C-DW	736	238-258-166	74	
4					
1-1965	TBP-1C-DW	733	238-258-240	0	
2					
3	TBP-1C-DW	733	238-258-240	0	
4	TBP-1C-DW	733	238-258-240	0	
1-1966	TBP-1C-DW	733	238-258-240	0	
2	TBP-1C-DW	733	238-258-240	0	
3	TBP-1C-DW	574	238-336	0	162M to 118-TX
4	TBP	62	62	0	374M to 118-TX
1-1967	TBP	62	62	0	
2	TBP-DW	171	62-109	0	Rec'd 109M from 115-TX
3	TBP-DW	369	62-307	0	198M from 115-TX
4	TBP-DW	719	62-657	0	
1-1968	TBP-DW	719	62-657	0	
2	TBP-DW	718	62-656	0	
3	TBP-DW	718	62-656	0	
4	TBP-DW	717	62-655	0	

9212556161

Waste Status Summary of 104-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	TBP-DW	717	62-655	0	
2	TBP-DW	717	62-655	0	
3	TBP-DW	717	62-655	0	
4	TBP-DW	714	62-609	43	Rec'd 7 flush water, 10 to 118-TX
1-1970	DW-R	679	533-103	43	333 from 104-TY, 367 to 118-TX
2	DW	182	169	13	498 to 118-TX
3	DW	182	169	13	
4	DW-OWW-RIX	724	169-281-261	13	542 from 103-TY
1-1971	DW-OWW-RIX	724	169-281-261	13	
2	DW-OWW-RIX	724	169-281-261	13	
3 *	DW-OWW-RIX	724	169-281-261	13	
4	DW-OWW-RIX	724	169-281-261	13	
1-1972	BL-OWW-RIX	725	169-282-261	13	
2	BL-OWW-RIX	725	169-282-261	13	
3	BL-OWW-RIX	725	169-282-261	13	
4	BL-OWW-RIX	726	169-283-261	13	
1-1973	BL-OWW-RIX	726	169-283-261	13	
2	BL-OWW-RIX	726	169-283-261	13	
3	BL-OWW-RIX	731	170-285-263	13	
4	BL-OWW-RIX	730	170-284-263	13	
1-1974	BL-OWW-RIX	51	9-15-14	13	678 to 110-S
2	BL-OWW-RIX	51	9-15-14	13	
3	---	41	0	41	2 to 102-TY
4	BL-OWW-RIX	40	3-4-4	29	Removed from service, 1 to 102-TY
1-1975	BL-OWW-RIX	40	3-4-4	29	Removed from service
2	BL-OWW-RIX	40	3-4-4	29	Removed from service
3	BL-OWW-RIX	40	3-4-4	29	Removed from service
4	BL-OWW-RIX	40	3-4-4	29	Removed from service
1-1976	BL-OWW-RIX	40	3-4-4	29	Removed from service
2	BL-OWW-RIX	46	5-6-6	29	Removed from service
3	EVAP	43	14	29	Inactive
4	EVAP	43	14	29	Inactive
1-1977	EVAP	43	14	29	Inactive
2	EVAP	43	14	29	Inactive
3	EVAP	43	14	29	Inactive, Cur.
4	EVAP	43	14	29	Inactive, Cur.

* Dry Wells No.s 52-04-02, 52-04-06 and 52-04-09 were drilled.

9 2 1 2 5 5 6 1 6 6 2

104-TY-4

Waste Status Summary of 104-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	43	14	29	Inactive
2-	NCP2X	43	14	29	
3-	NCP2X	43	14	29	
4-	—	46	0	46	Solid Level Adjusted 11/30/78 Primary stabilized
1-1979	—	46	0	46	
2-1979	—	46	0	46	Questionable Integrity
3-1979	—	46	0	46	
4-1979	—	46	0	46	
1-1980	—	46	0	46	
2-	—	46	0	46	
3-	—	46	0	46	
4-	—	46	0	46	

9212561663

Waste Status Summary of 104-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	43	14	29	Inactive
2-	NCPLX	43	14	29	
3-	NCPLX	43	14	29	
4-	-	46	0	46	Solid Level Adj. 11-30-78, Prim. Stab.
1-1979	-	46	0	46	
2-	-	46	0	46	
3-	-	46	0	46	
4-	-	46	0	46	
1-1980	-	46	0	46	
2-	-	46	0	46	
3-	-	46	0	46	
4-	-	46	0	46	

9 2 1 2 5 5 6 1 6 6 4

Waste Status Summary of 105-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	TBP	252	252	0	
3	TBP	758	758	0	
4	TBP	517	517	0	Rec'd TBP waste
1-1954	TBP	758	758	0	Cascading receives TBP waste and pumps to 118-TX
2	TBP	758	758	0	
3	TBP	758	758	0	Receives TBP waste & pumps to 118-T
4	TBP	758	600	158	
1-1955	TBP	758	600	158	
2	TBP	758	600	158	
3	TBP	758	600	158	
4	TBP	758	600	158	
1-1956	TBP	758	600	158	
2	TBP	758	600	158	
3	TBP	758	600	158	
4	TBP	758	600	158	
1-1957	TBP	706	706	---	Latest electrode rdg.
2	TBP	750	750	---	Latest electrode rdg.
3	TBP	752	752	---	
4	TBP	752	752	---	
1-1958	TBP	750	750	---	
2	TBP	750	750	---	
3	TBP	750	750	---	
4	TBP	750	750	---	
1-1959	TBP	750	750	---	
2	TBP	750	750	---	
3	TBP	744	744	---	Latest electrode rdg.
4	TBP	744	744	---	

9 2 1 2 5 5 6 1 6 6 5

Waste Status Summary of 105-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	TBP	744	744	---	
2	TBP	744	744	---	
3	TBP	724	724	---	New electrode installed
4	TBP	609	609	---	1 1/4 drop during Oct., Unavailable 93M pumped to 108-TX, pumped 24M to 108-TX
1-1961	TBP	312	312	---	Pumped 294M to 108-TY
2					
3	TBP	312	312	---	
4					
1-1962	TBP	307	307	---	
2					
3	TBP	307	307	---	Tank leaks
4					
1-1963	TBP	304	304	---	Tank leaks
2					
3	TBP	304	304	---	Tank leaks
4					
1-1964	TBP	304	304	---	Tank leaks
2					
3	TBP	298	298	---	Tank leaks
4					
1-1965	TBP	299	6	293	Tank leaks
2					
3	TBP	299	6	293	
4	TBP	299	6	293	
1-1966	TBP	299	6	293	
2	TBP	299	6	293	
3	TBP	296	3	293	
4	TBP	296	3	293	
1-1967	TBP	296	3	293	
2	TBP	296	3	293	
3	TBP	296	3	293	
4	TBP	296	3	293	
1-1968	TBP	296	3	293	
2	TBP	293	0	293	
3	TBP	292	0	292	
4	TBP	292	0	292	

9 2 1 2 5 5 6 1 6 6 6

Waste Status Summary of 105-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1969	TBP	291	0	291	
2	TBP	291	0	291	
3	TBP	290	0	290	
4	---	290	96	194	
1-1970	---	289	95	194	
2	---	288	94	194	
3	---	285	0	285	
4	---	285	0	285	
1-1971	---	285	0	285	
2	---	285	0	285	
3	---	285	0	285	
4	---	285	0	285	
1-1972	---	285	0	285	Tank leaks
2	---	285	0	285	Tank leaks
3	---	285	0	285	Tank leaks
4	---	285	0	285	Tank leaks
1-1973	---	285	0	285	Tank leaks
2	---	285	0	285	Tank leaks
3	---	285	0	285	Tank leaks
4	---	285	0	285	Tank leaks
1-1974	---	285	0	285	Tank leaks
2	---	285	0	285	Tank leaks
3 *	---	285	0	285	Tank leaks
4	---	285	0	285	Tank leaks
1-1975	---	285	0	285	Tank leaks
2	---	285	0	285	Tank leaks
3	---	285	0	285	Tank leaks
4	---	285	0	285	Tank leaks
1-1976	---	285	0	285	Tank leaks
2	---	285	0	285	Tank leaks
3	---	285	0	285	Inactive leaker
4	---	284	0	285	Inactive leaker
1-1977	Isolated	285	0	285	Inactive leaker
2	Isolated	285	0	285	Inactive leaker, isolated
3	EVAP	285	0	285	Inactive leaker, isolated
4	EVAP	285	0	285	Inactive leaker, isolated

* Dry Well No. 52-05-07 was drilled.

9212556167

105-TY-4

Waste Status Summary of 105-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	285	0	285	Leaker
2-	—	285	0	285	Partially Interim Isolated PHOTO Taken 6-30-78
3-	—	285	0	285	Primary stabilized
4-	—	285	0	285	
1-1979	—	285	0	285	
2-1979	—	285	0	285	
3-1979	—	285	0	285	
4-1979	—	285	0	285	
1-1980	—	285	0	285	
2-	—	285	0	285	New Photo 9-16-80 100 gal Pool
3-	—	285	0	285	
4-	—	285	0	285	

9212556168 8

Waste Status Summary of 105-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	285	0	285	Leaker Partially Interim Isol.
2-	-	285	0	285	Photo taken 6-30-78
3-	-	285	0	285	Prim. Stabilized
4-	-	285	0	285	
1-1979	-	285	0	285	
2-	-	285	0	285	
3-	-	285	0	285	
4-	-	285	0	285	
1-1980	-	285	0	285	
2-	-	285	0	285	New Photo 9-16-80 100 gal. pool
3-	-	285	0	285	
4-	-	285	0	285	

9 2 1 2 5 5 6 1 6 6 9

Waste Status Summary of 106-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	
2	---	---	---	---	
3	TBP	752	752	---	
4	TBP	289	289	---	
1-1954	TBP	188	188	---	
2	TBP	662	662	---	
3	---	---	---	---	
4	TBP	758	758	---	
1-1955	TBP	758	758	---	
2	TBP	758	758	---	
3	TBP	758	758	---	
4	TBP	758	758	---	
1-1956	TBP	758	758	---	
2	TBP	758	758	---	
3	TBP	758	758	---	
4	TBP	758	758	---	
1-1957	TBP	706	706	---	
2	TBP	752	752	---	New electrode rdg.
3	TBP	739	739	---	
4	TBP	739	739	---	
1-1958	TBP	739	739	---	
2	TBP	739	739	---	
3	TBP	739	739	---	
4	TBP	736	736	---	
1-1959	TBP	739	739	---	
2	TBP	739	739	---	
3	TBP	224	224	---	New elelectrode installed; 74M waste pumped to 101-TY, electrode rdg indicates loss of about 500M; pumped 421M to 101 and 103-TY
4	TBP	20	20	---	Tank leaks; 207M to 103-TY

* Dry Wells No.'s 52-06-05 and 52-06-07 were drilled

9 2 1 2 5 5 6 1 6 7 0

Waste Status Summary of 106-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1960	TBP	20	20	---	Tank leaks
2	TBP	20	20	---	Tank leaks
3	TBP	20	20	---	Tank leaks
4	TBP	20	20	---	Tank leaks
1-1961	TBP	21	21	---	Tank leaks
2					
3	TBP	21	21	--	Tank leaks
4					
1-1962	TBP	17	17	---	Tank leaks
2					
3	TBP	17	17	---	Tank leaks
4					
1-1963	TBP	17	17	---	Tank leaks
2					
3	TBP	17	17	---	Tank leaks
4					
1-1964	TBP	17	17	---	Tank leaks
2					
3	TBP	17	17	---	Tank leaks
4					
1-1965	TBP	18	14	4	Tank leaks
2					
3	TBP	18	14	4	
4	TBP	18	14	4	
1-1966	TBP	18	14	4	
2	TBP	18	14	4	
3	TBP	18	14	4	
4	TBP	18	14	4	
1-1967	TBP	18	14	4	
2	TBP	18	14	4	
3	TBP	18	14	4	
4	TBP	18	14	4	
1-1968	TBP	18	14	4	
2	TBP	18	14	4	
3	TBP	18	14	4	
4	TBP	18	14	4	
1-1969	TBP	18	14	4	
2	TBP	18	14	4	
3	TBP	17	13	4	
4	TBP	17	13	4	

9 2 1 2 5 5 6 1 6 7 1

Waste Status Summary of 106-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	TBP	17	13	4	
2	TBP	17	13	4	
3	TBP	17	13	4	
4	TBP	17	13	4	
1-1971	TBP	17	13	4	
2	TBP	4	0	4	
3	TBP	4	0	4	
4	TBP	4	0	4	
1-1972	---	4	0	4	Tank leaks
2	---	4	0	4	
3	---	4	0	4	
4	---	4	0	4	Tank leaks. Contains diatomaceous earth
1-1973	---	4	0	4	Tank leaks. Contains diatomaceous earth
2	---	4	0	4	Tank leaks. Contains diatomaceous earth
3	---	4	0	4	Tank leaks. Contains diatomaceous earth
4	---	4	0	4	Tank leaks. Contains diatomaceous earth
1-1974	---	4	0	4	Tank leaks. Contains diatomaceous earth
2 *	---	4	0	4	Tank leaks. Contains diatomaceous earth
3	---	19	0	19	Tank leaks. Contains diatomaceous earth
4	---	18	0	18	Tank leaks. Contains diatomaceous earth
1-1975	---	18	0	18	Tank leaks. Contains diatomaceous earth
2	---	18	0	18	Tank leaks. Contains diatomaceous earth
3	---	18	0	18	Tank leaks. Contains diatomaceous earth
4	---	18	0	18	Tank leaks. Contains diatomaceous earth
1-1976	---	18	0	18	Tank leaks. Contains diatomaceous earth
2	---	18	0	18	Tank leaks. Contains diatomaceous earth
3	---	18	0	18	Cont. desiccant
4	---	18	0	18	

* Dry Well No.s 52-06-02, 52-06-04 and 52-06-06 were drilled.

9 2 1 2 5 5 6 1 6 7 2

106-TY-4

Waste Status Summary of 106-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	—	21	0	21	Primary Leaker Stabilized and Partially Interim Isolated
2-	—	21	0	21	
3-	—	21	0	21	Solids Level 1-19-78 PHOTO Taken 6-30-78
4-	—	21	0	21	
1-1979	—	21	0	21	
2-1979	—	21	0	21	
3-1979	—	21	0	21	
4-1979	—	21	0	21	
1-1980	—	21	0	21	New Photo 3-5-80
2-	—	21	0	21	
3-	—	21	0	21	
4-	—	21	0	21	

9212556173

Waste Status Summary of 106-TY Tank-Capacity 750,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1977	Isolated & Stabilized	18	0	18	
2	Isolated & Stabilized	18	0	18	Desicant added
3	Isolated & Stabilized	18	0	18	Inactive leaker, stabilized
4	Isolated & Stabilized	18	0	18	Inactive leaker, stabilized
1-1978	-	21	0	21	Leaker, Prim. Stab. and Partially Interim Isolated
2-	-	21	0	21	Solid Level 1-19-78
3-	-	21	0	21	Photo taken 6-30-78
4-	-	21	0	21	
1-1979	-	21	0	21	
2-	-	21	0	21	
3-	-	21	0	21	
4-	-	21	0	21	
1-1980	-	21	0	21	New Photo 3-5-80
2-	-	21	0	21	
3-	-	21	0	21	
4-	-	21	0	21	

9 2 1 2 5 5 6 1 6 7 4

Waste Status Summary of 101-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---		
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	MW	119	119	---	Cascade began filling Feb. 1946
2	MW	528	528	---	" " " " "
3	MW	528	528	---	" " " " "
4	MW	528	528	---	" " " " "
1-1947	MW	528	528	---	" " " " "
2	MW	528	528	---	" " " " "
3	MW	528	528	---	" " " " "
4	MW	528	528	---	Cascade Full
1-1948	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1949	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1950	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1951	MW	528	528	---	" "
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	---	Cascade now slurring for feed to TBP Plant
3	MW	530	530	---	
4	MW	530	530	---	Cascade now serving as feed for TBP Plant

9212556167 5

Waste Status Summary of 101-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	530	---	Cascades 101-106 now serving as feed tanks to TBP Plant
2	MW	146	146	---	T Plant active MW tank started filling 6-2-53
3	MW	385	385	---	T Plant active MW tank
4	MW	546	546	---	Filled approx. 6" above overflow T Plant active metal waste cascade
1-1954	MW	546	546	---	Filled approx. 6" above overflow T Plant active metal waste cascade
2	MW	543	543	---	Filled approx. 6" above overflow was full on 6-7-54
3	MW	543	543	---	
4	MW	543	543	---	
1-1955	MW	543	543	---	
2	MW	40	0	40	Sluicing tank
3	MW	79	0	---	Started recg. T Plant MW on Sept.27
4	MW	371	371	---	T Plant MW to be diverted to 105SX
1-1956	MW	371	371	---	
2	MW	371	371	---	
3	MW	5	---	5	Active sluicing
4	MW	1	1	---	
1-1957	MW	0	0	0	Declared MT
2	R	24	24	0	Latest electrode rdg.
3	"	24	24	0	
4	"	24	24	0	
1-1958	R	15	15	0	
2	R	540	540	0	481 M Rec'd from 103-SX
3	R	540	540	0	
4	R	540	540	0	
1-1959	R	540	540	0	
2	R	540	540	0	
3	R	540	540	0	
4	R	534	534	0	
1-1960	R	521	521	0	Electrode rdg's are being taken daily
2	R	516	516	0	
3	R	0	0	0	Pumping 475 M to 106U
4	R	26	26	0	

9 2 1 2 5 5 6 1 6 7 6

Waste Status Summary of 101-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1961	R				
2	R	29	29	0	6 months
3	R				
4	R	29	29	0	6 months
1-1962	R				
2	"	29	29	0	6 months
3	"				
4	"	29	29	0	6 months Tank leaks
1-1963	R				6 months
2	"	29	29	0	
3	"				6 months
4	"	29	29	0	
1-1964	R				6 months
2	"	29	29	0	
3	"				6 months
4	"	29	29	0	
1-1965	R	37	37	0	6 months
2	"				
3	"	37	37	0	6 months
4	"	37	37	0	
1-1966	R	15	15	0	Tank leaks
2	"	15	15	0	" "
3	"	15	15	0	" "
4	"	15	15	0	" "
1-1967	R	15	15	0	Tank leaks
2	"	17	17	0	" "
3	"	17	17	0	" "
4	"	17	17	0	" "
1-1968	R	17	17	0	" "
2	"	17	17	0	" "
3	"	17	17	0	" "
4	"	15	15	0	" "
1-1969	R	15	15	0	" "
2	"	15	15	0	" "
3	"	15	15	0	" "
4	"	73	33	40	New electrode: Tank Leaks: used for disposal of solid waste

9 2 1 2 5 5 6 1 6 7 7

Waste Status Summary of 101-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1970	R	75	36	39	New electrode:Tank Leaks: used for
2	R	74	35	39	disposal of solid waste
3	R	74	35	39	" "
4	R	43	34	39	" "
1-1971	R	73	34	39	" "
2	R	73	34	39	" "
3	R	73	33	40	" "
4	R	73	33	40	" "
1-1972	R	72	32	40	Tank leaks
2	R	72	32	40	
3	R	72	32	40	
4	R	72	32	40	
1-1973	R	72	32	40	
2	R	72	32	40	
3	R	72	32	40	
4	R	72	32	40	
1-1974	R	59	19	40	
2 *	R	59	19	40	
3	R	59	19	40	
4	R	59	19	40	
1-1975	R	59	19	40	
2	R	59	19	40	
3 **	R	59	19	40	
4	R	59	19	40	
1-1976	R	59	19	40	
2	R	59	19	40	
3	EVAP	57	17	40	Inactive Leaker
4	EVAP	59	19	40	Inactive Leaker
1-1977	EVAP	59	19	40	Inactive leaker, isolated
2	ISO	59	19	40	Inactive leaker, isolated
3	EVAP	59	19	40	Inactive leaker
4	EVAP	59	19	40	Inactive leaker

* Dry Well #60-01-08 was drilled

** Dry Well #60-01-10 was drilled

9 2 1 2 5 5 6 1 6 7 8

Waste Status Summary of 101-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	EVAP	59	19	40	Leaker-Interim Stabilized Partially Isolated
2-	NCPLX	59	19	40	
3-	NCPLX	47	19	28	
4-	NCPLX	59	19	40	
1-1979	NCPLX	40	0	49	
2-	NCPLX	40	0	40	New Photo 6-20-79
3-	NCPLX	40	0	40	
4-	NCPLX	40	0	40	
1-1980	NCPLX	26	5	21	Photo Evaluated
2-	NCPLX	26	5	21	
3-	NCPLX	26	5	21	
4-	NCPLX	26	5	21	

9212155179

Waste Status Summary of 102-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	---
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	MW	60	60	---	Cascade Began filling June
3	MW	216	216	---	" " " "
4	MW	416	416	---	" " " "
1-1947	MW	528	528	---	" " " "
2	MW	528	528	---	" " " "
3	MW	528	528	---	" " " "
4	MW	528	528	---	Cascade Full
1-1948	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1949	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1950	MW	528	528	---	" "
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1951	MW	528	528	---	" "
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	Cascade now serving as feed for TBP Plant
1-1953	MW	530	530	---	Cascades 101-106 now serving as feed tanks to TBP Plant.
2	MW	45	45	---	MW removal in progress
3	---	---	---	---	
4	MW	125	125	---	T Plant active metal waste cascade

9 2 1 2 5 5 6 1 6 8 0

Waste Status Summary of 102-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquids in Storage	Solids in Storage	Remarks
1-1954	MW	546	546	---	Filled approx. 6" above overflow T plant active metal waste
2	MW	543	543	---	Filled approx. 6" above overflow was full on 6/7/54
3	MW	543	543	---	
4	MW	543	543	---	
1-1955	MW	543	543	---	
2	MW	543	543	---	
3	MW	5	5	5	Sluicing
4	MW	443	443	---	
1-1956	MW	443	443	---	
2	MW	443	443	---	
3	MW	443	443	---	
4	MW	52	44	8	Active sluicing
1-1957	R	0	0	0	Sluicing heel declared MT
2	R	35	35	0	Latest electrode rdg.
3	R	35	35	0	
4	R	35	35	0	
1-1958	R	35	35	0	
2	R	35	35	0	
3	R	35	35	0	
4	R	472	472	0	60M from 111SX + 8M flush 369M from 102 and 111SX
1-1959	R	472	472	0	
2	R	472	472	0	
3	R	469	469	0	
4	R	469	469	0	
1-1960	R	469	469	0	
2	R	469	469	0	
3	R	469	469	0	
4	R	469	469	0	
1-1961					
2	R	466	466	0	6 months
3					
4	R	466	466	0	6 months
1-1962					
2	R	466	466	0	6 months
3					
4	R	466	466	0	6 months

Waste Status Summary of 102-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	R	466	466	0	6 months
3					
4	R	466	466	0	6 months
1-1964					
2	R	466	466	0	6 months
3					
4	R	466	466	0	6 months
1-1965	R	475	475	0	
2					6 months
3	R	475	475	0	
4	R	475	475	0	
1-1966	R	475	475	0	
2	R	475	475	0	
3	R	475	475	0	
4	R	475	475	0	
1-1967	R	475	475	0	
2	R	477	477	0	
3	R	477	477	0	
4	R	477	477	0	
1-1968	R	477	477	0	
2	R	477	477	0	
3	R	477	477	0	
4	R	477	477	0	
1-1969	R	477	477	0	
2	R	477	477	0	
3	R	477	477	0	
4	R	477	436	41	
1-1970	R	477	436	41	
2	R	477	436	41	
3	R	478	437	41	
4	R	478	437	41	
1-1971	R	479	438	41	
2	R	479	438	41	
3	R	479	436	43	
4	R	480	437	43	
1-1972	R	480	437	43	
2	R	480	437	43	
3	R	481	438	43	
4	R	481	438	43	

9 2 1 2 5 5 6 1 6 8 2

Waste Status Summary of 102-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1973	R	481	438	43	
2	R	475	432	43	
3	E	473	430	43	
4	R	475	432	43	
1-1974	R	97	54	43	7 water, 385 to 110-S
2	R	97	54	43	
3 *	R	100	57	43	
4	R	101	58	43	
1-1975	R	101	58	43	
2	EB-R	222	111-68	43	94 from 106-TX; 18 from 002-UR
3 **	EB	381	338	43	242-T bottoms & recycle (1)
4	EB	381	338	43	
1-1976	EB	128	85	43	242-T bottoms & recycle; 322 from 104C; 595 to 111-U (1)
2 ***	EB	447	404	43	242-T bottoms & recycle; 323 from 108-TX (1)
3	Evap feed	499	456	43	Evap. feed bottoms
4	Evap feed	334	291	43	
1-1977	Evap	497	454	43	Evap feed concentration
2	Evap	497	454	43	Evap feed concentration
3	Resid.	494	451	43	A residual liquor, high strontium waste concentration
4	Resid.	400	143	257	A residual liquor, high strontium waste concentration

* Dry Wells #'s 60-02-01, 60-02-07 and 60-02-10 were drilled.

** Dry Wells #'s 60-02-05, and 60-02-11 were drilled.

*** Dry Well #60-02-08 was drilled.

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of U Farm tanks.

9212556168 3

Waste Status Summary of 102-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	497	69	428	Hi SR Waste
2-	NCPLX	479	69	428	
3-	NCPLX	410	0	410	New Solids Level 9-30-78
4-	NCPLX	425	3	421	
1-1979	NCPLX	450	28	422	
2-	NCPLX	450	28	422	Dilute Feed - New Photo 5-3-79
3-	NCPLX	378	0	378	New Solids Level 9-25-79
4-	NCPLX	378	0	378	Inactive - New Photo 12-7-79
1-1980	NCPLX	378	0	378	
2-	NCPLX	378	0	378	
3-	NCPLX	378	0	378	
4-	NCPLX	378	0	378	

9212561634

Waste Status Summary of 103-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1945	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1946	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1947	MW	151	151	---	Cascade began filling Feb.
2	MW	410	410	---	" " " "
3	MW	528	528	---	Cascade filled in July
4	MW	528	528	---	Cascade full
1-1948	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1949	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1950	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1952	---	---	---	---	---
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	530	530	---	Cascade now serving as feed for TBP plant
1-1953	MW	530	530	---	Cascades 101-106 now serving as feed tanks to TBP plant
2	MW	147	147	---	MW removal in progress
3	---	---	---	---	
4	---	---	---	---	T plant active metal waste cascade

9 2 1 2 5 5 6 1 6 3 5

Waste Status Summary of 103-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	52	52	---	T Plant active metal waste cascade
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	519	519	---	
1-1955	MW	519	519	---	
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	13	13	---	MW Supernatant
1-1956	MW	13	13	---	" "
2	MW	1	1	---	
3	MW	1	1	---	Heel to be sluiced
4	MW	1	1	---	Active sluicing
1-1957	R	40	---	---	declared MT sluicing water
2	R	18	---	---	Latest electrode rdg.
3	R	18	---	---	
4	R	18	---	---	
1-1958	R	18	18	0	
2	R	24	24	0	Latest electrode rdg.
3	R	24	24	0	
4	R	517	517	0	492M from 102 & 1115X Received 1 M 111SX
1-1959	R	538	538	0	Latest electrode rdg.
2	R	538	538	0	
3	R	538	538	0	
4	R	535	535	0	
1-1960	R	539	539	0	
2	R	539	539	0	
3	R	539	539	0	
4	R	533	533	0	
1-1961	R				
2	R	530	530	0	6 months
3					
4	R	530	530	0	6 months
1-1962	R	530	530	0	
2					6 months
3	R	530	530	0	
4					6 months

9 2 1 2 1 5 6 1 6 3 6

Waste Status Summary of 103-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	R	530	530	0	{6 months
3					
4	R	530	530	0	{ 6 months
1-1964					
2	R	530	530	0	{6 months
3					
4	R	530	530	0	{6 months
1-1965	R	530	530		{6 months
2					
3	R	530	530	0	
4	R	530	530	0	
1-1966	R	530	530	0	
2	R	530	530	0	
3	R	530	530	0	
4	R	530	530	0	
1-1967	R	530	530	0	
2	R	531	531	0	
3	R	531	531	0	
4	R	531	531	0	
1-1968	R	531	531	0	
2	R	531	531	0	
3	R	531	531	0	
4	R	532	532	0	
1-1969	R	532	532	0	
2	R	533	533	0	
3	R	534	534	0	
4	R	534	502	32	
1-1970	R	534	502	32	
2	R	534	502	32	
3	R	534	502	32	
4	R	535	503	32	
1-1971	R	535	503	32	
2	R	535	503	32	
3	R	536	504	32	
4	R	536	504	32	

9 2 1 2 5 5 6 1 6 9 7

Waste Status Summary of 103-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1972	R	535	503	32	
2	R	536	504	32	
3	R	536	504	32	
4	R	536	504	32	
1-1973	R	536	504	32	
2	R	538	506	32	
3	R	536	504	32	
4	R	537	505	32	
1-1974	R	108	76	32	5 water, 162 to 101-S, 272 to 110-S
2 *	R	111	79	32	
3	R	111	79	32	
4	R	112	80	32	
1-1975	R	112	80	32	
2	EB-R	153	40-81	32	40 from 106-TX; 1 water, 7 water
3 **	EB	480	448	32	242-T bottoms & recycle (1)
4	"	480	448	32	
1-1976	EB	37	5	32	242-T bottoms & recycle 441 to 11-U
2	224-CW-IX EB - BL - RIX - R - DW - BNW	277	55-4-92-7-35-24-7-2-19	32	334 from 103-U, 234 from 101-T, 1 from 108-TX, 2 water, 332 to 102-S
3	Evap. feed	502	470	32	Evap. feed btms.
4	Evap. feed	65	33	32	Dilute
1-1977	Evap.	425	374	51	Evap. feed bottoms
2	Evap	222	171	51	Evap. feed bottoms
3	R	497	163	334	Evap. feed bottoms
4	R	439	28	411	Evap. feed bottoms

* Dry Wells #'s 60-03-05, 60-03-08 and 60-03-11 were drilled.

** Dry Wells #'s 60-03-01 and 60-03-10 were drilled.

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of U Farm tanks.

9 2 1 2 5 5 6 1 6 3 8

Waste Status Summary of 103-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	447	36	411	Feed Trans TK New Photo 3-28-78
2-	PNF	450	39	411	Inactive
3-	PNF	440	41	399	
4-	PNF	453	42	411	
1-1979	PNF	453	42	411	
2-	PNF	453	42	411	New photo 5-3-79
3-	PNF	453	42	411	
4-	PNF	453	42	411	
1-1980	PNF	453	42	411	
2-	PNF	453	42	411	
4-	PNF	453	42	411	
4-	DSSF	453	42	411	

9212161039

Waste Status Summary of 104-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	----	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	MW	253	253	---	Cascade began fill in July
4	MW	528	528	---	" " " " "
1-1948	MW	528	528	---	Cascade began fill in July
2	MW	528	528	---	" " " " "
3	MW	528	528	---	Cascade full
4	MW	528	528	---	" "
1-1949	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1950	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	296	296	---	Supernate from 104-U pumped to cascade 101-103-U

9 2 1 2 1 6 1 6 7 0

Waste Status Summary of 104-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1953	MW	530	530	---	
2	---	---	0	---	MW removal in progress
3	MW	182	182	---	
4	---	---	---	---	
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	530	530	---	
1-1955	MW	530	530	---	
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	
1-1956	MW	25	5	20	Pumped to 106-U sluicing
2	MW	30	22	8	Water for sluicing
3	MW	2	1	1	Tank bulged - leaks
4	MW	2	1	1	" : "
1-1957	R	2	1	1	Tank bulged - leaks
2	R	241	241	0	Testing water tank bulged
3	R	238	238	0	
4	---	---	---	---	
1-1958.	R	230	230	0	Tank bulged
2	R	230	230	0	" "
3	R	224	224	0	" "
4	R	222	222	0	Cor'd figure
1-1959	R	222	222	0	
2	R	220	220	0	
3	R	211	211	0	Latest electrode rdg.
4	R	211	211	0	
1-1960	R	211	211	0	
2	R	199	199	0	Tank bulged rdg being rechecked
3	R	196	196	0	Electrode readings indicate a 1 ¼" drop during past 3 months
4	R	194	194	0	
1-1961					
2	R	67	67	0	6 months
3					
4	R	67	67	0	6 months
1-1962					
2	R	64	64	0	6 months
3					
4	R	64	64	0	6 months Tank leaks

9211256169 1

Waste Status Summary of 104-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	R	59	59	0	6 months tank leaks
3					
4	R	59	59	0	6 months tank leaks
1-1964					
2	R	59	59	0	6 months tank leaks
3					
4	R	59	59	0	6 months
1-1965					
2	R	15	15	0	6 months
3	R	15	15	0	Tank leaks
4	R	15	15	0	" "
1-1966	R	15	15	0	Tank leaks
2	R	15	15	0	" "
3	R	15	15	0	" "
4	R	15	15	0	" "
1-1967	R	15	15	0	Tank leaks
2	R	15	15	0	" "
3	R	15	15	0	" "
4	R	15	15	0	" "
1-1968	R	15	15	0	Tank leaks
2	R	15	15	0	" "
3	R	15	15	0	" "
4	R	15	15	0	" "
1-1969	R	15	15	0	Tank leaks
2	R	15	15	0	" "
3	R	15	15	0	" "
4	R	106	66	40	New electrode: tank leaks
1-1970	R	106	66	40	
2	R	107	67	40	
3	R	105	65	40	
4	R	107	67	40	
1-1971	R	107	67	40	
2	R	107	67	40	
3	R	107	67	40	
4	R	107	67	40	
1-1972	R	106	66	40	
2	---	131	0	131	Tank leaks 60 tons of diatomaceous earth added
3	---	129	0	129	" " " " " " " "
4	---	128	0	128	" " " " " " " "

9 2 1 2 5 5 1 6 9 2

Waste Status Summary of 104-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1973	---	128	0	128	Tank leaks 60 tons of diatomaceous earth added
2	---	127	0	127	" " " " " " " "
3	---	127	0	127	" " " " " " " "
4	---	127	0	127	" " " " " " " "
1-1974	---	127	0	127	Tank leaks 60 tons of diatomaceous earth added
2 *	---	127	0	127	"" " " " " " "
3	---	127	0	127	"" " " " " " "
4	---	125	0	125	"" " " " " " "
1-1975	---	125	0	125	Tank leaks 60 tons of diatomaceous earth added
2	---	125	0	125	"" " " " " " "
3	---	125	0	125	"" " " " " " "
4	---	125	0	125	"" " " " " " "
1-1976	---	125	0	125	Tank leaks 60 tons of diatomaceous earth added
2	---	125	0	125	"" " " " " " "
3	---	125	0	125	"" " " " " " "
4	---	125	0	125	"" " " " " " "
1-1977	Isolated & Stabilized	125	0	125	Tank leaks, stabilized and isolated
2	Isolated & Stabilized	125	0	125	Tank leaks, stabilized and isolated, desicant added
3	---	125	0	125	Tank leaks, stabilized and isolated, desicant added
4	---	125	0	125	Tank leaks, stabilized and isolated, desicant added

* Dry Wells #'s 60-04-03, 60-04-08, 60-04-10 and 60-04-12 were drilled.

9 2 1 2 5 5 6 1 6 9 3

Waste Status Summary of 104-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	125	0	124	Interim Stabilized and Partially Isolated
2-	-	125	0	125	
3-	-	113	0	113	New Photo 8-31-78
4-	-	;25	0	125	Solids Level adj. 9-30-78
1-1979	-	125	0	125	
2-	-	125	0	125	
3-	-	125	0	125	
4-	-	125	0	125	
1-1980	-	125	0	125	500 gal pool
2-	-	125	0	125	
3-	-	125	0	125	
4-	-	125	0	125	

9 2 1 2 5 5 6 1 6 9 4

Waste Status Summary of 105-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1945	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1946	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1947	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	MW	62	62	---	Cascade began filling December
1-1948	MW	314	314	---	Cascade began filling December
2	MW	528	528	---	" " " "
3	MW	528	528	---	Cascade full
4	MW	528	528	---	" "
1-1949	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1950	MW	528	528	---	Cascade full
2	MW	528	528	---	" "
3	MW	528	528	---	" "
4	MW	528	528	---	" "
1-1951	MW	528	528	---	Cascade full
2	---	---			
3	---	---			
4	---	---			
1-1952	---	---			
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	

9 2 1 2 1 5 6 1 6 9 5

Waste Status Summary of 105-U Tank-Capacity 530,000 Gallons

Qtr-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	*Remarks
1-1953	MW	530	530	---	
2	MW	111	111	---	MW removal in progress
3	---	---	---	---	
4	---	---	---	---	
1-1954	---	----	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	MW	520	520	---	
1-1955	MW	520	520	---	
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	519	519	---	
1-1956	MW	530	530	---	
2	MW	20	17	3	Supernatant pumped to 106U
3	MW	92	92	---	Rec'd from 300 area Active sluicir tank
4	MW	117	117	---	mostly U from 300 area
1-1957	R	48	48	---	(1) sluicing heel (2) declared MT (3) sluicing water
2	R	0	---	---	
3	R	40	40	---	
4	R	40	40	---	
1-1958	R	40	40	0	
2	R	40	40	0	
3	R	40	40	0	
4	R	40	40	0	
1-1959	R	40	40	0	
2	R	40	40	0	
3	R	40	40	0	
4	R	40	40	0	
1-1960	R	40	40	0	
2	R	40	40	0	
3	R	40	40	0	
4	R	40	40	0	
1-1961	R	175	175	0	
2					6 months rec'd 135M from 104-U
3	R-CW	497	175-322	0	
4					6 months 322M from 108-U

* (1) (2) (3) designates month in each quarter that transfer occurred.

9 2 1 2 5 5 6 1 6 9 6

Waste Status Summary of 105-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solid in Storage	Remarks
1-1962					
2	R-CW	497	175-322	0	6 months
3					
4	R-CW	497	175-322	0	6 months
1-1963					
2	R-CW	497	175-322	0	6 months
3					
4	R-CW	497	175-322	0	6 months
1-1964					
2	R-CW	497	175-322	0	6 months
3					
4	R-CW	497	175-322	0	6 months
1-1965					
2	R-CW	499	175-324	0	6 months
3	R-CW	499	175-324	0	
4	R-CW	499	175-324	0	
1-1966	R-CW	499	175-324	0	
2	R-CW	499	175-324	0	
3	R-CW	499	175-324	0	
4	R-CW	499	175-324	0	
1-1967	R-CW	499	175-324	0	
2	R-CW	501	175-326	0	
3	R-CW	501	175-326	0	
4	R-CW	501	175-326	0	
1-1968	R-CW	501	175-326	0	
2	R-CW	501	175-326	0	
3	R-CW	501	175-326	0	
4	R-CW	501	175-326	0	
1-1969	R-CW	501	175-326	0	
2	R-CW	501	175-326	0	
3	R-CW	502	175-327	0	
4	R-CW	502	175-295	32	
1-1970	R-CW	502	175-295	32	
2	R-CW	502	175-295	32	
3	R-CW	502	175-295	32	
4	R-CW	502	175-295	32	
1-1971	R-CW	503	175-296	32	
2	R-CW	503	175-296	32	
3	R-CW	503	175-296	32	
4	R-CW	503	175-296	32	

9212556169 7

Waste Status Summary of 105-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1972	R-CW	505	176-297	32	
2	R-CW	505	176-297	32	
3	R-CW	505	176-297	32	
4	R-CW	506	176-298	32	
1-1973	R-CW	508	177-299	32	
2	R-CW	507	177-298	32	
3	R-CW	504	176-296	32	
4	R-CW	506	177-297	32	
1-1974	R-CW	85	20-33	32	434 to 110-S
2 *	R-CW	87	21-34	32	
3	R-CW	88	21-35	32	
4	R-CW	87	21-34	32	
1-1975	R-CW	92	23-37	32	
2	EB-R-CW	381	289-23-37	32	287 from 106-TX
3	EB	497	465	32	242-T bottoms & recycle; 275 to 111-U (1)
4**	EB	497	465	32	242-T bottoms & recycle; 275 to 111-U (1)
1-1976	EB	505	473	32	242-T bottoms & recycle; 275 to 111-U (1)
2	EB	513	481	32	242-T bottoms & recycle; 275 to 111-U (1)
3	Evap.feed	439	407	32	242-T bottoms & recycle; 275 to 111-U (1)
4	Evap.feed	252	146	106	242-T bottoms & recycle; 275 to 111-U (1)
1-1977	Resid.	378	129	249	Active residual liquor, high strontium waste concentration
2	R	376	127	249	Active residual liquor, high strontium waste concentration
3	R	510	261	249	Active residual liquor, high strontium waste concentration
4	R	403	154	249	Active residual liquor, high strontium waste concentration

* Dry Wells #'s 60-05-05, 60-05-07 and 60-05-08 were drilled.
** Dry well No. 60-05-10 was drilled.

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of U Farm tanks.

9 2 1 2 5 5 6 1 6 9 8

Waste Status Summary of 105-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	400	151	249	Salt Well Instald.
2-	CCPLX	442	0	442	Solids Level Adj. 4-19-78
3-	CCPLX	391	22	369	New Solids Level 9-30-78 New Photo taken 8-29-78
4-	CCPLX	406	25	381	Solids Level Adj.
1-1979	CCPLX	406	25	381	Inactive
2-	CCPLX	406	25	381	
3-	CCPLX	406	25	381	
4-	CCPLX	406	25	381	
1-1980	CCPLX	406	25	381	
2-	CCPLX	406	25	381	
3-	CCPLX	406	25	381	
4-	CCPXL	406	25	381	

9 2 1 2 3 5 6 1 6 0 9

Waste Status Summary of 106-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1945	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1947	---	---	---	---	---
2	---	---	---	---	---
3	---	---	---	---	---
4	---	---	---	---	---
1-1948	---	---	---	---	---
2	MW	192	192	---	Cascade began filling in May
3	MW	528	528	---	Cascade full September
4	MW	528	528	---	" " "
1-1949	MW	528	528	---	Cascade full September
2	MW	528	528	---	" " "
3	MW	528	528	---	" " "
4	MW	528	528	---	" " "
1-1950	MW	528	528	---	Cascade full September
2	MW	528	528	---	" " "
3	MW	528	528	---	" " "
4	MW	528	528	---	" " "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	519	519	---	
1-1953	MW	530	530	---	
2	MW	288	288	---	MW removal in progress
3	MW	28	28	---	
4	MW	30	30	---	MW supernatant blend tank

9 2 1 2 5 5 6 1 7 0

Waste Status Summary of 106-U Tank-Capacity 530,000-Galons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	* Remarks
1-1954	---	---	---	---	MW Supernatant blend tank
2	---	---	---	---	" " " "
3	---	---	---	---	" " " "
4	---	---	---	---	
1-1955	---	---	---	---	Supernatant blend tank
2	MW	131	131	---	Supernatant from 101-U
3	MW	80	80	---	" " "
4	MW	375	375	---	Supernatant supply tank
1-1956	MW	304	304	---	Supernatant supply tank
2	MW	478	472	6	" " "
3	MW	26	26	---	
4	MW	1	1	0	
1-1957	R	0	---	0	(1) to be blended (2) declared MT
2	R	0	---	0	
3	R	0	---	---	
4	R	0	---	0	
1-1958	R	0	0	0	
2	R	0	0	0	
3	R	0	0	0	
4	R	0	0	0	
1-1959	R	0	0	0	
2	R	0	0	0	
3	R	MT	0	0	
4	R	0	0	0	
1-1960	R	0	0	0	
2	R	0	0	0	
3	R	483	483	0	(1)Rec'd 456 from 101-U (3)Rec'd 26M from 101-U
4	R	502	502	0	Latest electrode reading
1-1961					
2	R	505	505	0	6 months
3					
4	R	505	505	0	6 months

* (1) (2) (3) designates month in each quarter that transfer occured.

9 2 1 2 5 5 6 1 7 0 1

Waste Status Summary of 106-U Tank-Capacity 530,000 Gallons

QTR.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1962					
2	R	505	505	0	6 months
3					
4	R	505	505	0	6 months
1-1963					
2	R	505	505	0	6 months
3					
4	R	505	505	0	6 months
1-1964					
2	R	505	505	0	6 months
3					
4	R	505	505	0	6 months
1-1965	R	502	502	0	6 months
2					
3	R	502	502	0	
4	R	502	502	0	
1-1966	R	502	502	0	
2	R	502	502	0	
3	R	505	505	0	
4	R	505	505	0	
1-1967	R	505	505	0	
2	R	505	505	0	
3	R	505	505	0	
4	R	505	505	0	
1-1968	R	505	505	0	
2	R	505	505	0	
3	R	505	505	0	
4	R	507	507	0	
1-1969	R	507	507	0	
2	R	507	507	0	
3	R	508	508	0	
4	R	508	482	26	
1-1970	R	508	482	26	
2	R	508	482	26	
3	R	508	482	26	
4	R	508	482	26	

9212561712

Waste Status Summary of 106-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1971	R	508	482	26	
2	R	508	482	26	
3	R	508	482	26	
4	R	508	482	26	
1-1972	R	509	483	26	
2	R	509	483	26	
3	R	509	483	26	
4	R	509	483	26	
1-1973	R	510	484	26	
2	R	509	48	26	
3	R	505	479	26	
4	R	506	480	26	
1-1974	R	85	59	26	424 to 110-S
2	R	86	60	26	
3 *	R	86	60	26	
4	R	84	58	26	
1-1975	R	87	61	26	
2	R	87	61	26	
3 **	R	87	61	26	
4	R-PL-BL	315	61-14-214	26	229 from 104-C
1-1976 ***	EB	403	377	26	173 from 104-C; 242-S bottom & recycle; 1475 to 111-U (1)
2	EB	406	380	26	242-S bottoms & recycle; (1)
3	Evap feed	376	350	26	Evap feed btms
4	Evap feed	362	336	26	Evap. feed btms
1-1977	Resid.	332	259	73	High strontium waste concentration
2	Resid.	227	154	73	High strontium waste concentration
3	Resid.	222	11	211	Inactive cur., high strontium waste concentration
4	Resid.	224	13	211	Inactive cur., high strontium waste concentration

* Dry Wells #60-06-07 and 60-06-10 were drilled.

** Dry Well #60-06-08 was drilled.

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of U Farm tanks.

*** Dry Well No. 60-06-11 was drilled.

9 2 1 2 5 5 6 1 7 0 3

Waste Status Summary of 106-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	222	11	211	Questionable Integrity
2-	CCPLX	224	13	211	
3-	CCPLX	215	17	198	
4-	CCPLX	227	16	211	
1-1979	CCPLX	227	16	211	
2-	CCPLX	227	16	211	
3-	CCPLX	227	16	211	
4-	CCPLX	227	16	211	
1-1980	CCPLX	227	16	211	
2-	CCPLX	227	16	211	
3-	CCPLX	227	16	211	New Photo & new solids level 5-1-80
4-	CCPLX	227	16	211	

9 2 1 2 3 5 6 1 7 0 4

Waste Status Summary of 107-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	----	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	MW	16	16	---	Cascade began fill September
4	MW	528	528	---	Cascade full in December
1-1949	MW	528	528	---	Cascade full in December
2	MW	528	528	---	" " " "
3	MW	528	528	---	Cascade full as of July
4	MW	528	528	---	" " " " "
1-1950	MW	528	528	---	Cascade full as of July
2	MW	528	528	---	" " " " "
3	MW	528	528	---	" " " " "
4	MW	528	528	---	" " " " "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	

9 2 1 2 5 5 6 1 7 0 5

Waste Status Summary of 107-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	* Remarks
1-1953	MW	530	530	---	
2	MW	530	530	---	
3	MW	6	0	6	Sluicing sludge
4	MW	189	189	---	Metal waste removal in progress
1-1954	MW	8	0	8	Metal waste removal in progress
2	MW	278	278	---	T-Plant active metal cascade- started 6/7/54 - sludge removal completed 6/29/54 reserve capaci gained by self-evaporation & solution shrinkage
3	MW	549	549		T-Plant active waste cascade
4	MW	543	543	---	
1-1955	MW	543	543	---	
2	MW	543	543	---	
3	MW	543	543	---	To be sluiced next
4	MW	530	530	---	
1-1956	MW	1	0	1	water jetting to 101 - being inspected visually
2	MW	2	1	1	Sluiced during month
3	MW	2	1	1	To be sluiced
4	MW	1	0	1	" " "
1-1957	CW	0	---	0	(1) sluicing (2) declared MT
2	CW	0	---	0	
3	CW	0	---	0	
4	CW	200	200	0	(1) 202M rec'd from 107 (3) latest electrode rdg.
1-1958	CW	285	285	0	85M from 107-S
2	CW	477	477	0	192M from 107-S
3	CW	475	475	0	Latest electrode rdg.
4	CW	475	475	0	
1-1959	CW	472	472	0	Latest electrode rdg.
2	CW	510	510	0	(2) Rec'd 38M CW from 102-S
3	CW	508	508	0	Latest electrode rdg.
4	CW	508	508	0	
1-1960	CW	505	505	0	Reading to be checked & new electrode installed
2	CW	505	505	0	
3	CW	505	505	0	
4	CW	510	510	0	

* (1) (2) (3) designates month in each quarter that transfer occurred.

9212556170 6

Waste Status Summary of 107-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1961					
2	CW	510	510	0	6 months
3					
4	CW	510	510	0	6 months
1-1962					
2	CW	508	508	0	6 months → latest electrode rdg.
3					
4	CW	508	508	0	6 months
1-1963					
2	CW	508	508	0	6 months
3					
4	CW	510	510	0	6 months latest electrode reading
1-1964					
2	CW	510	510	0	6 months
3					
4	CW	510	510	0	6 months
1-1965	CW	541	541	0	6 months
2					
3	CW	541	541	0	
4	CW	541	541	0	
1-1966	CW	541	541	0	
2	CW	541	541	0	
3	CW	541	541	0	
4	CW	541	541	0	
1-1967	CW	541	541	0	
2	CW	543	543	0	
3	CW	543	543	0	
4	CW	543	543	0	
1-1968	CW	543	543	0	
2	CW	543	543	0	
3	CW	134	134	0	350 from 107S 750 to 108-U
4	CW	136	60	76	
1-1969	CW-EB	271	61-134	76	134 from 105 SX
2	CW-EB	482	61-345	76	615 from 107-SX; Rec'd 58 dilu. water; 463 to 108U
3	CW-EB	479	61-342	76	
4	CW-EB	508	47-371	90	283 from 107-S; 253 to 109-U

9212556170 7

Waste Status Summary of 107-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1970	CW-EB	508	47-371	90	
2	CW-EB	508	47-371	90	
3	CW-EB	508	47-371	90	
4	CW-EB	508	47-371	90	
1-1971	CW-EB	509	47-372	90	
2	CW-EB	509	47-372	90	
3	CW-EB	508	47-371	90	
4	CW-EB	508	47-371	90	
1-1972	CW-EB	160	8-62	90	349 to 101-TX
2	CW-EB	160	8-62	90	
3	N-BNW-DW-CW-EB	560	317-51-51-6-45	90	441 from 100-N, 71 from BNW, 71 from 112-T, 183 to 108-U
4	N-BNW-DW-CW-EB	458	138-60-148-2-20	90	286 from 112-T, 88 from BNW, 309 to 104-C, 166 to 108-U
1-1973	DW-BNW	266	143-33	90	332 from 112-T, 210 from BNW, 15 from 100-N, 748 to 104-C
2	LW-CW-N BNW-DW-IX-BL	470	38-36-94-70-128-11-3	90	126 from BNW, 214 from 100-N, 180 from 112-T, 165 from 110-U, 481 to 104-C
3	LW-CW-N-BNW-DW-IX-EB	380	2-4-161-88-8-20-7	90	83 from BNW, 154 from 100-N, 32 from 103-T, 354 to 104-C
4	BNW-N-DW EB-R	485	89-86-105-35-80	90	87 from BNW, 101 from UNI, 112 from T-Plant, 298 from 106-S, 131 from 107-S, 14 water, 367 to 104-C, 273 to 101-S
1-1974 *	BNW-N-DW	290	79-33-88	90	101 from BNW, 105 from UNI, 101 from T-Plant, 23 water, 210 to 101-S, 316 to 110-S
2	BNW-N-DW	388	51-237-10	90	
3	BNW-N-DW	267	109-10-58	90	275 from BNW, 121 from UNI, 121 from T-Plant, 639 to 110-S
4	BNW-N-DW	403	219-30-139	15	106 from BNW, 79 from T-Plant, 20 from UNI, 72 to 107-S
1-1975	BNW-N-DW	332	153-15-149	15	45 from BNW, 81 from T-plant, 45 from 204-4S, 14 from 001-UR, 9 from 002-TX, 260 to 107-S
2	BNW-N-DW	321	143-26-137	15	84 from BNW, 80 from T-plant, 20 from N, 30 from 002-UR, 11 from 002-TX
3	DW-LW-N-BNW	189	39-8-119-8	15	41 from BNW, 608 from N, 80 from T-plant, 40 H_2O, 14 from 222-S 8 from 204-S-4, 923 to 108-U
4	DW-LW-N-BNW	345	118-30-81-101	15	140 from BNW, 133 from T-plant, 36 from 222-S, 151 to 108-U

* Dry Wells No.'s 60-07-02 and 60-07-11 were drilled.

9212556170 8

Waste Status Summary of 107-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1976	DW-LW-N-BNW	428	172-43-28-170	15	123 from BNW, 115 from T-plant, 30 from 222-S, 182 to 108-U
2	N-LW-BNW-DW	312	18-83-130-66	15	91 from BNW, 15 from N, 82 from T-plant, 22 from 222-S, 9 from TX-302-C, 334 to 103-U
*					
3	Evap. feed	450	435	15	Evap. feed dilu.
4	Evap feed	197	182	15	Waste Receiver
1-1977	Evap.	431	317	114	Waste receiver
2	Evap.	268	154	114	Waste receiver
3	Evap.	246	96	150	Waste receiver
4	Evap. Feed Dil.	428	327	101	Waste receiver
1-1978	EVAP	486	385	101	
2-	NCPLX	466	286	180	Solids Level Adj. 4-19-78
3-	NCPLX	437	247	190	Active Waste Receiver
4-	NCPLX	442	286	156	Solids Level Adj. 12-18-78 New Photo 12-7-78
1-1979	CPLX	450	294	156	Dilute Feed
2-	CPLX	450	294	156	
3-	CPLX	442	286	156	
4-	CPLX	481	335	156	
1-1980	CPLX	398	242	156	
2-	CPLX	425	269	156	
3-	CPLX	380	224	156	
4-	DSSF	391	16	375	Inactive-New Solids Level 11-17-80

* Dry Wells No.'s 60-07-01 and 60-07-10 were drilled.

9 2 1 2 5 5 6 1 7 0 9

Waste Status Summary of 108-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	---
2	---	---	---	---	
3 *	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	MW	528	528	---	Cascade full in March
2	MW	528	528	---	" " " "
3	MW	528	528	---	" " " "
4	MW	528	528	---	" " " "
1-1950	MW	528	528	---	Cascade full in March
2	MW	528	528	---	" " " "
3	MW	528	528	---	" " " "
4	MW	528	528	---	" " " "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	530	530	---	
3	MW	530	530	---	
4	MW	530	530	---	
1-1953	MW	530	530	---	
2	MW	338	338	---	Supernatant supply
3	MW	458	458	---	
4	---	---	---	---	Metal waste removal in progress

* Dry Well No. 60-08-10 was drilled.

9212556171 0

Waste Status Summary of 108-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	---	---	---	---	Metal waste removal in progress
2	---	---	---	---	
3	MW	552	552	---	T-plant active waste cascade
4	MW	552	552	---	
1-1955	MW	552	552	---	
2	MW	552	552	---	
3	MW	552	552	---	
4	MW	530	530	---	
1-1956	MW	1	0	1	Pumped to 106U ready for periscope
2	MW	2	1	1	Sluicing during month
3	MW	2	1	1	To be sluiced
4	MW	0		0	Declared MT
1-1957	CW	0		0	
2	CW	0		0	
3	CW	0		0	
4	CW	0		0	
1-1958	CW	0	0	0	
2	CW	0	0	0	
3	CW	0	0	0	
4	CW	0	0	0	
1-1959	CW	0	0	0	
2	CW	182	182	0	Rec'd 182 from 107S
3	CW	182	182	0	
4	CW	182	182	0	
1-1960	CW	182	182	0	
2	CW	316	316	0	Rec'd 134M CW from 107-SX
3	CW	316	316	0	
4	CW	420	420	0	Rec'd 104 R-CW from 107-S
1-1961					
2	CW	420	420	0	6 months
3					
4	CW	299	299	0	6 months 322M to 105 U, 201 M from 107S
1-1962					
2	CW	295	295	0	6 months → latest electrode rdg.
3					
4	CW	508	508	0	6 months Rec'd 213M from 107S

9212556171

Waste Status Summary of 108-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1963					
2	CW	246	246	0	6 months 170M from 107-S, 432M to
3					
4	CW	246	246	0	6 months
1-1964					
2	CW	444	444	0	6 months Rec'd 198M
3					
4	CW	507	507	0	6 months Rec'd 63M from 107-S
1-1965					
2	CW	508	508	0	
3	CW	508	508	0	6 months
4	CW	508	508	0	
1-1966	CW	508	508	0	
2	CW	508	508	0	
3	CW	508	508	0	
4	CW	508	508	0	
1-1967	CW	508	508	0	
2	CW	510	510	0	
3	CW	510	510	0	
4	CW	510	510	0	
1-1968	CW	510	510	0	
2	CW	211	211	0	299 to 118 TX
3	CW	402	402	0	750 Rec'd 558 to 118 TX
4	CW	64	64	0	338 to 118 TX
1-1969	CW	64	64	0	
2	CW-EB	527	64-463	0	463 from 107-U
3	CW-EB	523	64-459	0	
4	CW-EB	522	34-459	29	
1-1970	CW-EB	522	34-459	29	
2	CW-EB	522	34-459	29	
3	CW-EB	522	34-459	29	
4	CW	523	34-460	29	
1-1971	CW-EB	523	34-460	29	
2	CW-EB	523	34-460		
3	CW-EB	523	34-460	29	
4	CW-EB	523	34-460	29	

9 2 1 2 5 5 6 1 7 1 2

Waste Status Summary of 108-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1972	CW-EB	523	34-460	29	
2	CW-EB	84	4-51	29	
3	N-BNW-DW-CW-EB	267	122-21-21-6-68	29	183 from 107-U
4	N-BNW-DW CW-EB	433	185-48-87-7-77	29	166 from 107-U
1-1973	N-BNW-DW CW-EB	435	187-48-87-7-77	29	
2	N-BNW-DW CW-EB	435	187-48-87-7-77	29	
3	N-BNW-DW CW-EB	432	186-48-86-16-265	29	
4	N-BNW-DW CW-EB	93	30-8-13-1-12	29	335 to 101-S
1-1974	N-BNW-DW CW-EB	100	34-9-14-1-13	29	7 water
2 *	N-BNW-DW CW-EB	101	35-9-14-1-13	29	
3	N-BNW-DW CW-EB	101	35-9-14-1-13	29	
4	N-BNW-DW CW-EB	101	35-9-14-1-13	29	
1-1975	N-BNW-DW CW-EB	101	35-9-14-1-13	29	
2	N-BNW-DW CW-EB	101	46-120-123-1-13	29	228 from 107-U, 228 to 108-U
3	BNW-N-DW-LW	266	17-196-22-2	29	923 from 107-U, 990 to 111-U
4	EB	508	479	29	242-S bottoms & recycle 151 from 107-U (1)
1-1976	EB	508	308	200	242-S Bottoms & recycle 182 from 102-U (1)
2 **	EB	510	310	200	242-S bottoms & recycle 151 from 107-U (1)
3	Evap feed	513	313	200	Evap. feed btms
4	RESiD	488	211	277	Residual Liquor

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainity in the liquid-to-solid ratio of U Farm tanks.

* Dry Wells No's 60-08-04 and 60-08-09 were drilled.
** Dry Well No. 60-08-08 was drilled.

9 2 1 2 5 5 6 1 7 1 3

Waste Status Summary of 108-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1977	Resid.	461	201	260	Residual liquor
2	Resid.	442	182	260	Residual liquor
3	Resid.	450	190	260	Residual liquor
4	Resid.	453	193	260	Residual liquor
1-1978	HDRL	453	193	260	
2-	PNF	458	198	260	
3-	PNF	446	198	248	
4-	PNF	458	195	263	Solids Level Taken 12-18-78
1-1979	PNF	461	198	263	
2-	PNF	461	198	263	
3-	PNF	461	17	444	New Solids Level 8-20-79 New photo 7-31-79
4-	PNF	461	17	444	Inactive
1-1980	PNF	461	17	444	
2-	PNF	461	17	444	
3-	PNF	461	17	444	
4-	NCPLX	461	17	444	

9 2 1 2 5 5 6 1 7 1 4

Waste Status Summary of 109-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	MW	150	150	---	Cascade began fill in March
2	MW	455	455	---	" " " " "
3	MW	528	528	---	" " " " "
4	MW	528	528	---	" " " " "
1-1950	MW	528	528	---	Cascade began fill in March
2	MW	528	528	---	" " " " "
3	MW	528	528	---	" " " " "
4	MW	528	528	---	" " " " "
1-1951	MW	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	MW	519	519	---	
3	MW	519	519	---	
4	MW	519	519	---	
1-1953	MW	519	519	---	
2	MW	276	276	---	Supernatant supply
3	MW	280	280	---	
4	MW	44	44	---	Metal waste removal in progress

9 2 1 2 5 5 6 1 7 1 5

Waste Status Summary of 109-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	MW	58	58	---	
2	---	---	---	---	
3	MW	363	363	---	
4	MW	490	490	---	
1-1955	MW	490	490	---	
2	MW	490	490	---	
3	MW	490	490	---	
4	MW	490	490	---	
1-1956	MW	490	490	---	
2	MW	0	0	---	Heel jet sluicing for Redox ctg. waste
3	R	188(CW)	188	---	For Redox ctg. waste
4	MW	410(CW)	410	---	Rec'd from 110U
1-1957	CW	411	411	---	Latest electrode rdg.
2	CW	381	381	---	" " "
3	CW	381	381	---	
4	CW	381	381	---	
1-1958	CW	381	381	0	
2	CW	381	381	0	
3	CW	425	425	0	44 from 301-U catch TK
4	CW	425	425	0	
1-1959	CW	425	425	0	
2	CW	425	425	0	
3	CW	442	442	0	Rec'd 17M from 301-U catch tank
4	CW	442	442	0	
1-1960	CW	442	442	0	
2	CW	442	442	0	
3	CW	442	442	0	
4	CW	442	442	0	
1-1961					
2	CW	442	442	0	6 months
3					
4	CW	442	442	0	6 months
1-1962					
2	CW	442	442	0	6 months
3					
4	CW	442	442	0	6 months
1-1963					
2	CW	442	442	0	6 months
3					
4	CW	442	442	0	6 months

9212556171 6

Waste Status Summary of 109-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	CW	442	442	0	6 months
3					
4	CW	442	442	0	6 months
1-1965	CW	458	423	35	6 months
2					
3	CW	458	423	35	
4	CW	458	423	35	
1-1966	CW	466	431	35	Latest electrode reading
2	CW	458	423	35	" " "
3	CW	490	455	35	" " "
4	CW	490	455	35	
1-1967	CW	490	455	35	
2	CW	490	455	35	
3	CW	490	455	35	
4	CW	490	455	35	
1-1968	CW	490	455	35	
2	CW	490	455	35	
4	CW	490	455	35	
1-1969	CW	345	310	35	147 to 118-TX
2	CW	62	27	35	283 to 118-TX
3	CW	63	28	35	
4	CW-EB	316	15-253	48	253 from 107-U
1-1970	CW-EB	315	15-252	48	
2	CW-EB	315	15-252	48	
3	CW-EB	314	15-251	48	
4	CW-EB	314	15-251	48	
1-1971	CW-EB	314	15-251	48	
2	CW-EB	314	15-251	48	
3	CW-EB	314	15-251	48	
4	CW-EB	314	15-251	48	
1-1972	CW-EB	314	15-251	48	
2	CW-EB	316	15-253	48	
3	CW-EB	316	15-253		
4	CW-EB	328	16-264	48	15 from 301-U catch tank

9212556117

Waste Status Summary of 109-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1973	CW-EB	329	16-265	48	
2	CW-EB	332	16-268	48	
3	CW-EB	329	16-265	48	
4	CW-EB	330	16-266	48	
1-1974	CW-EB	127	4-25	48	5 water, 209 to 109-U
2	CW-EB	127	4-75	48	
3 *	CW-EB	127	4-75	48	
4	CW-EB-R	153	4-75-26	48	23 from 112-U
1-1975	CW-EB-R	156	4-75-27	48	1 from 112-U
2	CW-EB-R	156	4-77-27	48	
3	CW-EB-R	161	4-81-28	48	4 from 112-U
4	EB	513	465	48	242-S bottoms & recycle (1)
1-1976	EB	505	249	256	242-S bottoms & recycle (1)
2	EB	508	253	255	242-S bottoms & recycle (1)
3 **	Evap feed	513	258	255	242-S bottoms & recycle
4	Resid	376	3	373	Residual Liquor
1-1977	Resid.	499	236	263	Residual liquor
2	Resid.	455	192	263	Residual liquor
3	Resid.	458	195	263	Residual liquor
4	Resid.	450	6	440	Residual liquor

* Dry Wells No.'s 60-09-08 and 60-09-10 were drilled.

** Dry Wells No.'s 60-09-01 and 60-09-07 were drilled.

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainty in the liquid-to-solid ratio of U Farm tanks.

9212556178

Waste Status Summary of 109-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	HDRL	450	6	444	Inactive
2-	PNF	453	9	444	
3-	PNF	443	11	432	
4-	PNF	455	11	444	
1-1979	PNF	455	11	444	
2-	PNF	455	11	444	
3-	PNF	455	11	444	
4-	PNF	455	11	444	
1-1980	PNF	455	11	444	
2-	PNF	455	11	444	
3-	PNF	455	11	444	
4-	NCPLX	455	11	444	

9 2 1 2 1 5 6 1 7 1 9

Waste Status Summary of 110-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
3	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	--	---	---	---	
3	1 C	90	90	---	Cascade began filling July 46
4	1 C	271	271	---	" " " " "
1-1947	1 C	512	512	---	Cascade began filling July 46
2	1 C	528	528	---	"
3	1 C	528	528	---	"
4	1 C	528	528	---	"
1-1948	1 C	528	528	---	Cascade began filling July 46
2	1 C	528	528	---	Cascade full
3	1 C	528	528	---	" "
4	1 C	528	528	---	" "
1-1949	1 C	528	528	---	Cascade full
2	1 C	528	528	---	" "
3	1 C	528	528	---	" "
4	1 C	528	528	---	" "
1-1950	1 C	528	528	---	Cascade full
2	1 C	528	528	---	" "
3	1 C	528	528	---	" "
4	1 C	528	528	---	" "
1-1951	1 C	528	528	---	Cascade full
2 ---	---	---	---	---	
3 ---	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1 C	336	336	---	Cascade being held as Redox reserve space
3	1 C	336	336	---	" " " "
4	1 C	336	336	---	" " " "

9 2 1 2 5 6 1 7 2 0

Waste Status Summary of 110-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1953	1C	336	---	336	3 tanks held as Redox waste reserve
2	1C	337	1	336	
3	1C	335	0	335	
4	1C	335	0	335	Being held for Redox wastes
1-1954	1C-R	530	0-195	335	Cascade rec'd Redox concentrated salt waste
2	1C-R	463	0-128	335	
3	1C-R	391	0-56	335	Reserve capacity gained self-evapo ation 2nd solution shrinkage
4	1C-R	353	0-18	335	Reserve cap. gained by self. evapo
1-1955	1C-R	329	0-0	329	Reserve capacity gained by self-evaporation
2	1C-R	329	0-0	329	
3	1C-R	410	91	319	Receives Redox ctg. waste
4	1C-R	484	165	319	
1-1956	1C-R	530	211	319	Receives S Plant ctg.
2	1C-R	385	66	319	(1) To be pumped to 204C (2) Pumpe to 106-T, 112-U & 204U (3) S.S. rec'd Redox ctg. waste
3	1C-R	389	70	319	(1) Rec'd 19M (2) Rec'd 31M SS 143M pumped to 109U
4	1C-R	347	36	311	(1) SS 69M Rec'd (2) SS pumped to 109U (3) SS 35M coating waste rec
1-1957	1C-CW	392	81	319	(1) SS 15M CW rec'd (2) SS 11M gal rec'd (3)Rec'd 19 M CW
2	1C-CW	453	142	311	(1) SS recd 22M gals CW (2) SS rec 21M CW (3) SS rec'd 18M CW
3	1C-CW	480	169	311	(1) 24M CW rec'd
4	1C-CW	480	169	311	
1-1958	1C-CW	477	166	311	
2	1C-CW	477	166	311	
3	1C-CW	513	202	311	39M H_2O from 240-S
4	1C-CW	513	202	311	
1-1959	1C-CW	510	199	311	Latest electrode rdg.
2	1C-CW	513	202	311	" " "
3	1C-CW	513	202	311	
4	1C-CW	510	199	311	Latest electrode rdg.
1-1960	1C-CW	510	199	311	
2	1C-CW	510	199	311	
3	1C-CW	311-199	179	331	
4	1C-CW	311-199	179	331	

(1) (2) (3) designates month in each quarter that transfer occurred.

9 2 1 2 5 5 6 1 7 2 1

Waste Status Summary of 110-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1961	1C-CW	311-199	179	331	
2					6 months
3	1C-CW	507	196	311	
4					6 months
1-1962					
2	1C-CW	505	194	311	6 months→latest electrode rdg.
3					
4	1C-CW	505	194	311	6 months
1-1963					
2	1C-CW	510	199	311	6 months
3					
4	1C-CW	510	199	311	6 months
1-1964					
2	1C-CW	510	199	311	6 months
3					
4	1C-CW	510	199	311	6 months
1-1965	1C-CW	497	186	311	
2					6 months
3	1C-CW	497	186	311	
4	1C-CW	497	186	311	
1-1966	1C-CW	497	186	311	
2	1C-CW	497	186	311	
3	1C-CW	497	186	311	
4	1C-CW	497	186	311	
1-1967	1C-CW	497	186	311	
2	1C-CW	497	186	311	
3	1C-CW	497	186	311	
4	1C-CW	497	186	311	
1-1968	1C-CW	497	186	311	
2	1C-CW	497	186	311	
3	1C-CW	497	186	311	
4	CW	497	186	311	
1-1969	CW	496	185	311	
2	CW	340	29	311	157 to 118-TX
3	CW	340	29	311	
4	CW	339	155	184	
1-1970	CW	340	156	184	
2	CW	340	156	184	
3	CW	339	155	184	
4	CW	339	155	184	

9 2 1 2 5 5 6 1 7 2 2

Waste Status Summary of 110-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1971	CW	339	155	184	
2	CW	339	155	184	
3	CW	339	156	183	
4	CW	339	156	183	
1-1972	CW	338	155	183	
2	CW	342	159	183	
3	LW-CW	398	61-154	183	61 from 222-S
4	LW-CW	449	112-154	183	52 from 222-S
1-1973	LW-CW	493	156-154	183	44 from 222-S
2	LW-CW	353	90-80	183	16 from 222-S, 4 water, 165 to 107-
3	LW-CW	367	97-87	183	15 from 222-S
4	LW-CW	382	112-87	183	16 from 222-S
1-1974	LW-CW	408	138-87	183	29 from 222-S
2 *	LW-CW	268	61-24	183	29 from 222-S, 168 to 107-U
3	LW-CW	292	85-24	183	24 from 222-S
4	LW-CW	315	108-24	183	26 from 222-S
1-1975	LW-CW	345	138-24	183	30 from 222-S
2	LW-CW-BNW	384	156-24-21	183	18 from 222-S, 21 from BNW
3	---	195	0	195	Tank leaks 225 to 111-U; 5-6 to ground
4	---	175	0	175	Tank leaks
1-1976	---	161	0	161	Tank leaks
2 **	---	161	0	161	Tank leaks
3	---	161	0	161	Inactive leaker
4	---	161	0	161	Inactive leaker
1-1977	---	161	0	161	Inactive leaker
2	---	161	0	161	Inactive leaker
3	---	161	0	161	Inactive leaker
4	---	161	0	161	Inactive leaker

* Dry Wells No.'s 60-10-01, 60-10-05 and 60-10-07 were drilled.

**Dry Wells No.'s 60-10-02 and 60-10-11 were drilled.

9 2 1 2 5 5 6 1 7 2 3

Waste Status Summary of 110-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	-	161	0	161	Primary Leaker Stab. New photo 1-23-78
2-	-	161	0	161	
3-	-	149	0	149	
4-	-	161	0	161	
1-1979	-	161	0	161	
2-	-	161	0	161	
3-	-	161	0	161	New Photo 7-12-79
4-	-	161	0	161	
1-1980	0	161	0	161	
2-	-	161	0	161	
3-	-	161	0	161	
4-	-	161	0	161	

9212356172 4

Waste Status Summary of 111-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	----	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	1C	208	208	---	Cascade began filling April
3	1C	472	472	---	" " " "
4	1C	528	528	---	" " " "
1-1948	1C	528	528	---	Cascade began filling April
2	1C	528	528	---	Cascade full
3	1C	528	528	---	" "
4	1C	528	528	---	" "
1-1949	1C	528	528	---	Cascade full
2	1C	528	528	---	" "
3	1C	528	528	---	" "
4	1C	528	528	---	" "
1-1950	1C	528	528	---	Cascade full
2	1C	528	528	---	" "
3	1C	528	528	---	" "
4	1C	528	528	---	" "
1-1951	1C	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	14	14	---	
3	1C	14	14	---	
4	1C	14	14	---	
1-1953	1C	14	---	14	3 tanks being held as Redox waste reserve
2	1C	17	3	14	
3	1C	15	1	14	
4	1C	15	1	14	Being held for Redox wastes

9 2 1 2 5 5 6 1 7 2 5

Waste Status Summary of 111-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C-R	530	1-515	14	Cascade rec'd Redox concentrated salt waste
2	1C-R	530	1-515	14	
3	1C-R	530	1-515	14	
4	1C-R	530	1-515	14	
1-1955	1C-R	530	1-515	14	
2	1C-R	530	1-515	14	
3	1C-R	530	1-515	14	
4	1C-R	530	1-515	14	
1-1956	1C-R	530	1-515	14	
2	1C-R	519	505	14	
3	1C-R	519	505	14	
4	1C-R	519	504	15	
1-1957	1C-R	519	504	15	
2	1C-R	519	504	15	
3	1C-R	519	504	15	
4	1C-R	519	504	15	
1-1958	1C-R	519	504	15	
2	1C-R	519	504	15	
3	1C-R	519	504	15	
4	1C-R	519	504	15	
1-1959	1C-R	519	504	15	
2	1C-R	519	504	15	
3	1C-R	519	504	15	
4	1C-R	516	501	15	Latest electrode rdg.
1-1960	1C-R	516	501	15	
2	1C-R	516	501	15	
3	1C-R	516	501	15	
4	1C-R	516	501	15	
1-1961	1C-R	516	501	15	
2					6 months
3	1C-R	516	501	15	
4					6 months
1-1962					
2	1C-R	516	501	15	6 months
3					
4	1C-R	516	501	15	6 months
1-1963					
2	1C-R	516	501	15	6 months
3					
4	1C-R	516	501	15	6 months

9 2 1 2 5 6 1 7 2 6

Waste Status Summary of 111-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	1C-R	516	501	15	6 months
3					
4	1C-R	516	501	15	6 months
1-1965	1C-R	530	15-486	29	
2					6 months
3	1C-R	530	0-501	29	
4	1C-R	530	0-501	29	
1-1966	1C-R	530	0-501	29	
2	1C-R	530	0-501	29	
3	1C-R	530	0-501	29	
4	1C-R	530	0-501	29	
1-1967	1C-R	530	0-501	29	
2	1C-R	530	0-501	29	
3	1C-R	530	0-501	29	
4	1C-R	530	0-501	29	
1-1968	1C-R	530	0-501	29	
2	1C-R	530	0-501	29	
3	1C-R	530	0-501	29	
4	R	531	502	29	
1-1969	R	531	502	29	
2	R	530	501	29	
3	R	530	501	29	
4	R	530	504	26	
1-1970	R	530	504	26	
2	R	530	504	26	
3	R	530	504	26	
4	R	147	121	26	383 to 111-U
1-1971	R	148	122	26	
2	R	148	122	26	
3	R	147	121	26	
4	R	148	122	26	
1-1972	R	147	121	26	
2	R	147	121	26	
3	R	149	123	26	
4	R	149	123	26	
1-1973	R	148	122	26	
2	R	148	122	26	
3 *	R	148	122	26	
4	R	148	122	26	

* Dry Well No.'s 60-11-03, 60-11-06 and 60-11-12 were drilled.

9212556172 7

Waste Status Summary of 111-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	R	149	123	26	
2	R	148	122	26	
3 *	R	159	133	26	9 from 301-U catch tank
4	R	158	132	26	
1-1975	R	158	132	26	
2	R	172	146	26	13 from 301-U C.T.
3	BNW-N-DW-LW	343	15-280-18-4	26	275 from 105-U, 990 from 108-U, 225 from 110-U, 1319 to 102-S
4	EB	367	341	26	242-S bottoms & recycle
1-1976	EB	499	473	26	242-S bottoms & recycle, 475 from 106-U; 595 from 102-U
2	EB	499	473	26	242 bottoms & recycle (1)
3	Evap feed	488	462	26	Con. Evap. feed
4	Evap feed	244	218	26	H. SR waste Conc.
1-1977	Evap.	216	80	136	High strontium waste concentration
2	Evap.	450	314	136	Concentrated Evap. feed
3	Resid.	510	349	161	Concentrated evap. feed
4	Evap.Feed	436	201	235	Concentrated evap. feed

(1) Due to the characteristics of solids in the bottoms tanks and the inability to measure them precisely, there is a significant degree of uncertainity in the liquid-to-solid ratio of U Farm tanks.

* Dry Wells No.'s 60-11-05 and 60-11-07 were drilled.

9 2 1 2 5 5 6 1 7 2 8

Waste Status Summary of 111-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	NDRL	420	185	235	Active
2-	PNF	431	50	381	New solids level 4-19-78 New Photo 5-25-78
3-	PNF	421	52	369	New Solids Level 9-11-78
4-	PNF	400	19	381	New Solids Level 11-21-78
1-1979	CPLX	395	14	381	Future Slurry Receiver
2-	PNF	428	47	381	New Photo 5-1-79
3-	CPLX	431	50	381	
4-	PNF	497	116	381	
1-1980	PNF	497	116	381	
2-	PNF	402	21	381	
3-	PNF	328	104	224	New Solids Level 8-13-80
4-	DSSF	311	33	278	New Photo and NewSolids (10-14-80) (10-6-80)

9 2 1 2 1 5 6 1 7 2 9

Waste Status Summary of 112-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	----	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	----	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	1C	162	162	---	Cascade began filling October
1-1948	1C	418	418	---	Cascade began filling October
2	1C	528	528	---	Cascade filled May
3	1C	528	528	---	Cascade full
4	1C	528	528	---	" "
1-1949	1C	528	528	---	Cascade full
2	1C	528	528	---	" "
3	1C	528	528	---	" "
4	1C	528	528	---	" "
1-1950	1C	528	528	---	Cascade full
2	1C	528	528	---	" "
3	1C	528	528	---	" "
4	1C	528	528	---	" "
1-1951	1C	528	528	---	Cascade full
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	1C	32	32	---	
3	1C	32	32	---	
4	1C	32	32	---	
1-1953	1C	32	---	32	3 tanks being held as Redox waste reserve
2	1C	34	2	32	
3	1C	34	2	32	
4	1C	32	0	32	Being held for Redox wastes

9212561730

Waste Status Summary of 112-U Tank Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	1C-R	263	16-215	32	Cascade rec'd. Redox concentrated salt waste
2	1C-R	514	16-466	32	
3	1C-R	514	16-466	32	
4	1C-R	514	16-466	32	
1-1955	1C-R	514	16-466	32	
2	1C-R	514	16-466	32	
3	1C-R	514	16-466	32	
4	1C-R	514	16-466	32	
1-1956	1C-R	509	16-461	32	For Redox ctg. waste
2	1C-R	540	16-482	32	Rec'd from 110-U
3	1C-R	540	16-482	32	
1-1957	1C-R	549	16-501	32	
2	1C-R	549	16-501	32	
3	1C-R	549	16-501	32	Latest electrode rdg.
4					
1-1958	1C-R	549	16-501	32	
2	1C-R	549	16-501	32	
3	1C-R	549	16-501	32	
4	1C-R	549	16-501	32	
1-1959	1C-R	549	16-501	32	
2	1C-R	549	16-501	32	
3	1C-R	549	16-501	32	
4	1C-R	549	16-501	32	
1-1960	1C-R	549	16-501	32	
2	1C-R	549	16-501	32	
3	1C-R	549	16-501	32	
4	1C-R	549	16-501	32	
1-1961					
2	1C-R	549	16-501	32	6 months report
3					
4	1C-R	549	16-501	32	6 months report
1-1962					
2	1C-R	549	16-501	32	6 months report
3					
4	1C-R	549	16-501	32	6 months report
1-1963					
2	1C-R	549	16-501	32	6 months report
3					
4	1C-R	549	16-501	32	6 months report

9212561731

Waste Status Summary of 112-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	1C-R	549	16-501	32	6 months
3					
4	1C-R	549	16-501	32	6 months
1-1965	1C-R	535	2-487	46	6 months
2					
3	1C-R	535	2-487	46	
4	1C-R	535	2-487	46	
1-1966	1C-R	535	2-487	46	
2	1C-R	535	2-487	46	
3	1C-R	535	2-487	46	
4	1C-R	535	2-487	46	
1-1967	1C-R	521	2-473	46	
2	1C-R	519	2-471	46	
3	1C-R	518	2-470	46	
4	1C-R	517	2-469	46	
1-1968	1C-R	514	2-466	46	
2	1C-R	511	2-463	46	
3	1C-R	509	2-461	46	
4	1C-R	507	461	46	
1-1969	1C-R	504	458	46	
2	1C-R	502	456	46	
3	R	500	454	46	
4	R	498	450	48	
1-1970	R	81	33	48	
2	R	80	32	48	
3 *	R	80	32	48	
4	R	80	32	48	
1-1971	R	79	31	48	
2	R	79	31	48	
3	R	79	31	48	
1-1972	R	78	30	48	
2	R	78	30	48	
3	R	77	29	48	
4	R	77	29	48	
1-1973	R	78	30	48	
2	R	76	28	48	
3 **	R	76	28	48	
4	R	76	28	48	

* Dry Wells No.'s 60-12-05, 60-12-07 and 60-12-10 were drilled.
** Dry Well No. 60-12-03 was drilled.

9212561732

Waste Status Summary of 112-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	R	76	16	60	Suspect leaker
2	R	76	16	60	
3 *	R	73	13	60	
4	---	62	0	62	Suspect leaker 23 to 109-U
1-1975	---	51	0	51	Suspect leaker 1 to 109-U
2	---	51	0	51	Removed from service
3	---	51	0	51	Removed from service 4 to 109-U
4	---	51	0	51	Removed from service
1-1976	---	51	0	51	Removed from service
2	R	48	11	37	RFS
3	Evap feed	48	11	37	Inactive SW Pmpg.
4	Evap feed	48	11	37	Inactive SW pmpg.
1-1977	Evap.	48	11	37	Inactive salt well, pump
2	Evap.	48	11	37	Inactive salt well, pump
3		48	11	37	Inactive cur.
4		48	11	37	Inactive cur., salt well installed

* Dry Well No. 60-12-01 was drilled.

9 2 1 2 5 5 6 1 7 3 3

Waste Status Summary of 112-U Tank-Capacity 530,000 Gallons

Qtr.-Year	Type Waste	Total Vol.	Liquid in Storage	Solids in Storage	Remarks
1-1978	EVAP	48	11	37	Questionable Integrity Interim Stabilized
2-	NCPLX	48	11	37	New Photo
3-	NCPLX	36	11	25	
4-	NCPLX	48	11	37	
1-1979	NCPLX	48	11	37	
2-	NCPLX	48	11	37	
3-	NCPLX	48	11	37	
4-	NCPLX	48	11	37	
1-1980	NCPLX	48	2	46	Solid Level Adjusted
2-	NCPLX	48	2	46	
3-	NCPLX	48	2	46	
4-	NCPLX	48	2	46	

9212561734

Waste Status Summary of 204-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	-----	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	----	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	----	---	---	
2	---	---	---	---	Plan overhead filling with TBP waste
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	Held as Redox reserve
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 5 5 6 1 7 3 5

Waste Status Summary of 204-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	R-2C	35	35	---	Diversion box flush material
2	R-2C	35	35	---	" " " "
3	R-2C	35	35	---	" " " "
4	R-2C	35	35	---	" " " "
1-1955	R-2C	35	35	---	Diversion box flush material
2	R-2C	35	35	---	" " " "
3	R-2C	35	35	---	" " " "
4	R-2C	35	35	---	" " " "
1-1956	R-2C	35	35	---	
2	2C-R	53	35-18	---	
3	2C-R	53	35-18	---	
4	2C-R	53	35-18	---	
1-1957	2C-CW	53	35-18	---	
2	2C-CW	51	35-16	---	
3	2C-CW	51	35-16	---	
4	2C-CW	51	35-16	---	
1-1958	2C-CW	51	35-16	0	
2	2C-CW	51	35-16	0	
3	2C-CW	51	35-16	0	
4	2C-CW	51	35-16	0	New electrode rdg.
1-1959	2C-CW	51	35-16	0	
2	2C-CW	51	35-16	0	
3	2C-CW	51	35-16	0	
4	2C-CW	50	35-15	0	Latest electrode rdg.
1-1960	2C-CW	50	35-15	0	
2	2C-CW	50	35-15	0	
3	2C-CW	50	35-15	0	
4	2C-CW	50	35-15	0	
1-1961	2C-CW	50	35-15	0	
2					6 months
3	2C-CW	50	35-15	0	
4					6 months
1-1962					
2	2C-CW	50	35-15	0	6 months
3					
4	2C-CW	50	35-15	0	6 months
1-1963					
2	2C-CW	50	35-15	0	6 months
3					
4	2C-CW	50	35-15	0	6 months

9 2 1 2 5 5 6 1 7 3 6

Waste Status Summary of 204-U Tank Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	2C-CW	50	35-15	0	6 months
3					
4	2C-CW	50	35-15	0	6 months
1-1965	2C-CW	51	35-15	1	6 months
2					
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1966	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1967	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1968	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1969	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1970	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1971	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1972	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1973	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	

9 2 1 2 3 5 6 1 7 3 7

Waste Status Summary of 204-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1975	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	2C-CW	51	35-15	1	
4	2C-CW	51	35-15	1	
1-1976	2C-CW	51	35-15	1	
2	2C-CW	51	35-15	1	
3	Evap feed	51	50	1	Active restricted
4	Evap feed	51	50	1	Active restricted
1-1977	Evap.	51	50	1	R - restricted
2	Evap.	51	50	1	R - restricted
3	Evap.	2	0	2	Inactive cur.
4	Evap.	2	0	2	Inactive cur.
1-1978	-	2	0	2	Inactive-Interim Stab.
2-	-	2	0	2	
3-	NCPLX	2	1	1	Solid Level Adjusted
4-	NCPLX	2	1	1	
1-1979	NCPLX	2	1	1	
2-	NCPLX	2	1	1	
3-	NCPLX	2	1	1	New Solids Level 8-15-79
4-	NCPLX	2	1	1	
1-1980	NCPLX	2	1	1	
2-	NCPLX	2	1	1	
3-	NCPLX	2	1	1	
4-	NCPLX	2	1	1	

9212556173 8

Waste Status Summary of 203-U Tank Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	----	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	Plan overhead filling with TBP wast
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	Held as Redox reserve
2	---	---	---	---	
3	---	---	---	---	
4	---	----	---	---	

9 2 1 2 5 6 1 7 3 9

Waste Status Summary of 203-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1956	R	51	51	0	Rec'd from 110U
2	R	51	51	0	
3	R	51	51	0	
4	R	51	51	0	
1-1958	CW	51	51	0	
2	CW	46	46	0	
3	CW	46	46	0	
4	CW	46	46	0	
1-1958	CW	46	46	0	
2	CW	46	46	0	
3	CW	46	46	0	
4	CW	46	46	0	
1-1959	CW	46	46	0	
2	CW	46	46	0	
3	CW	46	46	0	
4	CW	46	46	0	
1-1960	CW	46	46	0	
2	CW	46	46	0	
3	CW	46	46	0	
4	CW	46	46	0	
1-1961	CW	46	46	0	
2					6 months
3	CW	46	46	0	
4					6 months
1-1962					
2	CW	46	46	0	6 months
3					
4	CW	46	46	0	6 months
1-1962					
2	CW	46	46	0	6 months
3					
4	CW	46	46	0	6 months

9 2 1 2 5 5 6 1 7 4 0

Waste Status Summary of 203-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	CW	46	46	0	6 months
3					
4	CW	46	46	0	6 months
1-1965	CW	46	42	4	6 months
2					
3	CW	46	42	4	
4	CW	46	42	4	
1-1966	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1967	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1968	CW	46	42	4	
2	CW	47	43	4	
3	CW	47	43	4	
4	CW	46	42	4	
1-1969	CW	46	42	4	
2	CW	48	44	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1970	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1971	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1972	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1973	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	

9212161741

Waste Status Summary of 203-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1975	CW	46	42	4	
2	CW	46	42	4	
3	CW	46	42	4	
4	CW	46	42	4	
1-1976	CW	46	42	4	
2	CW	46	42	4	
3	Evap feed	46	42	4	Active restricted
4	evap feed	46	42	4	Active restricted
1-1977	Evap.	46	42	4	R - restricted
2	Evap.	46	42	4	R - restricted
3		4	0	4	Inactive cur.
4		3	0	3	Inactive cur.
1-1978	NCPLX	3	0	3	
2-	NCPLX	3	0	3	
3-	NCPLX	3	1	2	Solid Level Adj.
4-	NCPLX	3	1	2	
1-1979	NCPLX	3	1	2	
2-	NCPLX	3	1	2	
3-	NCPLX	3	1	2	New Solids Level 8-15-79 New Photo 7-3-79
4-	NCPLX	3	1	2	
1-1980	NCPLX	3	1	2	
2-	NCPLX	3	1	2	
3-	NCPLX	3	1	2	
4-	NCPLX	3	1	2	

9 2 1 2 5 5 6 1 7 4 2

Waste Status Summary of 202-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---	---	---	
2	---	---	---	---	Plan overhead filling with TBP wast
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	Held as Redox reserve
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 5 6 1 7 3

Waste Status Summary of 202-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1956	R	51	51	---	Rec'd from 110-U
2	R	51	51	---	
3	R	51	51	---	
4	R	51	51	---	
1-1957	CW	51	51	---	
2	CW	48	48	---	Latest electrode rdg.
3	CW	48	48	---	
4	CW	48	48	---	
1-1958	CW	48	48	0	
2	CW	48	48	0	
3	CW	48	48	0	
4	CW	51	51	0	New electrode rdg.
1-1959	CW	51	51	0	
2	CW	51	51	0	
3	CW	51	51	0	
4	CW	51	51	0	
1-1960	CW	51	51	0	
2	CW	51	51	0	
3	CW	51	51	0	
4	CW	51	51	0	
1-1961	CW	51	51	0	
2					6 months
3	CW	51	51	0	
4					6 months
1-1962					
2	CW	51	51	0	6 months
3					
4	CW	51	51	0	6 months
1-1963					
2	CW	51	51	0	6 months
3					
4	CW	51	51	0	6 months

9 2 1 2 5 5 6 1 7 4 4

Waste Status Summary of 202-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	CW	51	51	0	6 months
3					
4	CW	51	51	0	6 months
1-1965	CW	51	47	4	
2					6 months
3	CW	51	47	4	
4	CW	51	47	4	
1-1966	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1967	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1968	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1969	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1970	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1971	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1972	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1973	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	

9 2 1 2 1 5 6 1 7 4 5

Waste Status Summary of 202-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1975	CW	51	47	4	
2	CW	51	47	4	
3	CW	51	47	4	
4	CW	51	47	4	
1-1976	CW	51	47	4	
2	CW	51	47	4	
3	Evap. feed	51	47	4	Activity restricted
4	Evap feed	51	47	4	Activity restricted
1-1977	Evap.	51	47	4	R - restricted
2	Evap.	51	47	4	R - restricted
3	Evap.	4	0	4	Inactive cur.
4	Evap.	4	0	4	Inactive cur.
1-1978	NCPLX	4	0	4	Inactive-Interim Stabilized
2-	NCPLX	4	0	4	
3-	NCPLX	4	1	3	Solid Level Adjusted
4-	NCPLX	4	1	3	
1-1979	NCPLX	4	1	3	
2-	NCPLX	4	1	3	
3-	NCPLX	4	1	3	New Solids Level 8-15-79
4-	NCPLX	4	1	3	
1-1980	NCPLX	4	1	3	
2-	NCPLX	4	1	3	
3-	NCPLX	5	1	4	Solids Level Adjusted
4-	NCPLX	5	1	4	

9 2 1 2 5 6 1 7 1 6

Waste Status Summary of 201-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1944	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1945	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1946	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1947	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1948	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1949	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1950	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1951	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1952	---	---			
2	---	---	---	---	Plan overhead filling with TBP wast
3	---	---	---	---	
4	---	---	---	---	
1-1953	---	---	---	---	Held as Redox reserve
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	

9 2 1 2 5 5 6 1 7 4 7

Waste Status Summary of 201-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1954	---	---	---	---	
2	---	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1955	---	---	---	---	
2	----	---	---	---	
3	---	---	---	---	
4	---	---	---	---	
1-1956	R	48	48	---	
2	R	48	48	---	
3	R	48	48	---	
4	R	48	48	---	
1-1957	CW	48	48	---	
2	CW	48	48	---	
3	CW	48	48	---	
4	CW	48	48	---	
1-1958	CW	48	48	0	
2	CW	48	48	0	
3	CW	48	48	0	
4	CW	49	49	0	New electrode rdg.
1-1959	CW	49	49	0	
2	CW	49	49	0	
3	CW	49	49	0	
4	CW	49	49	0	
1-1960	CW	49	49	0	
2	CW	49	49	0	
3	CW	49	49	0	
4	CW	49	49	0	
1-1961	CW	49	49	0	
2					6 months
3	CW	49	49	0	
4					6 months
1-1962					
2	CW	49	49	0	6 months
3					
4	CW	49	49	0	6 months
1-1963					
2	CW	49	49	0	6 months
3					
4	CW	49	49	0	6 months

9 2 1 2 5 5 6 1 7 4 8

Waste Status Summary of 201-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1964					
2	CW	49	49	0	6 months
3					
4	CW	49	49	0	6 months
1-1965	CW	48	44	4	
2					6 months
3	CW	48	44	4	
4	CW	48	44	4	
1-1966	CW	48	44	4	
2	CW	48	44	4	
3	CW	48	44	4	
4	CW	48	44	4	
1-1967	CW	48	44	4	
2	CW	48	44	4	
3	CW	48	44	4	
4	Cw	48	44	4	
1-1968	CW	48	44	4	
2	CQ	48	44	4	
3	CW	48	44	4	
4	CW	49	45	4	
1-1969	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1970	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1971	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1972	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1973	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	

9212556174 9

Waste Status Summary of 201-U Tank-Capacity 55,000 Gallons

Qtr.-Year	Type Waste	Total Volume	Liquid in Storage	Solids in Storage	Remarks
1-1974	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1975	CW	49	45	4	
2	CW	49	45	4	
3	CW	49	45	4	
4	CW	49	45	4	
1-1976	CW	49	45	4	
2	CW	49	45	4	
3	Evap. feed	49	45	4	
4	Evap. feed	49	45	4	Active Restricted
1-1977	Evap.	49	45	4	Active restricted
2	Evap.	49	4	45	
3	Evap.	4	0	4	Inactive cur.
4	Evap.	4	0	4	Inactive cur.
1-1978	NCPLX	4	0	4	
2-	NCPLX	4	0	4	
3-	NCPLX	4	1	3	Solid Level Adjusted
4-	NCPLX	4	1	3	
1-1979	NCPLX	4	1	3	
2-	NCPLX	4	1	3	
3-	NCPLX	4	1	3	New Solids Level 8-15-79
4-	NCPLX	4	1	3	
1-1980	NCPLX	4	1	3	
2-	NCPLX	4	1	3	
3-	NCPLX	5	1	4	
4-	NCPLX	5	1	4	

9 2 1 2 5 6 1 7 5 0