S 0049683

ENGINEERING CHANGE NOTICE

Page 1 of 2

1. ECN 644488

Proj. ECN

2. ECN Category (mark one)	3. Originator's Name, Organization, MSIN, and Telephone No.	4. USQ Required?	5. Date
Supplemental [] Direct Revision [X] Change ECN ~~[X]~~ Temporary [] Standby [] Supersedure [] Cancel/Void []	M. J. Kupfer, LMHC, H5-49, 376-6631	[] Yes [X] No	7/15/98
	6. Project Title/No./Work Order No. Tank 241-SY-101	7. Bldg./Sys./Fac. No. NA	8. Approval Designator NA
	9. Document Numbers Changed by this ECN (includes sheet no. and rev.) WHC-SD-WM-ER-409, Rev. ~~0B~~ 0A	10. Related ECN No(s). NA	11. Related PO No. NA

12a. Modification Work	12b. Work Package No.	12c. Modification Work Complete	12d. Restored to Original Condition (Temp. or Standby ECN only)
[] Yes (fill out Blk. 12b) [X] No (NA Blks. 12b, 12c, 12d)	NA	NA Design Authority/Cog. Engineer Signature & Date	NA Design Authority/Cog. Engineer Signature & Date

13a. Description of Change

13b. Design Baseline Document? [] Yes [X] No

This ECN compiles all reconciliation changes to the Best-Basis Inventory made in FY98. Revisions were made to Appendix G, Evaluation to Establish Best-Basis Inventory for Double-Shell Tank 241-SY-101. Changes were made to both text and tables. The inventory estimates of several waste components were revised. The reconciliation process involved correction of errata, reassessment of data outlyers, verification of uranium isotopic distribution and other alpha isotope distribution, and removal of "less than" values, etc. This ECN replaces Appendix G.

14a. Justification (mark one)

Criteria Change	[]	Design Improvement	[]	Environmental	[]	Facility Deactivation	[]
As-Found	[X]	Facilitate Const	[]	Const. Error/Omission	[]	Design Error/Omission	[]

14b. Justification Details

Tank waste inventory estimates are being provided as standard source term for the various waste management activities. FY 1997 evaluation of available information for all 177 underground storage tanks was performed and published in TCRs, preliminary TCRs, or revisions to existing TCRs. In FY 1998, a reconciliation process is being performed to update the best-basis inventories. This process ensures that the latest inventory estimates are available as a consistent source-term to support the activities of TWRS disposal and other users.

15. Distribution (include name, MSIN, and no. of copies)

See distribution sheet.

Central Files	B1-07
DIMC	H6-15
DOE Reading Room	H2-53
TCSRC	R1-10
K. M. Hall	R2-12
K. M. Hodgson	R2-11
M. J. Kupfer	H5-49
M. D. LeClair (3)	H5-49
N. E. Wilkins	R2-12

SEP 1998 RECEIVED EDMC

RELEASE STAMP

JUL 23 1998 DATE: HANFORD RELEASE STA: 37 ID. 73

A-7900-013-2 (05/96) GEF095

A-7900-013-1

ENGINEERING CHANGE NOTICE

1. ECN (use no. from pg. 1): 644488

16. Design Verification Required	17. Cost Impact				18. Schedule Impact (days)	
	ENGINEERING		CONSTRUCTION			
[] Yes	Additional	[] $	Additional	[] $	Improvement	[]
[X] No	Savings	[] $	Savings	[] $	Delay	[]

19. Change Impact Review: Indicate the related documents (other than the engineering documents identified on Side 1) that will be affected by the change described in Block 13. Enter the affected document number in Block 20.

SDD/DD	[]	Seismic/Stress Analysis	[]	Tank Calibration Manual	[]
Functional Design Criteria	[]	Stress/Design Report	[]	Health Physics Procedure	[]
Operating Specification	[]	Interface Control Drawing	[]	Spares Multiple Unit Listing	[]
Criticality Specification	[]	Calibration Procedure	[]	Test Procedures/Specification	[]
Conceptual Design Report	[]	Installation Procedure	[]	Component Index	[]
Equipment Spec.	[]	Maintenance Procedure	[]	ASME Coded Item	[]
Const. Spec.	[]	Engineering Procedure	[]	Human Factor Consideration	[]
Procurement Spec.	[]	Operating Instruction	[]	Computer Software	[]
Vendor Information	[]	Operating Procedure	[]	Electric Circuit Schedule	[]
OM Manual	[]	Operational Safety Requirement	[]	ICRS Procedure	[]
FSAR/SAR	[]	IEFD Drawing	[]	Process Control Manual/Plan	[]
Safety Equipment List	[]	Cell Arrangement Drawing	[]	Process Flow Chart	[]
Radiation Work Permit	[]	Essential Material Specification	[]	Purchase Requisition	[]
Environmental Impact Statement	[]	Fac. Proc. Samp. Schedule	[]	Tickler File	[]
Environmental Report	[]	Inspection Plan	[]	Other	[X]
Environmental Permit	[]	Inventory Adjustment Request	[]		[]

20. Other Affected Documents: (NOTE: Documents listed below will not be revised by this ECN.) Signatures below indicate that the signing organization has been notified of other affected documents listed below.

Document Number/Revision	Document Number/Revision	Document Number Revision

21. Approvals

	Signature	Date		Signature	Date
Design Authority			Design Agent		
Cog. Eng.	M. J. Kupfer JW Cammann for	7/21/98	PE		
Cog. Mgr.	K. M. Hodgson K.M. Hodgson	7-20-98	QA		
QA			Safety		
Safety			Design		
Environ.			Environ.		
Other	N. E. Wilkins R2-12 N.E. Wilkins	7/20/98	Other		

DEPARTMENT OF ENERGY

Signature or a Control Number that tracks the Approval Signature

ADDITIONAL

S

WHC-SD-WM-ER-409, Rev. 0B

Tank Characterization Report for Double-Shell Tank 241-SY-101

S. L. Lambert
COGEMA Engineering Corporation, Richland, WA 99352
U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 644488 UC: 721
Org Code: 7A110 Charge Code: N4G3A
B&R Code: EW3120074 Total Pages:

Key Words: TCR, best-basis inventory, standard inventory

Abstract: The best-basis inventory provides waste inventory estimates that serve as standard characterization source terms for the various waste management activities. To establish a best-basis inventory for double-shell tank 241-SY-101, an evaluation of available information was performed. This work follows the methodology established in *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0A (Kupfer et al. 1997).

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

JUL 23 1998
DATE:
HANFORD RELEASE
STA: 37
ID. 73

Release Approval — Date 7/23/98 — Release Stamp

Approved for Public Release

RECORD OF REVISION	(1) Document Number WHC-SD-WM-ER-409	Page 1

(2) Title
Tank Characterization Report for Double-Shell Tank 241-SY-101

CHANGE CONTROL RECORD

(3) Revision	(4) Description of Change - Replace, Add, and Delete Pages	Authorized for Release (5) Cog. Engr.	(6) Cog. Mgr. Date
0	(7) Initially released 08/03/95 on EDT 613104.	D. L. Herting	J. G. Kristofzski
0A RS	Incorporate per ECN-643406.	M. J. Kupfer	K. M. Hodgson
		M J Kupfer 8-20-97	K M Hodgson 8-19-97
			K. M. Hodgson
0B RS	Incorporate per ECN-644488	M.J. Kupfer	K.M. Hodgson 7/20/98
		7/21/98 JW Cammann for	

A-7320-005 (08/91) WEF168

APPENDIX G

EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR DOUBLE-SHELL TANK 241-SY-101

This page intentionally left blank.

APPENDIX G

EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR DOUBLE-SHELL TANK 241-SY-101

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for the double-shell tank 241-SY-101 was performed, and a best-basis inventory was established. This work, detailed in the following sections, follows the methodology that was established by the standard inventory task.

G1.0 CHEMICAL INFORMATION SOURCES

Available waste (chemical) information for tank 241-SY-101 includes:

- The information included in Sections 2.0, 3.0, 4.0 and 5.0 of this tank characterization report (TCR) for DST 241-SY-101 on tank history, sampling, analyses, and data evaluation.
- Internal memo on the statistical analysis of tank 241-SY-101 data (Welsh 1995).
- Inventory estimates for this tank that were generated from the Hanford Defined Waste (HDW) model (Agnew et al. 1997a).

A list of references used in this evaluation is provided in Section G5.0.

G2.0 COMPARISON OF COMPONENT INVENTORY VALUES

Tank 241-SY-101 is one of three tanks making up the SY Tank Farm in the 200 West Area. Two of the three tanks in this farm (tanks 241-SY-101 and 241-SY-103) were filled in the 1977 to 1980 time frame with a mixture of highly concentrated double-shell slurry and complexant concentrate from B Plant cesium and strontium recovery campaigns. The B Plant processes introduced high concentrations of organic compounds to the waste. Both tanks have exhibited gas production and periodic gas release. Periodic gas releases have led to cyclic

changes in the waste volume in the tanks. Safety concerns about the gas release phenomenon have led to extensive characterization of the waste materials in tank 241-SY-101 and to a lesser extent tank 241-SY-103.

The HDW model inventory estimates for tank 241-SY-101 are listed in Tables G2-1 and G2-2. Also included in Tables G2-1 and G2-2 are tank inventory estimates based on analytical data. The chemical species are reported without charge designation per the best-basis inventory convention. Tank inventories are based on a liquid inventory of 2,300 kL (608 Kgal), a non-convective layer (solids) inventory of 1,670 kL (442 Kgal) and crust inventory of 220 kL (58 Kgal).

Table G2-1. Hanford Defined Waste Model-Based and Sample-Based Inventory Estimates for Nonradioactive Components in Tank 241-SY-101.

Analyte	Analytical-based inventory estimates[b] (kg)	HDW inventory estimate[a] (kg)	Analyte	Analytical-based inventory estimates[b] (kg)	HDW inventory estimate[a] (kg)
Al	219,000	239,000	Ni	1,030	2,100
Bi	NR	1,580	NO_2	744,000	605,000
Ca	2,410	7,570	NO_3	850,000	1.69 E+06
Cl	56,300	47,300	OH	149,000	904,000
Cr	24,600	40,300	Pb	NR	1,160
F	NR	7,080	PO_4	44,600	80,700
Fe	2,080	3,430	Si	NR	12,300
Hg	NR	10.3	SO_4	26,600	133,000
K	22,800	14,100	TIC as CO_3	252,000	150,000
Mn	NR	1,190	TOC	104,000	77,500
Na	1.39 E+06	1.77 E+06	U_{TOTAL}	265	12,900
H_2O (Wt%)	35.0	21.3	Zr	NR	128
			Density (g/mL)	1.61	1.79

HDW = Hanford Defined Waste
NR = not reported
[a] Agnew et al. (1997a)
[b] From Table 4-3 Tank 241-SY-101. Estimated Chemical Concentration and Inventory in this Tank Characterization Report.

Table G2-2. Hanford Defined Waste Model-Based and Sample-Based Inventory Estimates for Radioactive Components in Tank 241-SY-101.[a]

Analyte	Analytical Based Inventory Estimates[b] (Ci)	HDW Inventory Estimate[c] (Ci)	Analyte	Analytical Based Inventory Estimates[b] (Ci)	HDW Inventory Estimate[c] (Ci)
^{90}Sr	125,000	6.83 E+05	^{137}Cs	2.21 E+06	1.54 E+06
$^{239/240}Pu$	46.6	1,450	^{241}Am	635	345
^{99}Tc	1,460	1,450			

HDW = Hanford Defined Waste
[a] Radionuclides decayed to January 1, 1994
[b] From Table 4-3 in this Tank Characterization Report
[c] Agnew et al. (1997a).

G3.0 COMPONENT INVENTORY EVALUATION

The following evaluation was conducted to assess various estimates of tank contents.

G3.1 WASTE HISTORY FOR TANK 241-SY-101

The waste transfer history for tank 241-SY-101 is documented in Section 2.3.1 of this TCR. Tank 241-SY-101 began receiving double-shell slurry (DSS) waste (1,044 kL 276 kgal]) in April 1977 from the 242-S Evaporator. Between November 1977 and August 1978 the tank received complexant concentrate waste (2,112 kL [558 kgal]) from B Plant cesium and strontium recovery processes. The tank received 874 kL (231 kgal) of DSS from the 242-S Evaporator in October 1980. The tank received 30 kL (8 kgal) of water from water-lancing operations in the mid-1980's. A more detailed transfer history for this tank is available from Agnew et al. (1997b).

Shortly after the first waste was added to tank 241-SY-101, the waste began to exhibit slurry growth. The phenomenon involves the generation and retention of gases within the slurry, causing an increase in the overall waste volume with episodic gas releases. Slurry growth continued to be observed after the last waste additions in 1980. Concern over the slurry growth and episodic gas releases was heightened in 1989, when it was recognized that the gases generated and released included a mixture of hydrogen and nitrous oxide, a flammable and potentially explosive mixture. Extensive waste characterization activities were

initiated in this tank to address safety issues. In 1993, a mixing pump was installed in tank 241-SY-101 which has controlled the release of gases from the waste.

G3.2 EXPECTED TYPE OF WASTE BASED ON THIS ASSESSMENT

Agnew et al. (1997a) lists the waste volume as 4,160 kL (1,100 kgal). Hanlon (1997) lists the waste volume as 4,213 kL (1,113 kgal). Prior to the installation of a mixing pump in 1993, the surface level of this tank varied as a function of time because of the gas accumulation phenomenon. Prior to pump installation, the occupied volume of the waste in this tank increased with the gas accumulation and decreased when the gas was vented. Figure 2.4 in this TCR illustrates the cyclic changes of slurry growth and gas release events in tank 241-SY-101.

Agnew et al. (1997b) identifies the waste as being 2,120 kL (560 kgal) of Supernatant Mixing Model from 242-S Evaporator (salt cake generated from 1977 to 1980 [SMMS2]) solids and 2,044 kL (540 kgal) of liquids. Hanlon (1997) identifies the waste as being 155 kL (41 kgal) of sludge, and 4,058 kL (1,072 kgal) of supernatant liquids. This TCR used data from tank sampling events in 1990 and 1991 to estimate the convective (i.e., liquid) layer to be 2,300 kL (608 kgal), the non-convective (i.e., solids) layer to be 1,670 kL (442 kgal) and the crust to be 220 kL (58 kgal) (Section 4.1 of this Tank Characterization Report). The volumes developed in the TCR were used to develop tank inventory estimates.

Based on process history, tank 241-SY-101 would be expected to contain large quantities of organic complexing agents from the complexant concentrate. The tank would also be expected to contain large quantities of aluminum, sodium, hydroxide, nitrite, and nitrate from the DSS.

G3.3 BASIS FOR CALCULATIONS USED IN THIS ENGINEERING EVALUATION

The general approach of an engineering assessment is to utilize all available information to formulate the best-basis estimate of the tank's contents. The sources of information may include analytical data from samples taken from the tank of interest, analytical data from other tanks believed to contain waste types similar to those believed to be in the tank of interest, and data from models utilizing historical process records. The confidence level assigned to the best-basis inventory values then depends on the level of agreement among the various information sources.

Since 1980, the surface level in tank 241-SY-101 (and also in tank 241-SY-103) was observed to periodically rise and fall. This behavior was attributed to the accumulation of hydrogen and other gases in the non-convecting layer in the tank. When it was realized that a potentially significant safety issue was associated with the levels of reactive gases being

periodically vented from the two SY tank farm tanks, a focused characterization effort was initiated. (Details of the safety issue are discussed elsewhere in this TCR.) The waste characterization efforts for tank 241-SY-101 are detailed in sections 4.0 and 5.0 of this TCR.

To address the very serious safety issues that had been raised by the gas venting episodes in tank 241-SY-101, the tank was sampled a number of times in 1990 and 1991. The sampling events followed separate releases of accumulated gases. In November 1990, three crust samples were obtained from the tank. In May 1991, eight crust samples and a core sample consisting of 26 segments were taken. In December 1991, a second core sample was taken from a separate riser. The analyses of these samples and the data interpretation received extensive oversight from both internal U.S. Department of Energy (DOE) and external technical reviewers. The rigor of the tank sampling efforts and the analytical characterization data generated from the samples taken from tank 241-SY-101 represent the highest quality that were available from the Hanford Site staff. For this reason these data are used as the best-basis for estimating the tank inventory.

The estimated composition for each of the three layers in tank 241-SY-101 are reported in Section 4.0, Table 4-2 of this TCR. The tank inventory estimates are shown in Section 4.0, Table 4-3. Appendix A of this TCR contains the data from physical, chemical, and radiological characterization of window C and E core samples. Considerably more analytical data are included in Appendix A than is summarized in Tables 4-2 and 4-3. Tables 4-2 and 4-3 only include the analytes where sufficient data were available for calculation of a tank inventory estimate. However, many analyses were completed on selected sample splits. In such cases, there were insufficient data to develop a tank inventory estimate.

This page intentionally left blank.

G4.0 DEFINE THE BEST-BASIS AND ESTABLISH COMPONENT INVENTORIES

Information about chemical, radiological, and/or physical properties is used to perform safety analyses, engineering evaluations, and risk assessments associated with waste management activities, as well as regulatory issues. These activities include overseeing tank farm operations and identifying, monitoring, and resolving safety issues associated with these operations and with the tank wastes. Disposal activities involve designing equipment and facilities for retrieving wastes and processing them into a form that is suitable for long-term storage or disposal.

Chemical and radiological inventory information are generally derived using three approaches: (1) component inventories are estimated using results of sample analyses, (2) component inventories are estimated using the HDW model-based on process knowledge and historical information, or (3) a tank-specific process estimate is made based on process flowsheets, reactor fuel data, essential material usage, and other operating data. The information derived from these different approaches is often inconsistent.

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for tank 241-SY-101 was performed. An assessment of available chemical information for tank 241-SY-101 was performed, including the following:

- The information in Sections 2.0, 3.0, 4.0 and 5.0 of this TCR for tank 241-SY-101 history, sampling, analyses, and data evaluation.
- Internal memo on the statistical analysis of tank 241-SY-101 data (Welsh 1995).
- Inventory estimates for this tank that were generated from the HDW model (Agnew et al. 1997a).

Based on this engineering assessment, a best-basis inventory was developed for tank 241-SY-101 using concentration data developed in this TCR, when available, or the HDW model tank inventory estimates reported by Agnew et al. (1997a). Because of the intense interest in understanding the composition of the wastes in this tank stemming from serious safety concerns, the characterization data are considered to be the most reliable available for any tank at Hanford.

Best-basis tank inventory values are derived for 46 key radionuclides (as defined in Section 3.1 of Kupfer et al. 1997), all decayed to a common report date of January 1, 1994. Often, waste sample analyses have only reported ^{90}Sr, ^{137}Cs, $^{239/240}Pu$, and total uranium (or total beta and total alpha), while other key radionuclides such as ^{60}Co, ^{99}Tc, ^{129}I, ^{154}Eu, ^{155}Eu, and ^{241}Am, etc., have been infrequently reported. For this reason it has been necessary to

derive most of the 46 key radionuclides by computer models. These models estimate radionuclide activity in batches of reactor fuel, account for the split of radionuclides to various separations plant waste streams, and track their movement with tank waste transactions. (These computer models are described in Kupfer et al. 1997, Section 6.1 and in Watrous and Wootan 1997.) Model generated values for radionuclides in any of 177 tanks are reported in the HDW Rev. 4 model results (Agnew et al. 1997a). The best-basis value for any one analyte may be either a model result or a sample or engineering assessment-based result if available. For a discussion of typical error between model derived values and sample derived values, see Kupfer et al. 1997, Section 6.1.10. The uranium isotopic values are based on the total uranium inventory, with appropiate corrections derived from the uranium isotopic ratios in the HDW model.

Once the best-basis inventories were determined, the hydroxide inventory was calculated by performing a charge balance with valences of other analytes. This charge balance approach is consistent with that used by Agnew et al. (1997a).

Best-basis inventory values for tank 241-SY-101 are reported in Tables G4-1 and G4-2. The inventory values are subject to change. Refer to the Tank Characterization Database (TCD) for the most current inventory values.

Table G4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-SY-101 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (kg)	Basis (S, M, or C)[1]	Comment
Al	219,000	S	
Bi	0	E	Bi is relatively insoluble. Solubilities used in HDW were not correct
Ca	2,410	S	
Cl	56,300	S	
TIC as CO_3	252,000	S	
Cr	24,600	S	
F	7,080	M	
Fe	2,080	S	
Hg	0	E	Hg associated with coating wastes which were not introduced to this tank
K	22,800	S	
La	0	E	La is relatively insoluble in the supernates added to tank 241-SY-101
Mn	1,190	M	
Na	1.39 E+06	S	
Ni	1,030	S	
NO_2	744,000	S	
NO_3	850,000	S	
OH_{TOTAL}	702,000	C	
Pb	1,160	M	
PO_4	44,600	S	IC analysis
Si	12,300	M	
SO_4	26,600	S	IC analysis
Sr	1.8	E	Assume 50% of Sr consists of ^{90}Sr
TOC	104,000	S	Expected to decrease due to radiolytic decomposition

Table G4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-SY-101 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (kg)	Basis (S, M, or C)[1]	Comment
U_{TOTAL}	265	S	
Zr	128	M	

[1]S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

C = Calculated by charge balance; includes oxides as hydroxide not including CO_3, NO_2, NO_3, PO_4, SO_4, and SiO_3.

Table G4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-SY-101 Decayed to January 1, 1994 (Effective May 31, 1997). (3 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E)[1]	Comment
^{3}H	1,380	M	
^{14}C	204	M	
^{59}Ni	13	M	
^{60}Co	228	M	
^{63}Ni	1,280	M	
^{79}Se	20.3	M	
^{90}Sr	125,000	S	
^{90}Y	125,000	S	Referenced to ^{90}Sr
^{93}Zr	99.5	M	
^{93m}Nb	72.1	M	
^{99}Tc	1,460	S	
^{106}Ru	0.0416	M	
^{113m}Cd	526	M	
^{125}Sb	989	M	
^{126}Sn	30.6	M	
^{129}I	2.79	M	
^{134}Cs	16.8	M	
^{137}Cs	2.21 E+06	S	
^{137m}Ba	2.09 E+06	S	Referenced to ^{137}Cs
^{151}Sm	71,400	M	
^{152}Eu	24.6	M	
^{154}Eu	3,730	M	
^{155}Eu	1,460	M	
^{226}Ra	8.54 E-04	M	
^{227}Ac	0.00542	M	
^{228}Ra	0.865	M	
^{229}Th	0.0203	M	
^{231}Pa	0.025	M	
^{232}Th	0.0584	M	

Table G4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-SY-101 Decayed to January 1, 1994 (Effective May 31, 1997). (3 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E)[1]	Comment
^{232}U	0.090	M/S	Based on U (total): Used HDW isotopic ratios
^{233}U	0.346	M/S	Based on U (total): Used HDW isotopic ratios
^{234}U	0.0974	M/S	Based on U (total): Used HDW isotopic ratios
^{235}U	0.00395	M/S	Based on U (total): Used HDW isotopic ratios
^{236}U	3.07E-03	M/S	Based on U (total): Used HDW isotopic ratios
^{237}Np	5.24	M	
^{238}Pu	1.17	M/S	Based on ^{239}Pu: Used HDW isotopic ratios
^{238}U	0.0884	M/S	Based on U (total): Used HDW isotopic ratios
^{239}Pu	39.8	M/S	Based on $^{239/240}Pu$: Used HDW isotopic ratios
^{240}Pu	6.78	M/S	Based on $^{239/240}Pu$: Used HDW isotopic ratios
^{241}Am	633	S	
^{241}Pu	79.6	S/M	Based on ^{239}Pu: Used HDW isotopic ratios
^{242}Cm	1.72	S/M	Based on ^{241}Am: Used HDW isotopic ratios
^{242}Pu	4.38E-04	S/M	Based on ^{239}Pu: Used HDW isotopic ratios
^{243}Am	0.0226	S/M	Based on ^{241}Am: Used HDW isotopic ratios

Table G4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-SY-101 Decayed to January 1, 1994 (Effective May 31, 1997). (3 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E)[1]	Comment
^{243}Cm	0.16	S/M	Based on ^{241}Am: Used HDW isotopic ratios
^{244}Cm	1.54	S/M	Based on ^{241}Am: Used HDW isotopic ratios

[1]S = Sample-based
M = Hanford Defined Waste model-based, Agnew et al. (1997a)
E = Engineering assessment-based.

This page intentionally left blank.

G5.0 APPENDIX G REFERENCES

Agnew, S. F., J. Boyer, R. A. Corbin, T. B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997a, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev. 4*, LA-UR-96-3860, Los Alamos National Laboratory, Los Alamos, New Mexico.

Agnew, S. F., R. A. Corbin, T. B. Duran, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997b, *Waste Status and Transaction Record Summary (WSTRS, Rev. 4)*, LA-UR-97-311, Los Alamos National Laboratory, Los Alamos, New Mexico.

Hanlon, B. M., 1997, *Waste Tank Summary Report for Month Ending February 28, 1997*, HNF-EP-0182-107, Lockheed Martin Hanford Corporation, Richland, Washington.

Hodgson, K. M, and M. D. LeClair, 1996, *Work Plan for Defining a Standard Inventory Estimate for Wastes Stored in Hanford Site Underground Tanks*, WHC-SD-WM-WP-311, Rev. 1, Lockheed Martin Hanford Corp., Richland, Washington.

Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, B. C. Simpson, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W^2S Corporation), 1997, *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0A, Lockheed Martin Hanford Corporation, Richland, Washington.

Watrous, R. A., and D. W. Wootan, 1997, *Activity of Fuel Batches Processed Through Hanford Separations Plants, 1944 Through 1989*, HNF-SD-WM-TI-794, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

Welsh, T. L, 1995, *Statistical Analysis of Tank 241-SY-101 Data*, Internal Memo 75980-PCS95-063, Westinghouse Hanford Company, Richland, Washington.

This page intentionally left blank.