

2. To: (Receiving Organization) Distribution	3. From: (Originating Organization) Geoscience Group 81234	4. Related EDT No.:
5. Proj./Prog./Dept./Div.: Environmental Restoration Org. #81234	6. Cog. Engr.: K. A. Bergstrom/ T. H. Mitchell	7. Purchase Order No.:
8. Originator Remarks: Document approved and released		9. Equip./Component No.:
11. Receiver Remarks:		10. System/Bldg./Facility:
		12. Major Assm. Dwg. No.:
		13. Permit/Permit Application No.:
		14. Required Response Date:

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Impact Level	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	WHC-SD-EN-TI-117		0	Ground Penetrating Radar Investigation for Riverland ERA	4	1/2	1	

16. KEY		
Impact Level (F)	Reason for Transmittal (G)	Disposition (H) & (I)
1, 2, 3, or 4 (see MRP 5.43)	1. Approval 2. Release 3. Information 4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)	1. Approved 2. Approved w/comment 3. Disapproved w/comment 4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Impact Level for required signatures)												
(G)	(H)	(J) Name (K) Signature (L) Date (M) MSIN				(J) Name (K) Signature (L) Date (M) MSIN				(G)	(H)	
Reason	Disp.									Reason	Disp.	
1	1	Cog. Eng. K.A. Bergstrom	<i>K.A. Bergstrom</i>	66-50	T.H. MITCHELL				66-50	3		
1	1	Cog. Mgr. K.R. Fecht	<i>K.R. Fecht</i>	66-06	G.C. HENCKEL				66-04	3		
		QA			J. FASSETT				66-06	3		
		Safety			CENTRAL FILES (2)				68-04	3		
3		Env. R.J. VALCICH		66-04	EDMC (2)				66-08	3		
3		C.E. HEIDEN		66-04	ERC				66-07	3		

18. <i>K.A. Bergstrom</i> K.A. BERGSTROM Signature of EDT Originator Date: 3-25-93	19. _____ Authorized Representative for Receiving Organization Date: _____	20. <i>K.R. Fecht</i> K.R. FECHT Cognizant/Project Engineer's Manager Date: 3/23/93	21. DOE APPROVAL (if required) Ltr. No. _____ <input type="checkbox"/> Approved <input type="checkbox"/> Approved w/comments <input type="checkbox"/> Disapproved w/comments
---	--	--	--

73129701641



**THIS PAGE INTENTIONALLY
LEFT BLANK**



Complete for all Types of Release

Purpose <input type="checkbox"/> Speech or Presentation <input type="checkbox"/> Full Paper (Check only one suffix) <input type="checkbox"/> Summary <input type="checkbox"/> Abstract <input type="checkbox"/> Visual Aid <input type="checkbox"/> Speakers Bureau <input type="checkbox"/> Poster Session <input type="checkbox"/> Videotape		<input type="checkbox"/> Reference <input checked="" type="checkbox"/> Technical Report <input type="checkbox"/> Thesis or Dissertation <input type="checkbox"/> Manual <input type="checkbox"/> Brochure/Flier <input type="checkbox"/> Software/Database <input type="checkbox"/> Controlled Document <input type="checkbox"/> Other
ID Number (include revision, volume, etc.) WHC-SD-EN-TI-117, Rev.0		
List attachments.		
Date Release Required <p align="center">4/1/93</p>		

Title Ground Penetrating Radar Investigation for Riverland ERA	Unclassified Category UC-	Impact Level 4
---	-------------------------------------	-----------------------

New or novel (patentable) subject matter? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If "Yes", has disclosure been submitted by WHC or other company? <input type="checkbox"/> No <input type="checkbox"/> Yes Disclosure No(s).	Information received from others in confidence, such as proprietary data, trade secrets, and/or inventions? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (Identify)
---	---

Copyrights? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If "Yes", has written permission been granted? <input type="checkbox"/> No <input type="checkbox"/> Yes (Attach Permission)	Trademarks? <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes (Identify)
---	---

Complete for Speech or Presentation

Title of Conference or Meeting N/A	Group or Society Sponsoring N/A
Date(s) of Conference or Meeting	City/State
Will proceedings be published? <input type="checkbox"/> Yes <input type="checkbox"/> No Will material be handed out? <input type="checkbox"/> Yes <input type="checkbox"/> No	

Title of Journal

CHECKLIST FOR SIGNATORIES

Review Required per WHC-CM-3-4	Yes	No	Reviewer - Signature Indicates Approval
			Name (printed) Signature Date
Classification/Uncontrolled Nuclear Information	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<i>SWBERGAM</i> <i>Swbergam</i> <i>3/30/93</i>
Patent - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Legal - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Applied Technology/Export Controlled Information or International Program	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
WHC Program/Project	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Communications	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
RL Program/Project	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
Publication Services	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<i>L. Hermann</i> <i>L. Hermann</i> <i>4/6/93</i>
Other Program/Project	<input type="checkbox"/>	<input checked="" type="checkbox"/>	

Information conforms to all applicable requirements. The above information is certified to be correct.

References Available to Intended Audience <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Transmit to DOE-HQ/Office of Scientific and Technical Information <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Author/Requestor (Printed/Signature) Date K. A. Bergstrom <i>KA Bergstrom</i> <i>2-25-93</i>	INFORMATION RELEASE ADMINISTRATION APPROVAL STAMP Stamp is required before release. Release is contingent upon resolution of mandatory comments.
Intended Audience <input type="checkbox"/> Internal <input type="checkbox"/> Sponsor <input checked="" type="checkbox"/> External Responsible Manager (Printed/Signature) Date K. R. Fecht <i>K. R. Fecht</i> <i>2/24/93</i>	
Date Cancelled	Date Disapproved

3129701642

**THIS PAGE INTENTIONALLY
LEFT BLANK**

SUPPORTING DOCUMENT

1. Total Pages 29

2. Title

Ground-Penetrating Radar Investigation for Riverland ERA

3. Number

WHC-SD-EN-TI-117

4. Rev No.

0

5. Key Words

Geophysics, Riverland Railroad Maintenance Shop, Antiaircraft Artillery Site 70

6. Author

Name: K. A. Bergstrom
T. H. Mitchell

Signature

Organization/Charge Code 81234/PB62K

APPROVED FOR
PUBLIC RELEASE

4/6/93 N. Solis

7. Abstract

Bergstrom, K. A., and T. H. Mitchell, 1993, *Ground-Penetrating Radar Investigation for Riverland ERA*, WHC-SD-EN-TI-117, Rev. 0, Westinghouse Hanford Company, Richland, Washington.

~~8. PURPOSE AND USE OF DOCUMENT - This document was prepared for use within the U.S. Department of Energy and its contractors. It is to be used only to perform, direct, or integrate work under U.S. Department of Energy contracts. This document is not approved for public release until reviewed.~~

~~PATENT STATUS - This document copy, since it is transmitted in advance of patent clearance, is made available in confidence solely for use in performance of work under contracts with the U.S. Department of Energy. This document is not to be published nor its contents otherwise disseminated or used for purposes other than specified above before patent approval for such release or use has been secured, upon request, from the Patent Counsel, U.S. Department of Energy Field Office, Richland, WA.~~

~~DISCLAIMER - This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.~~

10. RELEASE STAMP

OFFICIAL RELEASE

BY WHC

DATE APR 07 1993

Station # 12

11

9. Impact Level 4

93129701643

**THIS PAGE INTENTIONALLY
LEFT BLANK**

CONTENTS

1.0 INTRODUCTION 1

2.0 GEOLOGIC SETTING 1

3.0 GROUND PENETRATING RADAR METHODOLOGY 2

4.0 GRIDS 2

5.0 RESULTS 3

 5.1 RRMP SITE 3

 5.1.1 RRMP Pits Phase I 3

 5.1.2 RRMP Diesel Tank Phase II 3

 5.1.3 Phase III Extensions 5

 5.2 AAA SITES 5

 5.2.1 AAA #1 5

 5.2.2 AAA #2 6

 5.2.3 AAA #3 6

6.0 SUMMARY 6

7.0 REFERENCES 7

FIGURES:

1. Location Map for Riverland ERA 8

2. Riverland ERA Facility Map 9

3. Diesel Fuel Tank and Surrounding Facilities 10

4. Riverland ERA Antiaircraft Site Grids 11

5. Generalized Upper Geostratigraphic Column for the
 100-H Area 12

6. Ground Penetrating Radar Summary Interpretation
 of the Riverland ERA Railroad Depot 13

7. Interpretation Summary of RRWP with Facility Overlay 14

8. Interpreted "Pits" Surrounded by Slab-Like
 Anomalous Features 15

9. Interpreted Long Axis of "Pit" 17

10. Summary Interpretation of Diesel Tank Investigation
 Overlaid by Apparent Facility Locations 19

11. Summary Interpretation, Phase III West Extension 20

12. Tracking of Pipe from Railroad Wash Pit 21

13. GPR Interpretation Summary of Riverland
 ERA AAA Site #1 22

14. GPR Profile, AAA Site #1 23

15. GPR Interpretation Summary of Riverland
 ERA AAA Site #2 24

16. GPR Profile, AAA Site #2 25

17. GPR Interpretation Summary of Riverland
 ERA AAA Site #3 26

18. GPR Profile, AAA Site #3 27

201614

**THIS PAGE INTENTIONALLY
LEFT BLANK**

1.0 INTRODUCTION

The Riverland expedited response action (ERA) includes four sites within the 100-IU-1 Operable Unit. Ground penetrating radar (GPR) was conducted at two of the four sites, Riverland Railroad Maintenance Shop (RRMP) and the anti-aircraft artillery (AAA) site number 70 (Figure 1).

The RRMP operated from 1943 through 1954 where radioactive decontamination was conducted on outgoing railcars from the Hanford Site in the locomotive house maintenance pits. In 1963, the RRMP facilities (Figure 2) were decontaminated, demolished, and the remains buried (Valcich 1992).

The AAA site was established in 1951, but remained active for only a few years (Valcich 1992). The site was demolished and all that remains are a few "outcrops" of foundations and three enigmatic mounds.

Five individual GPR investigations were conducted as part of the overall Riverland ERA package; two locations at the RRMP (Figure 3), and three at the AAA (Figure 4). Three extensions to the original surveys were necessary at the RRMP site. Each investigation consisted of a gridded survey designed specifically for each individual site.

GPR geophysical surveys at RRMP had two primary objectives; to locate the buried maintenance pits and to determine whether a 12,000-gal, underground diesel fuel storage tank was removed during decommissioning. During the initial phases of the investigation, two pipes of unknown origin were detected. Subsequent survey extensions were required to determine their extent.

At the AAA site, GPR was conducted over the three "mounds" to determine what, if anything, was buried beneath them.

This report summarizes the interpretation of the GPR investigations for all five sites. The GPR data are contained in a data package (Bergstrom and Mitchell 1992).

2.0 GEOLOGIC SETTING

The RRMP is situated on the south limb of the Waluke syncline, which lies between two, topographically high, anticlinal ridges: Saddle Mountain and the Umtanum Ridge. The suprabasalt sediments that underlie the site include the Ringold Formation, Hanford formation, and Holocene surficial deposits (Figure 5).

Regionally, the Ringold Formation varies from gravel dominated intervals to mud dominated intervals. The upper Ringold, which consists primarily of silts and sands, has most likely been removed during the Missoula floods. In its place is the Hanford formation, which in this area is dominated by high-energy fluvial flood gravel deposits.

The Holocene sediments are primarily Columbia River and eolian deposits. The river deposits consist of gravel and coarse-grained sands deposited in channels and overbank silts and fine sands. Eolian deposits consist of a thin veneer of fine silty sands overlying the coarse Columbia River gravels and/or Hanford formation gravels (Lindsey 1992). The depth investigated with the GPR was limited to the Holocene and possibly the upper Hanford formation.

The AAA site is located on the south limb of the Umtanum Ridge structure. The suprabasalt sediments are thin in this area with the depth to the top of the basalt being <25 feet. The Ringold Formation is not present and the Hanford formation, if present, is limited to slack-water Touchet bed silts and sands, and scattered gravels from iceberg remnants related to the Missoula floods. Eolian silty loam is believed to be the predominant material overlying the basalt. However a petrocalcic horizon consisting primarily of basalt colluvium immediately overlies the basalt and may be up to 10 to 15 feet thick.

3.0 GROUND PENETRATING RADAR METHODOLOGY

The GPR system used for this work used a 300-MHz antenna to transmit the electromagnetic energy into the ground. The transmitted energy is reflected back to a receiving antenna where variations in the return signal are recorded. Common reflectors include natural geologic conditions such as bedding, cementation, moisture, and clay, or man-made objects such as pipes, barrels, foundations, and buried wires.

Depth of penetration at Hanford is generally between 1 to 15 feet, depending on the subsurface conditions, which can vary from site to site. The method is limited in depth by transmit power, receiver sensitivity, and attenuation of the transmitted energy. Depth of investigation is also influenced by highly conductive material, such as metal drums, which reflect all the energy back to the receiver. Therefore, the method cannot "see" below such objects.

Display and interpretation of the data are similar to seismic reflection data. In some areas, interpretations can be straightforward, but often unknown parameters within a highly variable subsurface yields complex data.

Data for these surveys were collected with a Geophysical Survey Systems Inc. (GSSI) Subsurface Interface Radar (SIR) System 8, model 4800. The data were digitally stored on a GSSI DT6000A tape drive. A recording window of 100 nsec, two-way travel time, was used.

4.0 GRIDS

All five GPR investigations and subsequent extensions were gridded surveys. Distances were measured and posted in feet. Green stakes mark the corners of each grid. The southeast corner of each grid is designated E100/N100 and serves as the "origin" for the survey locations. The number

refers to a distance in feet. For example, grid point E135/N120 lies 35 feet "east" and 20 feet "north" of grid point E100/N100. The letters "N" or "E" refers to a direction that trends generally north or east, respectively. Two sets of orthogonal profiles were collected at each site with a 5-foot spacing between profiles.

5.0 RESULTS

5.1 RRMP SITE

The RRMP survey was conducted in three phases. The first phase was directed at detecting the wash pits within the railroad maintenance building. Phase II was designed to investigate the buried diesel tank. Phase III included extensions to Phase I and II grids to determine the extent of two pipes of unknown origin.

5.1.1 RRMP "Pits" Phase I

The objective of Phase I was to locate the buried maintenance pits in the locomotive house (Figure 3). Aerial photographs (before and after demolition) were used for approximating the location of the locomotive house. A 60- by 120-foot grid (Figure 3) was established over the assumed location. Several GPR profiles were extended beyond the grid to enhance the interpretation on a "real-time" basis.

A summary of the interpretation of the GPR data is shown in Figure 6. The data revealed several strong near-surface reflectors that are similar in character to concrete slabs. In the northwest corner of the grid, a shallow "slab-like" reflector has a consistent signature. The slab-like reflectors throughout other portions of the grid display more discontinuity. Two parallel disturbed areas, with similar reflective characteristics, pass through the middle of the grid. They correlate with a pair of railroad tracks that went through the locomotive house (Figure 2). The rails may have been removed, leaving the foundation for the tracks. In the western half of the grid, there is an "H-shaped" disturbed zone, 2 to 5 feet below the surface. Portions of the "H" zone contain some slab-like reflectors.

The interpretation of the GPR data was compared to the construction plans for the facility; there were no "as-built" drawings available. The comparison yielded definite similarities; enough to conclude that the survey was conducted over the location of the original RRMP building (Figure 3).

It is believed that the H-shaped anomalous zone includes portions of the original pits as shown in Figure 7. The pits appear to be partially filled with debris. Figures 8 and 9 show GPR data across the pits.

5.1.2 RRMP Diesel Tank Phase II

The objective of Phase II was to determine if a 12,000-gal diesel tank had been removed, and if not, where the tank was located. From facility plans

and aerial photographs, it was determined that the tank, if present, should be located approximately 50 feet to the southwest of the locomotive house (Figure 3). An EM-31 electromagnetic induction (EMI) instrument was used for reconnaissance investigation. The area was full of metallic debris making it difficult to differentiate between individual anomalies. However, an area with a greater density of anomalies was found in the proximity of the tank location, based on available facility maps and photographs. The EMI surveys were conducted and interpreted in "real time" as a tool to refine the size and location of the grid that would be used for GPR. The EMI data were not recorded.

Based on the reconnaissance EMI survey and the facility plans, a 50- by 100-foot grid (Figure 3) was selected for the investigation. The data revealed a complex mixture of disturbed zones, buried debris, linears, geologic features, and numerous isolated anomalies.

A disturbed zone, between N70 to N90 and E10 to E40, is the only anomalous area identified, within the grid, that is large enough for a 12,000-gallon tank (Figure 10). There is no large "tank-like" anomaly within this zone, rather the zone is filled with buried, scattered, conductive debris. According to facility drawings, the boiler house was at this location indicating that this location is unlikely as a possible tank location.

A smaller disturbed zone, located 10 to 15 feet east of the large zone, displays a relatively strong, buried anomaly at E60/N74 (Figure 10). This anomaly does not appear to be large enough for a 12,000-gallon tank, though.

Centered around E45/N100 is a shallow slab-like feature that appears to be a portion of one of the original buildings, specifically the coal storage building.

Three linears were identified that potentially represent utilities/pipes. Two are east-west trending features, at N95 and N100. The third is a north-south linear at E68. These linears probably correlate with the east-west and north-south trending pipes in the drawing even though their locations do not perfectly match. A fourth, southwest-northeast trending linear, located in the northeast corner of the grid is more puzzling since there are no pipes or utilities in the plans that have a similar orientation (Figure 10). However, this linear lies in the most direct path from the locomotive house to a potential, fuel tank location.

A small anomaly at E85/N60 appears to correlate with a manhole related to a sewer line shown on the facility drawings (Figure 3). The pipes into the manhole were not detected, suggesting that they may be tile pipes.

Based on correlations between the GPR data, aerial photographs, and facility drawings, it appears that the grid was adequately located. However, there are no anomalies that appear to be from a 12,000-gallon tank.

It is possible that the tank is located beyond the survey boundaries. But it seems unlikely since the GPR data, facility drawings, and photographs indicate that the locations of buildings are relatively accurate.

Even though the facility drawing for the diesel tank and its feeder lines do not correlate exactly with the GPR data, the general "pattern" of linears, disturbed areas, and possible concrete slabs resemble those of the aerial photographs and facility drawings.

5.1.3 Phase III Extensions

During the interpretation of the diesel tank data, a pipe of unknown origin or purpose was detected in the northwest corner of the survey along profile N95 (Figure 10). The pipe was not shown on any of the supplied drawings. The GPR Phase II grid was extended an additional 80 feet to the west (Phase III west extension) to determine the extent of the pipe and whether there were any unknown structures that the pipe serviced.

The data revealed no evidence for additional buildings. However, the pipe was traced to a 4- by 4-foot wooden box/crib (Figure 11) that has the appearance of a drainage/drywell.

The objective of the Phase III east extension was to trace a pipe that was uncovered during an exploratory excavation that was conducted immediately south of the locomotive house (Figure 3). The pipe was suspected as a possible drainpipe from the wash pits. It was traced by excavation approximately 40 feet to the south where it came to a "T". GPR was then used to determine the extent of the pipe. The pipe was traced approximately 300 feet to the east where it emptied into an open ditch along the railroad tracks (Figure 12). An interpretation of the GPR signature over the pipe leads to the conclusion that the pipe is probably nonmetallic (e.g., vitrified clay).

5.2 AAA SITES

The objective of the AAA investigations was to determine if debris was buried beneath three enigmatic mounds. There was concern that the mounds might include buried hazardous material. No site plans, aerial photographs, or facility plans were available for the AAA site.

A grid was constructed over each mound, the grid size being dictated by the size of the mound to be investigated. Adjacent, heavy vegetation limited the size of the investigation in some cases.

5.2.1 AAA #1

Gun site AAA #1 appears to be the remains of a foundation for a building. A strong shallow reflector (Figure 13), 1 to 2 feet below the surface, dominates the data. It has the characteristics of a buried concrete slab. Exposures of concrete appear to be the remains from the foundation walls of a structure. These exposures and the shallow reflector are assumed to be directly related. Minor amounts of debris were detected outside of the apparent slab (Figure 14), but all of these anomalies appear to be relatively isolated and insignificant.

The relationship of an exposed vertical pipe (Valcich 1992) located in the southwest corner of the grid to a possible subsurface feature was not apparent in the data. An extension of the grid to the west and south would be required to more thoroughly investigate the feature. This area is heavily vegetated with sage brush. Additional data could be acquired after removal of sagebrush.

5.2.2 AAA #2

The primary features identified in AAA #2 were an anomalous zone between N108 and N155 and a shallow, east-west trending linear between N100 and N110 (Figure 15). The zone includes a shallow, pervasive, near-surface reflector (<2 feet deep), which overlies a second reflective horizon 1 to 2 feet below (Figure 16). The shallower, reflective horizon appears to be another slab-like anomaly. The lower reflector is more puzzling. It is less pervasive, which could be a function of depth or partial masking by the upper reflector. It is not detected outside of the extent of the upper horizon. Both seem to be the remnants of a building or structure.

There are several small scattered anomalies within the mound. They appear to be debris left from the demolition of the original structures.

The linear anomaly has the characteristics of a utility line or buried pipe. A possible scenario is that the linear represents a utility line that led to a building that was located in the anomalous area described above.

5.2.3 AAA #3



The primary features in AAA #3 are two anomalous zones and a north-south trending linear between E120 and E130 (Figure 17). The northern most anomalous zone has the characteristics of a shallow (1 to 2 feet below the surface) concrete slab. The southern anomalous zone is characterized as more "disturbed" relative to the surrounding area. Some debris appears to be buried within the mound. The linear anomaly is approximately 2 feet below the surface. It could be a section of pipe, cable, or the remnants of a foundation wall.

6.0 SUMMARY

The comparison of the interpretation of the GPR data and the facility drawings for the RRMP site yielded enough similarities to conclude that portions of the original "pits" were identified as shown in Figure 7. The pits appear to be partly filled with debris.

Based on a comparison of the GPR interpretation, facility drawings, and aerial photographs, it was concluded that the survey had been conducted over the apparent location of the diesel tank. No anomalies of the size and character of a 12,000-gallon diesel tank were detected, indicating that it may have been removed.

Figure 1. Location Map for Riverland ERA.



- A- Riverland Red Yard Site
- B- Anil-Mitrell Artillery Site
- C- Manibens Coche Site
- D- Pesticide/Herbicide Site

3129701652

Locomotive House and Diesel Oil Tank
(Primary Targets)






Figure 2. Riverland ERA Facility Map.

Figure 3. Diesel Fuel Tank and Surrounding Facilities.



(From a compilation of drawings and aerial photographs.)

Figure 4. Riverland ERA Antiaircraft Site Grids.



A - contour of the site
B - antiaircraft site
C - location of the site
D - location of the site

93129701655





Figure 5. Generalized Upper Geostratigraphic Column for the 100-H Area.



93129701656

Figure 6. Ground Penetrating Radar Summary Interpretation of the Riverland ERA Railroad Depot.




Figure 7. Interpretation Summary of RRWP with Facility Overlay.





Figure 8. Interpreted "Pits" Surrounded by Slab-Like Anomalous Features.



A = Interpreted "Pits"

96129701659

93129701660

Riverland, ERA, MIDWAY RR
N135 S-4-92 90 nsec
E35 - E220

Approximate Depth
in feet

0






Figure 9. Interpreted Long Axis of "Pit".

93129701661

**THIS PAGE INTENTIONALLY
LEFT BLANK**

Figure 10. Summary Interpretation of Diesel Tank Investigation Overlaid by Apparent Facility Locations.



	Buried Anomaly with depth in feet		"Slab-like" horizon 1-2 feet below the surface
	Buried Anomaly less than 2 feet deep		Conductive feature 1-2 feet below the surface.
	Linear Anomaly with depth in feet		Zone with abundant west to east dipping reflectors (10 ³) that are not apparent in eastern portion of survey area.
	Disturbed area		Small disturbed zone 2-3 feet below the surface
	Continuity of feature not certain		
	Disturbed zone that is dominated by scattered conductive objects		



93129701662

20





Figure 11. Summary Interpretation, Phase III West Extension.

Figure 12. Tracking of Pipe from Railroad Wash Pit.

21





Figure 13. GPR Interpretation Summary of Riverland ERA AAA Site #1.



93129701665

	Shallow, strong, reflective horizon
	Buried Anomaly with depth in feet
	Buried Anomaly less than 2 feet deep
	Linear Anomaly with depth in feet
	Continuity of feature not certain
	Disturbed area
	Concrete exposed at surface





Figure 14. GPR Profile, AAA Site #1.

Riverland, ERA (Anti-Aircraft)
Site #1
E145 AUGUST 1992 90 nsec
N100 - N150


Approximate Depth
in feet



93129701666

A = Shallow "Slab-like" Reflector


Figure 15. GPR Interpretation Summary of Riverland ERA AAA Site #2.



	Buried Anomaly with depth in feet		Zone with near surface reflector overlying less pervasive reflector 1-2 feet beneath it.
	Buried Anomaly less than 2 feet deep		
	Linear Anomaly with depth in feet		
	Buried layer with depth in feet		
	Disturbed area		
	Continuity of feature not certain		

95129701657

Figure 16. GPR Profile, AAA Site #2.






93129701668

- A = Shallow "Slab-like" Reflector
- B = Intermittent Reflector Generally Found
1 to 3 Ft Below "Slab-like" Reflector

Figure 17. GPR Interpretation Summary of Riverland ERA AAA Site #3.


August 1992



03122701609

Figure 18. GPR Profile, AAA Site #3.

Riverland, ERA:(Anti-Aircraft)
Site #3
E115 AUGUST 1992 90 nsec
N100 - N150



93129701670

- A - Disturbed Zone Containing "Buried Debris"
1 to 3 Ft Below the Surface
- B - "Slab-like" Reflector 1 to 2 Ft Below
the Surface

**THIS PAGE INTENTIONALLY
LEFT BLANK**